
HealthBot Python client Documentation

Release 4.1.0-dirty

Juniper Networks, Inc.

Dec 29, 2021

Contents

1	jnpr.healthbot	3
2	HealthBot Models generated using Swagger	37
3	Indices and tables	475
	Python Module Index	477
	Index	479

Juniper HbEZ is a Python library to remotely manage/automate **HealthBot** server

Contents:

1.1 jnpr.healthbot.modules

1.1.1 jnpr.healthbot.modules

administration

devices

class jnpr.healthbot.modules.devices.**Device** (*hbot*)

Bases: jnpr.healthbot.modules.BaseModule

__init__ (*hbot*)

Parameters *hbot* (*object*) – jnpr.healthbot.HealthBotClient client instance

add (*device_id: str = None, host: str = None, username: str = None, password: str = None, schema: jnpr.healthbot.swagger.models.device_schema.DeviceSchema = None, **kwargs*)
Add device to HealthBot

Parameters

- **device_id** (*str*) – The name of the device as provided by the User
- **host** (*str*) – The hostname/ip-address of the target device
- **username** (*str*) – The login user-name for the target device
- **password** (*str*) – The login password for the user
- **schema** (*object*) – [DeviceSchema](#)

Example:

```
from jnpr.healthbot import HealthBotClient
from jnpr.healthbot import DeviceSchema
```

(continues on next page)

(continued from previous page)

```
with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    ds = DeviceSchema(device_id='xyz', host='xx.xxx.xxx.xxx',
        authentication={"password": {"password": "xxxxx", "username": "xxxxx"
→ }})

    # we can also later assign values like this
    ds.description = "HbEZ testing"

    # This will add device in candidate DB
    hb.device.add(schema=ds)

    # commit changes to master DB
    hb.commit()
```

delete (*device_id: str, force: bool = False*)

Remove device from HealthBot

Parameters

- **device_id** (*str*) – The name of the device as provided by the User
- **force** (*bool*) – If True, Delete given device from all the device group (if present)

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    # This will delete device in candidate DB
    hb.device.delete('xyz')

    # commit changes to master DB
    hb.commit()
```

Returns True when OK**get_ids** ()

Return Device IDs for all the devices in HealthBot system

Returns list of device IDs

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    print(hb.device.get_ids())
```

get (*device_id: str = None, uncommitted: bool = True*)Get `DeviceSchema` for given device id or list for all devices**Parameters**

- **device_id** (*str*) – The name of the device as provided by the User
- **uncommitted** (*bool*) – True includes fetches uncommitted changes,

False restricts data set to only committed changes

Example:


```

from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    device = hb.device.get('vmx')
    print(device)

    devices = hb.device.get()
    for device in devices:
        print(device)

```

Returns DeviceSchema(s)

update (*schema: jnpr.healthbot.swagger.models.device_schema.DeviceSchema = None, **kwargs*)

Update DeviceSchema for given device schema

Passing Schema invoke *put* and *kwargs post*

Parameters

- **schema** (*obj*) – DeviceSchema
- **kwargs** (*object*) – key values, which can be used to create DeviceSchema Check DeviceSchema for details about which all keys can be used

Example:

```

from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    schemaObj = hb.device.get('xyz')
    schemaObj.description = 'changed description'
    hb.device.update(schemaObj)

    hb.device.update(device_id="xyz", host='xx.xxx.x.xx', system_id="xxxx")

```

Returns True when OK

get_facts (*device_id: str = None, uncommitted: bool = True*)

Get device(s) facts. Get facts for provided device id, if device id is not provided, get facts for all devices

Parameters

- **device_id** (*str*) – The name of the device as provided by the User
- **uncommitted** (*bool*) – True includes fetches uncommitted changes,

False restricts data set to only committed changes

Example:

```

from jnpr.healthbot import HealthBotClient
from pprint import pprint

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    facts = hb.device.get_facts('vmx')
    pprint(facts)
    facts = hb.device.get_facts()
    pprint(facts)

```

Returns Single/List of dicts of facts

health (*device_id*: *str*)

Returns health of given Device id [DeviceHealthTree](#)

Parameters **device_id** (*str*) – The name of the device as provided by the User

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    print(hb.device.health('core'))
```

Returns

[DeviceHealthTree](#)

class jnpr.healthbot.modules.devices.**DeviceGroup** (*hbot*)

Bases: jnpr.healthbot.modules.BaseModule

__init__ (*hbot*)

Parameters **hbot** (*object*) – jnpr.healthbot.HealthBotClient client instance

add (*schema*: *jnpr.healthbot.swagger.models.device_group_schema.DeviceGroupSchema* = *None*, ***kwargs*)

Add device group to HealthBot

Parameters

- **schema** (*object*) – [DeviceGroupSchema](#)
- **kwargs** (*object*) – key values, which can be used to create DeviceGroupSchema Check [DeviceGroupSchema](#) for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient
from jnpr.healthbot import DeviceSchema
from jnpr.healthbot import DeviceGroupSchema

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    ds = DeviceSchema(device_id='xyz', host='xx.xxx.xxx.xxx',
                      authentication={"password": {"password": "xxxxx", "username": "xxxxx"},
                                     "↪": ""})

    # This will add device in candidate DB
    hb.device.add(schema=ds)

    dgs = DeviceGroupSchema(device_group_name="edge",
                             description="All devices on the edge",
                             devices=['xyz'])

    hb.device_group.add(dgs)

    # commit changes to master DB
    hb.commit()
```

Returns True when OK

delete (*device_group_name: str, force: bool = False*)

Remove device group to HealthBot

Parameters

- **device_group_name** (*str*) – The name of the device group to be deleted
- **force** (*bool*) – If True, First delete services for given device group

Example:

```
hb.devices.delete('edge')
hb.commit()
```

Returns True when OK

get (*device_group_name: str = None, uncommitted: bool = True*)

Get [DeviceGroupSchema](#) for given device group name or list for all device groups

Parameters

- **device_group_name** (*str*) – Name of the device-group
- **uncommitted** (*bool*) – True includes fetches uncommitted changes, False restricts data set to only committed changes

Example:

```
device_group_schema = hb.device_group.get('edge')

groups = hb.device_group.get()
for group in groups:
    print(group)
```

Returns [DeviceGroupSchema\(s\)](#)

update (*schema: jnpr.healthbot.swagger.models.device_group_schema.DeviceGroupSchema = None, **kwargs*)

Update [DeviceGroupSchema](#) for given device schema

Passing Schema invoke *put* and kwargs *post*

Parameters

- **schema** (*obj*) – [DeviceGroupSchema](#)
- **kwargs** (*object*) – key values, which can be used to create [DeviceGroupSchema](#) Check [DeviceGroupSchema](#) for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    schemaObj = hb.device_group.get('Core')
    schemaObj.description = "Changed"
    hb.device_group.update(schemaObj)
```

Returns True when OK

check_device_in_group (*device_name: str, device_group_name: str*)

This method check if the device is a member of the given device-group

Parameters

- **device_name** (*str*) – Name of the device
- **device_group_name** (*str*) – Name of the device-group

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    print(hb.device_group.check_device_in_group('vmx', 'QFabric'))
```

Returns: True if action successful

add_device_in_group (*device_name: str, device_group_name: str*)

This method ensures that the given device is a member of the given device-group

Parameters

- **device_name** (*str*) – Name of the device
- **device_group_name** (*str*) – Name of the device-group

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    hb.device_group.add_device_in_group('vmx', 'QFabric')
```

Raises: HTTPError: When error making changes via the HBOT API

Returns: True if action successful

health (*device_group_name: str*)

Returns health of given Device id [DeviceGroupHealthTree](#)

Parameters **device_group_name** (*str*) – The name of the device group

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    print(hb.device_group.health('edge'))
```

Returns

[DeviceGroupHealthTree](#)

class jnpr.healthbot.modules.devices.**NetworkGroup** (*hbot*)

Bases: jnpr.healthbot.modules.BaseModule

__init__ (*hbot*)

Parameters **hbot** (*object*) – jnpr.healthbot.HealthBotClient client instance

add (*schema*: *jnpr.healthbot.swagger.models.network_group_schema.NetworkGroupSchema* = *None*, ***kwargs*)
Create Network Group

Parameters

- **schema** (*object*) – [NetworkGroupSchema](#)
- **kwargs** (*object*) – key values, which can be used to create [NetworkGroupSchema](#)
Check [NetworkGroupSchema](#) for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    hb.devices.add_network_group(network_group_name="HbEZ")

# or
from jnpr.healthbot import HealthBotClient
from jnpr.healthbot import NetworkGroupSchema

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    ngs = NetworkGroupSchema(network_group_name="HbEZ")
    hb.network_group.add(schema = ngs)
```

delete (*network_group_name*: *str*)
Delete Network Group

Parameters **network_group_name** (*str*) – The name of the network group to be deleted

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    hb.network_group.delete(network_group_name="HbEZ")
```

get (*network_group_name*: *str* = *None*, *uncommitted*: *bool* = *True*)
get Network Group(s) details

Parameters

- **network_group_name** (*str*) – The name of the network group to be fetched
- **uncommitted** (*bool*) – True includes fetches uncommitted changes, False restricts data set to only committed changes

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    print(hb.network_group.get(network_group_name="HbEZ"))
    # for all network groups
    print(hb.network_group.get())
```

update (*schema*: *jnpr.healthbot.swagger.models.network_group_schema.NetworkGroupSchema* = *None*, ***kwargs*)
Update [NetworkGroupSchema](#) for given network schema object

Passing Schema invoke *put* and kwargs *post*

Parameters

- **schema** (*obj*) – [NetworkGroupSchema](#)
- **kwargs** (*object*) – key values, which can be used to create [NetworkGroupSchema](#).

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    schemaObj = hb.network_group.get("HbEZ")
    schemaObj.description = "HbEZ example"
    hb.network_group.update(schemaObj)
```

Returns True when OK

health (*network_group_name: str*)

Returns health of given Device id [NetworkHealthTree](#)

Parameters **network_group_name** (*str*) – The name of the network group

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    print(hb.network_group.health('core'))
```

Returns

[NetworkHealthTree](#)

rule

class jnpr.healthbot.modules.rules.**Rule** (*hbot*)

Bases: jnpr.healthbot.modules.BaseModule

__init__ (*hbot*)

Parameters **hbot** (*object*) – jnpr.healthbot.HealthBotClient client instance

add (*topic_name: str, schema: jnpr.healthbot.swagger.models.rule_schema.RuleSchema = None, **kwargs*)

Create Rule under given topic

Parameters

- **topic_name** (*str*) – Rules to be created under this given topic name
- **schema** (*object*) – [RuleSchema](#)
- **kwargs** (*object*) – key values, which can be used to create [RuleSchema](#) Check [RuleSchema](#) for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient
from jnpr.healthbot import RuleSchema
```

(continues on next page)

(continued from previous page)

```

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    rs = RuleSchema(rule_name="hbez-fpc-heap-utilization")

    rs.description = "HealthBot EZ example"
    rs.synopsis = "Using python client for demo"

    rs.sensor = [{'description': 'Monitors FPC buffer, heap and cpu_
↪utilization',
                    'iAgent': {'file': 'fpc-utilization.yml',
                                'frequency': '30s',
                                'table': 'FPCCPUHEAPutilizationTable'},
                    'sensor-name': 'fpccpuheaputilization'}]

    from jnpr.healthbot.swagger.models.rule_schema_field import_
↪RuleSchemaField
    from jnpr.healthbot.swagger.models.rule_schema_constant import_
↪RuleSchemaConstant

    rs.field = [RuleSchemaField(constant=RuleSchemaConstant(value='{{fpc-
↪buffer-usage-threshold}}'),
                                description='This field is for buffer usage_
↪threshold',
                                field_name='linecard-buffer-usage-threshold'),
                RuleSchemaField(constant=RuleSchemaConstant(value='{{fpc-cpu-
↪usage-threshold}}'),
                                description='This field is for linecard cpu_
↪usage threshold',
                                field_name='linecard-cpu-usage-threshold'),
                RuleSchemaField(constant=RuleSchemaConstant(value='{{fpc-heap-
↪usage-threshold}}'),
                                description='This field is for linecard heap_
↪usage threshold',
                                field_name='linecard-heap-usage-threshold')]

    rs.keys = ['slot']

    rs.variable = [{'description': 'Linecard Buffer Memory usage threshold_
↪value',
                    'name': 'fpc-buffer-usage-threshold',
                    'type': 'int',
                    'value': '80'},
                    {'description': 'Linecard CPU usage threshold value',
                    'name': 'fpc-cpu-usage-threshold',
                    'type': 'int',
                    'value': '80'},
                    {'description': 'Linecard Heap Memory usage threshold value
↪',
                    'name': 'fpc-heap-usage-threshold',
                    'type': 'int',
                    'value': '80'}]

    rs.trigger = [{'description': 'Sets health based on linecard buffer memory
↪',
                    'frequency': '60s',
                    'synopsis': 'Linecard buffer memory kpi',
                    'term': [{'term-name': 'is-buffer-memory-utilization-
↪greater-than-threshold',

```

(continues on next page)

(continued from previous page)

```

        'then': {'status': {'color': 'red',
                             'message': 'FPC buffer_
↪memory '
                                     'utilization '
                                     '($memory-buffer-
↪utilization) '
                                     'is over_
↪threshold '
                                     '($linecard-
↪buffer-usage-threshold)'}}},
        'when': {'greater-than': [{'left-operand': '
↪$memory-buffer-utilization',
                                     'right-operand': '
↪$linecard-buffer-usage-threshold'}]}},
        {'term-name': 'buffer-utilization-less-than-
↪threshold',
         'then': {'status': {'color': 'green'}}},
        'trigger-name': 'fpc-buffer-memory-utilization',
        {'description': 'Sets health based on linecard cpu_
↪utilization',
         'frequency': '60s',
         'synopsis': 'Linecard cpu utilization kpi',
         'term': [{'term-name': 'is-cpu-utilization-greater-than-80
↪',
                    'then': {'status': {'color': 'red',
                                         'message': 'FPC CPU_
↪utilization '
                                         '($cpu-total) is_
↪over '
                                         'threshold '
                                         '($linecard-cpu-
↪usage-threshold)'}}},
                    'when': {'greater-than': [{'left-operand': '$cpu-
↪total',
                                                'right-operand': '
↪$linecard-cpu-usage-threshold',
                                                'time-range': '180s'}
                    ]}},
                    {'term-name': 'cpu-utilization-less-than-threshold
↪',
                     'then': {'status': {'color': 'green'}}},
                     'trigger-name': 'fpc-cpu-utilization',
                     {'description': 'Sets health based on linecard heap memory '
                                      'utilization',
                      'frequency': '60s',
                      'synopsis': 'Linecard heap memory kpi',
                      'term': [{'term-name': 'is-heap-memory-utilization-greater-
↪than-threshold',
                                  'then': {'status': {'color': 'red',
                                                         'message': 'FPC heap memory '
                                                         'utilization '
                                                         '($memory-heap-
↪utilization) '
                                                         'is over_
↪threshold '
                                                         '($linecard-heap-
↪usage-threshold)'}}},

```

(continues on next page)

(continued from previous page)

```

        'when': {'greater-than': [{'left-operand': '
↪$memory-heap-utilization',
                                                                    'right-operand': '
↪$linecard-heap-usage-threshold'}]}],
        {'term-name': 'heap-memory-utilization-less-than-
↪threshold',
          'then': {'status': {'color': 'green'}}}],
        'trigger-name': 'fpc-heap-memory-utilization'})
hb.rule.add('hbez', schema=rs)

```

Returns: True if action successful

delete (*topic_name: str, rule_name: str*)

Delete rule under given topic

Parameters

- **topic_name** (*str*) – The name of the topic under which rule need to deleted
- **rule_name** (*str*) – The name of the rule to be deleted

Example:

```

from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxx', 'xxx') as hb:
    hb.rule.delete('linecard.ospf', 'check-ddos-statistics')

```

get (*topic_name: str, rule_name: str = None, uncommitted: bool = True*)

get rule(s) details under given topic

Parameters

- **topic_name** (*str*) – The name of the topic under which rule need to be fetched
- **rule_name** (*str*) – The name of the rule under given topic If none return list for all Rule
- **uncommitted** (*bool*) – True includes fetches uncommitted changes, False restricts data set to only committed changes

Example:

```

from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxx', 'xxx') as hb:
    print(hb.rule.get('linecard.ospf', 'check-ddos-statistics'))

    print(hb.rule.get('linecard.ospf'))

```

update (*topic_name: str, schema: jnpr.healthbot.swagger.models.rule_schema.RuleSchema = None, **kwargs*)

Update [RuleSchema](#) for given rule schema object

Passing Schema invoke *put* and kwargs *post*

Parameters

- **topic_name** (*str*) – The name of the topic under which rule need to be updated
- **schema** (*obj*) – [RuleSchema](#)

- **kwargs** (*object*) – key values, which can be used to create RuleSchema

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    schemaObj = hb.rule.get(topic_name='hbez', rule_name="hbez-fpc-heap-
↪utilization")
    schemaObj.description = "HbEZ example"
    hb.rule.update(topic_name='hbez', schemaObj)
```

Returns True when OK

upload_rule_file (*filename*)

Parameters **filename** – File to be loaded

Returns return True of OK

class jnpr.healthbot.modules.rules.**Topic** (*hbot*)

Bases: jnpr.healthbot.modules.BaseModule

__init__ (*hbot*)

Parameters **hbot** (*object*) – jnpr.healthbot.HealthBotClient client instance

get (*topic_name: str = None, uncommitted: bool = True*)

Get **TopicSchema(s)** for given topic name or all topics in HealthBot system

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    print(hb.topic.get('linecard.ospf'))
    topics = hb.topic.get()
    for topic in topics:
        print(topic)
```

Returns Single/list of **TopicSchema**

playbook

class jnpr.healthbot.modules.playbooks.**Playbook** (*hbot*)

Bases: jnpr.healthbot.modules.BaseModule

__init__ (*hbot*)

Parameters **hbot** (*object*) – jnpr.healthbot.HealthBotClient client instance

add (*schema: jnpr.healthbot.swagger.models.playbook_schema.PlaybookSchema = None, **kwargs*)
Add playbook

Parameters

- **schema** (*object*) – **PlaybookSchema**
- **kwargs** (*object*) – key values, which can be used to create PlaybookSchema Check **PlaybookSchema** for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    hb.playbook.add(playbook_name="HbEZ-example",
                    rules = ['protocol.infra/check-task-memory-usage'])

# or
from jnpr.healthbot import HealthBotClient
from jnpr.healthbot import PlaybookSchema

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    pbs = PlaybookSchema(playbook_name="HbEZ-example",
                        rules = ['protocol.infra/check-task-memory-usage'])
    hb.playbook.add(pbs)
```

Returns: True if action successful

delete (*playbook_name: str*)

Delete playbook

Parameters **playbook_name** (*str*) – The playbook name to deleted

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    hb.playbook.delete('linecard-kpis-playbook')
```

get (*playbook_name: str = None, uncommitted: bool = True*)

get playbook details

Parameters

- **playbook_name** (*str*) – Name of the playbook
- **uncommitted** (*bool*) – True includes fetches uncommitted changes, False restricts data set to only committed changes

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    print(hb.playbook.get('linecard-kpis-playbook'))

# for all
print(hb.playbook.get())
```

update (*schema: jnpr.healthbot.swagger.models.playbook_schema.PlaybookSchema = None, **kwargs*)

Update [PlaybookSchema](#) for given playbook schema

Passing Schema invoke *put* and kwargs *post*

Parameters

- **schema** (*obj*) – [PlaybookSchema](#)

- **kwargs** (*object*) – key values, which can be used to create PlaybookSchema Check `PlaybookSchema` for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    schemaObj = hb.playbook.get('xyz')
    schemaObj.description = 'changed description'
    hb.playbook.update(schemaObj)
```

Returns True when OK

upload_playbook_file (*filename*)

Parameters **filename** – File to be loaded

Returns return True of OK

```
class jnpr.healthbot.modules.playbooks.PlayBookInstanceBuilder(hbot, playbook: str, instance: str = None, device_group_name: str = None)
```

Bases: `jnpr.healthbot.modules.playbooks.Playbook`

__init__ (*hbot, playbook: str, instance: str = None, device_group_name: str = None*)

Help in building and applying playbook instance

Parameters

- **hbot** – HealthBOTClient instance
- **playbook** – Playbook name for which instance need to be created
- **instance** – Playbook instance name
- **device_group_name** – Device group which will be associated with instance

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:

    from jnpr.healthbot import PlayBookInstanceBuilder
    pbb = PlayBookInstanceBuilder(hb, 'forwarding-table-summary', 'HbEZ-
↪instance', 'Core')

    variable = pbb.rule_variables["protocol.routesummary/check-fib-summary"]
    variable.route_address_family = 'pqr'
    variable.route_count_threshold = 100

    # Apply variable to given device(s)
    pbb.apply(device_ids=['vmx'])

    #clear all the variable if you want to set it something else for group or_
↪other device(s)
    pbb.clear()
```

(continues on next page)

(continued from previous page)

```

variable = pbb.rule_variables["protocol.routesummary/check-fib-summary"]
variable.route_address_family = 'abc'
variable.route_count_threshold = 200

pbb.apply()

hb.commit()

```

apply (*device_ids: list = None, commit: bool = False*)

Apply the playbook instance

Parameters

- **device_ids** – if the rule variables need to be associated for given device id(s). Default to device group
- **commit** – Pass true if need to commit the changes

Example:

```

from jnpr.healthbot import PlayBookInstanceBuilder
pbb = PlayBookInstanceBuilder(hb, 'forwarding-table-summary', 'HbEZ-instance',
↪ 'Core')
pbb.apply()

```

Returns True if all OK

clear ()

Clear the old set values to rule variables :return: None

delete ()

Delete playbook instance

Example:

```

from jnpr.healthbot import PlayBookInstanceBuilder
pbb = PlayBookInstanceBuilder(hb, 'forwarding-table-summary', 'HbEZ-instance',
↪ 'Core')
pbb.delete()

```

Returns True if success

playbook_schema

rules

rule_variables

device_variable

health

settings

class jnpr.healthbot.modules.settings.**Settings** (*hbot*)

Bases: object

__init__ (*hbot*)

Parameters **hbot** (*object*) – jnpr.healthbot.HealthBotClient client instance

class jnpr.healthbot.modules.settings.**Notification** (*hbot*)

Bases: jnpr.healthbot.modules.BaseModule

__init__ (*hbot*)

Parameters **hbot** (*object*) – jnpr.healthbot.HealthBotClient client instance

get (*notification_name: str = None, uncommitted: bool = True*)

Get NotificationSchema(s) for given notification name or list for all

Parameters

- **notification_name** – ID of notification-name
- **uncommitted** (*bool*) – True includes fetches uncommitted changes, False restricts data set to only committed changes

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    print(hb.settings.notification.get('xyz'))
```

Returns

NotificationSchema(s)

add (*schema: jnpr.healthbot.swagger.models.notification_schema.NotificationSchema = None, **kwargs*)

Add notification to HealthBot

Parameters

- **schema** (*object*) – NotificationSchema
- **kwargs** (*object*) – key values, which can be used to create NotificationSchema Check NotificationSchema for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient
from jnpr.healthbot import NotificationSchema, NotificationSchemaSlack

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    ns = NotificationSchema(notification_name='HbEZ-notification')
    ns.description = "example of adding notification via API"
    ns.slack = NotificationSchemaSlack(channel="HbEZ", url='http://testing')
    hb.settings.notification.add(ns)
```

Returns True when OK

delete (*notification_name: str*)

Remove notification from settings

Parameters **notification_name** (*str*) – The name of the notification to be deleted

Example:

```
hb.settings.notification.delete('xyz')
hb.commit()
```

Returns True when OK

update (*schema*: `jnpr.healthbot.swagger.models.notification_schema.NotificationSchema` = None, ***kwargs*)

Update `NotificationSchema` for given `NotificationSchema` schema

Passing Schema invoke *put* and kwargs *post*

Parameters

- **schema** (*obj*) – `NotificationSchema`
- **kwargs** (*object*) – key values, which can be used to create `RetentionPolicySchema`
Check `NotificationSchema` for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient
with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    schemaObj = hb.settings.notification.get('xyz')
    schemaObj.description = 'changed description'
    hb.settings.notification.update(schemaObj)
```

Returns True when OK

class `jnpr.healthbot.modules.settings.RetentionPolicy` (*hbot*)

Bases: `jnpr.healthbot.modules.BaseModule`

__init__ (*hbot*)

Parameters *hbot* (*object*) – `jnpr.healthbot.HealthBotClient` client instance

get (*retention_policy_name*: *str* = None, *uncommitted*=True)

Get `RetentionPolicySchema(s)` for given retention policy name or list for all

Parameters

- **retention_policy_name** – ID of retention-policy-name
- **uncommitted** (*bool*) – True includes fetches uncommitted changes, False restricts data set to only committed changes

Example:

```
from jnpr.healthbot import HealthBotClient
with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    print(hb.settings.retention_policy.get('xyz'))

    # for all
    print(hb.settings.retention_policy.get())
```

Returns

`RetentionPolicySchema(s)`

add (*schema*: *jnpr.healthbot.swagger.models.retention_policy_schema.RetentionPolicySchema* = *None*, ***kwargs*)
Add notification to HealthBot

Parameters

- **schema** (*object*) – [RetentionPolicySchema](#)
- **kwargs** (*object*) – key values, which can be used to create [RetentionPolicySchema](#)
Check [RetentionPolicySchema](#) for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient
from jnpr.healthbot import RetentionPolicySchema

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    rps = RetentionPolicySchema(retention_policy_name='HbEZ-retention-policy
    ↪')
    hb.settings.retention_policy.add(rps)
```

Returns True when OK

delete (*retention_policy_name*: *str*)
Remove notification from settings

Parameters **retention_policy_name** (*str*) – The name of the retention policy to be deleted

Example:

```
hb.settings.retention_policy.delete('xyz')
hb.commit()
```

Returns True when OK

update (*schema*: *jnpr.healthbot.swagger.models.retention_policy_schema.RetentionPolicySchema* = *None*, ***kwargs*)

Update [RetentionPolicySchema](#) for given [RetentionPolicySchema](#) schema

Passing Schema invoke *put* and kwargs *post*

Parameters

- **schema** (*obj*) – [RetentionPolicySchema](#)
- **kwargs** (*object*) – key values, which can be used to create [RetentionPolicySchema](#)
Check [RetentionPolicySchema](#) for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    schemaObj = hb.settings.retention_policy.get('xyz')
    schemaObj.description = 'changed description'
    hb.settings.retention_policy.update(schemaObj)
```

Returns True when OK

class `jnpr.healthbot.modules.settings.Scheduler` (*hbot*)

Bases: `jnpr.healthbot.modules.BaseModule`

__init__ (*hbot*)

Parameters *hbot* (*object*) – `jnpr.healthbot.HealthBotClient` client instance

get (*name: str = None, uncommitted: bool = True*)

Get `SchedulerSchema(s)` for given scheduler name or list for all

Parameters

- **name** – scheduler name
- **uncommitted** (*bool*) – True includes fetches uncommitted changes, False restricts data set to only committed changes

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    print(hb.settings.scheduler.get('xyz'))

    # for all
    print(hb.settings.scheduler.get())
```

Returns

`SchedulerSchema(s)`

add (*schema: jnpr.healthbot.swagger.models.scheduler_schema.SchedulerSchema = None, **kwargs*)

Add scheduler to HealthBot

Parameters

- **schema** (*object*) – `SchedulerSchema`
- **kwargs** (*object*) – key values, which can be used to create `SchedulerSchema` Check `SchedulerSchema` for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient
from jnpr.healthbot import SchedulerSchema

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    sc = SchedulerSchema(name='HbEZ', repeat={'every': 'week'},
                        start_time="2019-07-22T05:32:23Z")
    hb.settings.scheduler.add(sc)
```

Returns True when OK

delete (*name: str*)

Remove notification from settings

Parameters **name** (*str*) – The name of the scheduler to be deleted

Example:

```
hb.settings.scheduler.delete('xyz')
hb.commit()
```

Returns True when OK

update (*schema*: *jnpr.healthbot.swagger.models.scheduler_schema.SchedulerSchema* = *None*,
***kwargs*)

Update [SchedulerSchema](#) for given scheduler schema

Passing Schema invoke *put* and *kwargs post*

Parameters

- **schema** (*obj*) – [SchedulerSchema](#)
- **kwargs** (*object*) – key values, which can be used to create [SchedulerSchema](#) Check [SchedulerSchema](#) for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient
with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    schemaObj = hb.settings.scheduler.get('xyz')
    schemaObj.description = 'changed description'
    hb.settings.scheduler.update(schemaObj)
```

Returns True when OK

class `jnpr.healthbot.modules.settings.Destination` (*hbot*)

Bases: `jnpr.healthbot.modules.BaseModule`

__init__ (*hbot*)

Parameters **hbot** (*object*) – `jnpr.healthbot.HealthBotClient` client instance

get (*name*: *str* = *None*, *uncommitted*: *bool* = *True*)

Get [DestinationSchema\(s\)](#) for given destination name or list for all

Parameters

- **name** – destination ID
- **uncommitted** (*bool*) – True includes fetches uncommitted changes, False restricts data set to only committed changes

Example:

```
from jnpr.healthbot import HealthBotClient
with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    print(hb.settings.destination.get('xyz'))

    # for all
    print(hb.settings.destination.get())
```

Returns

[DestinationSchema\(s\)](#)

add (*schema*: *jnpr.healthbot.swagger.models.destination_schema.DestinationSchema* = *None*,
***kwargs*)
 Add destination to HealthBot

Parameters

- **schema** (*object*) – [DestinationSchema](#)
- **kwargs** (*object*) – key values, which can be used to create [DestinationSchema](#) Check [DestinationSchema](#) for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient
from jnpr.healthbot import DestinationSchema

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    ds = DestinationSchema(name='HbEZ-destination')
    hb.settings.destination.add(ds)
```

Returns True when OK

delete (*name*: *str*)
 Remove destination from settings

Parameters **name** (*str*) – The ID name of the destination to be deleted

Example:

```
hb.settings.destination.delete('xyz')
hb.commit()
```

Returns True when OK

update (*schema*: *jnpr.healthbot.swagger.models.destination_schema.DestinationSchema* = *None*,
***kwargs*)
 Update [DestinationSchema](#) for given destination schema

Passing Schema invoke *put* and kwargs *post*

Parameters

- **schema** (*obj*) – [DestinationSchema](#)
- **kwargs** (*object*) – key values, which can be used to create [DestinationSchema](#) Check [DestinationSchema](#) for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient
with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    schemaObj = hb.settings.destination.get('xyz')
    schemaObj.description = 'changed description'
    hb.settings.destination.update(schemaObj)
```

Returns True when OK

class *jnpr.healthbot.modules.settings.Report* (*hbot*)
 Bases: *jnpr.healthbot.modules.BaseModule*

`__init__(hbot)`

Parameters `hbot` (*object*) – `jnpr.healthbot.HealthBotClient` client instance

get (*name: str = None, uncommitted: bool = True*)

Get `ReportSchema(s)` for given report name or list for all

Parameters

- **name** – report ID
- **uncommitted** (*bool*) – True includes fetches uncommitted changes, False restricts data set to only committed changes

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    print(hb.settings.report.get('xyz'))

    # for all
    print(hb.settings.report.get())
```

Returns

`ReportSchema(s)`

add (*schema: jnpr.healthbot.swagger.models.report_schema.ReportSchema = None, **kwargs*)

Add report to HealthBot

Parameters

- **schema** (*object*) – `ReportSchema`
- **kwargs** (*object*) – key values, which can be used to create `ReportSchema` Check `ReportSchema` for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient
from jnpr.healthbot import ReportSchema

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:

    from jnpr.healthbot import SchedulerSchema
    sc = SchedulerSchema(name='HbEZ-schedule', repeat={'every': 'week'},
                        start_time="2019-07-22T05:32:23Z")
    hb.settings.scheduler.add(sc)

    from jnpr.healthbot import DestinationSchema
    ds = DestinationSchema(name='HbEZ-destination',
                        email={'id': 'nitinkr@juniper.net'})
    hb.settings.destination.add(ds)

    from jnpr.healthbot import ReportSchema
    rs = ReportSchema(name="HbEZ-report", destination=['HbEZ-destination'],
                    format="html", schedule=["HbEZ-schedule"])
    hb.settings.report.add(rs)
```

Returns True when OK

delete (*name: str*)

Remove report from settings

Parameters **name** (*str*) – The name of the report to be deleted

Example:

```
hb.settings.report.delete('xyz')
hb.commit()
```

Returns True when OK

update (*schema: jnpr.healthbot.swagger.models.report_schema.ReportSchema = None, **kwargs*)

Update [ReportSchema](#) for given report schema

Passing Schema invoke *put* and kwargs *post*

Parameters

- **schema** (*obj*) – [ReportSchema](#)
- **kwargs** (*object*) – key values, which can be used to create [ReportSchema](#) Check [ReportSchema](#) for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient
with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    schemaObj = hb.settings.report.get('xyz')
    schemaObj.description = 'changed description'
    hb.settings.report.update(schemaObj)
```

Returns True when OK

class `jnpr.healthbot.modules.settings.LicenseKeyManagement` (*hbot*)

Bases: `jnpr.healthbot.modules.BaseModule`

__init__ (*hbot*)

Parameters **hbot** (*object*) – `jnpr.healthbot.HealthBotClient` client instance

get_features ()

Get [LicenseFeatureSchema\(s\)](#) for given license id or for all licence id

Parameters **license_id** – License ID

Example:

```
from jnpr.healthbot import HealthBotClient
with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    print(hb.settings.license.get_features())
```

Returns

[LicenseFeatureSchema\(s\)](#)

get_ids ()

List of all licence id

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    # print all existing licence ids
    print(hb.settings.license.get())
```

Returns *List of license ids*

get (*license_id: str = None*)

Get `LicenseKeySchema(s)` for given license id or for all licence id

Parameters `license_id` – License ID

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    print(hb.settings.license.get())

    # for given licence id
    print(hb.settings.report.get('xxxxx'))
```

Returns

`LicenseKeySchema(s)`

add (*license_file*)

Add report to HealthBot

Parameters `license_file` (*path*) – license file path

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    hb.settings.license.add(license_file='/var/tmp/xyz')
```

Returns `license_id` if OK

delete (*license_id: str*)

Remove report from settings

Parameters `license_id` (*str*) – The license id be deleted

Example:

```
hb.settings.license.delete('xx-xxx-xxx-xxx-xx')
```

Returns True when OK

profile

class `jnpr.healthbot.modules.profiles.Profile` (*hbot*)

Bases: `object`

```
__init__(hbot)
```

Parameters **hbot** (*object*) – jnpr.healthbot.HealthBotClient client instance

```
class jnpr.healthbot.modules.profiles.Security(hbot)
```

Bases: object

```
__init__(hbot)
```

Parameters **hbot** (*object*) – jnpr.healthbot.HealthBotClient client instance

```
class jnpr.healthbot.modules.profiles.CaProfile(hbot)
```

Bases: jnpr.healthbot.modules.BaseModule

```
__init__(hbot)
```

Parameters **hbot** (*object*) – jnpr.healthbot.HealthBotClient client instance

get (*name: str = None, uncommitted: bool = True*)

Get [CaProfileSchema\(s\)](#) for given ca profile name or list for all

Parameters

- **name** – ID of name
- **uncommitted** (*bool*) – True includes fetches uncommitted changes, False restricts data set to only committed changes

Example:

```
:: from jnpr.healthbot import HealthBotClient
```

```
with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb: print(hb.settings.security.ca_profile.get('xyz'))
```

```
# for all print(hb.settings.security.ca_profile.get())
```

Returns

[CaProfileSchema\(s\)](#)

add (*schema: jnpr.healthbot.swagger.models.ca_profile_schema.CaProfileSchema = None, **kwargs*)

Add ca profile to HealthBot. The onus of uploading helper file certificate_authority.crt is on user. They should use hb.upload_helper_file API to make sure these crt file are uploaded in system. We don't do that validation as user can also upload these file after configuring profiles.

Parameters

- **schema** (*object*) – [CaProfileSchema](#)
- **kwargs** (*object*) – key values, which can be used to create [CaProfileSchema](#) Check [CaProfileSchema](#) for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient
from jnpr.healthbot import CaProfileSchema

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    ca_prof_schema = CaProfileSchema(certificate_authority.crt='abc.crt',
    ↪ name='hbez')
    hb.settings.security.ca_profile.add(ca_prof_schema)
```

Returns True when OK

delete (*name: str*)

Remove ca profile from security settings

Parameters **name** (*str*) – The name of the ca_profile to be deleted

Example:

```
hb.settings.security.ca_profile.delete('xyz')
hb.commit()
```

Returns True when OK

update (*schema: jnpr.healthbot.swagger.models.ca_profile_schema.CaProfileSchema = None, **kwargs*)

Update `CaProfileSchema` for given ca profile schema

Passing Schema invoke *put* and kwargs *post*

Parameters

- **schema** (*obj*) – `CaProfileSchema`
- **kwargs** (*object*) – key values, which can be used to create `CaProfileSchema` Check `CaProfileSchema` for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    schemaObj = hb.settings.security.ca_profile.get('xyz')
    schemaObj.certificate_authority_cert = 'pqr.crt'
    hb.settings.security.ca_profile.update(schemaObj)
```

Returns True when OK

class `jnpr.healthbot.modules.profiles.LocalCertificate` (*hbot*)

Bases: `jnpr.healthbot.modules.BaseModule`

__init__ (*hbot*)

Parameters **hbot** (*object*) – `jnpr.healthbot.HealthBotClient` client instance

get (*name: str = None, uncommitted: bool = True*)

Get `LocalCertificateSchema(s)` for given local certificate name or list for all

Parameters

- **name** – ID of name
- **uncommitted** (*bool*) – True includes fetches uncommitted changes, False restricts data set to only committed changes

Example:

```
:: from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    print(hb.settings.security.local_certificate.get('xyz'))
    # for all print(hb.settings.security.local_certificate.get())
```


Returns`LocalCertificateSchema(s)`

add (*schema*: `jnpr.healthbot.swagger.models.local_certificate_schema.LocalCertificateSchema = None`, ***kwargs*)

Add local certificate to security settings of HealthBot. The onus of uploading helper file (cert and key) is on user. They should use `hb.upload_helper_file` API to make sure these crt/key file are uploaded in system. We don't do that validation as user can also upload these file after configuring profiles.

Parameters

- **schema** (*object*) – `LocalCertificateSchema`
- **kwargs** (*object*) – key values, which can be used to create `LocalCertificateSchema`. Check `LocalCertificateSchema` for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient
from jnpr.healthbot import LocalCertificateSchema

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    local_cert_schema = LocalCertificateSchema(client_crt='abc.crt', client_
    key='pqr.key', name='hbez')
    hb.settings.security.local_certificate.add(local_cert_schema)
```

Returns True when OK

delete (*name*: `str`)

Remove local certificate from security settings

Parameters **name** (`str`) – The name of the local_certificate to be deleted

Example:

```
hb.settings.security.local_certificate.delete('xyz')
hb.commit()
```

Returns True when OK

update (*schema*: `jnpr.healthbot.swagger.models.local_certificate_schema.LocalCertificateSchema = None`, ***kwargs*)

Update `LocalCertificateSchema` for given local certificate schema

Passing Schema invoke *put* and *kwargs post*

Parameters

- **schema** (*obj*) – `LocalCertificateSchema`
- **kwargs** (*object*) – key values, which can be used to create `LocalCertificateSchema`. Check `LocalCertificateSchema` for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    schemaObj = hb.settings.security.local_certificate.get('xyz')
```

(continues on next page)

(continued from previous page)

```

schemaObj.client_key = 'xyz.key'
hb.settings.security.local_certificate.update(schemaObj)

```

Returns True when OK

class jnpr.healthbot.modules.profiles.SshKeyProfile (hbot)

Bases: jnpr.healthbot.modules.BaseModule

__init__ (hbot)

Parameters **hbot** (*object*) – jnpr.healthbot.HealthBotClient client instance

get (*name: str = None, uncommitted: bool = True*)

Get SshKeyProfileSchema(s) for given ssh key profile name or list for all

Parameters

- **name** – ID of name
- **uncommitted** (*bool*) – True includes fetches uncommitted changes, False restricts data set to only committed changes

Example:

```

:: from jnpr.healthbot import HealthBotClient

    with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb: print(hb.settings.security.ssh_key_profile.get('xyz'))

    # for all print(hb.settings.security.ssh_key_profile.get())

```

Returns

SshKeyProfileSchema(s)

add (*schema: jnpr.healthbot.swagger.models.ssh_key_profile_schema.SshKeyProfileSchema = None, **kwargs*)

Add ssh key profile to HealthBot. The onus of uploading helper file ssh_private_key_file is on user. They should use hb.upload_helper_file API to make sure these key file are uploaded in system. We don't do that validation as user can also upload these file after configuring profiles.

Parameters

- **schema** (*object*) – SshKeyProfileSchema
- **kwargs** (*object*) – key values, which can be used to create SshKeyProfileSchema Check SshKeyProfileSchema for details about which all keys can be used

Example:

```

from jnpr.healthbot import HealthBotClient
from jnpr.healthbot import SshKeyProfileSchema

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    ssh_key_prof_schema = SshKeyProfileSchema(name='hbez', ssh_private_key_
↪file='abc.crt',
        ssh_private_key_passphrase='%$#@#')
    hb.settings.security.ssh_key_profile.add(ssh_key_prof_schema)

```

Returns True when OK

delete (*name: str*)

Remove ssh key profile from security settings

Parameters **name** (*str*) – The name of the ssh key profile to be deleted

Example:

```
hb.settings.security.ssh_key_profile.delete('xyz')
hb.commit()
```

Returns True when OK

update (*schema: jnpr.healthbot.swagger.models.ssh_key_profile_schema.SshKeyProfileSchema = None, **kwargs*)

Update [SshKeyProfileSchema](#) for given ssh key profile schema

Passing Schema invoke *put* and *kwargs post*

Parameters

- **schema** (*obj*) – [SshKeyProfileSchema](#)
- **kwargs** (*object*) – key values, which can be used to create [SshKeyProfileSchema](#)
Check [SshKeyProfileSchema](#) for details about which all keys can be used

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    schemaObj = hb.settings.security.ssh_key_profile.get('xyz')
    schemaObj.certificate_authority_cert = 'pqr.crt'
    hb.settings.security.ssh_key_profile.update(schemaObj)
```

Returns True when OK

class jnpr.healthbot.modules.profiles.**DataSummarization** (*hbot*)

Bases: jnpr.healthbot.modules.BaseModule

__init__ (*hbot*)

Parameters **hbot** (*object*) – jnpr.healthbot.HealthBotClient client instance

class jnpr.healthbot.modules.profiles.**Raw** (*hbot*)

Bases: jnpr.healthbot.modules.BaseModule

__init__ (*hbot*)

Parameters **hbot** (*object*) – jnpr.healthbot.HealthBotClient client instance

get ()

add ()

delete (*name: str*)

update ()

database

```
class jnpr.healthbot.modules.database.Database(hbot)
```

Bases: `influxdb.client.InfluxDBClient`

```
__init__(hbot)
```

Parameters `hbot` (*object*) – `jnpr.healthbot.HealthBotClient` client instance

Example:

```
hb.tsdbs.query("show databases")
hb.tsdbs.query('select * from "protocol-eventd-host/check-host-traffic/packet-
↪loss" limit 10',
               database='Core:vmx')
```

api

```
get_table()
```

Get list of tables

Returns list of `TableSchema`

1.2 HealthBotClient

```
class jnpr.healthbot.healthbot.HealthBotClient(server: str, user: str, password: str,
                                                *args, **kwargs)
```

Bases: `object`

```
apiopt_candidate = '/?working=true'
```

```
__init__(server: str, user: str, password: str, *args, **kwargs)
```

An instance of this class represents the HealthBot Service

Parameters

- **server** (*str*) – HealthBot Server IP Address
- **user** (*str*) – HealthBot Server (not the Linux user) UserName
- **password** (*str*) – HealthBot Server (not the Linux user) password
- **port** (*int*) – *OPTIONAL* HealthBot Server port (defaults to 8080)

Example:

```
from jnpr.healthbot import HealthBotClient
from pprint import pprint

with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx', port=8000) as hb:

    # Get list of all existing devices
    print(hb.device.get_ids())

    # Get config details of a given device id
    pprint(hb.device.get('core-01'))

    # Get config details of all the device
    pprint(hb.device.get())
```

(continues on next page)

(continued from previous page)

```

# Get device facts of a given device id
pprint(hb.device.get_facts('avro'))

# Get device facts for all the devices in HB
pprint(hb.device.get_facts())

# Add a device
from jnpr.healthbot import DeviceSchema
ds = DeviceSchema(device_id='xyz', host='xx.xxx.xxx.xxx',
                  authentication={"password": {"password": "xxxxx", "username": "xxxxx
→ }}})

# we can also later assign values like this
ds.description = "HbEZ testing"

# This will add device in candidate DB
hb.device.add(schema=ds)

# Add device group
print(hb.device_group.add(device_group_name="edge",
description="All devices on the edge", devices=['demo']))

# commit changes to master DB
hb.commit()

# get details of a given topic/rule
pprint(hb.rule.get('linecard.ospf', 'check-ddos-statistics'))

```

open()

Open session with HealthBot server. First sets user token (for healthbot 3.0.0 and above) and check a top level URL for confirmation of API to be working.

login()

Open session with HealthBot server. First sets user token (for healthbot 3.0.0 and above) and check a top level URL for confirmation of API to be working.

set_user_token()

From HealthBot 3.0.0 APIs will be token based. This function helps in setting user based token. This token will be used in header of any REST API calls.

tenant**hbot_session**

Property provides requests module session object. Also help in updating Access token key when expires. Any call to hbot_session.apis should go through this property to keep a check on token key expiry.

user_token**logout()**

Call user logout function to discard access tokens.

tsdb

Connection to the tsdb

Returns InfluxDBClient

config_url

This function will give config URL

url

Initials of URL to be used for API call. :returns:

str: Initials of URL to be used for API call.

grafana_url

version

TO get the version of Healthbot Server

Returns str: API server version.

api

commit()

Commit any candidate configuration

Example:

```
from jnpr.healthbot import HealthBotClient
from jnpr.healthbot import DeviceSchema

with HealthBotClient('xx.xxx.x.xx', 'xxx', 'xxx') as hb:
    ds = DeviceSchema(device_id='xyz', host='xx.xxx.xxx.xxx',
                      authentication={"password": {"password": "xxxxx", "username": "xxxxx"}
    })

    # we can also later assign values like this
    ds.description = "HbEZ testing"

    # This will add device in candidate DB
    hb.device.add(schema=ds)

    # commit changes to master DB
    hb.commit()
```

Raises Any requests exception

Returns True when OK

rollback()

Rollback any candidate configuration

Example:

```
from jnpr.healthbot import HealthBotClient

with HealthBotClient('xx.xxx.x.xx', 'xxx', 'xxx') as hb:
    # This will delete device in candidate DB
    hb.device.delete('xyz')

    # rollback candidate configuration
    hb.rollback()
```

Raises Any requests exception

Returns True when OK

upload_helper_file(filename)

Upload a “helper-file” to the server. A helper-file, cab be YAML/.py/.rule/.playbook file.

Parameters `filename` (*str*) – The name of the file to be uploaded.

health()

Returns health of network-groups and devices in device-groups [HealthSchema](#)

Example:

```
from jnpr.healthbot import HealthBotClient
with HealthBotClient('xx.xxx.x.xx', 'xxxx', 'xxxx') as hb:
    print(hb.health())
```

Returns

[HealthSchema](#)

close()

HealthBot Models generated using Swagger

2.1 Schemas

2.2 AssociatedUserSchema

2.2.1 Properties

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.3 DevicegroupSchemaAuthenticationPassword

2.3.1 Properties

Name	Type	Description	Notes
password	str	Password for authentication	
username	str	Username for authentication	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.4 RuleSchemaRulepropertiesSupporteddevicesJuniperReleases

2.4.1 Properties

Name	Type	Description	Notes
release_name	str	Release name, Should be of pattern (d){1,2}.{1}([w-_.]*)	
release_support	str	Specifies the min/max support for this release	[optional]
sensors	list[str]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.5 RuleSchemaWhere

2.5.1 Properties

Name	Type	Description	Notes
query	str	Query to filter ingest data	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.6 DevicegroupSchemaLoggingOpenconfig

2.6.1 Properties

Name	Type	Description	Notes
daemons	list[str]		[optional]
log_level	str	Set the logging level	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.7 RuleSchemaFormula

2.7.1 Properties

Name	Type	Description	Notes
anomaly_detection	**RuleSchemaFormulaAnomalydetection**		[optional]
count	**RuleSchemaFormulaCount**		[optional]
dynamic_threshold	**RuleSchemaFormulaDynamicthreshold**		[optional]
eval	**RuleSchemaFormulaEval**		[optional]
max	**RuleSchemaFormulaMax**		[optional]
mean	**RuleSchemaFormulaMean**		[optional]
concatenate	**RuleSchemaFormulaConcatenate**		[optional]
microburst	**RuleSchemaFormulaMicroburst**		[optional]
min	**RuleSchemaFormulaMin**		[optional]
outlier_detection	**RuleSchemaFormulaOutlierdetection**		[optional]
predict	**RuleSchemaFormulaPredict**		[optional]
rate_of_change	**RuleSchemaFormulaRateofchange**		[optional]
elapsed_time	**RuleSchemaFormulaElapsedtime**		[optional]
value_difference	**RuleSchemaFormulaValuedifference**		[optional]
stddev	**RuleSchemaFormulaStddev**		[optional]
sum	**RuleSchemaFormulaSum**		[optional]
user_defined_function	**RuleSchemaFormulaUserdefinedfunction**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.8 RuleSchemaThenUserdefinedaction

2.8.1 Properties

Name	Type	Description	Notes
argument	**list[RuleSchemaThenArgument]**		[optional]
function_name	str	Function name	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.9 ReportsSchema

2.9.1 Properties

Name	Type	Description	Notes
report	**list[ReportSchema]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.10 NetworkgroupSchemaLogging

2.10.1 Properties

Name	Type	Description	Notes
log_level	str	Global log level	[optional]
non_sensor_rules	**DevicegroupSchemaLoggingNonsensorrules**		[optional]
reports_generation	**DevicegroupSchemaLoggingReportsgeneration**		[optional]
trigger_evaluation	**DevicegroupSchemaLoggingTriggerevaluation**		[optional]
ml_model_builder	**DevicegroupSchemaLoggingMLmodelbuilder**		[optional]
resource_discovery	**DevicegroupSchemaLoggingResourcediscovery**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.11 ProfileSchemaSecurity

2.11.1 Properties

Name	Type	Description	Notes
ca_profile	**list[CaProfileSchema]**		[optional]
local_certificate	**list[LocalCertificateSchema]**		[optional]
ssh_key_profile	**list[SshKeyProfileSchema]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.12 DevicegroupSchemaAuthenticationSsl

2.12.1 Properties

Name	Type	Description	Notes
ca_profile	str	Name of the ca-profile to be used	
local_certificate	str	Name of the local-certificate-profile to be used	[optional]
server_common_name	str	Common name used while creating server certificate	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.13 InlineResponse2006

2.13.1 Properties

Name	Type	Description	Notes
access_token	str	Access token generated by system	[optional]
refresh_token	str	Refresh token generated by system	[optional]
first_login	bool	Flag to indicate if the user changed default password or not	[optional]
refresh_token_expires	str	Refresh token validity duration	[optional]
token_expires	str	Access token validity duration	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.14 RuleSchemaSensor

2.14.1 Properties

Name	Type	Description	Notes
data_if_missing	**RuleSchema-Dataifmissing**		[optional]
path	str	Sensor path	
sensor_name	str	Name of the sensor	
where	**list[RuleSchemaWhere]**	List of where clauses to filter ingest data	[optional]
zero_suppression	list[object]	Assign zero as default value for field in case of zero-suppression	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.15 CustompluginSchemaParameters

2.15.1 Properties

Name	Type	Description	Notes
key	str	Key of the parameter	
value	str	Value of the parameter	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.16 swagger_client.LogsApi

All URIs are relative to *http://api-server/api/v2*

Method	HTTP request	Description
**re- trieve_logs_for_device_group	GET /logs/device-group/{device_group_name}/	Logs for the given device-group.
**re- trieve_logs_for_device_group	GET /logs/device-group/{device_group_name}/service/{service_name}/	Get the logs for the given service running on the given device-group.
**re- trieve_logs_for_network_group	GET /logs/network-group/{network_group_name}/	Logs for the given network group.
**re- trieve_logs_for_network_group	GET /logs/network-group/{network_group_name}/service/{service_name}/	Get the logs for the given service running on the given network-group.

2.17 retrieve_logs_for_device_group

```
retrieve_logs_for_device_group(device_group_name, x_iam_token=x_iam_token, download=download,
                               filename=filename)
```

Logs for the given device-group.

Get the logs for all the services for the given {device_group_name}

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.LogsApi()
device_group_name = 'device_group_name_example' # str | Device group name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
download = True # bool | Download the logs (optional) (default to true)
filename = 'filename_example' # str | Name of the log file (optional)

try:
    # Logs for the given device-group.
    api_instance.retrieve_logs_for_device_group(device_group_name, x_iam_token=x_iam_token,
    ↪token, download=download, filename=filename)
except ApiException as e:
    print("Exception when calling LogsApi->retrieve_logs_for_device_group: %s\n" % e)
```

Name	Type	Description	Notes
device_group_name	str	Device group name	
x_iam_token	str	authentication header object	[optional]
download	bool	Download the logs	[optional] [default to true]
filename	str	Name of the log file	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/gzip, application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.18 retrieve_logs_for_device_group_service

```
retrieve_logs_for_device_group_service(device_group_name, service_name,
x_iam_token=x_iam_token, download=download, filename=filename, num-
ber_of_lines=number_of_lines)
```

Get the logs for the given service running for the given device-group.

Get the logs for the service {service_name} for the given {device_group_name}

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.LogsApi()
device_group_name = 'device_group_name_example' # str | Device group name
service_name = 'service_name_example' # str | Device-group service name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
download = True # bool | Download the logs (optional) (default to true)
filename = 'filename_example' # str | Name of the log file (optional)
number_of_lines = 100000 # int | Number of lines to show from the end of the logs_
↳ (optional) (default to 100000)

try:
    # Get the logs for the given service running for the given device-group.
    api_instance.retrieve_logs_for_device_group_service(device_group_name, service_
↳ name, x_iam_token=x_iam_token, download=download, filename=filename, number_of_
↳ lines=number_of_lines)
except ApiException as e:
    print("Exception when calling LogsApi->retrieve_logs_for_device_group_service:
↳ %s\n" % e)
```

Name	Type	Description	Notes
device_group_name	str	Device group name	
service_name	str	Device-group service name	
x_iam_token	str	authentication header object	[optional]
download	bool	Download the logs	[optional] [default to true]
filename	str	Name of the log file	[optional]
number_of_lines	int	Number of lines to show from the end of the logs	[optional] [default to 100000]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/gzip, application/json, text/plain

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.19 retrieve_logs_for_network_group

```
retrieve_logs_for_network_group(network_group_name, x_iam_token=x_iam_token, download=download, filename=filename)
```

Logs for the given network group.

Get the logs for the service {service_name} for the given {network_group_name}

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.LogsApi()
network_group_name = 'network_group_name_example' # str | Network group name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
download = True # bool | Download the logs (optional) (default to true)
filename = 'filename_example' # str | Name of the log file (optional)

try:
    # Logs for the given network group.
    api_instance.retrieve_logs_for_network_group(network_group_name, x_iam_token=x_iam_token, download=download, filename=filename)
except ApiException as e:
    print("Exception when calling LogsApi->retrieve_logs_for_network_group: %s\n" % e)
```

Name	Type	Description	Notes
network_group_name	str	Network group name	
x_iam_token	str	authentication header object	[optional]
download	bool	Download the logs	[optional] [default to true]
filename	str	Name of the log file	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/gzip, application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.20 retrieve_logs_for_network_group_service

```
retrieve_logs_for_network_group_service(network_group_name, service_name, x_iam_token=x_iam_token, download=download, filename=filename, number_of_lines=number_of_lines)
```

Get the logs for the given service running for the given network-group.

Get the logs for all the services for the given {network_group_name}


```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.LogsApi()
network_group_name = 'network_group_name_example' # str | Network group name
service_name = 'service_name_example' # str | Network group service name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
download = True # bool | Download the logs (optional) (default to true)
filename = 'filename_example' # str | Name of the log file (optional)
number_of_lines = 100000 # int | Number of lines to show from the end of the logs_
↳ (optional) (default to 100000)

try:
    # Get the logs for the given service running for the given network-group.
    api_instance.retrieve_logs_for_network_group_service(network_group_name, service_
↳ name, x_iam_token=x_iam_token, download=download, filename=filename, number_of_
↳ lines=number_of_lines)
except ApiException as e:
    print("Exception when calling LogsApi->retrieve_logs_for_network_group_service:
↳ %s\n" % e)

```

Name	Type	Description	Notes
net-work_group_name	str	Network group name	
service_name	str	Network group service name	
x_iam_token	str	authentication header object	[optional]
download	bool	Download the logs	[optional] [default to true]
filename	str	Name of the log file	[optional]
number_of_lines	int	Number of lines to show from the end of the logs	[optional] [default to 100000]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/gzip, application/json, text/plain

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.21 RuleSchemaFormulaOutlierdetectionAlgorithmKfold3sigma

2.21.1 Properties

Name	Type	Description	Notes
learning_period	str	Time period on which to detect outliers	
sensitivity	**RuleSchemaFormulaOutlierdetectionAlgorithmDbscanSensitivity**		[optional]
sigma_coefficient	float	Number of standard deviations past which outliers are marked	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.22 DeviceSchemaSnmpV2

2.22.1 Properties

Name	Type	Description	Notes
community	str	Community name. 'public' will be used if not configured	[optional]
source_id	**DeviceSchemaSnmpV2Sourceid**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.23 TliveKafkaOcsSchema

2.23.1 Properties

Name	Type	Description	Notes
tlive_kafka_oc	**list[TliveKafkaOcSchema]**		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.24 ProfileSchema

2.24.1 Properties

Name	Type	Description	Notes
security	**ProfileSchemaSecurity**		[optional]
data_summarization	**ProfileSchemaDatsummarization**		[optional]
rollup_summarization	**ProfileSchemaRollupsummarization**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.25 ApplymacroSchemaData

2.25.1 Properties

Name	Type	Description	Notes
name	str	Keyword part of the keyword-value pair	
value	str	Value part of the keyword-value pair	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.26 NotificationSchemaMicrosoftteams

2.26.1 Properties

Name	Type	Description	Notes
channel	str	Connector channel on which notification is to be posted	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.27 RuleSchemaVariable

2.27.1 Properties

Name	Type	Description	Notes
description	str	Description about the variable	[optional]
name	str	Variable name used in the playbook. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	
type	str	Type of value supported. This information will be used by UI to display options available for the values	
value	str	Default value for the variable	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.28 DevicegroupSchemaVariable

2.28.1 Properties

Name	Type	Description	Notes
in- stance_id	str	Unique ID of the variable instance. This should be unique per play-book and rule combination. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	
play- book	str	Name of the playbook in which the variable instance needs to be used	
rule	str	Name of the rule. This must be of the format <topic-name>.<rule-name>;	
run- ning_state	str	Current running state of the playbook instance	[op- tional]
vari- able_value	**list[DevicegroupSchemaVariablevalue]**		[op- tional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.29 FrequencyprofileSchemaSensor

2.29.1 Properties

Name	Type	Description	Notes
fre- quency	str	Sensor subscription duration. Specify integer > 0 followed by seconds/minutes/hours/days/weeks/years. Eg: 2seconds. A frequency of zero should be used only in case of events subscription	
sen- sor_name	str	Name of sensor. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.30 DevicegroupSchemaAuthenticationSsh

2.30.1 Properties

Name	Type	Description	Notes
ssh_key_profile	str	Name of the ssh-key-profile to be used	
username	str	Username for authentication	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.31 SchedulerSchema

2.31.1 Properties

Name	Type	Description	Notes
scheduler	**list[SchedulerSchema]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.32 RuleSchemaRulepropertiesSupporteddevicesOthervendor

2.32.1 Properties

Name	Type	Description	Notes
ap- ply_macro	**list[ApplyMacroSchema]**		[optional]
operat- ing_system	str	[Deprecated] Vendor operating system, Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	[optional]
operat- ing_systems	**list[RuleSchemaRulepropertiesSupportedOperatingSystemoftheDevice]**	Operating system of the device	[optional]
sensors	list[str]		[optional]
ven- dor_identifier	str	Unique key to identify the other vendor specific products	
ven- dor_name	str	Vendor name	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.33 ReportSchemaGraphcanvas

2.33.1 Properties

Name	Type	Description	Notes
canvas_panel	**list[ReportSchemaCanvaspanel]**	Canvas panel	[optional]
name	str	Name of the canvas.	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.34 LicenseRawKeySchema

2.34.1 Properties

Name	Type	Description	Notes
raw_key	str	License key string	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.35 IngestmappingSchemaNativegpb

2.35.1 Properties

Name	Type	Description	Notes
for_device_groups	list[str]		[optional]
use_plugin	**IngestmappingSchemaAgentUseplugin**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.36 DeviceGroupHealthTree

2.36.1 Properties

Name	Type	Description	Notes
children	**list[DeviceGroupHealthTree]**		
color	str		[optional]
data	str		[optional]
name	str		
timestamp	datetime		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.37 IngestmappingSchemaSyslog

2.37.1 Properties

Name	Type	Description	Notes
for_device_groups	list[str]		[optional]
use_plugin	**IngestmappingSchemaAgentUseplugin**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.38 InlineResponse2002

2.38.1 Properties

Name	Type	Description	Notes
access_token	str	Access token generated by system	[optional]
refresh_token	str	Refresh token generated by system	[optional]
refresh_token_expires	str	Refresh token validity duration	[optional]
token_expires	str	Access token validity duration	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.39 RuleSchemaRulepropertiesSupporteddevicesJuniper

2.39.1 Properties

Name	Type	Description	Notes
operating_system	**list[RuleSchemaRulepropertiesSupporteddevicesJuniperOperatingSystem]	Operating system of the device	[optional]
sensors	list[str]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.40 PatternSchema

2.40.1 Properties

Name	Type	Description	Notes
constant	**list[PatternSchemaConstant]	Constant details	[optional]
description	str	Pattern description	[optional]
event_id	str	Event id that identifies a log uniquely. Field names also can be part of event-id. Example my-event+\$field1	
field	**list[PatternSchemaField]	Field details	[optional]
filter	str	Filter to match a log line	[optional]
filter_type	str	Filter type, default is grok	[optional]
key_fields	list[str]		[optional]
name	str	Name of a pattern. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.41 Group

2.41.1 Properties

Name	Type	Description	Notes
group_description	str	Details of the group	[optional]
roles	**list[GroupgroupidRoles]**	list of roles associated	[optional]
users	**list[GroupgroupidUsers]**	list of users associated	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.42 DevicesSchema

2.42.1 Properties

Name	Type	Description	Notes
device	**list[DeviceSchema]**		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.43 RuleSchemaDataifmissing

2.43.1 Properties

Name	Type	Description	Notes
value	str	Assign given default value for field in case of data missing	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.44 RuleSchemaTerm

2.44.1 Properties

Name	Type	Description	Notes
term_name	str	Term name. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	
then	**RuleSchemaThen**		[optional]
when	**RuleSchemaWhen**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.45 TlivekafkaocSchemaSecurity

2.45.1 Properties

Name	Type	Description	Notes
sasl	**TlivekafkaocSchemaSecuritySasl**		[optional]
tls	**CustompluginSchemaSecurityparametersTls**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.46 RuleSchemaFormula1Unique

2.46.1 Properties

Name	Type	Description	Notes
vec-tor_name	str	Vector name in which unique elements needs to be computed. Pattern for giving vector name is @[a-z][a-zA-Z0-9_-]*	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.47 RoleSchema

2.47.1 Properties

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.48 DevicegroupSchemaLogging

2.48.1 Properties

Name	Type	Description	Notes
i_agent	**DevicegroupSchemaLoggingIAgent**		[optional]
log_level	str	Global log level	[optional]
native_gpb	**DevicegroupSchemaLoggingNativegpb**		[optional]
non_sensor_rules	**DevicegroupSchemaLoggingNonsensorrules**		[optional]
open_config	**DevicegroupSchemaLoggingOpenconfig**		[optional]
server_monitoring	**DevicegroupSchemaLoggingServermonitoring**		[optional]
reports_generation	**DevicegroupSchemaLoggingReportsgeneration**		[optional]
snmp	**DevicegroupSchemaLoggingSnmp**		[optional]
trigger_evaluation	**DevicegroupSchemaLoggingTriggerevaluation**		[optional]
ml_model_builder	**DevicegroupSchemaLoggingMLmodelbuilder**		[optional]
resource_discovery	**DevicegroupSchemaLoggingResourcediscovery**		[optional]
flow	**DevicegroupSchemaLoggingFlow**		[optional]
sflow	**DevicegroupSchemaLoggingSflow**		[optional]
byoi	**DevicegroupSchemaLoggingByoi**		[optional]
snmp_notification	**DevicegroupSchemaLoggingSnmpnotification**		[optional]
syslog	**DevicegroupSchemaLoggingSyslog**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.49 NotificationSchemaHttppost

2.49.1 Properties

Name	Type	Description	Notes
basic	**NotificationSchemaHttppostBasic**		[optional]
url	str	URL on which http notification needs to be posted	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.50 User1

2.50.1 Properties

Name	Type	Description	Notes
first_name	str	First name of the user	[optional]
last_name	str	Last name of the user	[optional]
email	str	Email of the user	[optional]
password	str	Password of the user	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.51 LicensekeySchemaFeatures

2.51.1 Properties

Name	Type	Description	Notes
feature_id	int	Unique ID of the licensed feature	
feature_name	str	Name of the licensed feature	
feature_description	str	Brief description of the licensed feature	
capacity_value	int	Total capacity of the licensed feature	
capacity_flag	bool	Flag indicating if the feature is capacity or non-capacity type	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.52 SystemSettingsSchema

2.52.1 Properties

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.53 IngestsettingsSchemaIngestsettingsFlow

2.53.1 Properties

Name	Type	Description	Notes
template	**list[IngestsettingsSchemaIngestsettingsFlowTemplate]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.54 RuleSchemaWhenEqualto

2.54.1 Properties

Name	Type	Description	Notes
all	list[object]	With this flag, result is set to True only if all the data matches the given condition	[optional]
any	list[object]	With this flag, result is set to True if any one of the data matches the condition	[optional]
left_operand	int	Left operand	
right_operand	int	right operand	
time_range	str	How much back in time should we look for data. Specify positive integer followed by s/m/h/d/w/y/o representing seconds/minutes/hours/days/weeks/years/offset. Eg: 2s	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.55 DevicegroupSchemaNotification

2.55.1 Properties

Name	Type	Description	Notes
enable	list[object]	Turn on notifications	[optional]
major	list[str]		[optional]
minor	list[str]		[optional]
no_initial_normal_notify_suppression	bool	If true, Don't suppress the initial normal notifications	[optional]
normal	list[str]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.56 InlineResponse2003

2.56.1 Properties

Name	Type	Description	Notes
user_id	str	ID generated by system	[optional]
user_name	str	Name of the user	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.57 RuleSchemaFormula1

2.57.1 Properties

Name	Type	Description	Notes
_and	**RuleSchemaFormula1And**		[optional]
_or	**RuleSchemaFormula1Or**		[optional]
unique	**RuleSchemaFormula1Unique**		[optional]
unless	**RuleSchemaFormula1Unless**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.58 DevicegroupSchemaRawdataSummarize

2.58.1 Properties

Name	Type	Description	Notes
summarization_profile	list[str]		[optional]
time_span	str	Timespan for aggregate functions	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.59 CommandRpc

2.59.1 Properties

Name	Type	Description	Notes
args	dict(str, str)	Optional key/value pair arguments to table	[optional]
filename	str	Command-rpc table filename in which the table is defined	
host	str	Host name or ip-address of the device in which command will be inspected	
password	str	Password to connect to device	
table-name	str	Command-rpc table name	
target	str	To run command on FPC, specify FPC target	[optional]
username	str	Username to connect to device	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.60 TimeRangeMandatory

2.60.1 Properties

Name	Type	Description	Notes
time_range	str	How much back in time should we look for data	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.61 WhenLhsRhsGroup

2.61.1 Properties

Name	Type	Description	Notes
left_operand	str	Left operand	[optional]
right_operand	str	right operand	[optional]
time_range	str	How much back in time should we look for data	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.62 DevicegroupSchemaFlow

2.62.1 Properties

Name	Type	Description	Notes
deploy_nodes	list[str]		[optional]
netflow	**DevicegroupSchemaFlowNetflow**		[optional]
sflow	**DevicegroupSchemaFlowSflow**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.63 GroupgroupidUsers

2.63.1 Properties

Name	Type	Description	Notes
id	str		[optional]
name	str		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.64 DevicegroupSchemaRawdata

2.64.1 Properties

Name	Type	Description	Notes
persist	object	Enables persist-raw-data	[optional]
summarize	**DevicegroupSchemaRawdataSummarize**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.65 RuleSchemaFlow

2.65.1 Properties

Name	Type	Description	Notes
template_name	str		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.66 FrequencyprofileSchemaNonsensor

2.66.1 Properties

Name	Type	Description	Notes
frequency	str	Sensor subscription duration. Specify integer > 0 followed by s/m/h/d/w/y representing seconds/minutes/hours/days/weeks/years. Eg: 2s. A frequency of zero should be used only in case of events subscription	
rule_name	str	Name of non-sensor or network rule i.e topic-name/rule-name	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.67 DevicegroupSchemaLoggingTriggerevaluation

2.67.1 Properties

Name	Type	Description	Notes
log_level	str	Set the logging level	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.68 TopicsSchema

2.68.1 Properties

Name	Type	Description	Notes
topic	**list[TopicSchema]**		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.69 GroupgroupidRoles

2.69.1 Properties

Name	Type	Description	Notes
role_id	str		[optional]
role_name	str		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.70 FlowSchemaFlowRecognitionpattern

2.70.1 Properties

Name	Type	Description	Notes
exclude_fields	list[str]		[optional]
include_fields	list[str]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.71 CaProfileSchema

2.71.1 Properties

Name	Type	Description	Notes
certificate_authority_cert	str	Certificate Authority certificate file name. Should be of pattern .+.cert	
name	str	Certificate Authority profile name. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.72 DeviceHealthSchema

2.72.1 Properties

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.73 RuleSchemaVector

2.73.1 Properties

Name	Type	Description	Notes
formula	**RuleSchemaFor- mula**		[optional]
path	list[str]		[optional]
time_range	str	How much back in time should we look for data. Specify positive integer followed by s/m/h/d/w/y/o representing seconds/minutes/hours/days/weeks/yours/offset. Eg: 2s	[optional]
vector_name	str	Name of the vector. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.74 FrequencyProfileSchema

2.74.1 Properties

Name	Type	Description	Notes
name	str	Frequency profile name	
non_sensor	**list[FrequencyprofileSchemaNonsensor]**		[optional]
sensor	**list[FrequencyprofileSchemaSensor]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.75 DestinationSchemaEmail

2.75.1 Properties

Name	Type	Description	Notes
id	str	Email ID	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.76 InlineResponse2007

2.76.1 Properties

Name	Type	Description	Notes
access_token	str	Access token generated by system	[optional]
refresh_token	str	Refresh token generated by system	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.77 NotificationsSchema

2.77.1 Properties

Name	Type	Description	Notes
notification	**list[NotificationSchema]**		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.78 RuleSchemaFormula1Unless

2.78.1 Properties

Name	Type	Description	Notes
left_vector	str	Vector name. Pattern for giving vector name is @[a-z][a-zA-Z0-9_-]*	
right_vector	str	Vector name. Pattern for giving vector name is @[a-z][a-zA-Z0-9_-]*	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.79 RuleSchemaWhenRange

2.79.1 Properties

Name	Type	Description	Notes
all	list[object]	With this flag, result is set to True only if all the data matches the given condition	[optional]
any	list[object]	With this flag, result is set to True if any one of the data matches the condition	[optional]
field_name	str	Field name on which range should be applied	
max	float	Maximum value in the range	
min	float	Minumum value in the range	
time_range	str	How much back in time should we look for data. Specify positive integer followed by s/m/h/d/w/y/o representing seconds/minutes/hours/days/weeks/years/offset. Eg: 2s	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.80 InstanceScheduleStateSchema

2.80.1 Properties

Name	Type	Description	Notes
group_name	str	Name of the group	
group_type	str	Type of the group. Can be one of device-group or network-group	
name	str	Name of the instance	
rule	str	Name of the rule associated with the instance	
playbook	str	Name of the playbook associated with the instance	
state	str	Scheduled state of the instance. Can be one of active or inactive	
up-date_time	object	Time the current status is updated for this instance in elapsed seconds since epoch	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.81 RuleSchemaRulepropertiesHelperfiles

2.81.1 Properties

Name	Type	Description	Notes
file_type	str		
list_of_files	list[str]		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.82 RuleSchemaFormulaMax

2.82.1 Properties

Name	Type	Description	Notes
field_name	str	Field name on which max operation needs to be performed	
time_range	str	How much back in time should we look for data. Specify positive integer followed by s/m/h/d/w/y/o representing seconds/minutes/hours/days/weeks/years/offset. Eg: 2s	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.83 RuleSchemaThenStatus

2.83.1 Properties

Name	Type	Description	Notes
color	str	Color that needs to be shown in the health tree	
message	str	Description that needs to be show in the health tree	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.84 DevicegroupSchemaLoggingSyslog

2.84.1 Properties

Name	Type	Description	Notes
daemons	list[str]		[optional]
log_level	str	Set the logging level	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.85 DevicegroupSchemaVariablevalue

2.85.1 Properties

Name	Type	Description	Notes
name	str	Variable name used in the playbook/rule. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	
value	str	Value for the variable	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.86 DevicegroupSchemaLoggingSnmp

2.86.1 Properties

Name	Type	Description	Notes
daemons	list[str]		[optional]
log_level	str	Set the logging level	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.87 PlaybooksSchema

2.87.1 Properties

Name	Type	Description	Notes
playbook	**list[PlaybookSchema]**		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.88 RawSchemaDatatype

2.88.1 Properties

Name	Type	Description	Notes
aggregation_functions	list[str]		
name	str	Name of the data-type for which summarization should be changed	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.89 RuleSchemaFormulaPredict

2.89.1 Properties

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.90 IngestsettingsSchemaIngestsettingsSyslogConstant

2.90.1 Properties

Name	Type	Description	Notes
description	str	Constant description	[optional]
name	str	Constant field name	
type	str		[optional]
value	str	Value of the constant	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.91 Credential

2.91.1 Properties

Name	Type	Description	Notes
user_name	str	username of the user	
password	str	Password of the user	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.92 DeviceSchemaSyslog

2.92.1 Properties

Name	Type	Description	Notes
source_ip_addresses	list[str]		[optional]
hostnames	list[str]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.93 DevicegroupSchemaNativegpb

2.93.1 Properties

Name	Type	Description	Notes
ports	list[int]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.94 IngestsettingsSchemaIngestsettingsSyslog

2.94.1 Properties

Name	Type	Description	Notes
pattern	**list[IngestsettingsSchemaIngestsettingsSyslogPattern]	Pattern details	[optional]
pattern_set	**list[IngestsettingsSchemaIngestsettingsSyslogPatternSet]	Pattern set details	[optional]
port	int	Port to listen for syslog messages, default is 514	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.95 RuleSchemaConstant

2.95.1 Properties

Name	Type	Description	Notes
value	str	Value for the constant	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.96 LicenseKeysSchema

2.96.1 Properties

Name	Type	Description	Notes
license_key	**list[LicenseKeySchema]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.97 RuleSchemaByoiPlugin

2.97.1 Properties

Name	Type	Description	Notes
name	str	Name of the input plugin	
parameters	**list[RuleSchemaByoiPluginParameters]**	Plugin specific parameters (config)	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.98 swagger_client.ServicesApi

All URIs are relative to *http://api-server/api/v2*

Method	HTTP request	Description
create_services_device_groups_device_group_by_device_group_name	POST /config/services/device-group/{device_group_name}/	Start a device-group's services.
create_services_network_group_by_network_group_name	POST /config/services/network-group/{network_group_name}/	Start a network-group's services.
delete_services_device_groups_device_group_by_device_group_name	DELETE /config/services/device-group/{device_group_name}/	Stop and remove a device-group's services.
delete_services_network_group_by_network_group_name	DELETE /config/services/network-group/{network_group_name}/	Stop and remove a network-group's services.
retrieve_services_device_groups_device_group_by_device_group_name	GET /config/services/device-group/{device_group_name}	Get running `device-group-name`s.
retrieve_services_network_group	GET /config/services/network-group/{network_group_name}	Get running `network-group-name`s.

2.99 create_services_device_groups_device_group_by_device_group_name

```
create_services_device_groups_device_group_by_device_group_name(device_group_name,
x_iam_token=x_iam_token)
```

Start a device-group's services.

Start services of a device group. Use this to start stopped services.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ServicesApi()
device_group_name = 'device_group_name_example' # str | Name of device group
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Start a device-group's services.
    api_instance.create_services_device_groups_device_group_by_device_group_
↪name(device_group_name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ServicesApi->create_services_device_groups_device_
↪group_by_device_group_name: %s\n" % e)

```

Name	Type	Description	Notes
device_group_name	str	Name of device group	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.100 create_services_network_group_by_network_group_name

```

create_services_network_group_by_network_group_name(network_group_name,
x_iam_token=x_iam_token)

```

Start a network-group's services.

Start services of a network group. Use this to start stopped services.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ServicesApi()
network_group_name = 'network_group_name_example' # str | Name of network group
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Start a network-group's services.
    api_instance.create_services_network_group_by_network_group_name(network_group_
↪name, x_iam_token=x_iam_token)

```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling ServicesApi->create_services_network_group_by_
↳network_group_name: %s\n" % e)
```

Name	Type	Description	Notes
network_group_name	str	Name of network group	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.101 delete_services_device_groups_device_group_by_device_group_name

```
delete_services_device_groups_device_group_by_device_group_name(device_group_name,
x_iam_token=x_iam_token)
```

Stop and remove a device-group's services.

Stop and clean services of a device-group. This will remove all the services for a device-group, however, it will not clean up the collected data.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ServicesApi()
device_group_name = 'device_group_name_example' # str | Name of device group
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Stop and remove a device-group's services.
    api_instance.delete_services_device_groups_device_group_by_device_group_
↳name(device_group_name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ServicesApi->delete_services_device_groups_device_
↳group_by_device_group_name: %s\n" % e)
```

Name	Type	Description	Notes
device_group_name	str	Name of device group	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.102 delete_services_network_group_by_network_group_name

```
delete_services_network_group_by_network_group_name(network_group_name,
x_iam_token=x_iam_token)
```

Stop and remove a network-group's services.

Stop and clean the services of a network group. This will remove all the services for a network-group, however, it will not clean up the collected data.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ServicesApi()
network_group_name = 'network_group_name_example' # str | Name of network group
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Stop and remove a network-group's services.
    api_instance.delete_services_network_group_by_network_group_name(network_group_
↪name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ServicesApi->delete_services_network_group_by_
↪network_group_name: %s\n" % e)
```

Name	Type	Description	Notes
network_group_name	str	Name of network group	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.103 retrieve_services_device_groups_device_group_device_group

```
list[str] retrieve_services_device_groups_device_group_device_group(x_iam_token=x_iam_token)
```

Get running device-group-names.

Get the list of device-group-names of device-groups whose services are running.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ServicesApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Get running `device-group-name`s.
    api_response = api_instance.retrieve_services_device_groups_device_group_device_
↪group(x_iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ServicesApi->retrieve_services_device_groups_device_
↪group_device_group: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.104 retrieve_services_network_group

list[str] retrieve_services_network_group(x_iam_token=x_iam_token)

Get running network-group-names

Get the list of network-group-names of network-groups whose services are running.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ServicesApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Get running `network-group-name`s
    api_response = api_instance.retrieve_services_network_group(x_iam_token=x_iam_
↪token)
    pprint(api_response)

```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling ServicesApi->retrieve_services_network_group: %s\n"
    ↪ % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.105 RuleSchemaFormulaRateofchange

2.105.1 Properties

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.106 LocalCertificateSchema

2.106.1 Properties

Name	Type	Description	Notes
client_cert	str	Client certificate file name. Should be of pattern .+.cert	
client_key	str	Client Key file name. Should be of pattern .+.key	
name	str	Local Certificate profile name. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.107 IngestsettingsSchemaIngestsettingsSyslogPattern

2.107.1 Properties

Name	Type	Description	Notes
constant	<code>**list[IngestsettingsSchemaIngestsettingsSyslogPatternConstantDetailsConstant]**</code>	Constant details	[optional]
description	<code>str</code>	Pattern description	[optional]
event_id	<code>str</code>	Event id that identifies a log uniquely. Field names also can be part of event-id. Example my-event+\$field1	
field	<code>**list[IngestsettingsSchemaIngestsettingsSyslogPatternFieldDetailsField]**</code>	Field details	[optional]
filter	<code>str</code>	Filter to match a log line	[optional]
filter_type	<code>str</code>	Filter type, default is grok	[optional]
key_fields	<code>list[str]</code>		[optional]
name	<code>str</code>	Name of a pattern. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.108 RuleSchemaFormulaOutlierdetectionAlgorithmDbscan

2.108.1 Properties

Name	Type	Description	Notes
learning_period	<code>str</code>	Time period on which to detect outliers	
sensitivity	<code>**RuleSchemaFormulaOutlierdetectionAlgorithmDbscanSensitivity**</code>		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.109 PlaybookSchema

2.109.1 Properties

Name	Type	Description	Notes
description	str	Description about this playbook	[optional]
playbook_name	str	Name of the playbook. Should be of pattern [a-zA-Z][a-zA-Z0-9_]*	
rules	list[str]		[optional]
synopsis	str	Short description about this playbook	[optional]
classification	str	Classification info for this playbook	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.110 DebugArgumentsSchema

2.110.1 Properties

Name	Type	Description	Notes
arguments	object	Optional key/value pair arguments to table	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.111 DeviceSchemaOpenconfig

2.111.1 Properties

Name	Type	Description	Notes
initial_sync	bool	If true, enable initial sync packets processing	[optional]
gnmi	**DevicegroupSchemaOpenconfig-Gnmi**		[optional]
port	int	Port on which gRPC connection needs to be established	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.112 RuleSchemaField

2.112.1 Properties

Name	Type	Description	Notes
constant	<code>**RuleSchemaConstant**</code>		[optional]
description	<code>str</code>	Description about this field	[optional]
field_name	<code>str</code>	Name of the field. Should be of pattern [a-z][a-zA-Z0-9_-]*	
formula	<code>**RuleSchemaFormula**</code>		[optional]
reference	<code>**RuleSchemaReference**</code>		[optional]
sensor	<code>**list[RuleSchemaSensor]**</code>		[optional]
type	<code>str</code>		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.113 LicenseFeatureSchema

2.113.1 Properties

Name	Type	Description	Notes
feature_id	<code>int</code>	Unique ID of the licensed feature	[optional]
feature_name	<code>str</code>	Name of the licensed feature	
feature_description	<code>str</code>	Brief description of the licensed feature	
license_total	<code>int</code>	Total license count for feature	
license_remaining	<code>int</code>	Remaining license count for feature	[optional]
license_requested	<code>int</code>	Local requested license count for feature	[optional]
license_usage	<code>int</code>	License feature usage count	
max_remaining_days	<code>int</code>	Maximum remaining time of the feature's license in days	
validity_type	<code>str</code>	License validity type	
mode	<code>str</code>	License mode of operation	
compliance	<code>bool</code>	Compliance status indicating if the feature usage is in compliance or not	
end_date	<code>int</code>	Feature end date timestamp	
valid_until	<code>str</code>	Validity information of license feature	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.114 InlineResponse2008

2.114.1 Properties

Name	Type	Description	Notes
group_id	str	ID generated by system	[optional]
group_name	str	Name of the group	[optional]
group_description	str	Details of the group	[optional]
roles	**AssociatedRoleSchema**		[optional]
users	**AssociatedUserSchema**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.115 LicenseRawKeysSchema

2.115.1 Properties

Name	Type	Description	Notes
license_raw_key	**list[LicenseRawKeySchema]**		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.116 DeviceSchema

2.116.1 Properties

Name	Type	Description	Notes
authentication	**Devicegroup- SchemaAuthentica- tion**		[optional]
description	str	Description about the device	[optional]
device_id	str	Identifier for the device. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	
uuid	str	EMS: uuid of the EMS-advertised device	[optional]
flow	**De- viceSchemaFlow**		[optional]
host	str	Name or IP of the device	
i_agent	**DeviceSchema- IAgent**		[optional]
open_config	**De- viceSchemaOpen- config**		[optional]
server_monitoring	**De- viceSchemaOpen- config**		[optional]
out-bound_ssh	**De- viceSchemaOut- boundssh**		[optional]
owner	str	Owner of the device: this is a read-only attribute and should not be added to the request payload, value if added will be discarded.	[optional]
snmp	**DeviceSchemaS- nmp**		[optional]
syslog	**De- viceSchemaSys- log**		[optional]
tag- ging_profile	list[str]		[optional]
timezone	str	Timezone in the format +/-hh:mm, Example: -08:00	[optional]
system_id	str	ID which is sent in the JTI UDP messages	[optional]
use_ingest_receive_time	list[object]	Enable using ingest receive time in formulas like elapsed-time and rate-of-change	[optional]
variable	**list[DeviceSchemaVariable]**	Playbook variable configuration	[optional]
vendor	**De- viceSchemaVen- dor**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.117 CustompluginSchemaSecurityparametersUserauthentication

2.117.1 Properties

Name	Type	Description	Notes
password	str	Password	
username	str	Username	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.118 RuleSchemaWhenIncreasingatleastbyvalue

2.118.1 Properties

Name	Type	Description	Notes
all	list[object]	With this flag, result is set to True only if all the data matches the given condition	[optional]
any	list[object]	With this flag, result is set to True if any one of the data matches the condition	[optional]
field_name	str	Field name. Should match the pattern <code>\$(a-z)[a-zA-Z0-9_-]*</code>	
time_range	str	How much back in time should we look for data. Specify positive integer followed by s/m/h/d/w/y/o representing seconds/minutes/hours/days/weeks/years/offset. Eg: 2s	[optional]
value	str	Value of increase between current and last reported values	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.119 swagger_client.AuthenticationApi

All URIs are relative to `http://api-server/api/v2`

Method	HTTP request	Description
refresh_token	POST /token/	Re-issue tokens from existing token
user_login	POST /login/	User login
user_logout	POST /logout/	User logout

2.120 refresh_token

`InlineResponse2002 refresh_token(token)`

Re-issue tokens from existing token

Re-issue tokens from existing token

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.AuthenticationApi()
token = swagger_client.Token() # Token / Token object

try:
    # Re-issue tokens from existing token
    api_response = api_instance.refresh_token(token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling AuthenticationApi->refresh_token: %s\n" % e)

```

Name	Type	Description	Notes
token	**Token**	Token object	

****InlineResponse2002****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.121 user_login

InlineResponse2002 user_login(credential)

User login

User login and recive tokens

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.AuthenticationApi()
credential = swagger_client.Credential() # Credential / topics body object

try:
    # User login
    api_response = api_instance.user_login(credential)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling AuthenticationApi->user_login: %s\n" % e)

```

Name	Type	Description	Notes
credential	**Credential**	topics body object	

****InlineResponse2002****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.122 user_logout

user_logout(refresh_token)

User logout

User logout

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.AuthenticationApi()
refresh_token = swagger_client.RefreshToken() # RefreshToken | request body object

try:
    # User logout
    api_instance.user_logout(refresh_token)
except ApiException as e:
    print("Exception when calling AuthenticationApi->user_logout: %s\n" % e)
```

Name	Type	Description	Notes
refresh_token	**RefreshToken**	request body object	

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.123 RuleSchemaFunction

2.123.1 Properties

Name	Type	Description	Notes
argument	<code>**list[RuleSchemaArgument]**</code>		[optional]
description	<code>str</code>	Description of the function	[optional]
function_name	<code>str</code>	Name of the function. Should be of pattern [a-zA-Z][a-zA-Z0-9_]*	
method	<code>str</code>	Function to be called	
path	<code>str</code>	File in which function is defined. This is relative path to the data directory	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.124 DeviceSchemaSnmp

2.124.1 Properties

Name	Type	Description	Notes
port	<code>int</code>	Port on which SNMP requests need to be sent. Port 161 is used if not configured.	[optional]
v2	<code>**DeviceSchemaSnmpV2**</code>		[optional]
v3	<code>**DeviceSchemaSnmpV3**</code>		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.125 NetworkGroupSchema

2.125.1 Properties

Name	Type	Description	Notes
description	str	Description about the network group	[optional]
ingest_frequency	list[str]		[optional]
network_group_name	str	Name of the network group. Should be of pattern [a-zA-Z][a-zA-Z0-9-]*	
publish	**NetworkgroupSchemaPublish**		[optional]
logging	**NetworkgroupSchemaLogging**		[optional]
reports	list[str]		[optional]
root_cause_analysis	**DevicegroupSchemaRootcauseanalysis**		[optional]
notification	**NetworkgroupSchemaNotification**		[optional]
playbooks	list[str]		[optional]
tagging_profile	list[str]		[optional]
scheduler	**list[DevicegroupSchemaScheduler]**	List of schedulers associated with the playbook instances	[optional]
variable	**list[DevicegroupSchemaVariable]**	Playbook variable configuration	[optional]
action_scheduler	**DevicegroupSchemaActionscheduler**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.126 IngestSettingsSchema

2.126.1 Properties

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.127 swagger_client.DocumentationApi

All URIs are relative to *http://api-server/api/v2*

Method	HTTP request	Description
retrieve_defined_api	GET /	Get all All API's.
retrieve_insights_api	GET /insights/	Get all All API's.

2.128 retrieve_defined_api

retrieve_defined_api()

Get all All API's.

GET static api documentation

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DocumentationApi()

try:
    # Get all All API's.
    api_instance.retrieve_defined_api()
except ApiException as e:
    print("Exception when calling DocumentationApi->retrieve_defined_api: %s\n" % e)
```

This endpoint does not need any parameter.

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** text/html

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.129 retrieve_insights_api

retrieve_insights_api()

Get all All API's.

GET static api documentation

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DocumentationApi()

try:
    # Get all All API's.
    api_instance.retrieve_insights_api()
except ApiException as e:
    print("Exception when calling DocumentationApi->retrieve_insights_api: %s\n" % e)
```

This endpoint does not need any parameter.

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** text/html

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.130 SchedulerSchemaRepeat

2.130.1 Properties

Name	Type	Description	Notes
every	str	Repeat every	[optional]
interval	**SchedulerSchemaRepeatInterval**		[optional]
never	list[object]	Never repeat scheduling	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.131 DeviceSchemaVendorJuniper

2.131.1 Properties

Name	Type	Description	Notes
operating_system	str	Operating system of the device	
platform	str	Platform name of the device, Example: MX240	[optional]
product	str	Product category of the device, Example: MX	[optional]
release	str	Release string of the device, Example: 19.2R1	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.132 PatternSchemaConstant

2.132.1 Properties

Name	Type	Description	Notes
description	str	Constant description	[optional]
name	str	Constant field name	
type	str	Data type of constant field	[optional]
value	str	Value of the constant	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.133 UserSchemaGroups

2.133.1 Properties

Name	Type	Description	Notes
group_id	str		[optional]
group_name	str		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.134 InlineResponse200

2.134.1 Properties

Name	Type	Description	Notes
job_id	str		[optional]
job_result	str		[optional]
job_status	str		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.135 TopicSchema

2.135.1 Properties

Name	Type	Description	Notes
description	str	Description about this topic	[optional]
resource	**list[TopicSchemaResource]**		[optional]
rule	**list[RuleSchema]**		[optional]
sub_topics	list[str]		[optional]
synopsis	str	Short description about this topic	[optional]
topic_name	str	Name of the topic. Should be of pattern [a-z][a-z-](.1)/[a-z0-9-]+)	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.136 IngestsettingsSchemaIngestsettingsSyslogField

2.136.1 Properties

Name	Type	Description	Notes
description	str	Field description	[optional]
_from	str	Field from the structured syslog which supplies the value	[optional]
name	str	Field name	
type	str		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.137 DeviceGroupSchema

2.137.1 Properties

Name	Type	Description	Notes
authentication	**Devicegroup-SchemaAuthentication**		[optional]
edge	str	JFM: edge this device group belongs to. This should be of the format <organization-name>.<site-name>.<edge-name>;	[optional]
action_scheduler	**Devicegroup-SchemaActionscheduler**		[optional]
description	str	Description about the device group	[optional]
device_group_name	str	Name of the group. Should be of pattern [a-zA-Z][a-zA-Z0-9-]*	
devices	list[str]		[optional]
logging	**Devicegroup-SchemaLogging**		[optional]
native_gpb	**DevicegroupSchemaNativegpb**		[optional]
flow	**Devicegroup-SchemaFlow**		[optional]
ingest_frequency	list[str]		[optional]
raw_data	**Devicegroup-SchemaRawdata**		[optional]
field_data	**Devicegroup-SchemaFielddata**		[optional]
notification	**DevicegroupSchemaNotification**		[optional]
open_config	**Devicegroup-SchemaOpenconfig**		[optional]
outbound_ssh	**Devicegroup-SchemaOutboundssh**		[optional]
playbooks	list[str]		[optional]
publish	**Devicegroup-SchemaPublish**		[optional]
reports	list[str]		[optional]
retention_policy	str	Name of the retention policy to be applied	[optional]
root_cause_analysis	**Devicegroup-SchemaRootcauseanalysis**		[optional]
scheduler	**list[DevicegroupSchemaScheduler]**	List of schedulers associated with the playbook instances	[optional]
variable	**list[DevicegroupSchemaPlaybookvariable]**	Playbook variable configuration	[optional]
snmp	**Devicegroup-SchemaSnmp**		[optional]
syslog	**Devicegroup-		[op-

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.138 swagger_client.DefaultApi

All URIs are relative to *http://api-server/api/v2*

Method	HTTP request
backup_grafana	GET /grafana/backup/
backup_helper_files	GET /config/files/helper-files/backup/
create_dynamic_tagging_by_key	POST /config/dynamic-tagging/key/
create_files_certificates_by_file_name	POST /config/files/certificates/{file_name}
create_files_helper_files_by_file_name	POST /config/files/helper-files/{file_name}
create_healthbot_deployment_deployment_by_id	POST /config/deployment/
create_healthbot_dynamic_tagging	POST /config/dynamic-tagging/keys/
create_healthbot_ingest_byoi_custom_plugin_by_id	POST /config/ingest/byoi/custom-plugin/{
create_healthbot_ingest_byoi_default_plugin_tlive_kafka_by_id	POST /config/ingest/byoi/default-plugin/tl
create_healthbot_ingest_byoi_ingest_mapping_by_id	POST /config/ingest/byoi/ingest-mapping/
create_healthbot_ingest_frequency_profile_by_id	POST /config/ingest/frequency-profile/{na
create_healthbot_ingest_outbound_ssh	POST /config/ingest/outbound-ssh/
create_healthbot_ingest_settings_byoi_custom_plugin_by_id	POST /config/ingest-settings/byoi/custom-
create_healthbot_ingest_settings_byoi_default_plugin_tlive_kafka_by_id	POST /config/ingest-settings/byoi/default-
create_healthbot_ingest_settings_byoi_ingest_mapping_by_id	POST /config/ingest-settings/byoi/ingest-r
create_healthbot_ingest_settings_frequency_profile_by_id	POST /config/ingest-settings/frequency-pr
create_healthbot_ingest_settings_tagging_profile_by_id	POST /config/ingest-settings/data-enrichm
create_healthbot_ingest_settings_tagging_profiles	POST /config/ingest-settings/data-enrichm
create_healthbot_ingest_sflow	POST /config/ingest/sflow/
create_healthbot_ingest_sflow_counter_record_by_id	POST /config/ingest/sflow/counter-record/
create_healthbot_ingest_sflow_flow_record_by_id	POST /config/ingest/sflow/flow-record/{re
create_healthbot_ingest_sflow_protocol_by_id	POST /config/ingest/sflow/protocol/{proto
create_healthbot_ingest_sflow_sample_by_id	POST /config/ingest/sflow/sample/{sample
create_healthbot_ingest_snmp_notification	POST /config/ingest/snmp-notification/
create_healthbot_ingest_snmp_notification_v3_usm_user_by_id	POST /config/ingest/snmp-notification/v3/
create_healthbot_ingest_syslog_header_pattern_by_id	POST /config/ingest/syslog/header-pattern
create_healthbot_ingest_tagging_profile_by_id	POST /config/ingest/data-enrichment/tagg
create_healthbot_ingest_tagging_profiles	POST /config/ingest/data-enrichment/tagg
create_healthbot_organization_organization_by_id	POST /config/organization/{organization_
create_healthbot_profile_rollup_summarization_field_profile_field_profile_by_id	POST /config/profile/rollup-summarization
create_healthbot_system_time_series_database_time_series_database_by_id	POST /config/system/tsdb/
create_healthbot_system_trigger_action	POST /config/system/trigger_action/
create_iceberg_ingest	POST /config/ingest/
create_iceberg_ingest_flow	POST /config/ingest/flow/
create_iceberg_ingest_flow_template_by_id	POST /config/ingest/flow/template/{name
create_iceberg_ingest_native_gpb	POST /config/ingest/native-gpb/
create_iceberg_ingest_settings	POST /config/ingest-settings/
create_iceberg_ingest_settings_flow	POST /config/ingest-settings/flow/
create_iceberg_ingest_settings_flow_template_by_id	POST /config/ingest-settings/flow/templat
create_iceberg_ingest_settings_syslog	POST /config/ingest-settings/syslog/
create_iceberg_ingest_settings_syslog_pattern_by_id	POST /config/ingest-settings/syslog/patter
create_iceberg_ingest_settings_syslog_pattern_set_by_id	POST /config/ingest-settings/syslog/patter
create_iceberg_ingest_syslog	POST /config/ingest/syslog/

Table 1 – continued from previ

Method	HTTP request
<code>**create_iceberg_ingest_syslog_pattern_by_id**</code>	POST /config/ingest/syslog/pattern/{name}
<code>**create_iceberg_ingest_syslog_pattern_set_by_id**</code>	POST /config/ingest/syslog/pattern-set/{name}
<code>**create_iceberg_profile_data_summarization_raw_by_id**</code>	POST /config/profile/data-summarization/{name}
<code>**create_iceberg_profile_security_ca_profile_by_id**</code>	POST /config/profile/security/ca-profile/{name}
<code>**create_iceberg_profile_security_local_certificate_by_id**</code>	POST /config/profile/security/local-certificate/{name}
<code>**create_iceberg_profile_security_ssh_key_profile_by_id**</code>	POST /config/profile/security/ssh-key-profile/{name}
<code>**create_iceberg_profiles**</code>	POST /config/profiles/
<code>**delete_dynamic_tagging_by_key**</code>	DELETE /config/dynamic-tagging/key/{key}
<code>**delete_files_certificates_by_file_name**</code>	DELETE /config/files/certificates/{file_name}
<code>**delete_files_helper_files_by_file_name**</code>	DELETE /config/files/helper-files/{file_name}
<code>**delete_healthbot_deployment_deployment_by_id**</code>	DELETE /config/deployment/{id}
<code>**delete_healthbot_dynamic_tagging**</code>	DELETE /config/dynamic-tagging/keys/
<code>**delete_healthbot_ingest_byoi_custom_plugin_by_id**</code>	DELETE /config/ingest/byoi/custom-plugin/{id}
<code>**delete_healthbot_ingest_byoi_default_plugin_tlive_kafka_by_id**</code>	DELETE /config/ingest/byoi/default-plugin/{id}
<code>**delete_healthbot_ingest_byoi_ingest_mapping_by_id**</code>	DELETE /config/ingest/byoi/ingest-mapping/{id}
<code>**delete_healthbot_ingest_frequency_profile_by_id**</code>	DELETE /config/ingest/frequency-profile/{id}
<code>**delete_healthbot_ingest_outbound_ssh**</code>	DELETE /config/ingest/outbound-ssh/
<code>**delete_healthbot_ingest_settings_byoi_custom_plugin_by_id**</code>	DELETE /config/ingest-settings/byoi/custom-plugin/{id}
<code>**delete_healthbot_ingest_settings_byoi_default_plugin_tlive_kafka_by_id**</code>	DELETE /config/ingest-settings/byoi/default-plugin/{id}
<code>**delete_healthbot_ingest_settings_byoi_ingest_mapping_by_id**</code>	DELETE /config/ingest-settings/byoi/ingest-mapping/{id}
<code>**delete_healthbot_ingest_settings_frequency_profile_by_id**</code>	DELETE /config/ingest-settings/frequency-profile/{id}
<code>**delete_healthbot_ingest_settings_tagging_profile_by_id**</code>	DELETE /config/ingest-settings/data-enrichment/{id}
<code>**delete_healthbot_ingest_settings_tagging_profiles**</code>	DELETE /config/ingest-settings/data-enrichment/
<code>**delete_healthbot_ingest_sflow**</code>	DELETE /config/ingest/sflow/
<code>**delete_healthbot_ingest_sflow_counter_record_by_id**</code>	DELETE /config/ingest/sflow/counter-record/{id}
<code>**delete_healthbot_ingest_sflow_flow_record_by_id**</code>	DELETE /config/ingest/sflow/flow-record/{id}
<code>**delete_healthbot_ingest_sflow_protocol_by_id**</code>	DELETE /config/ingest/sflow/protocol/{id}
<code>**delete_healthbot_ingest_sflow_sample_by_id**</code>	DELETE /config/ingest/sflow/sample/{id}
<code>**delete_healthbot_ingest_snmp_notification**</code>	DELETE /config/ingest/snmp-notification/
<code>**delete_healthbot_ingest_snmp_notification_v3_usm_user_by_id**</code>	DELETE /config/ingest/snmp-notification/{id}
<code>**delete_healthbot_ingest_syslog_header_pattern_by_id**</code>	DELETE /config/ingest/syslog/header-pattern/{id}
<code>**delete_healthbot_ingest_tagging_profile_by_id**</code>	DELETE /config/ingest/data-enrichment/{id}
<code>**delete_healthbot_ingest_tagging_profiles**</code>	DELETE /config/ingest/data-enrichment/
<code>**delete_healthbot_organization_organization_by_id**</code>	DELETE /config/organization/{organization_id}
<code>**delete_healthbot_profile_rollup_summarization_field_profile_field_profile_by_id**</code>	DELETE /config/profile/rollup-summarization/{id}
<code>**delete_healthbot_system_time_series_database_time_series_database_by_id**</code>	DELETE /config/system/tsdb/{id}
<code>**delete_healthbot_system_trigger_action**</code>	DELETE /config/system/trigger_action/
<code>**delete_iceberg_ingest**</code>	DELETE /config/ingest/
<code>**delete_iceberg_ingest_flow**</code>	DELETE /config/ingest/flow/
<code>**delete_iceberg_ingest_flow_template_by_id**</code>	DELETE /config/ingest/flow/template/{id}
<code>**delete_iceberg_ingest_native_gpb**</code>	DELETE /config/ingest/native-gpb/
<code>**delete_iceberg_ingest_settings**</code>	DELETE /config/ingest-settings/
<code>**delete_iceberg_ingest_settings_flow**</code>	DELETE /config/ingest-settings/flow/
<code>**delete_iceberg_ingest_settings_flow_template_by_id**</code>	DELETE /config/ingest-settings/flow/template/{id}
<code>**delete_iceberg_ingest_settings_syslog**</code>	DELETE /config/ingest-settings/syslog/
<code>**delete_iceberg_ingest_settings_syslog_pattern_by_id**</code>	DELETE /config/ingest-settings/syslog/pattern/{id}
<code>**delete_iceberg_ingest_settings_syslog_pattern_set_by_id**</code>	DELETE /config/ingest-settings/syslog/pattern-set/{id}
<code>**delete_iceberg_ingest_syslog**</code>	DELETE /config/ingest/syslog/
<code>**delete_iceberg_ingest_syslog_pattern_by_id**</code>	DELETE /config/ingest/syslog/pattern/{name}

Table 1 – continued from previ

Method	HTTP request
<code>**delete_iceberg_ingest_syslog_pattern_set_by_id**</code>	DELETE /config/ingest/syslog/pattern-set/
<code>**delete_iceberg_profile_data_summarization_raw_by_id**</code>	DELETE /config/profile/data-summarization/
<code>**delete_iceberg_profile_security_ca_profile_by_id**</code>	DELETE /config/profile/security/ca-profile/
<code>**delete_iceberg_profile_security_local_certificate_by_id**</code>	DELETE /config/profile/security/local-certificate/
<code>**delete_iceberg_profile_security_ssh_key_profile_by_id**</code>	DELETE /config/profile/security/ssh-key-profile/
<code>**delete_iceberg_profiles**</code>	DELETE /config/profiles/
<code>**get_dynamic_tagging_by_key**</code>	GET /config/dynamic-tagging/key/
<code>**get_fields_from_xpath**</code>	GET /field-capture/
<code>**grafana_login**</code>	GET /grafana/login/
<code>**inspect_command_rpc_table_on_device**</code>	POST /inspect/command-rpc/table/
<code>**restore_grafana**</code>	POST /grafana/restore/
<code>**restore_helper_files**</code>	POST /config/files/helper-files/backup/
<code>**retrieve_configuration_jobs**</code>	GET /config/configuration/jobs/
<code>**retrieve_data_database_table**</code>	GET /data/database/table/
<code>**retrieve_data_database_table_column_by_table_name**</code>	GET /data/database/table/column/
<code>**retrieve_data_database_tags_by_table_name**</code>	GET /data/database/table/tags/
<code>**retrieve_debug_jobs**</code>	GET /debug/jobs/
<code>**retrieve_event**</code>	GET /event/
<code>**retrieve_event_by_event_name**</code>	GET /event/{event_name}/
<code>**retrieve_event_by_event_name_device_group**</code>	GET /event/device-group/{event_name}/
<code>**retrieve_event_by_event_name_network_group**</code>	GET /event/network-group/{event_name}/
<code>**retrieve_event_device_group**</code>	GET /event/device-group/
<code>**retrieve_event_network_group**</code>	GET /event/network-group/
<code>**retrieve_events**</code>	GET /events/
<code>**retrieve_files_certificates_by_file_name**</code>	GET /config/files/certificates/{file_name}/
<code>**retrieve_files_helper_files**</code>	GET /config/files/helper-files/
<code>**retrieve_files_helper_files_by_file_name**</code>	GET /config/files/helper-files/{file_name}/
<code>**retrieve_health_all**</code>	GET /health/
<code>**retrieve_health_tree_by_device_group**</code>	GET /health-tree/device-group/{device_group}/
<code>**retrieve_health_tree_by_id**</code>	GET /health-tree/{device_id}/
<code>**retrieve_health_tree_by_network_group**</code>	GET /health-tree/network-group/{network_group}/
<code>**retrieve_healthbot_deployment_deployment**</code>	GET /config/deployment/
<code>**retrieve_healthbot_device_details_by_uuids**</code>	POST /deployed-device-details/
<code>**retrieve_healthbot_dynamic_tagging**</code>	GET /config/dynamic-tagging/keys/
<code>**retrieve_healthbot_ingest_byoi_custom_plugin_by_id**</code>	GET /config/ingest/byoi/custom-plugin/{plugin_id}/
<code>**retrieve_healthbot_ingest_byoi_custom_plugins**</code>	GET /config/ingest/byoi/custom-plugins/
<code>**retrieve_healthbot_ingest_byoi_default_plugin_tlive_kafka_by_id**</code>	GET /config/ingest/byoi/default-plugin/tlive-kafka/{plugin_id}/
<code>**retrieve_healthbot_ingest_byoi_default_plugin_tlive_kafkas**</code>	GET /config/ingest/byoi/default-plugin/tlive-kafkas/
<code>**retrieve_healthbot_ingest_byoi_ingest_mapping_by_id**</code>	GET /config/ingest/byoi/ingest-mapping/{mapping_id}/
<code>**retrieve_healthbot_ingest_byoi_ingest_mappings**</code>	GET /config/ingest/byoi/ingest-mappings/
<code>**retrieve_healthbot_ingest_frequency_profile**</code>	GET /config/ingest/frequency-profiles/
<code>**retrieve_healthbot_ingest_frequency_profile_by_id**</code>	GET /config/ingest/frequency-profile/{profile_id}/
<code>**retrieve_healthbot_ingest_outbound_ssh**</code>	GET /config/ingest/outbound-ssh/
<code>**retrieve_healthbot_ingest_settings_byoi_custom_plugin_by_id**</code>	GET /config/ingest-settings/byoi/custom-plugin/{plugin_id}/
<code>**retrieve_healthbot_ingest_settings_byoi_custom_plugins**</code>	GET /config/ingest-settings/byoi/custom-plugins/
<code>**retrieve_healthbot_ingest_settings_byoi_default_plugin_tlive_kafka_by_id**</code>	GET /config/ingest-settings/byoi/default-plugin/tlive-kafka/{plugin_id}/
<code>**retrieve_healthbot_ingest_settings_byoi_default_plugin_tlive_kafkas**</code>	GET /config/ingest-settings/byoi/default-plugin/tlive-kafkas/
<code>**retrieve_healthbot_ingest_settings_byoi_ingest_mapping_by_id**</code>	GET /config/ingest-settings/byoi/ingest-mapping/{mapping_id}/
<code>**retrieve_healthbot_ingest_settings_byoi_ingest_mappings**</code>	GET /config/ingest-settings/byoi/ingest-mappings/

Table 1 – continued from previ

Method	HTTP request
retrieve_healthbot_ingest_settings_frequency_profile	GET /config/ingest-settings/frequency-pro
retrieve_healthbot_ingest_settings_frequency_profile_by_id	GET /config/ingest-settings/frequency-pro
retrieve_healthbot_ingest_settings_tagging_profile_by_id	GET /config/ingest-settings/data-enrichme
retrieve_healthbot_ingest_settings_tagging_profiles	GET /config/ingest-settings/data-enrichme
retrieve_healthbot_ingest_sflow	GET /config/ingest/sflow/
retrieve_healthbot_ingest_sflow_counter_record_by_id	GET /config/ingest/sflow/counter-record/{
retrieve_healthbot_ingest_sflow_flow_record_by_id	GET /config/ingest/sflow/flow-record/{rec
retrieve_healthbot_ingest_sflow_protocol_by_id	GET /config/ingest/sflow/protocol/{protoc
retrieve_healthbot_ingest_sflow_sample_by_id	GET /config/ingest/sflow/sample/{sample
retrieve_healthbot_ingest_snmp_notification	GET /config/ingest/snmp-notification/
retrieve_healthbot_ingest_snmp_notification_v3_usm_user_by_id	GET /config/ingest/snmp-notification/v3/u
retrieve_healthbot_ingest_snmp_notification_v3_usm_usernames	GET /config/ingest/snmp-notification/v3/u
retrieve_healthbot_ingest_snmp_notification_v3_usm_users	GET /config/ingest/snmp-notification/v3/u
retrieve_healthbot_ingest_syslog_header_pattern_by_id	GET /config/ingest/syslog/header-pattern/
retrieve_healthbot_ingest_syslog_header_pattern_ids	GET /config/ingest/syslog/header-pattern/
retrieve_healthbot_ingest_syslog_header_patterns	GET /config/ingest/syslog/header-patterns
retrieve_healthbot_ingest_tagging_profile_by_id	GET /config/ingest/data-enrichment/taggin
retrieve_healthbot_ingest_tagging_profiles	GET /config/ingest/data-enrichment/taggin
retrieve_healthbot_organization_organization	GET /config/organization/
retrieve_healthbot_organization_organization_by_id	GET /config/organization/{organization_n
retrieve_healthbot_profile_rollup_summarization_field_profile_field_profile_by_id	GET /config/profile/rollup-summarization/
retrieve_healthbot_profile_rollup_summarization_field_profile_profile	GET /config/profile/rollup-summarization/
retrieve_healthbot_system_time_series_database_time_series_database	GET /config/system/tsdb/
retrieve_healthbot_system_trigger_action	GET /config/system/trigger_action/
retrieve_healthbot_topic_resource_resource	GET /config/topic/{topic_name}/resource
retrieve_healthbot_topic_resource_resource_by_id	GET /config/topic/{topic_name}/resource
retrieve_iceberg_ingest	GET /config/ingest/
retrieve_iceberg_ingest_flow	GET /config/ingest/flow/
retrieve_iceberg_ingest_flow_template_by_id	GET /config/ingest/flow/template/{name}
retrieve_iceberg_ingest_flow_template_ids	GET /config/ingest/flow/template/
retrieve_iceberg_ingest_native_gpb	GET /config/ingest/native-gpb/
retrieve_iceberg_ingest_settings	GET /config/ingest-settings/
retrieve_iceberg_ingest_settings_flow	GET /config/ingest-settings/flow/
retrieve_iceberg_ingest_settings_flow_template_by_id	GET /config/ingest-settings/flow/template/
retrieve_iceberg_ingest_settings_flow_template_ids	GET /config/ingest-settings/flow/template/
retrieve_iceberg_ingest_settings_syslog	GET /config/ingest-settings/syslog/
retrieve_iceberg_ingest_settings_syslog_pattern_by_id	GET /config/ingest-settings/syslog/pattern
retrieve_iceberg_ingest_settings_syslog_pattern_ids	GET /config/ingest-settings/syslog/pattern
retrieve_iceberg_ingest_settings_syslog_pattern_set_by_id	GET /config/ingest-settings/syslog/pattern
retrieve_iceberg_ingest_settings_syslog_pattern_set_ids	GET /config/ingest-settings/syslog/pattern
retrieve_iceberg_ingest_settings_syslog_pattern_sets	GET /config/ingest-settings/syslog/pattern
retrieve_iceberg_ingest_settings_syslog_patterns	GET /config/ingest-settings/syslog/pattern
retrieve_iceberg_ingest_syslog	GET /config/ingest/syslog/
retrieve_iceberg_ingest_syslog_pattern_by_id	GET /config/ingest/syslog/pattern/{name}
retrieve_iceberg_ingest_syslog_pattern_ids	GET /config/ingest/syslog/pattern/
retrieve_iceberg_ingest_syslog_pattern_set_by_id	GET /config/ingest/syslog/pattern-set/{na
retrieve_iceberg_ingest_syslog_pattern_set_ids	GET /config/ingest/syslog/pattern-set/
retrieve_iceberg_ingest_syslog_pattern_sets	GET /config/ingest/syslog/pattern-sets/
retrieve_iceberg_ingest_syslog_patterns	GET /config/ingest/syslog/patterns/

Table 1 – continued from previ

Method	HTTP request
retrieve_iceberg_profile_data_summarization_raw_by_id	GET /config/profile/data-summarization/ra
retrieve_iceberg_profile_data_summarizations_raw	GET /config/profile/data-summarizations/
retrieve_iceberg_profile_security_ca_profile_by_id	GET /config/profile/security/ca-profile/{na
retrieve_iceberg_profile_security_ca_profiles	GET /config/profile/security/ca-profiles/
retrieve_iceberg_profile_security_local_certificate_by_id	GET /config/profile/security/local-certifica
retrieve_iceberg_profile_security_local_certificates	GET /config/profile/security/local-certifica
retrieve_iceberg_profile_security_ssh_key_profile_by_id	GET /config/profile/security/ssh-key-profi
retrieve_iceberg_profile_security_ssh_key_profiles	GET /config/profile/security/ssh-key-profi
retrieve_iceberg_profiles	GET /config/profiles/
retrieve_sensors	GET /config/sensors/
update_dynamic_tagging_by_key	PUT /config/dynamic-tagging/key/
update_healthbot_deployment_deployment_by_id	PUT /config/deployment/
update_healthbot_dynamic_tagging	PUT /config/dynamic-tagging/keys/
update_healthbot_ingest_byoi_custom_plugin_by_id	PUT /config/ingest/byoi/custom-plugin/{n
update_healthbot_ingest_byoi_default_plugin_tlive_kafka_by_id	PUT /config/ingest/byoi/default-plugin/tliv
update_healthbot_ingest_byoi_ingest_mapping_by_id	PUT /config/ingest/byoi/ingest-mapping/{
update_healthbot_ingest_frequency_profile_by_id	PUT /config/ingest/frequency-profile/{nam
update_healthbot_ingest_outbound_ssh	PUT /config/ingest/outbound-ssh/
update_healthbot_ingest_settings_byoi_custom_plugin_by_id	PUT /config/ingest-settings/byoi/custom-p
update_healthbot_ingest_settings_byoi_default_plugin_tlive_kafka_by_id	PUT /config/ingest-settings/byoi/default-p
update_healthbot_ingest_settings_byoi_ingest_mapping_by_id	PUT /config/ingest-settings/byoi/ingest-ma
update_healthbot_ingest_settings_frequency_profile_by_id	PUT /config/ingest-settings/frequency-pro
update_healthbot_ingest_settings_tagging_profile_by_id	PUT /config/ingest-settings/data-enrichme
update_healthbot_ingest_settings_tagging_profiles	PUT /config/ingest-settings/data-enrichme
update_healthbot_ingest_sflow	PUT /config/ingest/sflow/
update_healthbot_ingest_sflow_counter_record_by_id	PUT /config/ingest/sflow/counter-record/{
update_healthbot_ingest_sflow_flow_record_by_id	PUT /config/ingest/sflow/flow-record/{rec
update_healthbot_ingest_sflow_protocol_by_id	PUT /config/ingest/sflow/protocol/{protoc
update_healthbot_ingest_sflow_sample_by_id	PUT /config/ingest/sflow/sample/{sample_
update_healthbot_ingest_snmp_notification	PUT /config/ingest/snmp-notification/
update_healthbot_ingest_snmp_notification_v3_usm_user_by_id	PUT /config/ingest/snmp-notification/v3/u
update_healthbot_ingest_syslog_header_pattern_by_id	PUT /config/ingest/syslog/header-pattern/{
update_healthbot_ingest_tagging_profile_by_id	PUT /config/ingest/data-enrichment/taggin
update_healthbot_ingest_tagging_profiles	PUT /config/ingest/data-enrichment/taggin
update_healthbot_organization_organization_by_id	PUT /config/organization/{organization_n
update_healthbot_profile_rollup_summarization_field_profile_field_profile_by_id	PUT /config/profile/rollup-summarization/
update_healthbot_system_time_series_database_time_series_database_by_id	PUT /config/system/tsdb/
update_healthbot_system_trigger_action	PUT /config/system/trigger_action/
update_iceberg_ingest	PUT /config/ingest/
update_iceberg_ingest_flow	PUT /config/ingest/flow/
update_iceberg_ingest_flow_template_by_id	PUT /config/ingest/flow/template/{name}/
update_iceberg_ingest_native_gpb	PUT /config/ingest/native-gpb/
update_iceberg_ingest_settings	PUT /config/ingest-settings/
update_iceberg_ingest_settings_flow	PUT /config/ingest-settings/flow/
update_iceberg_ingest_settings_flow_template_by_id	PUT /config/ingest-settings/flow/template/
update_iceberg_ingest_settings_syslog	PUT /config/ingest-settings/syslog/
update_iceberg_ingest_settings_syslog_pattern_by_id	PUT /config/ingest-settings/syslog/pattern
update_iceberg_ingest_settings_syslog_pattern_set_by_id	PUT /config/ingest-settings/syslog/pattern
update_iceberg_ingest_syslog	PUT /config/ingest/syslog/

Table 1 – continued from previ

Method	HTTP request
<code>**update_iceberg_ingest_syslog_pattern_by_id**</code>	PUT /config/ingest/syslog/pattern/{ name }
<code>**update_iceberg_ingest_syslog_pattern_set_by_id**</code>	PUT /config/ingest/syslog/pattern-set/{ name }
<code>**update_iceberg_profile_data_summarization_raw_by_id**</code>	PUT /config/profile/data-summarization/raw/{ name }
<code>**update_iceberg_profile_security_ca_profile_by_id**</code>	PUT /config/profile/security/ca-profile/{ name }
<code>**update_iceberg_profile_security_local_certificate_by_id**</code>	PUT /config/profile/security/local-certificate/{ name }
<code>**update_iceberg_profile_security_ssh_key_profile_by_id**</code>	PUT /config/profile/security/ssh-key-profile/{ name }
<code>**update_iceberg_profiles**</code>	PUT /config/profiles/

2.139 backup_grafana

file backup_grafana(x_iam_token=x_iam_token)

Take backup of Grafana configuration

Take backup of Grafana configuration

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Take backup of Grafana configuration
    api_response = api_instance.backup_grafana(x_iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->backup_grafana: %s\n" % e)
```

Name	Type	Description	Notes
<code>x_iam_token</code>	<code>str</code>	authentication header object	[optional]

`**file**`

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.140 backup_helper_files

file backup_helper_files(x_iam_token=x_iam_token)

Download the tar file containing all helper files.

Download helper files tar file, which will include the config and input directory.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Download the tar file containing all helper files.
    api_response = api_instance.backup_helper_files(x_iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->backup_helper_files: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

****file****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.141 create_dynamic_tagging_by_key

create_dynamic_tagging_by_key(key_name, dynamic_tagging_obj, x_iam_token=x_iam_token)

Creates Dynamic-tagging key-value

Creates a key in Dynamic-tagging

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
key_name = 'key_name_example' # str | Dynamic-tagging Key
dynamic_tagging_obj = swagger_client.DynamicTaggingSchemaObject() # DynamicTaggingSchemaObject | Dynamic-tagging object containing key-value pair
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Creates Dynamic-tagging key-value
    api_instance.create_dynamic_tagging_by_key(key_name, dynamic_tagging_obj, x_iam_token=x_iam_token)

```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling DefaultApi->create_dynamic_tagging_by_key: %s\n" %
↳e)
```

Name	Type	Description	Notes
key_name	str	Dynamic-tagging Key	
dynamic_tagging_obj	**DynamicTaggingSchemaObject**	Dynamic-tagging object containing key-value pair	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.142 create_files_certificates_by_file_name

```
create_files_certificates_by_file_name(up_file, file_name, x_iam_token=x_iam_token, password=password, certificate_type=certificate_type)
```

Upload a certificate file.

Upload the specified certificate-file.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
up_file = '/path/to/file.txt' # file | File content
file_name = 'file_name_example' # str | File name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
password = 'password_example' # str | password (optional)
certificate_type = 'certificate_type_example' # str | Certificate type (optional)

try:
    # Upload a certificate file.
    api_instance.create_files_certificates_by_file_name(up_file, file_name, x_iam_
↳token=x_iam_token, password=password, certificate_type=certificate_type)
except ApiException as e:
    print("Exception when calling DefaultApi->create_files_certificates_by_file_name:
↳%s\n" % e)
```

Name	Type	Description	Notes
up_file	file	File content	
file_name	str	File name	
x_iam_token	str	authentication header object	[optional]
password	str	password	[optional]
certificate_type	str	Certificate type	[optional]

void (empty response body)

No authorization required

- **Content-Type:** multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.143 create_files_helper_files_by_file_name

create_files_helper_files_by_file_name(up_file, file_name, x_iam_token=x_iam_token)

Upload a helper-file.

Upload the specified helper-file.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
up_file = '/path/to/file.txt' # file | File content
file_name = 'file_name_example' # str | File name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Upload a helper-file.
    api_instance.create_files_helper_files_by_file_name(up_file, file_name, x_iam_
↪token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_files_helper_files_by_file_name:
↪%s\n" % e)
```

Name	Type	Description	Notes
up_file	file	File content	
file_name	str	File name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** multipart/form-data

- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.144 create_healthbot_deployment_deployment_by_id

create_healthbot_deployment_deployment_by_id(deployment, x_iam_token=x_iam_token)

Create deployment by ID

Create operation of resource: deployment

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
deployment = swagger_client.DeploymentSchema() # DeploymentSchema | deployment body_
↳object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create deployment by ID
    api_instance.create_healthbot_deployment_deployment_by_id(deployment, x_iam_
↳token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_deployment_deployment_
↳by_id: %s\n" % e)
```

Name	Type	Description	Notes
deployment	**DeploymentSchema**	deployment body object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.145 create_healthbot_dynamic_tagging

list[str] create_healthbot_dynamic_tagging(dynamic_tagging, x_iam_token=x_iam_token)

Create dynamic-tagging by ID

Create operation of resource: dynamic-tagging

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
dynamic_tagging = swagger_client.DynamicTaggingsSchemaObject() #_
↳DynamicTaggingsSchemaObject | dynamic_taggingbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create dynamic-tagging by ID
    api_response = api_instance.create_healthbot_dynamic_tagging(dynamic_tagging, x_
↳iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_dynamic_tagging: %s\n"
↳ % e)

```

Name	Type	Description	Notes
dynamic_tagging	**DynamicTaggingsSchemaObject**	dynamic_taggingbody object	
x_iam_token	str	authentication header object	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.146 create_healthbot_ingest_byoi_custom_plugin_by_id

create_healthbot_ingest_byoi_custom_plugin_by_id(name, custom_plugin, x_iam_token=x_iam_token)

Create custom-plugin by ID

Create operation of resource: custom-plugin

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of custom-plugin
custom_plugin = swagger_client.CustomPluginSchema() # CustomPluginSchema | custom_
↳pluginbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

```

(continues on next page)

(continued from previous page)

```

try:
    # Create custom-plugin by ID
    api_instance.create_healthbot_ingest_byoi_custom_plugin_by_id(name, custom_plugin,
↳ x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_byoi_custom_
↳ plugin_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of custom-plugin	
custom_plugin	**CustomPluginSchema**	custom_pluginbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.147 create_healthbot_ingest_byoi_default_plugin_tlive_kafka_by_id

```
create_healthbot_ingest_byoi_default_plugin_tlive_kafka_by_id(name, tlive_kafka,
x_iam_token=x_iam_token)
```

Create tlive-kafka-oc by ID

Add/Merge a tlive-kafka-oc configuration.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of tlive-kafka-oc
tlive_kafka = swagger_client.TliveKafkaOcSchema() # TliveKafkaOcSchema | tlive_
↳ kafkabody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create tlive-kafka-oc by ID
    api_instance.create_healthbot_ingest_byoi_default_plugin_tlive_kafka_by_id(name,
↳ tlive_kafka, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_byoi_default_
↳ plugin_tlive_kafka_by_id: %s\n" % e)

```


Name	Type	Description	Notes
name	str	Name of tlive-kafka-oc	
tlive_kafka	**TliveKafkaOcSchema**	tlive_kafkabody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.148 create_healthbot_ingest_byoi_ingest_mapping_by_id

```
create_healthbot_ingest_byoi_ingest_mapping_by_id(name, ingest_mapping,
x_iam_token=x_iam_token)
```

Create ingest-mapping by ID

Create ingest-mapping by name

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of ingest-mapping
ingest_mapping = swagger_client.IngestMappingSchema() # IngestMappingSchema | ingest_
↳mappingbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create ingest-mapping by ID
    api_instance.create_healthbot_ingest_byoi_ingest_mapping_by_id(name, ingest_
↳mapping, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_byoi_ingest_
↳mapping_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of ingest-mapping	
ingest_mapping	**IngestMappingSchema**	ingest_mappingbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json

- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.149 create_healthbot_ingest_frequency_profile_by_id

`create_healthbot_ingest_frequency_profile_by_id(name, frequency_profile, x_iam_token=x_iam_token)`

Create frequency-profile by ID

Create operation of resource: frequency-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | ID of name
frequency_profile = swagger_client.FrequencyProfileSchema() # FrequencyProfileSchema_
↪ | frequency_profilebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create frequency-profile by ID
    api_instance.create_healthbot_ingest_frequency_profile_by_id(name, frequency_
↪ profile, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_frequency_
↪ profile_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	ID of name	
frequency_profile	**FrequencyProfileSchema**	frequency_profilebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.150 create_healthbot_ingest_outbound_ssh

`create_healthbot_ingest_outbound_ssh(outbound_ssh, x_iam_token=x_iam_token)`

Create outbound-ssh by ID

Create operation of resource: outbound-ssh

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
outbound_ssh = swagger_client.OutboundSshSchema() # OutboundSshSchema | outbound_ssh_
↳body object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create outbound-ssh by ID
    api_instance.create_healthbot_ingest_outbound_ssh(outbound_ssh, x_iam_token=x_iam_
↳token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_outbound_ssh:
↳%s\n" % e)

```

Name	Type	Description	Notes
outbound_ssh	**OutboundSshSchema**	outbound_ssh body object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.151 create_healthbot_ingest_settings_byoi_custom_plugin_by_id

```

create_healthbot_ingest_settings_byoi_custom_plugin_by_id(name, custom_plugin,
x_iam_token=x_iam_token)

```

Create custom-plugin by ID

Create operation of resource: custom-plugin

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of custom-plugin
custom_plugin = swagger_client.CustomPluginSchema() # CustomPluginSchema | custom_
↳pluginbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

```

(continues on next page)

(continued from previous page)

```

try:
    # Create custom-plugin by ID
    api_instance.create_healthbot_ingest_settings_byoi_custom_plugin_by_id(name,
↳ custom_plugin, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_settings_byoi_
↳ custom_plugin_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of custom-plugin	
custom_plugin	**CustomPluginSchema**	custom_pluginbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.152 create_healthbot_ingest_settings_byoi_default_plugin_tlive_kafka_by_id

```

create_healthbot_ingest_settings_byoi_default_plugin_tlive_kafka_by_id(name,
x_iam_token=x_iam_token)

```

Create tlive-kafka-oc by ID

Add/Merge a tlive-kafka-oc configuration.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of tlive-kafka-oc
tlive_kafka = swagger_client.TliveKafkaOcSchema() # TliveKafkaOcSchema | tlive_
↳ kafkabody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create tlive-kafka-oc by ID
    api_instance.create_healthbot_ingest_settings_byoi_default_plugin_tlive_kafka_by_
↳ id(name, tlive_kafka, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_settings_byoi_
↳ default_plugin_tlive_kafka_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of tlive-kafka-oc	
tlive_kafka	**TliveKafkaOcSchema**	tlive_kafkabody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.153 create_healthbot_ingest_settings_byoi_ingest_mapping_by_id

```
create_healthbot_ingest_settings_byoi_ingest_mapping_by_id(name, ingest_mapping,
x_iam_token=x_iam_token)
```

Create ingest-mapping by ID

Create ingest-mapping by name

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of ingest-mapping
ingest_mapping = swagger_client.IngestMappingSchema() # IngestMappingSchema | ingest_
↳mappingbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create ingest-mapping by ID
    api_instance.create_healthbot_ingest_settings_byoi_ingest_mapping_by_id(name,
↳ingest_mapping, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_settings_byoi_
↳ingest_mapping_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of ingest-mapping	
ingest_mapping	**IngestMappingSchema**	ingest_mappingbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json

- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.154 create_healthbot_ingest_settings_frequency_profile_by_id

```
create_healthbot_ingest_settings_frequency_profile_by_id(name, frequency_profile,
x_iam_token=x_iam_token)
```

Create frequency-profile by ID

Create operation of resource: frequency-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | ID of name
frequency_profile = swagger_client.FrequencyProfileSchema() # FrequencyProfileSchema_
↪ | frequency_profilebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create frequency-profile by ID
    api_instance.create_healthbot_ingest_settings_frequency_profile_by_id(name, ↪
↪ frequency_profile, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_settings_
↪ frequency_profile_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	ID of name	
frequency_profile	**FrequencyProfileSchema**	frequency_profilebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.155 create_healthbot_ingest_settings_tagging_profile_by_id

```
create_healthbot_ingest_settings_tagging_profile_by_id(name, tagging_profile,
x_iam_token=x_iam_token)
```

Create tagging-profile by ID

Create operation of resource: tagging-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | ID of name
tagging_profile = swagger_client.TaggingProfileSchema() # TaggingProfileSchema |
↳tagging_profilebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create tagging-profile by ID
    api_instance.create_healthbot_ingest_settings_tagging_profile_by_id(name, tagging_
↳profile, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_settings_
↳tagging_profile_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	ID of name	
tagging_profile	**TaggingProfileSchema**	tagging_profilebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.156 create_healthbot_ingest_settings_tagging_profiles

```
list[str] create_healthbot_ingest_settings_tagging_profiles(tagging_profile, x_iam_token=x_iam_token)
```

Create tagging-profile by ID

Create operation of resource: tagging-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
tagging_profile = swagger_client.TaggingProfilesSchema() # TaggingProfilesSchema |
↳tagging_profilebody object
```

(continues on next page)

(continued from previous page)

```

x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create tagging-profile by ID
    api_response = api_instance.create_healthbot_ingest_settings_tagging_
    ↪profiles(tagging_profile, x_iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_settings_
    ↪tagging_profiles: %s\n" % e)

```

Name	Type	Description	Notes
tagging_profile	**TaggingProfilesSchema**	tagging_profilebody object	
x_iam_token	str	authentication header object	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.157 create_healthbot_ingest_sflow

```
create_healthbot_ingest_sflow(sflow, x_iam_token=x_iam_token)
```

Create sflow by ID

Create operation of resource: sflow

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
sflow = swagger_client.SflowSchema() # SflowSchema | sflowbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create sflow by ID
    api_instance.create_healthbot_ingest_sflow(sflow, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_sflow: %s\n" %
    ↪e)

```

Name	Type	Description	Notes
sflow	**SflowSchema**	sflowbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.158 create_healthbot_ingest_sflow_counter_record_by_id

```
create_healthbot_ingest_sflow_counter_record_by_id(record_name, counter_record,
x_iam_token=x_iam_token)
```

Create counter-record by ID

Create operation of resource: counter-record

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
record_name = 'record_name_example' # str | ID of record-name
counter_record = swagger_client.CounterRecordSchema() # CounterRecordSchema | counter_
↳recordbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create counter-record by ID
    api_instance.create_healthbot_ingest_sflow_counter_record_by_id(record_name,
↳counter_record, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_sflow_counter_
↳record_by_id: %s\n" % e)
```

Name	Type	Description	Notes
record_name	str	ID of record-name	
counter_record	**CounterRecordSchema**	counter_recordbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.159 create_healthbot_ingest_sflow_flow_record_by_id

```
create_healthbot_ingest_sflow_flow_record_by_id(record_name, flow_record,
x_iam_token=x_iam_token)
```

Create flow-record by ID

Create operation of resource: flow-record

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
record_name = 'record_name_example' # str | ID of record-name
flow_record = swagger_client.FlowRecordSchema() # FlowRecordSchema | flow_recordbody_
↳object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create flow-record by ID
    api_instance.create_healthbot_ingest_sflow_flow_record_by_id(record_name, flow_
↳record, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_sflow_flow_
↳record_by_id: %s\n" % e)
```

Name	Type	Description	Notes
record_name	str	ID of record-name	
flow_record	**FlowRecordSchema**	flow_recordbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.160 create_healthbot_ingest_sflow_protocol_by_id

```
create_healthbot_ingest_sflow_protocol_by_id(protocol_name, protocol, x_iam_token=x_iam_token)
```

Create protocol by ID

Create operation of resource: protocol

```
from __future__ import print_function
import time
import swagger_client
```

(continues on next page)

(continued from previous page)

```

from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
protocol_name = 'protocol_name_example' # str | ID of protocol-name
protocol = swagger_client.ProtocolSchema() # ProtocolSchema | protocolbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create protocol by ID
    api_instance.create_healthbot_ingest_sflow_protocol_by_id(protocol_name, protocol,
↪ x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_sflow_protocol_
↪by_id: %s\n" % e)

```

Name	Type	Description	Notes
protocol_name	str	ID of protocol-name	
protocol	**ProtocolSchema**	protocolbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.161 create_healthbot_ingest_sflow_sample_by_id

create_healthbot_ingest_sflow_sample_by_id(sample_name, sample, x_iam_token=x_iam_token)

Create sample by ID

Create operation of resource: sample

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
sample_name = 'sample_name_example' # str | ID of sample-name
sample = swagger_client.SampleSchema() # SampleSchema | samplebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create sample by ID
    api_instance.create_healthbot_ingest_sflow_sample_by_id(sample_name, sample, x_
↪ iam_token=x_iam_token)

```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_sflow_sample_by_
↳id: %s\n" % e)
```

Name	Type	Description	Notes
sample_name	str	ID of sample-name	
sample	**SampleSchema**	samplebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.162 create_healthbot_ingest_snmp_notification

```
create_healthbot_ingest_snmp_notification(snmp_notification, x_iam_token=x_iam_token)
```

Create snmp-notification by ID

Create operation of resource: snmp-notification

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
snmp_notification = swagger_client.SnmpNotificationSchema() # SnmpNotificationSchema_
↳| snmp_notification body object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create snmp-notification by ID
    api_instance.create_healthbot_ingest_snmp_notification(snmp_notification, x_iam_
↳token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_snmp_
↳notification: %s\n" % e)
```

Name	Type	Description	Notes
snmp_notification	**SnmpNotificationSchema**	snmp_notification body object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.163 create_healthbot_ingest_snmp_notification_v3_usm_user_by_id

```
create_healthbot_ingest_snmp_notification_v3_usm_user_by_id(name, usm_user,
x_iam_token=x_iam_token)
```

Create SNMPv3 user by UserName(ID)

Create operation of resource: snmp v3 usm user

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | User Name
usm_user = swagger_client.Snmpv3UsmUserSchema() # Snmpv3UsmUserSchema | snmp_v3_usm_
↳user object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create SNMPv3 user by UserName(ID)
    api_instance.create_healthbot_ingest_snmp_notification_v3_usm_user_by_id(name,
↳usm_user, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_snmp_
↳notification_v3_usm_user_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	User Name	
usm_user	**Snmpv3UsmUserSchema**	snmp_v3_usm user object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.164 create_healthbot_ingest_syslog_header_pattern_by_id

```
create_healthbot_ingest_syslog_header_pattern_by_id(name, pattern, x_iam_token=x_iam_token)
```

Create pattern by ID

Create operation of resource: header-pattern

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | ID of name
pattern = swagger_client.HeaderPatternSchema() # HeaderPatternSchema | header_
↳patternbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create pattern by ID
    api_instance.create_healthbot_ingest_syslog_header_pattern_by_id(name, pattern, x_
↳iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_syslog_header_
↳pattern_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	ID of name	
pattern	**HeaderPatternSchema**	header_patternbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.165 create_healthbot_ingest_tagging_profile_by_id

create_healthbot_ingest_tagging_profile_by_id(name, tagging_profile, x_iam_token=x_iam_token)

Create tagging-profile by ID

Create operation of resource: tagging-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | ID of name
```

(continues on next page)

(continued from previous page)

```

tagging_profile = swagger_client.TaggingProfileSchema() # TaggingProfileSchema |
↳tagging_profilebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create tagging-profile by ID
    api_instance.create_healthbot_ingest_tagging_profile_by_id(name, tagging_profile,
↳x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_tagging_profile_
↳by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	ID of name	
tagging_profile	**TaggingProfileSchema**	tagging_profilebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.166 create_healthbot_ingest_tagging_profiles

```
list[str] create_healthbot_ingest_tagging_profiles(tagging_profile, x_iam_token=x_iam_token)
```

Create tagging-profile by ID

Create operation of resource: tagging-profile

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
tagging_profile = swagger_client.TaggingProfilesSchema() # TaggingProfilesSchema |
↳tagging_profilebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create tagging-profile by ID
    api_response = api_instance.create_healthbot_ingest_tagging_profiles(tagging_
↳profile, x_iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_ingest_tagging_
↳profiles: %s\n" % e)

```

Name	Type	Description	Notes
tagging_profile	**TaggingProfilesSchema**	tagging_profilebody object	
x_iam_token	str	authentication header object	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.167 create_healthbot_organization_organization_by_id

```
create_healthbot_organization_organization_by_id(organization_name, organization,  
x_iam_token=x_iam_token)
```

Create organization by ID

Create operation of resource: organization

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
organization_name = 'organization_name_example' # str | ID of organization-name
organization = swagger_client.OrganizationSchema() # OrganizationSchema | ↪organizationbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create organization by ID
    api_instance.create_healthbot_organization_organization_by_id(organization_name, ↪
    ↪organization, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_organization_
    ↪organization_by_id: %s\n" % e)
```

Name	Type	Description	Notes
organization_name	str	ID of organization-name	
organization	**OrganizationSchema**	organizationbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.168 create_healthbot_profile_rollup_summarization_field_profile_field_profile

```
create_healthbot_profile_rollup_summarization_field_profile_field_profile_by_id(profile_id,
field_profile, x_iam_token=x_iam_token)
```

Create field-profile by ID

Create operation of resource: field-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
profile_id = 'profile_id_example' # str | ID of profile-id
field_profile = swagger_client.RollupSummarizationSchema() # RollupSummarizationSchema | field_profilebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create field-profile by ID
    api_instance.create_healthbot_profile_rollup_summarization_field_profile_field_
    profile_by_id(profile_id, field_profile, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_profile_rollup_
    summarization_field_profile_field_profile_by_id: %s\n" % e)
```

Name	Type	Description	Notes
profile_id	str	ID of profile-id	
field_profile	**RollupSummarizationSchema**	field_profilebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.169 create_healthbot_system_time_series_database_time_series_database

```
create_healthbot_system_time_series_database_time_series_database_by_id(time_series_database,
force_tsdb=force_tsdb)
```

Create time-series-database by ID

Create operation of resource: time-series-database

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
time_series_database = swagger_client.TsdbSchema() # TsdbSchema | time_series_
↳databasebody object
force_tsdb = False # bool | force update tsdb when force is set to True (optional)
↳(default to false)

try:
    # Create time-series-database by ID
    api_instance.create_healthbot_system_time_series_database_time_series_database_by_
↳id(time_series_database, force_tsdb=force_tsdb)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_system_time_series_
↳database_time_series_database_by_id: %s\n" % e)

```

Name	Type	Description	Notes
time_series_database	**Tsdb-Schema**	time_series_databasebody object	
force_tsdb	bool	force update tsdb when force is set to True	[optional] [default to false]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.170 create_healthbot_system_trigger_action

create_healthbot_system_trigger_action(trigger_action)

Create trigger-action

Create operation of resource: trigger-action

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
trigger_action = swagger_client.TriggerActionSchema() # TriggerActionSchema | trigger_
↳action object

```

(continues on next page)

(continued from previous page)

```

try:
    # Create trigger-action
    api_instance.create_healthbot_system_trigger_action(trigger_action)
except ApiException as e:
    print("Exception when calling DefaultApi->create_healthbot_system_trigger_action:
↪ %s\n" % e)

```

Name	Type	Description	Notes
trigger_action	**TriggerActionSchema**	trigger_action object	

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.171 create_iceberg_ingest

create_iceberg_ingest(ingest_settings, x_iam_token=x_iam_token)

Create ingest by ID

Create operation of resource: ingest

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
ingest_settings = swagger_client.IngestSettingsSchema() # IngestSettingsSchema | ↪ ingest_settingsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create ingest by ID
    api_instance.create_iceberg_ingest(ingest_settings, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_ingest: %s\n" % e)

```

Name	Type	Description	Notes
ingest_settings	**IngestSettingsSchema**	ingest_settingsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json

- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.172 create_iceberg_ingest_flow

create_iceberg_ingest_flow(flow, x_iam_token=x_iam_token)

Create flow by ID

Create operation of resource: flow

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
flow = swagger_client.FlowSchema() # FlowSchema | flowbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create flow by ID
    api_instance.create_iceberg_ingest_flow(flow, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_ingest_flow: %s\n" % e)
```

Name	Type	Description	Notes
flow	**FlowSchema**	flowbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.173 create_iceberg_ingest_flow_template_by_id

create_iceberg_ingest_flow_template_by_id(name, template, x_iam_token=x_iam_token)

Create template by ID

Create operation of resource: template

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
```

(continues on next page)

(continued from previous page)

```

from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of template
template = swagger_client.TemplateSchema() # TemplateSchema | templatebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create template by ID
    api_instance.create_iceberg_ingest_flow_template_by_id(name, template, x_iam_
↪token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_ingest_flow_template_by_
↪id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of template	
template	**TemplateSchema**	templatebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.174 create_iceberg_ingest_native_gpb

create_iceberg_ingest_native_gpb(native_gpb, x_iam_token=x_iam_token)

Create native-gpb by ID

Create operation of resource: native-gpb

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
native_gpb = swagger_client.NativeGpbSchema() # NativeGpbSchema | native_gpbbody_
↪object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create native-gpb by ID
    api_instance.create_iceberg_ingest_native_gpb(native_gpb, x_iam_token=x_iam_token)

```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_ingest_native_gpb: %s\n"
    ↪ % e)
```

Name	Type	Description	Notes
native_gpb	**NativeGpbSchema**	native_gpbbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.175 create_iceberg_ingest_settings

create_iceberg_ingest_settings(ingest_settings, x_iam_token=x_iam_token)

Create ingest-settings by ID

Create operation of resource: ingest-settings

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
ingest_settings = swagger_client.IngestSettingsSchema() # IngestSettingsSchema | ↪
    ↪ ingest_settingsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create ingest-settings by ID
    api_instance.create_iceberg_ingest_settings(ingest_settings, x_iam_token=x_iam_
    ↪ token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_ingest_settings: %s\n" % ↪
    ↪ e)
```

Name	Type	Description	Notes
ingest_settings	**IngestSettingsSchema**	ingest_settingsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data

- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.176 create_iceberg_ingest_settings_flow

create_iceberg_ingest_settings_flow(flow, x_iam_token=x_iam_token)

Create flow by ID

Create operation of resource: flow

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
flow = swagger_client.FlowSchema() # FlowSchema | flowbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create flow by ID
    api_instance.create_iceberg_ingest_settings_flow(flow, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_ingest_settings_flow:
↪ %s\n" % e)
```

Name	Type	Description	Notes
flow	**FlowSchema**	flowbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.177 create_iceberg_ingest_settings_flow_template_by_id

create_iceberg_ingest_settings_flow_template_by_id(name, template, x_iam_token=x_iam_token)

Create template by ID

Create operation of resource: template

```
from __future__ import print_function
import time
import swagger_client
```

(continues on next page)

(continued from previous page)

```

from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of template
template = swagger_client.TemplateSchema() # TemplateSchema | templatebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create template by ID
    api_instance.create_iceberg_ingest_settings_flow_template_by_id(name, template, x_
    ↪iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_ingest_settings_flow_
    ↪template_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of template	
template	**TemplateSchema**	templatebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.178 create_iceberg_ingest_settings_syslog

create_iceberg_ingest_settings_syslog(syslog, x_iam_token=x_iam_token)

Create syslog by ID

Create operation of resource: syslog

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
syslog = swagger_client.SyslogSchema() # SyslogSchema | syslogbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create syslog by ID
    api_instance.create_iceberg_ingest_settings_syslog(syslog, x_iam_token=x_iam_
    ↪token)

```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_ingest_settings_syslog:
↳ %s\n" % e)
```

Name	Type	Description	Notes
syslog	**SyslogSchema**	syslogbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.179 create_iceberg_ingest_settings_syslog_pattern_by_id

create_iceberg_ingest_settings_syslog_pattern_by_id(name, pattern, x_iam_token=x_iam_token)

Create pattern by ID

Create operation of resource: pattern

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of pattern
pattern = swagger_client.PatternSchema() # PatternSchema | patternbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create pattern by ID
    api_instance.create_iceberg_ingest_settings_syslog_pattern_by_id(name, pattern, x_
↳ iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_ingest_settings_syslog_
↳ pattern_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of pattern	
pattern	**PatternSchema**	patternbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.180 create_iceberg_ingest_settings_syslog_pattern_set_by_id

```
create_iceberg_ingest_settings_syslog_pattern_set_by_id(name, pattern_set,
x_iam_token=x_iam_token)
```

Create pattern-set by ID

Create operation of resource: pattern-set

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of pattern-set
pattern_set = swagger_client.PatternSetSchema() # PatternSetSchema | pattern_setbody_
↳object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create pattern-set by ID
    api_instance.create_iceberg_ingest_settings_syslog_pattern_set_by_id(name,
↳pattern_set, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_ingest_settings_syslog_
↳pattern_set_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of pattern-set	
pattern_set	**PatternSetSchema**	pattern_setbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.181 create_iceberg_ingest_syslog

```
create_iceberg_ingest_syslog(syslog, x_iam_token=x_iam_token)
```

Create syslog by ID

Create operation of resource: syslog

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
syslog = swagger_client.SyslogSchema() # SyslogSchema | syslogbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create syslog by ID
    api_instance.create_iceberg_ingest_syslog(syslog, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_ingest_syslog: %s\n" % e)
```

Name	Type	Description	Notes
syslog	**SyslogSchema**	syslogbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.182 create_iceberg_ingest_syslog_pattern_by_id

create_iceberg_ingest_syslog_pattern_by_id(name, pattern, x_iam_token=x_iam_token)

Create pattern by ID

Create operation of resource: pattern

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of pattern
pattern = swagger_client.PatternSchema() # PatternSchema | patternbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create pattern by ID
```

(continues on next page)

(continued from previous page)

```

    api_instance.create_iceberg_ingest_syslog_pattern_by_id(name, pattern, x_iam_
↪token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_ingest_syslog_pattern_by_
↪id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of pattern	
pattern	**PatternSchema**	patternbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.183 create_iceberg_ingest_syslog_pattern_set_by_id

create_iceberg_ingest_syslog_pattern_set_by_id(name, pattern_set, x_iam_token=x_iam_token)

Create pattern-set by ID

Create operation of resource: pattern-set

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of pattern-set
pattern_set = swagger_client.PatternSetSchema() # PatternSetSchema | pattern_setbody_
↪object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create pattern-set by ID
    api_instance.create_iceberg_ingest_syslog_pattern_set_by_id(name, pattern_set, x_
↪iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_ingest_syslog_pattern_
↪set_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of pattern-set	
pattern_set	**PatternSetSchema**	pattern_setbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.184 create_iceberg_profile_data_summarization_raw_by_id

```
create_iceberg_profile_data_summarization_raw_by_id(name, raw_data_summarization,
x_iam_token=x_iam_token)
```

Create raw-data-summarization by ID

Create operation of resource: raw-data-summarization

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of raw-data-summarization
raw_data_summarization = swagger_client.RawSchema() # RawSchema | raw_data_
↳summarizationbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create raw-data-summarization by ID
    api_instance.create_iceberg_profile_data_summarization_raw_by_id(name, raw_data_
↳summarization, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_profile_data_
↳summarization_raw_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of raw-data-summarization	
raw_data_summarization	**RawSchema**	raw_data_summarizationbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.185 create_iceberg_profile_security_ca_profile_by_id

```
create_iceberg_profile_security_ca_profile_by_id(name, ca_profile, x_iam_token=x_iam_token)
```

Create ca-profile by ID

Create operation of resource: ca-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of ca-profile
ca_profile = swagger_client.CaProfileSchema() # CaProfileSchema | ca_profilebody_
↳object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create ca-profile by ID
    api_instance.create_iceberg_profile_security_ca_profile_by_id(name, ca_profile, x_
↳iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_profile_security_ca_
↳profile_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of ca-profile	
ca_profile	**CaProfileSchema**	ca_profilebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.186 create_iceberg_profile_security_local_certificate_by_id

```
create_iceberg_profile_security_local_certificate_by_id(name, local_certificate,
x_iam_token=x_iam_token)
```

Create local-certificate by ID

Create operation of resource: local-certificate

```
from __future__ import print_function
import time
import swagger_client
```

(continues on next page)

(continued from previous page)

```

from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of local-certificate
local_certificate = swagger_client.LocalCertificateSchema() # LocalCertificateSchema_
↪ | local_certificatebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create local-certificate by ID
    api_instance.create_iceberg_profile_security_local_certificate_by_id(name, local_
↪ certificate, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_profile_security_local_
↪ certificate_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of local-certificate	
local_certificate	**LocalCertificateSchema**	local_certificatebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.187 create_iceberg_profile_security_ssh_key_profile_by_id

```
create_iceberg_profile_security_ssh_key_profile_by_id(name, ssh_key_profile, authoriza-
tion=authorization)
```

Create ssh-key-profile by ID

Create operation of resource: ssh-key-profile

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of ssh-key-profile
ssh_key_profile = swagger_client.SshKeyProfileSchema() # SshKeyProfileSchema | ssh_
↪ key_profilebody object
authorization = 'authorization_example' # str | authentication header object_
↪ (optional)

```

(continues on next page)

(continued from previous page)

```

try:
    # Create ssh-key-profile by ID
    api_instance.create_iceberg_profile_security_ssh_key_profile_by_id(name, ssh_key_
    ↪profile, authorization=authorization)
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_profile_security_ssh_key_
    ↪profile_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of ssh-key-profile	
ssh_key_profile	**SshKeyProfileSchema**	ssh_key_profilebody object	
authorization	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.188 create_iceberg_profiles

create_iceberg_profiles(profile, x_iam_token=x_iam_token)

Create profile by ID

Create entire profile configuration.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
profile = swagger_client.ProfilesSchema() # ProfilesSchema | profilebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create profile by ID
    api_instance.create_iceberg_profiles(profile, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->create_iceberg_profiles: %s\n" % e)

```

Name	Type	Description	Notes
profile	**ProfilesSchema**	profilebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.189 delete_dynamic_tagging_by_key

`delete_dynamic_tagging_by_key(key_name, x_iam_token=x_iam_token)`

Delete Dynamic-tagging key-value

Update a key in Dynamic-tagging

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
key_name = 'key_name_example' # str | Dynamic-tagging Key
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete Dynamic-tagging key-value
    api_instance.delete_dynamic_tagging_by_key(key_name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_dynamic_tagging_by_key: %s\n" % e)
    # e)
```

Name	Type	Description	Notes
key_name	str	Dynamic-tagging Key	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.190 delete_files_certificates_by_file_name

`delete_files_certificates_by_file_name(file_name, x_iam_token=x_iam_token, input_path=input_path, certificate_type=certificate_type)`

Delete a certificate-file.

Delete the specified certificate-file. Delete will not fail if the certificate-file is being used by some service.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
file_name = 'file_name_example' # str | File name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
input_path = 'input_path_example' # str | Input path (optional)
certificate_type = 'certificate_type_example' # str | Certificate type (optional)

try:
    # Delete a certificate-file.
    api_instance.delete_files_certificates_by_file_name(file_name, x_iam_token=x_iam_
↪token, input_path=input_path, certificate_type=certificate_type)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_files_certificates_by_file_name:
↪ %s\n" % e)

```

Name	Type	Description	Notes
file_name	str	File name	
x_iam_token	str	authentication header object	[optional]
input_path	str	Input path	[optional]
certificate_type	str	Certificate type	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.191 delete_files_helper_files_by_file_name

```
delete_files_helper_files_by_file_name(file_name, x_iam_token=x_iam_token, input_path=input_path)
```

Delete a helper-file.

Delete the specified helper-file. Delete will not fail if the helper-file is being used by some service.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
file_name = 'file_name_example' # str | File name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

```

(continues on next page)

(continued from previous page)

```

input_path = 'input_path_example' # str | Input path (optional)

try:
    # Delete a helper-file.
    api_instance.delete_files_helper_files_by_file_name(file_name, x_iam_token=x_iam_
↳ token, input_path=input_path)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_files_helper_files_by_file_name:
↳ %s\n" % e)

```

Name	Type	Description	Notes
file_name	str	File name	
x_iam_token	str	authentication header object	[optional]
input_path	str	Input path	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.192 delete_healthbot_deployment_deployment_by_id

delete_healthbot_deployment_deployment_by_id(x_iam_token=x_iam_token)

Delete deployment by ID

Delete operation of resource: deployment

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete deployment by ID
    api_instance.delete_healthbot_deployment_deployment_by_id(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_deployment_deployment_
↳ by_id: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.193 delete_healthbot_dynamic_tagging

delete_healthbot_dynamic_tagging(x_iam_token=x_iam_token)

Delete dynamic-tagging by ID

Delete operation of resource: dynamic-tagging

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete dynamic-tagging by ID
    api_instance.delete_healthbot_dynamic_tagging(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_dynamic_tagging: %s\n"
          % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.194 delete_healthbot_ingest_byoi_custom_plugin_by_id

delete_healthbot_ingest_byoi_custom_plugin_by_id(name, x_iam_token=x_iam_token)

Delete custom-plugin by ID

Delete operation of resource: custom-plugin

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of custom-plugin
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete custom-plugin by ID
    api_instance.delete_healthbot_ingest_byoi_custom_plugin_by_id(name, x_iam_token=x_
↳ iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_byoi_custom_
↳ plugin_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of custom-plugin	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.195 delete_healthbot_ingest_byoi_default_plugin_tlive_kafka_by_id

delete_healthbot_ingest_byoi_default_plugin_tlive_kafka_by_id(name, x_iam_token=x_iam_token)

Delete tlive-kafka-oc by ID

Delete operation of resource: tlive-kafka-oc

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of tlive-kafka-oc
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete tlive-kafka-oc by ID
    api_instance.delete_healthbot_ingest_byoi_default_plugin_tlive_kafka_by_id(name,
↳ x_iam_token=x_iam_token)

```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_byoi_default_
    ↪plugin_tlive_kafka_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of tlive-kafka-oc	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.196 delete_healthbot_ingest_byoi_ingest_mapping_by_id

delete_healthbot_ingest_byoi_ingest_mapping_by_id(name, x_iam_token=x_iam_token)

Delete ingest-mapping by ID

Delete ingest-mapping by name

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of ingest-mapping
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete ingest-mapping by ID
    api_instance.delete_healthbot_ingest_byoi_ingest_mapping_by_id(name, x_iam_
    ↪token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_byoi_ingest_
    ↪mapping_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of ingest-mapping	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json

- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.197 delete_healthbot_ingest_frequency_profile_by_id

delete_healthbot_ingest_frequency_profile_by_id(name, x_iam_token=x_iam_token)

Delete frequency-profile by ID

Delete operation of resource: frequency-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | ID of name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete frequency-profile by ID
    api_instance.delete_healthbot_ingest_frequency_profile_by_id(name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_frequency_profile_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	ID of name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.198 delete_healthbot_ingest_outbound_ssh

delete_healthbot_ingest_outbound_ssh(x_iam_token=x_iam_token)

Delete outbound-ssh by ID

Delete operation of resource: outbound-ssh

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete outbound-ssh by ID
    api_instance.delete_healthbot_ingest_outbound_ssh(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_outbound_ssh:
↪ %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.199 delete_healthbot_ingest_settings_byoi_custom_plugin_by_id

delete_healthbot_ingest_settings_byoi_custom_plugin_by_id(name, x_iam_token=x_iam_token)

Delete custom-plugin by ID

Delete operation of resource: custom-plugin

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of custom-plugin
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete custom-plugin by ID
    api_instance.delete_healthbot_ingest_settings_byoi_custom_plugin_by_id(name, x_
↪ iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_settings_byoi_
↪ custom_plugin_by_id: %s\n" % e)
```


Name	Type	Description	Notes
name	str	Name of custom-plugin	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.200 delete_healthbot_ingest_settings_byoi_default_plugin_tlive_kafka_by_id

```
delete_healthbot_ingest_settings_byoi_default_plugin_tlive_kafka_by_id(name,
x_iam_token=x_iam_token)
```

Delete tlive-kafka-oc by ID

Delete operation of resource: tlive-kafka-oc

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of tlive-kafka-oc
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete tlive-kafka-oc by ID
    api_instance.delete_healthbot_ingest_settings_byoi_default_plugin_tlive_kafka_by_
↪id(name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_settings_byoi_
↪default_plugin_tlive_kafka_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of tlive-kafka-oc	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.201 delete_healthbot_ingest_settings_byoi_ingest_mapping_by_id

```
delete_healthbot_ingest_settings_byoi_ingest_mapping_by_id(name, x_iam_token=x_iam_token)
```

Delete ingest-mapping by ID

Delete ingest-mapping by name

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of ingest-mapping
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete ingest-mapping by ID
    api_instance.delete_healthbot_ingest_settings_byoi_ingest_mapping_by_id(name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_settings_byoi_ingest_mapping_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of ingest-mapping	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.202 delete_healthbot_ingest_settings_frequency_profile_by_id

```
delete_healthbot_ingest_settings_frequency_profile_by_id(name, x_iam_token=x_iam_token)
```

Delete frequency-profile by ID

Delete operation of resource: frequency-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
```

(continues on next page)

(continued from previous page)

```

api_instance = swagger_client.DefaultApi()
name = 'name_example' # str / ID of name
x_iam_token = 'x_iam_token_example' # str / authentication header object (optional)

try:
    # Delete frequency-profile by ID
    api_instance.delete_healthbot_ingest_settings_frequency_profile_by_id(name, x_iam_
    ↪token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_settings_
    ↪frequency_profile_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	ID of name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.203 delete_healthbot_ingest_settings_tagging_profile_by_id

delete_healthbot_ingest_settings_tagging_profile_by_id(name, x_iam_token=x_iam_token)

Delete tagging-profile by ID

Delete operation of resource: tagging-profile

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str / ID of name
x_iam_token = 'x_iam_token_example' # str / authentication header object (optional)

try:
    # Delete tagging-profile by ID
    api_instance.delete_healthbot_ingest_settings_tagging_profile_by_id(name, x_iam_
    ↪token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_settings_
    ↪tagging_profile_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	ID of name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.204 delete_healthbot_ingest_settings_tagging_profiles

`delete_healthbot_ingest_settings_tagging_profiles(x_iam_token=x_iam_token)`

Delete tagging-profile by ID

Delete operation of resource: tagging-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str / authentication header object (optional)

try:
    # Delete tagging-profile by ID
    api_instance.delete_healthbot_ingest_settings_tagging_profiles(x_iam_token=x_iam_
↪token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_settings_
↪tagging_profiles: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.205 delete_healthbot_ingest_sflow

`delete_healthbot_ingest_sflow(x_iam_token=x_iam_token)`

Delete sflow by ID

Delete operation of resource: sflow

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str / authentication header object (optional)

try:
    # Delete sflow by ID
    api_instance.delete_healthbot_ingest_sflow(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_sflow: %s\n" % e)
    e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.206 delete_healthbot_ingest_sflow_counter_record_by_id

delete_healthbot_ingest_sflow_counter_record_by_id(record_name, x_iam_token=x_iam_token)

Delete counter-record by ID

Delete operation of resource: counter-record

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
record_name = 'record_name_example' # str / ID of record-name
x_iam_token = 'x_iam_token_example' # str / authentication header object (optional)

try:
    # Delete counter-record by ID
    api_instance.delete_healthbot_ingest_sflow_counter_record_by_id(record_name, x_iam_token=x_iam_token)
```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_sflow_counter_
↳record_by_id: %s\n" % e)
```

Name	Type	Description	Notes
record_name	str	ID of record-name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.207 delete_healthbot_ingest_sflow_flow_record_by_id

delete_healthbot_ingest_sflow_flow_record_by_id(record_name, x_iam_token=x_iam_token)

Delete flow-record by ID

Delete operation of resource: flow-record

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
record_name = 'record_name_example' # str | ID of record-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete flow-record by ID
    api_instance.delete_healthbot_ingest_sflow_flow_record_by_id(record_name, x_iam_
↳token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_sflow_flow_
↳record_by_id: %s\n" % e)
```

Name	Type	Description	Notes
record_name	str	ID of record-name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json

- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.208 delete_healthbot_ingest_sflow_protocol_by_id

delete_healthbot_ingest_sflow_protocol_by_id(protocol_name, x_iam_token=x_iam_token)

Delete protocol by ID

Delete operation of resource: protocol

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
protocol_name = 'protocol_name_example' # str | ID of protocol-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete protocol by ID
    api_instance.delete_healthbot_ingest_sflow_protocol_by_id(protocol_name, x_iam_
↪token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_sflow_protocol_
↪by_id: %s\n" % e)
```

Name	Type	Description	Notes
protocol_name	str	ID of protocol-name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.209 delete_healthbot_ingest_sflow_sample_by_id

delete_healthbot_ingest_sflow_sample_by_id(sample_name, x_iam_token=x_iam_token)

Delete sample by ID

Delete operation of resource: sample

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
sample_name = 'sample_name_example' # str | ID of sample-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete sample by ID
    api_instance.delete_healthbot_ingest_sflow_sample_by_id(sample_name, x_iam_
↪token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_sflow_sample_by_
↪id: %s\n" % e)
```

Name	Type	Description	Notes
sample_name	str	ID of sample-name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.210 delete_healthbot_ingest_snmp_notification

delete_healthbot_ingest_snmp_notification(x_iam_token=x_iam_token)

Delete snmp-notification

Delete operation of resource: snmp-notification

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete snmp-notification
    api_instance.delete_healthbot_ingest_snmp_notification(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_snmp_
↪notification: %s\n" % e)
```

(continues on next page)

(continued from previous page)

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.211 delete_healthbot_ingest_snmp_notification_v3_usm_user_by_id

delete_healthbot_ingest_snmp_notification_v3_usm_user_by_id(name, x_iam_token=x_iam_token)

Delete SNMPv3 user by UserName(ID)

Delete operation of resource: snmp v3 usm user

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str / User Name
x_iam_token = 'x_iam_token_example' # str / authentication header object (optional)

try:
    # Delete SNMPv3 user by UserName(ID)
    api_instance.delete_healthbot_ingest_snmp_notification_v3_usm_user_by_id(name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_snmp_notification_v3_usm_user_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	User Name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.212 delete_healthbot_ingest_syslog_header_pattern_by_id

delete_healthbot_ingest_syslog_header_pattern_by_id(name, x_iam_token=x_iam_token)

Delete pattern by ID

Delete operation of resource: header-pattern

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | ID of name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete pattern by ID
    api_instance.delete_healthbot_ingest_syslog_header_pattern_by_id(name, x_iam_
↪token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_syslog_header_
↪pattern_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	ID of name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.213 delete_healthbot_ingest_tagging_profile_by_id

delete_healthbot_ingest_tagging_profile_by_id(name, x_iam_token=x_iam_token)

Delete tagging-profile by ID

Delete operation of resource: tagging-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
```

(continues on next page)

(continued from previous page)

```

api_instance = swagger_client.DefaultApi()
name = 'name_example' # str / ID of name
x_iam_token = 'x_iam_token_example' # str / authentication header object (optional)

try:
    # Delete tagging-profile by ID
    api_instance.delete_healthbot_ingest_tagging_profile_by_id(name, x_iam_token=x_
↳iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_tagging_profile_
↳by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	ID of name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.214 delete_healthbot_ingest_tagging_profiles

delete_healthbot_ingest_tagging_profiles(x_iam_token=x_iam_token)

Delete tagging-profile by ID

Delete operation of resource: tagging-profile

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str / authentication header object (optional)

try:
    # Delete tagging-profile by ID
    api_instance.delete_healthbot_ingest_tagging_profiles(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_ingest_tagging_
↳profiles: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.215 delete_healthbot_organization_organization_by_id

```
delete_healthbot_organization_organization_by_id(organization_name, x_iam_token=x_iam_token)
```

Delete organization by ID

Delete operation of resource: organization

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
organization_name = 'organization_name_example' # str | ID of organization-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete organization by ID
    api_instance.delete_healthbot_organization_organization_by_id(organization_name,
↳x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_organization_
↳organization_by_id: %s\n" % e)
```

Name	Type	Description	Notes
organization_name	str	ID of organization-name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.216 delete_healthbot_profile_rollup_summarization_field_profile_field_profile

```
delete_healthbot_profile_rollup_summarization_field_profile_field_profile_by_id(profile_id,
x_iam_token=x_iam_token)
```

Delete field-profile by ID

Delete operation of resource: field-profile

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
profile_id = 'profile_id_example' # str | ID of profile-id
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete field-profile by ID
    api_instance.delete_healthbot_profile_rollup_summarization_field_profile_field_
    ↪profile_by_id(profile_id, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_profile_rollup_
    ↪summarization_field_profile_field_profile_by_id: %s\n" % e)

```

Name	Type	Description	Notes
profile_id	str	ID of profile-id	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.217 delete_healthbot_system_time_series_database_time_series_database_by_id

delete_healthbot_system_time_series_database_time_series_database_by_id()

Delete time-series-database

Delete operation of resource: time-series-database

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()

try:
    # Delete time-series-database
    api_instance.delete_healthbot_system_time_series_database_time_series_database_by_
    ↪id()
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_system_time_series_
    ↪database_time_series_database_by_id: %s\n" % e)

```

(continues on next page)

This endpoint does not need any parameter.

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.218 delete_healthbot_system_trigger_action

delete_healthbot_system_trigger_action()

Delete trigger-action schedulers

Delete operation of resource: trigger-action

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()

try:
    # Delete trigger-action schedulers
    api_instance.delete_healthbot_system_trigger_action()
except ApiException as e:
    print("Exception when calling DefaultApi->delete_healthbot_system_trigger_action: %s\n" % e)
```

This endpoint does not need any parameter.

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.219 delete_iceberg_ingest

delete_iceberg_ingest(x_iam_token=x_iam_token)

Delete ingest by ID

Delete operation of resource: ingest

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete ingest by ID
    api_instance.delete_iceberg_ingest(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_ingest: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.220 delete_iceberg_ingest_flow

delete_iceberg_ingest_flow(x_iam_token=x_iam_token)

Delete flow by ID

Delete operation of resource: flow

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete flow by ID
    api_instance.delete_iceberg_ingest_flow(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_ingest_flow: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.221 delete_iceberg_ingest_flow_template_by_id

delete_iceberg_ingest_flow_template_by_id(name, x_iam_token=x_iam_token)

Delete template by ID

Delete operation of resource: template

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of template
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete template by ID
    api_instance.delete_iceberg_ingest_flow_template_by_id(name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_ingest_flow_template_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of template	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.222 delete_iceberg_ingest_native_gpb

delete_iceberg_ingest_native_gpb(x_iam_token=x_iam_token)

Delete native-gpb by ID

Delete operation of resource: native-gpb

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete native-gpb by ID
    api_instance.delete_iceberg_ingest_native_gpb(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_ingest_native_gpb: %s\n"
          % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.223 delete_iceberg_ingest_settings

delete_iceberg_ingest_settings(x_iam_token=x_iam_token)

Delete ingest-settings by ID

Delete operation of resource: ingest-settings

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete ingest-settings by ID
    api_instance.delete_iceberg_ingest_settings(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_ingest_settings: %s\n" % e)
```

(continues on next page)

(continued from previous page)

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.224 delete_iceberg_ingest_settings_flow

delete_iceberg_ingest_settings_flow(x_iam_token=x_iam_token)

Delete flow by ID

Delete operation of resource: flow

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str / authentication header object (optional)

try:
    # Delete flow by ID
    api_instance.delete_iceberg_ingest_settings_flow(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_ingest_settings_flow:
↪ %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.225 delete_iceberg_ingest_settings_flow_template_by_id

delete_iceberg_ingest_settings_flow_template_by_id(name, x_iam_token=x_iam_token)

Delete template by ID

Delete operation of resource: template

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of template
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete template by ID
    api_instance.delete_iceberg_ingest_settings_flow_template_by_id(name, x_iam_
↪token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_ingest_settings_flow_
↪template_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of template	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.226 delete_iceberg_ingest_settings_syslog

delete_iceberg_ingest_settings_syslog(x_iam_token=x_iam_token)

Delete syslog by ID

Delete operation of resource: syslog

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
```

(continues on next page)

(continued from previous page)

```

api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str / authentication header object (optional)

try:
    # Delete syslog by ID
    api_instance.delete_iceberg_ingest_settings_syslog(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_ingest_settings_syslog:
↪ %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.227 delete_iceberg_ingest_settings_syslog_pattern_by_id

delete_iceberg_ingest_settings_syslog_pattern_by_id(name, x_iam_token=x_iam_token)

Delete pattern by ID

Delete operation of resource: pattern

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str / Name of pattern
x_iam_token = 'x_iam_token_example' # str / authentication header object (optional)

try:
    # Delete pattern by ID
    api_instance.delete_iceberg_ingest_settings_syslog_pattern_by_id(name, x_iam_
↪ token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_ingest_settings_syslog_
↪ pattern_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of pattern	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.228 delete_iceberg_ingest_settings_syslog_pattern_set_by_id

`delete_iceberg_ingest_settings_syslog_pattern_set_by_id(name, x_iam_token=x_iam_token)`

Delete pattern-set by ID

Delete operation of resource: pattern-set

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of pattern-set
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete pattern-set by ID
    api_instance.delete_iceberg_ingest_settings_syslog_pattern_set_by_id(name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_ingest_settings_syslog_pattern_set_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of pattern-set	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.229 delete_iceberg_ingest_syslog

`delete_iceberg_ingest_syslog(x_iam_token=x_iam_token)`

Delete syslog by ID

Delete operation of resource: syslog

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete syslog by ID
    api_instance.delete_iceberg_ingest_syslog(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_ingest_syslog: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.230 delete_iceberg_ingest_syslog_pattern_by_id

delete_iceberg_ingest_syslog_pattern_by_id(name, x_iam_token=x_iam_token)

Delete pattern by ID

Delete operation of resource: pattern

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of pattern
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete pattern by ID
    api_instance.delete_iceberg_ingest_syslog_pattern_by_id(name, x_iam_token=x_iam_
→token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_ingest_syslog_pattern_by_
→id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of pattern	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.231 delete_iceberg_ingest_syslog_pattern_set_by_id

delete_iceberg_ingest_syslog_pattern_set_by_id(name, x_iam_token=x_iam_token)

Delete pattern-set by ID

Delete operation of resource: pattern-set

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of pattern-set
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete pattern-set by ID
    api_instance.delete_iceberg_ingest_syslog_pattern_set_by_id(name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_ingest_syslog_pattern_set_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of pattern-set	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.232 delete_iceberg_profile_data_summarization_raw_by_id

delete_iceberg_profile_data_summarization_raw_by_id(name, x_iam_token=x_iam_token)

Delete raw-data-summarization by ID

Delete operation of resource: raw data-summarization

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of raw-data-summarization
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete raw-data-summarization by ID
    api_instance.delete_iceberg_profile_data_summarization_raw_by_id(name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_profile_data_summarization_raw_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of raw-data-summarization	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.233 delete_iceberg_profile_security_ca_profile_by_id

delete_iceberg_profile_security_ca_profile_by_id(name, x_iam_token=x_iam_token)

Delete ca-profile by ID

Delete operation of resource: ca-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
```

(continues on next page)

(continued from previous page)

```

api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of ca-profile
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete ca-profile by ID
    api_instance.delete_iceberg_profile_security_ca_profile_by_id(name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_profile_security_ca_profile_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of ca-profile	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.234 delete_iceberg_profile_security_local_certificate_by_id

delete_iceberg_profile_security_local_certificate_by_id(name, x_iam_token=x_iam_token)

Delete local-certificate by ID

Delete operation of resource: local-certificate

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of local-certificate
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete local-certificate by ID
    api_instance.delete_iceberg_profile_security_local_certificate_by_id(name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_profile_security_local_certificate_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of local-certificate	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.235 delete_iceberg_profile_security_ssh_key_profile_by_id

delete_iceberg_profile_security_ssh_key_profile_by_id(name, authorization=authorization)

Delete ssh-key-profile by ID

Delete operation of resource: ssh-key-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of ssh-key-profile
authorization = 'authorization_example' # str | authentication header object,
↳ (optional)

try:
    # Delete ssh-key-profile by ID
    api_instance.delete_iceberg_profile_security_ssh_key_profile_by_id(name,
↳ authorization=authorization)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_profile_security_ssh_key_
↳ profile_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of ssh-key-profile	
authorization	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.236 delete_iceberg_profiles

delete_iceberg_profiles(x_iam_token=x_iam_token)

Delete profile by ID

Delete entire profile configuration.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete profile by ID
    api_instance.delete_iceberg_profiles(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->delete_iceberg_profiles: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.237 get_dynamic_tagging_by_key

str get_dynamic_tagging_by_key(key_name, x_iam_token=x_iam_token)

Get value of corresponding Dynamic-tagging key

Get Value of corresponding key from dynamic-tagging

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
key_name = 'key_name_example' # str | Dynamic-tagging Key
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
```

(continues on next page)

(continued from previous page)

```

try:
    # Get value of corresponding Dynamic-tagging key
    api_response = api_instance.get_dynamic_tagging_by_key(key_name, x_iam_token=x_
    iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->get_dynamic_tagging_by_key: %s\n" % e)

```

Name	Type	Description	Notes
key_name	str	Dynamic-tagging Key	
x_iam_token	str	authentication header object	[optional]

str

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.238 get_fields_from_xpath

FieldCaptureSchema get_fields_from_xpath(xpath, timestamp=timestamp)

Get last value of all fields before a given timestamp.

Get the values of all fields

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
xpath = 'xpath_example' # str | XPATH
timestamp = 'timestamp_example' # str | Timestamp (optional)

try:
    # Get last value of all fields before a given timestamp.
    api_response = api_instance.get_fields_from_xpath(xpath, timestamp=timestamp)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->get_fields_from_xpath: %s\n" % e)

```

Name	Type	Description	Notes
xpath	str	XPATH	
timestamp	str	Timestamp	[optional]

****FieldCaptureSchema****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.239 grafana_login

grafana_login(x_iam_token=x_iam_token)

Login to grafana

Login to Grafana

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str / authentication header object (optional)

try:
    # Login to grafana
    api_instance.grafana_login(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->grafana_login: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.240 inspect_command_rpc_table_on_device

inspect_command_rpc_table_on_device(command_rpc_detail, x_iam_token=x_iam_token)

Inspect the given iAgent table.

Inspect the given iAgent table on a device and return the results.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint
```

(continues on next page)

(continued from previous page)

```
# create an instance of the API class
api_instance = swagger_client.DefaultApi()
command_rpc_detail = swagger_client.CommandRpc() # CommandRpc | command-rpc object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Inspect the given iAgent table.
    api_instance.inspect_command_rpc_table_on_device(command_rpc_detail, x_iam_
↪token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->inspect_command_rpc_table_on_device:
↪%s\n" % e)
```

Name	Type	Description	Notes
command_rpc_detail	**CommandRpc**	command-rpc object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.241 restore_grafana

```
restore_grafana(restore_file, x_iam_token=x_iam_token)
```

Restore Grafana configuration

Restore Grafana configuration

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
restore_file = '/path/to/file.txt' # file | File content
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Restore Grafana configuration
    api_instance.restore_grafana(restore_file, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->restore_grafana: %s\n" % e)
```

Name	Type	Description	Notes
restore_file	file	File content	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.242 restore_helper_files

```
restore_helper_files(restore_file, x_iam_token=x_iam_token)
```

Upload a helper-file.

Upload tar file of helper-files

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
restore_file = '/path/to/file.txt' # file | File content
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Upload a helper-file.
    api_instance.restore_helper_files(restore_file, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->restore_helper_files: %s\n" % e)
```

Name	Type	Description	Notes
restore_file	file	File content	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.243 retrieve_configuration_jobs

```
list[InlineResponse200] retrieve_configuration_jobs(x_iam_token=x_iam_token, job_id=job_id,
job_status=job_status)
```

Return list of all the Commit Job ID's

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
job_id = 'job_id_example' # str | Id of Job (optional)
job_status = 'job_status_example' # str | Type of job (optional)

try:
    api_response = api_instance.retrieve_configuration_jobs(x_iam_token=x_iam_token,
↪ job_id=job_id, job_status=job_status)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_configuration_jobs: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
job_id	**str**	Id of Job	[optional]
job_status	str	Type of job	[optional]

****list[InlineResponse200]****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.244 retrieve_data_database_table

```
list[TableSchema] retrieve_data_database_table(x_iam_token=x_iam_token, device_id=device_id, de-
vice_group_name=device_group_name, network_group_name=network_group_name)
```

Get information about tables for a device of a device-group.

Get information about different types of tables stored for a device of a device-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint
```

(continues on next page)

(continued from previous page)

```
# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
device_id = 'device_id_example' # str | Name of device (optional)
device_group_name = 'device_group_name_example' # str | Name of device-group
↳ (optional)
network_group_name = 'network_group_name_example' # str | Name of network-group
↳ (optional)

try:
    # Get information about tables for a device of a device-group.
    api_response = api_instance.retrieve_data_database_table(x_iam_token=x_iam_token,
↳ device_id=device_id, device_group_name=device_group_name, network_group_
↳ name=network_group_name)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_data_database_table: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
device_id	str	Name of device	[optional]
device_group_name	str	Name of device-group	[optional]
network_group_name	str	Name of network-group	[optional]

```
**list[TableSchema]**
```

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.245 retrieve_data_database_table_column_by_table_name

```
list[str] retrieve_data_database_table_column_by_table_name(table_name,
x_iam_token=x_iam_token, device_id=device_id, device_group_name=device_group_name, net-
work_group_name=network_group_name)
```

Get information about columns in a table.

Get information about columns in a table.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
table_name = 'table_name_example' # str | Name of table
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
device_id = 'device_id_example' # str | Name of device (optional)
```

(continues on next page)

(continued from previous page)

```

device_group_name = 'device_group_name_example' # str | Name of device-group_
↳ (optional)
network_group_name = 'network_group_name_example' # str | Name of network-group_
↳ (optional)

try:
    # Get information about columns in a table.
    api_response = api_instance.retrieve_data_database_table_column_by_table_
↳ name(table_name, x_iam_token=x_iam_token, device_id=device_id, device_group_
↳ name=device_group_name, network_group_name=network_group_name)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_data_database_table_column_by_
↳ table_name: %s\n" % e)

```

Name	Type	Description	Notes
table_name	str	Name of table	
x_iam_token	str	authentication header object	[optional]
device_id	str	Name of device	[optional]
device_group_name	str	Name of device-group	[optional]
network_group_name	str	Name of network-group	[optional]

list[str]

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.246 retrieve_data_database_tags_by_table_name

```

list[str]    retrieve_data_database_tags_by_table_name(table_name,      x_iam_token=x_iam_token,
device_id=device_id,                device_group_name=device_group_name,          net-
work_group_name=network_group_name, tag=tag, where_clause=where_clause)

```

Get information about tags keys and values in a table.

Get information about tags keys and values in a table.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
table_name = 'table_name_example' # str | Name of table
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
device_id = 'device_id_example' # str | Name of device (optional)
device_group_name = 'device_group_name_example' # str | Name of device-group_
↳ (optional)

```

(continues on next page)

(continued from previous page)

```

network_group_name = 'network_group_name_example' # str | Name of network-group.
↳ (optional)
tag = 'tag_example' # str | Tag key for which values are requested. (optional)
where_clause = 'where_clause_example' # str | Where condition to select values for.
↳ the requested key. This would not be processed if there is no `tag` query parameter.
↳ eg: `tag_key1=val1 AND tag_key2=val2` (optional)

try:
    # Get information about tags keys and values in a table.
    api_response = api_instance.retrieve_data_database_tags_by_table_name(table_name,
↳ x_iam_token=x_iam_token, device_id=device_id, device_group_name=device_group_name,
↳ network_group_name=network_group_name, tag=tag, where_clause=where_clause)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_data_database_tags_by_table_
↳ name: %s\n" % e)

```

Name	Type	Description	Notes
table_name	str	Name of table	
x_iam_token	str	authentication header object	[optional]
device_id	str	Name of device	[optional]
device_group_name	str	Name of device-group	[optional]
network_group_name	str	Name of network-group	[optional]
tag	str	Tag key for which values are requested.	[optional]
where_clause	str	Where condition to select values for the requested key. This would not be processed if there is no <code><tag></code> ; query parameter. eg: <code><tag_key1>;val1 AND tag_key2;<tag_key1>;val2</code> ;	[optional]

list[str]

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.247 retrieve_debug_jobs

object retrieve_debug_jobs(x_iam_token=x_iam_token, job_id=job_id)

Return the status of the last “/debug/” job

```

from __future__ import print_function
import time
import swagger_client

```

(continues on next page)

(continued from previous page)

```

from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
job_id = 'job_id_example' # str | Id of Job (optional)

try:
    api_response = api_instance.retrieve_debug_jobs(x_iam_token=x_iam_token, job_
    ↪id=job_id)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_debug_jobs: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
job_id	**str**	Id of Job	[optional]

object

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.248 retrieve_event

```

list[Event] retrieve_event(from_timestamp, device_id, x_iam_token=x_iam_token,
to_timestamp=to_timestamp, device_group_name=device_group_name, granularity=granularity,
color=color)

```

Get all events for a device.

Get the list of events for a device. Filtering is possible with the use of various query parameters.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
from_timestamp = '2013-10-20T19:20:30+01:00' # datetime | Starting timestamp
device_id = 'device_id_example' # str | device-id of the device for which events are_
    ↪requested
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
to_timestamp = '2013-10-20T19:20:30+01:00' # datetime | Ending timestamp (optional)
device_group_name = 'device_group_name_example' # str | Device group's device-group-
    ↪name of which the device is part (optional)
granularity = 'granularity_example' # str | Granularity of query (optional)

```

(continues on next page)

(continued from previous page)

```

color = 'color_example' # str | Color of events. (optional)

try:
    # Get all events for a device.
    api_response = api_instance.retrieve_event(from_timestamp, device_id, x_iam_
    ↪token=x_iam_token, to_timestamp=to_timestamp, device_group_name=device_group_name,
    ↪granularity=granularity, color=color)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_event: %s\n" % e)

```

Name	Type	Description	Notes
from_timestamp	datetime	Starting timestamp	
device_id	str	device-id of the device for which events are requested	
x_iam_token	str	authentication header object	[optional]
to_timestamp	datetime	Ending timestamp	[optional]
device_group_name	str	Device group's device-group-name of which the device is part	[optional]
granularity	str	Granularity of query	[optional]
color	str	Color of events.	[optional]

```

**list[Event]**

```

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.249 retrieve_event_by_event_name

```

list[Event]    retrieve_event_by_event_name(event_name,      from_timestamp,      device_id,
x_iam_token=x_iam_token,  to_timestamp=to_timestamp,  device_group_name=device_group_name,
granularity=granularity, color=color)

```

Get instances of a device event.

Get instances of a specified device event. Filtering is possible with the use of various query parameters.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
event_name = 'event_name_example' # str | Name of event
from_timestamp = '2013-10-20T19:20:30+01:00' # datetime | Starting timestamp
device_id = 'device_id_example' # str | device-id of the device for which events are
    ↪requested
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
to_timestamp = '2013-10-20T19:20:30+01:00' # datetime | Ending timestamp (optional)

```

(continues on next page)

(continued from previous page)

```

device_group_name = 'device_group_name_example' # str / device-group-name of which_
↳the device is part (optional)
granularity = 'granularity_example' # str / Granularity of query (optional)
color = 'color_example' # str / Color of events. (optional)

try:
    # Get instances of a device event.
    api_response = api_instance.retrieve_event_by_event_name(event_name, from_
↳timestamp, device_id, x_iam_token=x_iam_token, to_timestamp=to_timestamp, device_
↳group_name=device_group_name, granularity=granularity, color=color)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_event_by_event_name: %s\n" % e)

```

Name	Type	Description	Notes
event_name	str	Name of event	
from_timestamp	datetime	Starting timestamp	
device_id	str	device-id of the device for which events are requested	
x_iam_token	str	authentication header object	[optional]
to_timestamp	datetime	Ending timestamp	[optional]
device_group_name	str	device-group-name of which the device is part	[optional]
granularity	str	Granularity of query	[optional]
color	str	Color of events.	[optional]

```

**list[Event]**

```

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.250 retrieve_event_by_event_name_device_group

```

list[Event] retrieve_event_by_event_name_device_group(event_name, from_timestamp, de-
vice_group_name, x_iam_token=x_iam_token, to_timestamp=to_timestamp, granularity=granularity,
device_id=device_id, color=color)

```

Get instances of a device-group event.

Get instances of a specified device-group event. Filtering is possible with the use of various query parameters.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
event_name = 'event_name_example' # str / Name of event
from_timestamp = '2013-10-20T19:20:30+01:00' # datetime / Starting timestamp

```

(continues on next page)

(continued from previous page)

```

device_group_name = 'device_group_name_example' # str | device_group_name of the_
↳device-group for which events are requested
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
to_timestamp = '2013-10-20T19:20:30+01:00' # datetime | Ending timestamp (optional)
granularity = 'granularity_example' # str | Granularity of query (optional)
device_id = ['device_id_example'] # list[str] | list of devices under a device-group_
↳to be fetched (optional)
color = 'color_example' # str | Color of events. (optional)

try:
    # Get instances of a device-group event.
    api_response = api_instance.retrieve_event_by_event_name_device_group(event_name,
↳from_timestamp, device_group_name, x_iam_token=x_iam_token, to_timestamp=to_
↳timestamp, granularity=granularity, device_id=device_id, color=color)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_event_by_event_name_device_
↳group: %s\n" % e)

```

Name	Type	Description	Notes
event_name	str	Name of event	
from_timestamp	datetime	Starting timestamp	
device_group_name	str	device_group_name of the device-group for which events are requested	
x_iam_token	str	authentication header object	[optional]
to_timestamp	datetime	Ending timestamp	[optional]
granularity	str	Granularity of query	[optional]
device_id	**list[str]**	list of devices under a device-group to be fetched	[optional]
color	str	Color of events.	[optional]

****list[Event]****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.251 retrieve_event_by_event_name_network_group

```
list[Event] retrieve_event_by_event_name_network_group(event_name, from_timestamp, network_group_name, x_iam_token=x_iam_token, to_timestamp=to_timestamp, granularity=granularity, color=color)
```

Get instances of a network-group event.

Get instances of a specified network-group event. Filtering is possible with the use of various query parameters.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
event_name = 'event_name_example' # str | Name of event
from_timestamp = '2013-10-20T19:20:30+01:00' # datetime | Starting timestamp
network_group_name = 'network_group_name_example' # str | network_group_name of the_
↳network-group for which events are requested
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
to_timestamp = '2013-10-20T19:20:30+01:00' # datetime | Ending timestamp (optional)
granularity = 'granularity_example' # str | Granularity of query (optional)
color = 'color_example' # str | Color of events. (optional)

try:
    # Get instances of a network-group event.
    api_response = api_instance.retrieve_event_by_event_name_network_group(event_name,
↳ from_timestamp, network_group_name, x_iam_token=x_iam_token, to_timestamp=to_
↳timestamp, granularity=granularity, color=color)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_event_by_event_name_network_
↳group: %s\n" % e)
```

Name	Type	Description	Notes
event_name	str	Name of event	
from_timestamp	date-time	Starting timestamp	
net-work_group_name	str	network_group_name of the network-group for which events are requested	
x_iam_token	str	authentication header object	[optional]
to_timestamp	date-time	Ending timestamp	[optional]
granularity	str	Granularity of query	[optional]
color	str	Color of events.	[optional]

****list[Event]****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.252 retrieve_event_device_group

```
list[Event] retrieve_event_device_group(from_timestamp, device_group_name,
x_iam_token=x_iam_token, to_timestamp=to_timestamp, granularity=granularity, device_id=device_id,
color=color)
```

Get all events for a device-group.

Get the list of events for a device-group. Filtering is possible with the use of various query parameters.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
from_timestamp = '2013-10-20T19:20:30+01:00' # datetime | Starting timestamp
device_group_name = 'device_group_name_example' # str | device_group_name of the
↳device-group for which events are requested
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
to_timestamp = '2013-10-20T19:20:30+01:00' # datetime | Ending timestamp (optional)
granularity = 'granularity_example' # str | Granularity of query (optional)
device_id = ['device_id_example'] # list[str] | list of devices under a device-group
↳to be fetched (optional)
color = 'color_example' # str | Color of events. (optional)

try:
    # Get all events for a device-group.
    api_response = api_instance.retrieve_event_device_group(from_timestamp, device_
↳group_name, x_iam_token=x_iam_token, to_timestamp=to_timestamp,
↳granularity=granularity, device_id=device_id, color=color)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_event_device_group: %s\n" % e)
```

Name	Type	Description	Notes
from_timestamp	datetime	Starting timestamp	
device_group_name	str	device_group_name of the device-group for which events are requested	
x_iam_token	str	authentication header object	[optional]
to_timestamp	datetime	Ending timestamp	[optional]
granularity	str	Granularity of query	[optional]
device_id	**list[str]**	list of devices under a device-group to be fetched	[optional]
color	str	Color of events.	[optional]

****list[Event]****

No authorization required

- **Content-Type:** application/json, multipart/form-data

- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.253 retrieve_event_network_group

```
list[Event] retrieve_event_network_group(from_timestamp, network_group_name,
x_iam_token=x_iam_token, to_timestamp=to_timestamp, granularity=granularity, color=color)
```

Get all events for a network-group.

Get the list of events for a network-group. Filtering is possible with the use of various query parameters.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
from_timestamp = '2013-10-20T19:20:30+01:00' # datetime | Starting timestamp
network_group_name = 'network_group_name_example' # str | network_group_name of the
↳network-group for which events are requested
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
to_timestamp = '2013-10-20T19:20:30+01:00' # datetime | Ending timestamp (optional)
granularity = 'granularity_example' # str | Granularity of query (optional)
color = 'color_example' # str | Color of events. (optional)

try:
    # Get all events for a network-group.
    api_response = api_instance.retrieve_event_network_group(from_timestamp, network_
↳group_name, x_iam_token=x_iam_token, to_timestamp=to_timestamp,
↳granularity=granularity, color=color)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_event_network_group: %s\n" % e)
```

Name	Type	Description	Notes
from_timestamp	date-time	Starting timestamp	
net-work_group_name	str	network_group_name of the network-group for which events are requested	
x_iam_token	str	authentication header object	[optional]
to_timestamp	date-time	Ending timestamp	[optional]
granularity	str	Granularity of query	[optional]
color	str	Color of events.	[optional]

****list[Event]****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.254 retrieve_events

```
list[Event] retrieve_events(from_timestamp, x_iam_token=x_iam_token, to_timestamp=to_timestamp,
                           color=color)
```

Get all events.

Get the list of all events. Filtering is possible with the use of various query parameters.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
from_timestamp = '2013-10-20T19:20:30+01:00' # datetime | Starting timestamp
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
to_timestamp = '2013-10-20T19:20:30+01:00' # datetime | Ending timestamp (optional)
color = 'color_example' # str | Color of events. (optional)

try:
    # Get all events.
    api_response = api_instance.retrieve_events(from_timestamp, x_iam_token=x_iam_
    token, to_timestamp=to_timestamp, color=color)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_events: %s\n" % e)
```

Name	Type	Description	Notes
from_timestamp	datetime	Starting timestamp	
x_iam_token	str	authentication header object	[optional]
to_timestamp	datetime	Ending timestamp	[optional]
color	str	Color of events.	[optional]

****list[Event]****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.255 retrieve_files_certificates_by_file_name

```
file retrieve_files_certificates_by_file_name(file_name, x_iam_token=x_iam_token, in-
put_path=input_path, certificate_type=certificate_type)
```

Download a certificate-file.

Download the specified certificate-file.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
file_name = 'file_name_example' # str | File name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
input_path = 'input_path_example' # str | Input path (optional)
certificate_type = 'certificate_type_example' # str | Certificate type (optional)

try:
    # Download a certificate-file.
    api_response = api_instance.retrieve_files_certificates_by_file_name(file_name, x_
↳ iam_token=x_iam_token, input_path=input_path, certificate_type=certificate_type)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_files_certificates_by_file_
↳ name: %s\n" % e)
```

Name	Type	Description	Notes
file_name	str	File name	
x_iam_token	str	authentication header object	[optional]
input_path	str	Input path	[optional]
certificate_type	str	Certificate type	[optional]

****file****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/octet-stream, application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.256 retrieve_files_helper_files

list[str] retrieve_files_helper_files(x_iam_token=x_iam_token, input_path=input_path)

Get all helper-file names.

Get a list of all the helper-file file-names.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
```

(continues on next page)

(continued from previous page)

```

api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
input_path = 'input_path_example' # str | Input path (optional)

try:
    # Get all helper-file names.
    api_response = api_instance.retrieve_files_helper_files(x_iam_token=x_iam_token,
↳input_path=input_path)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_files_helper_files: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
input_path	str	Input path	[optional]

list[str]

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.257 retrieve_files_helper_files_by_file_name

```

file      retrieve_files_helper_files_by_file_name(file_name,      x_iam_token=x_iam_token,      in-
put_path=input_path)

```

Download a helper-file.

Download the specified helper-file.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
file_name = 'file_name_example' # str | File name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
input_path = 'input_path_example' # str | Input path (optional)

try:
    # Download a helper-file.
    api_response = api_instance.retrieve_files_helper_files_by_file_name(file_name, x_
↳iam_token=x_iam_token, input_path=input_path)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_files_helper_files_by_file_
↳name: %s\n" % e)

```

Name	Type	Description	Notes
file_name	str	File name	
x_iam_token	str	authentication header object	[optional]
input_path	str	Input path	[optional]

****file****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/octet-stream, application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.258 retrieve_health_all

HealthSchema retrieve_health_all(x_iam_token=x_iam_token)

Return a dict with health of devices in device groups and network groups

Returns health of network-groups and devices in device-groups

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Return a dict with health of devices in device groups and network groups
    api_response = api_instance.retrieve_health_all(x_iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_health_all: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

****HealthSchema****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.259 retrieve_health_tree_by_device_group

DeviceGroupHealthTree retrieve_health_tree_by_device_group(device_group_name,
x_iam_token=x_iam_token, timestamp=timestamp, tolerance=tolerance, device=device)

Get device-group health-tree.

Get health-tree of a specified device-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
device_group_name = 'device_group_name_example' # str | `device-group-name` of device-
↳group
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
timestamp = '2013-10-20T19:20:30+01:00' # datetime | Timestamp at which health tree
↳is requested. If not specified, current server timestamp is used. (optional)
tolerance = 789 # int | Timestamp tolerance in seconds. With this option, health-tree
↳will contain latest data between `timestamp-2*tolerance` and `timestamp`. Default
↳value is `2*frequency` where `frequency` is extracted from `trigger`. (optional)
device = ['device_example'] # list[str] | list of devices under a device-group to be
↳fetched (optional)

try:
    # Get device-group health-tree.
    api_response = api_instance.retrieve_health_tree_by_device_group(device_group_
↳name, x_iam_token=x_iam_token, timestamp=timestamp, tolerance=tolerance,
↳device=device)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_health_tree_by_device_group:
↳%s\n" % e)
```

Name	Type	Description	Notes
device_group_name	str	`device-group-name` of device-group	
x_iam_token	str	authentication header object	[optional]
timestamp	datetime	Timestamp at which health tree is requested. If not specified, current server timestamp is used.	[optional]
tolerance	int	Timestamp tolerance in seconds. With this option, health-tree will contain latest data between `timestamp-2tolerance` and `timestamp`. Default value is `2frequency` where `frequency` is extracted from `trigger`.	[optional]
device	list[str]	list of devices under a device-group to be fetched	[optional]

DeviceGroupHealthTree

No authorization required

- **Content-Type:** application/json, multipart/form-data

- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.260 retrieve_health_tree_by_id

DeviceHealthTree retrieve_health_tree_by_id(device_id, x_iam_token=x_iam_token, timestamp=timestamp, tolerance=tolerance)

Return a device's health-tree.

Return health-tree of a specified device identified by device-id.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
device_id = 'device_id_example' # str | `device-id` of device
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
timestamp = '2013-10-20T19:20:30+01:00' # datetime | Timestamp at which health tree
↳ is requested. If not specified, current server timestamp is used. (optional)
tolerance = 789 # int | Timestamp tolerance in seconds. With this option, health-tree
↳ will contain latest data between `timestamp-2*tolerance` and `timestamp`. Default
↳ value is `2*frequency` where `frequency` is extracted from `trigger`. (optional)

try:
    # Return a device's health-tree.
    api_response = api_instance.retrieve_health_tree_by_id(device_id, x_iam_token=x_
↳ iam_token, timestamp=timestamp, tolerance=tolerance)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_health_tree_by_id: %s\n" % e)
```

Name	Type	Description	Notes
device_id	str	`device-id` of device	
x_iam_token		authentication header object	[optional]
timestamp	datetime	Timestamp at which health tree is requested. If not specified, current server timestamp is used.	[optional]
tolerance	int	Timestamp tolerance in seconds. With this option, health-tree will contain latest data between `timestamp-2tolerance` and `timestamp`. Default value is `2frequency` where `frequency` is extracted from `trigger`.	[optional]

****DeviceHealthTree****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.261 retrieve_health_tree_by_network_group

```
NetworkHealthTree.retrieve_health_tree_by_network_group(network_group_name,
x_iam_token=x_iam_token, timestamp=timestamp, tolerance=tolerance)
```

Get network-group health-tree.

Get health-tree of a specified network-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
network_group_name = 'network_group_name_example' # str | `network-group-name` of
↳network-group
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
timestamp = '2013-10-20T19:20:30+01:00' # datetime | Timestamp at which health tree
↳is requested. If not specified, current server timestamp is used. (optional)
tolerance = 789 # int | Timestamp tolerance in seconds. With this option, health-tree
↳will contain latest data between `timestamp-2*tolerance` and `timestamp`. Default
↳value is `2*frequency` where `frequency` is extracted from `trigger`. (optional)

try:
    # Get network-group health-tree.
    api_response = api_instance.retrieve_health_tree_by_network_group(network_group_
↳name, x_iam_token=x_iam_token, timestamp=timestamp, tolerance=tolerance)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_health_tree_by_network_group:
↳%s\n" % e)
```

Name	Type	Description	Notes
network_group_name	str	`network-group-name`; of network-group	
x_iam_token	str	authentication header object	[optional]
timestamp	datetime	Timestamp at which health tree is requested. If not specified, current server timestamp is used.	[optional]
tolerance	int	Timestamp tolerance in seconds. With this option, health-tree will contain latest data between `timestamp-2tolerance`; and `timestamp`,. Default value is `2frequency`; where `frequency`; is extracted from `trigger`.	[optional]

****NetworkHealthTree****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.262 retrieve_healthbot_deployment_deployment

DeploymentSchema retrieve_healthbot_deployment_deployment(x_iam_token=x_iam_token, working=working)

Retrieve deployment

Retrieve operation of resource: deployment

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve deployment
    api_response = api_instance.retrieve_healthbot_deployment_deployment(x_iam_
↪token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_deployment_
↪deployment: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****DeploymentSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.263 retrieve_healthbot_device_details_by_uuids

DeviceDetailsSchema retrieve_healthbot_device_details_by_uuids(uuid_object, x_iam_token=x_iam_token)

Get device-identifying details by for specified UUIDs.

Get device-identifying details (device-id and TSDB databases if playbooks are deployed on it) for all the UUIDs present in the request body.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
uuid_object = swagger_client.UuidObject() # UuidObject | device_uuids object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Get device-identifying details by for specified UUIDs.
    api_response = api_instance.retrieve_healthbot_device_details_by_uuids(uuid_
↪object, x_iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_device_details_by_
↪uuids: %s\n" % e)

```

Name	Type	Description	Notes
uuid_object	**UuidObject**	device_uuids object	
x_iam_token	str	authentication header object	[optional]

****DeviceDetailsSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.264 retrieve_healthbot_dynamic_tagging

list[str] retrieve_healthbot_dynamic_tagging(x_iam_token=x_iam_token)

Retrieve dynamic-tagging by ID

Retrieve operation of resource: dynamic-tagging

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Retrieve dynamic-tagging by ID
    api_response = api_instance.retrieve_healthbot_dynamic_tagging(x_iam_token=x_iam_
↪token)

```

(continues on next page)

(continued from previous page)

```

pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_dynamic_tagging: %s\n"
    ↪ " % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.265 retrieve_healthbot_ingest_byoi_custom_plugin_by_id

CustomPluginSchema retrieve_healthbot_ingest_byoi_custom_plugin_by_id(name,
x_iam_token=x_iam_token, working=working)

Retrieve custom-plugin by ID

Retrieve operation of resource: custom-plugin

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of custom-plugin
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve custom-plugin by ID
    api_response = api_instance.retrieve_healthbot_ingest_byoi_custom_plugin_by_
    ↪ id(name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_byoi_custom_
    ↪ plugin_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of custom-plugin	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****CustomPluginSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.266 retrieve_healthbot_ingest_byoi_custom_plugins

CustomPluginSchema retrieve_healthbot_ingest_byoi_custom_plugins(x_iam_token=x_iam_token,
working=working)

Retrieve custom-plugin by ID

Retrieve all the custom-plugins configured.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve custom-plugin by ID
    api_response = api_instance.retrieve_healthbot_ingest_byoi_custom_plugins(x_iam_
↪token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_byoi_custom_
↪plugins: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****CustomPluginSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.267 retrieve_healthbot_ingest_byoi_default_plugin_tlive_kafka_by_id

TliveKafkaOcSchema retrieve_healthbot_ingest_byoi_default_plugin_tlive_kafka_by_id(name,
x_iam_token=x_iam_token, working=working)

Retrieve tlive-kafka-oc by ID

Retrieve operation of resource: tlive-kafka-oc

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of tlive-kafka-oc
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve tlive-kafka-oc by ID
    api_response = api_instance.retrieve_healthbot_ingest_byoi_default_plugin_tlive_
    kafka_by_id(name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_byoi_default_
    plugin_tlive_kafka_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of tlive-kafka-oc	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****TliveKafkaOcSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.268 retrieve_healthbot_ingest_byoi_default_plugin_tlive_kafkas

```
list[str] retrieve_healthbot_ingest_byoi_default_plugin_tlive_kafkas(x_iam_token=x_iam_token, work-
ing=working)
```

Retrieve tlive-kafka-oc

Retrieve all the tlive-kafka-ocs configured.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
```

(continues on next page)

(continued from previous page)

```

x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve tlive-kafka-oc
    api_response = api_instance.retrieve_healthbot_ingest_byoi_default_plugin_tlive_
↳kafkas(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_byoi_default_
↳plugin_tlive_kafkas: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.269 retrieve_healthbot_ingest_byoi_ingest_mapping_by_id

```

IngestMappingSchema      retrieve_healthbot_ingest_byoi_ingest_mapping_by_id(name,
x_iam_token=x_iam_token, working=working)

```

Retrieve ingest-mapping by ID

Retrieve ingest-mapping by name

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of ingest-mapping
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve ingest-mapping by ID
    api_response = api_instance.retrieve_healthbot_ingest_byoi_ingest_mapping_by_
↳id(name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_byoi_ingest_
↳mapping_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of ingest-mapping	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****IngestMappingSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.270 retrieve_healthbot_ingest_byoi_ingest_mappings

```
list[str] retrieve_healthbot_ingest_byoi_ingest_mappings(x_iam_token=x_iam_token, working=working)
```

Retrieve ingest-mapping

Retrieve all the ingest mappings configured.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve ingest-mapping
    api_response = api_instance.retrieve_healthbot_ingest_byoi_ingest_mappings(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_byoi_ingest_mappings: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.271 retrieve_healthbot_ingest_frequency_profile

```
list[str] retrieve_healthbot_ingest_frequency_profile(x_iam_token=x_iam_token, working=working)
```

Retrieve frequency-profile

Retrieve operation of resource: frequency-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve frequency-profile
    api_response = api_instance.retrieve_healthbot_ingest_frequency_profile(x_iam_
↪token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_frequency_
↪profile: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.272 retrieve_healthbot_ingest_frequency_profile_by_id

```
FrequencyProfileSchema retrieve_healthbot_ingest_frequency_profile_by_id(name,
x_iam_token=x_iam_token, working=working)
```

Retrieve frequency-profile by ID

Retrieve operation of resource: frequency-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint
```

(continues on next page)

(continued from previous page)

```
# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | ID of name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve frequency-profile by ID
    api_response = api_instance.retrieve_healthbot_ingest_frequency_profile_by_
    ↪id(name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_frequency_
    ↪profile_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	ID of name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****FrequencyProfileSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.273 retrieve_healthbot_ingest_outbound_ssh

OutboundSshSchema retrieve_healthbot_ingest_outbound_ssh(working=working,
x_iam_token=x_iam_token)

Retrieve outbound-ssh

Retrieve operation of resource: outbound-ssh

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
working = true # bool | true queries undeployed configuration (optional)
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Retrieve outbound-ssh
    api_response = api_instance.retrieve_healthbot_ingest_outbound_
    ↪ssh(working=working, x_iam_token=x_iam_token)
```

(continues on next page)

(continued from previous page)

```

pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_outbound_ssh:
↪ %s\n" % e)

```

Name	Type	Description	Notes
working	bool	true queries undeployed configuration	[optional]
x_iam_token	str	authentication header object	[optional]

****OutboundSshSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.274 retrieve_healthbot_ingest_settings_byoi_custom_plugin_by_id

CustomPluginSchema retrieve_healthbot_ingest_settings_byoi_custom_plugin_by_id(name,
x_iam_token=x_iam_token, working=working)

Retrieve custom-plugin by ID

Retrieve operation of resource: custom-plugin

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of custom-plugin
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve custom-plugin by ID
    api_response = api_instance.retrieve_healthbot_ingest_settings_byoi_custom_plugin_
↪by_id(name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_settings_byoi_
↪custom_plugin_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of custom-plugin	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****CustomPluginSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.275 retrieve_healthbot_ingest_settings_byoi_custom_plugins

CustomPluginSchema retrieve_healthbot_ingest_settings_byoi_custom_plugins(x_iam_token=x_iam_token, working=working)

Retrieve custom-plugin by ID

Retrieve all the custom-plugins configured.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve custom-plugin by ID
    api_response = api_instance.retrieve_healthbot_ingest_settings_byoi_custom_
↳ plugins(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_settings_byoi_
↳ custom_plugins: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****CustomPluginSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.276 retrieve_healthbot_ingest_settings_byoi_default_plugin_tlive_kafka_by_id

TliveKafkaOcSchema retrieve_healthbot_ingest_settings_byoi_default_plugin_tlive_kafka_by_id(name, x_iam_token=x_iam_token, working=working)

Retrieve tlive-kafka-oc by ID

Retrieve operation of resource: tlive-kafka-oc

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of tlive-kafka-oc
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve tlive-kafka-oc by ID
    api_response = api_instance.retrieve_healthbot_ingest_settings_byoi_default_
    plugin_tlive_kafka_by_id(name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_settings_byoi_
    default_plugin_tlive_kafka_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of tlive-kafka-oc	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****TliveKafkaOcSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.277 retrieve_healthbot_ingest_settings_byoi_default_plugin_tlive_kafkas

```
list[str] retrieve_healthbot_ingest_settings_byoi_default_plugin_tlive_kafkas(x_iam_token=x_iam_token,
working=working)
```

Retrieve tlive-kafka-oc

Retrieve all the tlive-kafka-ocs configured.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
```

(continues on next page)

(continued from previous page)

```

x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve tlive-kafka-oc
    api_response = api_instance.retrieve_healthbot_ingest_settings_byoi_default_
    ↪plugin_tlive_kafkas(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_settings_byoi_
    ↪default_plugin_tlive_kafkas: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.278 retrieve_healthbot_ingest_settings_byoi_ingest_mapping_by_id

```

IngestMappingSchema      retrieve_healthbot_ingest_settings_byoi_ingest_mapping_by_id(name,
x_iam_token=x_iam_token, working=working)

```

Retrieve ingest-mapping by ID

Retrieve ingest-mapping by name

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of ingest-mapping
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve ingest-mapping by ID
    api_response = api_instance.retrieve_healthbot_ingest_settings_byoi_ingest_
    ↪mapping_by_id(name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_settings_byoi_
    ↪ingest_mapping_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of ingest-mapping	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****IngestMappingSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.279 retrieve_healthbot_ingest_settings_byoi_ingest_mappings

```
list[str] retrieve_healthbot_ingest_settings_byoi_ingest_mappings(x_iam_token=x_iam_token, working=working)
```

Retrieve ingest-mapping

Retrieve all the ingest mappings configured.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve ingest-mapping
    api_response = api_instance.retrieve_healthbot_ingest_settings_byoi_ingest_
    mappings(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_settings_byoi_
    ingest_mappings: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.280 retrieve_healthbot_ingest_settings_frequency_profile

```
list[str] retrieve_healthbot_ingest_settings_frequency_profile(x_iam_token=x_iam_token, working=working)
```

Retrieve frequency-profile

Retrieve operation of resource: frequency-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve frequency-profile
    api_response = api_instance.retrieve_healthbot_ingest_settings_frequency_
    profile(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_settings_
    frequency_profile: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.281 retrieve_healthbot_ingest_settings_frequency_profile_by_id

```
FrequencyProfileSchema retrieve_healthbot_ingest_settings_frequency_profile_by_id(name, x_iam_token=x_iam_token, working=working)
```

Retrieve frequency-profile by ID

Retrieve operation of resource: frequency-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
```

(continues on next page)

(continued from previous page)

```

from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | ID of name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve frequency-profile by ID
    api_response = api_instance.retrieve_healthbot_ingest_settings_frequency_profile_
    by_id(name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_settings_
    frequency_profile_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	ID of name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****FrequencyProfileSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.282 retrieve_healthbot_ingest_settings_tagging_profile_by_id

TaggingProfileSchema retrieve_healthbot_ingest_settings_tagging_profile_by_id(name, x_iam_token=x_iam_token, working=working)

Retrieve tagging-profile by ID

Retrieve operation of resource: tagging-profile

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | ID of name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve tagging-profile by ID

```

(continues on next page)

(continued from previous page)

```

    api_response = api_instance.retrieve_healthbot_ingest_settings_tagging_profile_by_
    ↪id(name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_settings_
    ↪tagging_profile_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	ID of name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****TaggingProfileSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.283 retrieve_healthbot_ingest_settings_tagging_profiles

```
list[str]    retrieve_healthbot_ingest_settings_tagging_profiles(x_iam_token=x_iam_token,    work-
ing=working)
```

Retrieve tagging-profile by ID

Retrieve operation of resource: tagging-profile

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve tagging-profile by ID
    api_response = api_instance.retrieve_healthbot_ingest_settings_tagging_profiles(x_
    ↪iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_settings_
    ↪tagging_profiles: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.284 retrieve_healthbot_ingest_sflow

SflowSchema retrieve_healthbot_ingest_sflow(x_iam_token=x_iam_token, working=working)

Retrieve sflow

Retrieve operation of resource: sflow

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve sflow
    api_response = api_instance.retrieve_healthbot_ingest_sflow(x_iam_token=x_iam_
↪token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_sflow: %s\n"
↪% e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****SflowSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.285 retrieve_healthbot_ingest_sflow_counter_record_by_id

CounterRecordSchema retrieve_healthbot_ingest_sflow_counter_record_by_id(record_name, x_iam_token=x_iam_token, working=working)

Retrieve counter-record by ID

Retrieve operation of resource: counter-record

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
record_name = 'record_name_example' # str | ID of record-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve counter-record by ID
    api_response = api_instance.retrieve_healthbot_ingest_sflow_counter_record_by_
↪id(record_name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_sflow_counter_
↪record_by_id: %s\n" % e)
```

Name	Type	Description	Notes
record_name	str	ID of record-name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****CounterRecordSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.286 retrieve_healthbot_ingest_sflow_flow_record_by_id

```
FlowRecordSchema retrieve_healthbot_ingest_sflow_flow_record_by_id(record_name,
x_iam_token=x_iam_token, working=working)
```

Retrieve flow-record by ID

Retrieve operation of resource: flow-record

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
```

(continues on next page)

(continued from previous page)

```

record_name = 'record_name_example' # str | ID of record-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve flow-record by ID
    api_response = api_instance.retrieve_healthbot_ingest_sflow_flow_record_by_
    ↪id(record_name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_sflow_flow_
    ↪record_by_id: %s\n" % e)

```

Name	Type	Description	Notes
record_name	str	ID of record-name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****FlowRecordSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.287 retrieve_healthbot_ingest_sflow_protocol_by_id

```

ProtocolSchema                                retrieve_healthbot_ingest_sflow_protocol_by_id(protocol_name,
x_iam_token=x_iam_token, working=working)

```

Retrieve protocol by ID

Retrieve operation of resource: protocol

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
protocol_name = 'protocol_name_example' # str | ID of protocol-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve protocol by ID
    api_response = api_instance.retrieve_healthbot_ingest_sflow_protocol_by_
    ↪id(protocol_name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)

```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_sflow_
↳protocol_by_id: %s\n" % e)
```

Name	Type	Description	Notes
protocol_name	str	ID of protocol-name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****ProtocolSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.288 retrieve_healthbot_ingest_sflow_sample_by_id

SampleSchema retrieve_healthbot_ingest_sflow_sample_by_id(sample_name,
x_iam_token=x_iam_token, working=working)

Retrieve sample by ID

Retrieve operation of resource: sample

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
sample_name = 'sample_name_example' # str | ID of sample-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve sample by ID
    api_response = api_instance.retrieve_healthbot_ingest_sflow_sample_by_id(sample_
↳name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_sflow_sample_
↳by_id: %s\n" % e)
```

Name	Type	Description	Notes
sample_name	str	ID of sample-name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****SampleSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.289 retrieve_healthbot_ingest_snmp_notification

`SnmpNotificationSchema` `retrieve_healthbot_ingest_snmp_notification(x_iam_token=x_iam_token, working=working)`

Retrieve snmp-notification

Retrieve operation of resource: snmp-notification

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve snmp-notification
    api_response = api_instance.retrieve_healthbot_ingest_snmp_notification(x_iam_
↳token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_snmp_
↳notification: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****SnmpNotificationSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.290 retrieve_healthbot_ingest_snmp_notification_v3_usm_user_by_id

`Snmpv3UsmUserSchema` `retrieve_healthbot_ingest_snmp_notification_v3_usm_user_by_id(name, x_iam_token=x_iam_token, working=working)`

Retrieve SNMPv3 user by UserName(ID)

Retrieve operation of resource: snmp v3 usm user

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | User Name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve SNMPv3 user by UserName(ID)
    api_response = api_instance.retrieve_healthbot_ingest_snmp_notification_v3_usm_
    user_by_id(name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_snmp_
    notification_v3_usm_user_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	User Name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****Snmv3UsmUserSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.291 retrieve_healthbot_ingest_snmp_notification_v3_usm_usernames

```
list[str] retrieve_healthbot_ingest_snmp_notification_v3_usm_usernames(x_iam_token=x_iam_token,
working=working)
```

Retrieve snmp v3 usm user names

Retrieve operation of resource: snmp v3 usm user names

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
```

(continues on next page)

(continued from previous page)

```

x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve snmp v3 usm user names
    api_response = api_instance.retrieve_healthbot_ingest_snmp_notification_v3_usm_
↳ usernames(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_snmp_
↳ notification_v3_usm_usernames: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.292 retrieve_healthbot_ingest_snmp_notification_v3_usm_users

```
list[Snmpv3UsmUsersSchema] retrieve_healthbot_ingest_snmp_notification_v3_usm_users(x_iam_token=x_iam_token,
working=working)
```

Retrieve SNMP v3 USM users

Retrieve operation of resource: SNMP v3 USM users

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve SNMP v3 USM users
    api_response = api_instance.retrieve_healthbot_ingest_snmp_notification_v3_usm_
↳ users(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_snmp_
↳ notification_v3_usm_users: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

```
**list[Snmpv3UsmUsersSchema]**
```

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.293 retrieve_healthbot_ingest_syslog_header_pattern_by_id

HeaderPatternSchema retrieve_healthbot_ingest_syslog_header_pattern_by_id(name, x_iam_token=x_iam_token, working=working)

Retrieve pattern by ID

Retrieve operation of resource: header-pattern

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | ID of name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve pattern by ID
    api_response = api_instance.retrieve_healthbot_ingest_syslog_header_pattern_by_
↪id(name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_syslog_header_
↪pattern_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	ID of name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

```
**HeaderPatternSchema**
```

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.294 retrieve_healthbot_ingest_syslog_header_pattern_ids

```
list[str] retrieve_healthbot_ingest_syslog_header_pattern_ids(x_iam_token=x_iam_token,
                                                             working=working)
```

Retrieve header pattern names

Retrieve operation of resource: header-pattern

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve header pattern names
    api_response = api_instance.retrieve_healthbot_ingest_syslog_header_pattern_ids(x_
    iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_syslog_header_
    pattern_ids: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.295 retrieve_healthbot_ingest_syslog_header_patterns

```
list[HeaderPatternSchema] retrieve_healthbot_ingest_syslog_header_patterns(x_iam_token=x_iam_token,
                                                                            working=working)
```

Retrieve header patterns

Retrieve operation of resource: pattern

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve header patterns
    api_response = api_instance.retrieve_healthbot_ingest_syslog_header_patterns(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_syslog_header_patterns: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****list[HeaderPatternSchema]****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.296 retrieve_healthbot_ingest_tagging_profile_by_id

TaggingProfileSchema retrieve_healthbot_ingest_tagging_profile_by_id(name, x_iam_token=x_iam_token, working=working)

Retrieve tagging-profile by ID

Retrieve operation of resource: tagging-profile

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | ID of name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:

```

(continues on next page)

(continued from previous page)

```

# Retrieve tagging-profile by ID
api_response = api_instance.retrieve_healthbot_ingest_tagging_profile_by_id(name,
↳x_iam_token=x_iam_token, working=working)
pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_tagging_
↳profile_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	ID of name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****TaggingProfileSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.297 retrieve_healthbot_ingest_tagging_profiles

list[str] retrieve_healthbot_ingest_tagging_profiles(x_iam_token=x_iam_token, working=working)

Retrieve tagging-profile by ID

Retrieve operation of resource: tagging-profile

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve tagging-profile by ID
    api_response = api_instance.retrieve_healthbot_ingest_tagging_profiles(x_iam_
↳token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_ingest_tagging_
↳profiles: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.298 retrieve_healthbot_organization_organization

list[str] retrieve_healthbot_organization_organization(working=working)

Retrieve organization

Retrieve operation of resource: organization

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve organization
    api_response = api_instance.retrieve_healthbot_organization_
↪organization(working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_organization_
↪organization: %s\n" % e)
```

Name	Type	Description	Notes
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.299 retrieve_healthbot_organization_organization_by_id

OrganizationSchema retrieve_healthbot_organization_organization_by_id(organization_name, x_iam_token=x_iam_token, working=working)

Retrieve organization by ID

Retrieve operation of resource: organization

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
organization_name = 'organization_name_example' # str | ID of organization-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve organization by ID
    api_response = api_instance.retrieve_healthbot_organization_organization_by_
    id(organization_name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_organization_
    organization_by_id: %s\n" % e)
```

Name	Type	Description	Notes
organization_name	str	ID of organization-name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****OrganizationSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.300 retrieve_healthbot_profile_rollup_summarization_field_profile_field_profile

RollupSummarizationSchema retrieve_healthbot_profile_rollup_summarization_field_profile_field_profile_by_id(profile_id, working=working, x_iam_token=x_iam_token)

Retrieve field-profile by ID

Retrieve operation of resource: field-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
```

(continues on next page)

(continued from previous page)

```

profile_id = 'profile_id_example' # str | ID of profile-id
working = true # bool | true queries undeployed configuration (optional)
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Retrieve field-profile by ID
    api_response = api_instance.retrieve_healthbot_profile_rollup_summarization_field_
    ↪profile_field_profile_by_id(profile_id, working=working, x_iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_profile_rollup_
    ↪summarization_field_profile_field_profile_by_id: %s\n" % e)

```

Name	Type	Description	Notes
profile_id	str	ID of profile-id	
working	bool	true queries undeployed configuration	[optional]
x_iam_token	str	authentication header object	[optional]

****RollupSummarizationSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.301 retrieve_healthbot_profile_rollup_summarization_field_profile_profile

RollupSummarizationsSchema retrieve_healthbot_profile_rollup_summarization_field_profile_profile(working=working, x_iam_token=x_iam_token)

Retrieve field-profile

Retrieve operation of resource: field-profile

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
working = true # bool | true queries undeployed configuration (optional)
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Retrieve field-profile
    api_response = api_instance.retrieve_healthbot_profile_rollup_summarization_field_
    ↪profile_profile(working=working, x_iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_profile_rollup_
    ↪summarization_field_profile_profile: %s\n" % e)

```

(continues on next page)

(continued from previous page)

Name	Type	Description	Notes
working	bool	true queries undeployed configuration	[optional]
x_iam_token	str	authentication header object	[optional]

****RollupSummarizationsSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.302 retrieve_healthbot_system_time_series_database_time_series_database

TsdSchema retrieve_healthbot_system_time_series_database_time_series_database(working=working)

Retrieve time-series-database

Retrieve operation of resource: time-series-database

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve time-series-database
    api_response = api_instance.retrieve_healthbot_system_time_series_database_time_
↪series_database(working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_system_time_series_
↪database_time_series_database: %s\n" % e)
```

Name	Type	Description	Notes
working	bool	true queries undeployed configuration	[optional]

****TsdSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.303 retrieve_healthbot_system_trigger_action

TriggerActionSchema retrieve_healthbot_system_trigger_action(working=working)

Retrieve trigger-action

Retrieve operation of resource: trigger-action

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve trigger-action
    api_response = api_instance.retrieve_healthbot_system_trigger_
    ↪action(working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_system_trigger_
    ↪action: %s\n" % e)
```

Name	Type	Description	Notes
working	bool	true queries undeployed configuration	[optional]

****TriggerActionSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.304 retrieve_healthbot_topic_resource_resource

list[str] retrieve_healthbot_topic_resource_resource(topic_name, authorization=authorization, working=working)

List all resource-names in a topic

Get a list of all the resource-name's in a topic

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
```

(continues on next page)

(continued from previous page)

```

api_instance = swagger_client.DefaultApi()
topic_name = 'topic_name_example' # str | ID of topic-name
authorization = 'authorization_example' # str | authentication header object,
↳ (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # List all resource-names in a topic
    api_response = api_instance.retrieve_healthbot_topic_resource_resource(topic_name,
↳ authorization=authorization, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_topic_resource_
↳ resource: %s\n" % e)

```

Name	Type	Description	Notes
topic_name	str	ID of topic-name	
authorization	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.305 retrieve_healthbot_topic_resource_resource_by_id

ResourceSchema retrieve_healthbot_topic_resource_resource_by_id(topic_name, resource_name, authorization=authorization, working=working, download=download)

Get a resource's configuration

Get the configuration details of a resource by resource-name

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
topic_name = 'topic_name_example' # str | ID of topic-name
resource_name = 'resource_name_example' # str | ID of resource-name
authorization = 'authorization_example' # str | authentication header object,
↳ (optional)
working = True # bool | true queries un-committed configuration (optional)
download = True # bool | Download a compressed .resource file (optional)

try:

```

(continues on next page)

(continued from previous page)

```

# Get a resource's configuration
api_response = api_instance.retrieve_healthbot_topic_resource_resource_by_
↳id(topic_name, resource_name, authorization=authorization, working=working,
↳download=download)
pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_healthbot_topic_resource_
↳resource_by_id: %s\n" % e)

```

Name	Type	Description	Notes
topic_name	str	ID of topic-name	
resource_name	str	ID of resource-name	
authorization	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]
download	bool	Download a compressed .resource file	[optional]

****ResourceSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.306 retrieve_iceberg_ingest

IngestSettingsSchema retrieve_iceberg_ingest(x_iam_token=x_iam_token, working=working)

Retrieve ingest

Retrieve operation of resource: ingest

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve ingest
    api_response = api_instance.retrieve_iceberg_ingest(x_iam_token=x_iam_token,
↳working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****IngestSettingsSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.307 retrieve_iceberg_ingest_flow

FlowSchema retrieve_iceberg_ingest_flow(x_iam_token=x_iam_token, working=working)

Retrieve flow

Retrieve operation of resource: flow

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve flow
    api_response = api_instance.retrieve_iceberg_ingest_flow(x_iam_token=x_iam_token,
↳working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_flow: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****FlowSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.308 retrieve_iceberg_ingest_flow_template_by_id

```
TemplateSchema retrieve_iceberg_ingest_flow_template_by_id(name, x_iam_token=x_iam_token,
working=working)
```

Retrieve template by ID

Retrieve operation of resource: template

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of template
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve template by ID
    api_response = api_instance.retrieve_iceberg_ingest_flow_template_by_id(name, x_
    iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_flow_template_
    by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of template	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

TemplateSchema

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.309 retrieve_iceberg_ingest_flow_template_ids

```
list[str] retrieve_iceberg_ingest_flow_template_ids(x_iam_token=x_iam_token, working=working)
```

Retrieve template

Retrieve operation of resource: template

```
from __future__ import print_function
import time
import swagger_client
```

(continues on next page)

(continued from previous page)

```

from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve template
    api_response = api_instance.retrieve_iceberg_ingest_flow_template_ids(x_iam_
↪token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_flow_template_
↪ids: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.310 retrieve_iceberg_ingest_native_gpb

NativeGpbSchema retrieve_iceberg_ingest_native_gpb(x_iam_token=x_iam_token, working=working)

Retrieve native-gpb

Retrieve operation of resource: native-gpb

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve native-gpb
    api_response = api_instance.retrieve_iceberg_ingest_native_gpb(x_iam_token=x_iam_
↪token, working=working)
    pprint(api_response)

```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_native_gpb: %s\n"
    ↪ " % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****NativeGpbSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.311 retrieve_iceberg_ingest_settings

IngestSettingsSchema retrieve_iceberg_ingest_settings(x_iam_token=x_iam_token, working=working)

Retrieve ingest-settings

Retrieve operation of resource: ingest-settings

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve ingest-settings
    api_response = api_instance.retrieve_iceberg_ingest_settings(x_iam_token=x_iam_
    ↪ token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_settings: %s\n"
    ↪ % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****IngestSettingsSchema****

No authorization required

- **Content-Type:** application/json

- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.312 retrieve_iceberg_ingest_settings_flow

FlowSchema retrieve_iceberg_ingest_settings_flow(x_iam_token=x_iam_token, working=working)

Retrieve flow

Retrieve operation of resource: flow

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve flow
    api_response = api_instance.retrieve_iceberg_ingest_settings_flow(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_settings_flow: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****FlowSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.313 retrieve_iceberg_ingest_settings_flow_template_by_id

TemplateSchema retrieve_iceberg_ingest_settings_flow_template_by_id(name, x_iam_token=x_iam_token, working=working)

Retrieve template by ID

Retrieve operation of resource: template

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of template
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve template by ID
    api_response = api_instance.retrieve_iceberg_ingest_settings_flow_template_by_id(
        name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_settings_flow_template_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of template	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****TemplateSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.314 retrieve_iceberg_ingest_settings_flow_template_ids

```
list[str] = retrieve_iceberg_ingest_settings_flow_template_ids(x_iam_token=x_iam_token, working=working)
```

Retrieve template

Retrieve operation of resource: template

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

```

(continues on next page)

(continued from previous page)

```

try:
    # Retrieve template
    api_response = api_instance.retrieve_iceberg_ingest_settings_flow_template_ids(x_
    iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_settings_flow_
    template_ids: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.315 retrieve_iceberg_ingest_settings_syslog

SyslogSchema retrieve_iceberg_ingest_settings_syslog(x_iam_token=x_iam_token, working=working)

Retrieve syslog

Retrieve operation of resource: syslog

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve syslog
    api_response = api_instance.retrieve_iceberg_ingest_settings_syslog(x_iam_token=x_
    iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_settings_
    syslog: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****SyslogSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.316 retrieve_iceberg_ingest_settings_syslog_pattern_by_id

PatternSchema retrieve_iceberg_ingest_settings_syslog_pattern_by_id(name, x_iam_token=x_iam_token, working=working)

Retrieve pattern by ID

Retrieve operation of resource: pattern

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of pattern
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve pattern by ID
    api_response = api_instance.retrieve_iceberg_ingest_settings_syslog_pattern_by_id(
        name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_settings_syslog_pattern_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of pattern	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****PatternSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.317 retrieve_iceberg_ingest_settings_syslog_pattern_ids

```
list[str] retrieve_iceberg_ingest_settings_syslog_pattern_ids(x_iam_token=x_iam_token, working=working)
```

Retrieve pattern

Retrieve operation of resource: pattern

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve pattern
    api_response = api_instance.retrieve_iceberg_ingest_settings_syslog_pattern_ids(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_settings_syslog_pattern_ids: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.318 retrieve_iceberg_ingest_settings_syslog_pattern_set_by_id

```
PatternSetSchema retrieve_iceberg_ingest_settings_syslog_pattern_set_by_id(name, x_iam_token=x_iam_token, working=working)
```

Retrieve pattern-set by ID

Retrieve operation of resource: pattern-set

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
```

(continues on next page)

(continued from previous page)

```

from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of patter-set
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve pattern-set by ID
    api_response = api_instance.retrieve_iceberg_ingest_settings_syslog_pattern_set_
    by_id(name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_settings_syslog_
    by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of patter-set	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****PatternSetSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.319 retrieve_iceberg_ingest_settings_syslog_pattern_set_ids

```
list[str] retrieve_iceberg_ingest_settings_syslog_pattern_set_ids(x_iam_token=x_iam_token,
    working=working)
```

Retrieve pattern-set

Retrieve operation of resource: pattern-set

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve pattern-set
    api_response = api_instance.retrieve_iceberg_ingest_settings_syslog_pattern_set_
    ids(x_iam_token=x_iam_token, working=working)

```

(continues on next page)

(continued from previous page)

```

pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_settings_syslog_
    ↪pattern_set_ids: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.320 retrieve_iceberg_ingest_settings_syslog_pattern_sets

```
list[PatternSetSchema] retrieve_iceberg_ingest_settings_syslog_pattern_sets(x_iam_token=x_iam_token,
working=working)
```

Retrieve pattern-set by ID

Retrieve operation of resource: pattern-set

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve pattern-set by ID
    api_response = api_instance.retrieve_iceberg_ingest_settings_syslog_pattern_
    ↪sets(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_settings_syslog_
    ↪pattern_sets: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

```

**list[PatternSetSchema]**

```

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.321 retrieve_iceberg_ingest_settings_syslog_patterns

```
list[PatternSchema] retrieve_iceberg_ingest_settings_syslog_patterns(x_iam_token=x_iam_token, working=working)
```

Retrieve pattern by ID

Retrieve operation of resource: pattern

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve pattern by ID
    api_response = api_instance.retrieve_iceberg_ingest_settings_syslog_patterns(x_
    iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_settings_syslog_
    patterns: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****list[PatternSchema]****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.322 retrieve_iceberg_ingest_syslog

```
SyslogSchema retrieve_iceberg_ingest_syslog(x_iam_token=x_iam_token, working=working)
```

Retrieve syslog

Retrieve operation of resource: syslog


```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve syslog
    api_response = api_instance.retrieve_iceberg_ingest_syslog(x_iam_token=x_iam_
    token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_syslog: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****SyslogSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.323 retrieve_iceberg_ingest_syslog_pattern_by_id

PatternSchema retrieve_iceberg_ingest_syslog_pattern_by_id(name, x_iam_token=x_iam_token, working=working)

Retrieve pattern by ID

Retrieve operation of resource: pattern

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of pattern
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:

```

(continues on next page)

(continued from previous page)

```

# Retrieve pattern by ID
api_response = api_instance.retrieve_iceberg_ingest_syslog_pattern_by_id(name, x_
↳ iam_token=x_iam_token, working=working)
pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_syslog_pattern_
↳ by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of pattern	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****PatternSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.324 retrieve_iceberg_ingest_syslog_pattern_ids

```
list[str] retrieve_iceberg_ingest_syslog_pattern_ids(x_iam_token=x_iam_token, working=working)
```

Retrieve pattern

Retrieve operation of resource: pattern

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve pattern
    api_response = api_instance.retrieve_iceberg_ingest_syslog_pattern_ids(x_iam_
↳ token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_syslog_pattern_
↳ ids: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.325 retrieve_iceberg_ingest_syslog_pattern_set_by_id

PatternSetSchema retrieve_iceberg_ingest_syslog_pattern_set_by_id(name, x_iam_token=x_iam_token, working=working)

Retrieve pattern-set by ID

Retrieve operation of resource: pattern-set

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of pattern-set
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve pattern-set by ID
    api_response = api_instance.retrieve_iceberg_ingest_syslog_pattern_set_by_id(name,
    ↪ x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_syslog_pattern_
    ↪ set_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of pattern-set	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****PatternSetSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.326 retrieve_iceberg_ingest_syslog_pattern_set_ids

```
list[str] retrieve_iceberg_ingest_syslog_pattern_set_ids(x_iam_token=x_iam_token, working=working)
```

Retrieve pattern-set

Retrieve operation of resource: pattern-set

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve pattern-set
    api_response = api_instance.retrieve_iceberg_ingest_syslog_pattern_set_ids(x_iam_
↪token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_syslog_pattern_
↪set_ids: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.327 retrieve_iceberg_ingest_syslog_pattern_sets

```
list[PatternSetSchema] retrieve_iceberg_ingest_syslog_pattern_sets(x_iam_token=x_iam_token, work-
ing=working)
```

Retrieve pattern-set by ID

Retrieve operation of resource: pattern-set

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint
```

(continues on next page)

(continued from previous page)

```
# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve pattern-set by ID
    api_response = api_instance.retrieve_iceberg_ingest_syslog_pattern_sets(x_iam_
↪token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_syslog_pattern_
↪sets: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

```
**list[PatternSetSchema]**
```

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.328 retrieve_iceberg_ingest_syslog_patterns

```
list[PatternSchema]    retrieve_iceberg_ingest_syslog_patterns(x_iam_token=x_iam_token,    work-
ing=working)
```

Retrieve pattern by ID

Retrieve operation of resource: pattern

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve pattern by ID
    api_response = api_instance.retrieve_iceberg_ingest_syslog_patterns(x_iam_token=x_
↪iam_token, working=working)
    pprint(api_response)
```

(continues on next page)

(continued from previous page)

```

except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_ingest_syslog_
↳ patterns: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

```

**list[PatternSchema]**

```

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.329 retrieve_iceberg_profile_data_summarization_raw_by_id

RawSchema `retrieve_iceberg_profile_data_summarization_raw_by_id(name, x_iam_token=x_iam_token, working=working)`

Retrieve raw-data-summarization by ID

Retrieve operation of resource: raw-data-summarization

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of raw-data-summarization
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve raw-data-summarization by ID
    api_response = api_instance.retrieve_iceberg_profile_data_summarization_raw_by_
↳ id(name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_profile_data_
↳ summarization_raw_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of raw-data-summarization	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

```

**RawSchema**

```

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.330 retrieve_iceberg_profile_data_summarizations_raw

RawSchema retrieve_iceberg_profile_data_summarizations_raw(x_iam_token=x_iam_token, working=working)

Retrieve raw-data-summarization

Retrieve operation of resource: raw-data-summarization

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve raw-data-summarization
    api_response = api_instance.retrieve_iceberg_profile_data_summarizations_raw(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_profile_data_summarizations_raw: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****RawSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.331 retrieve_iceberg_profile_security_ca_profile_by_id

CaProfileSchema retrieve_iceberg_profile_security_ca_profile_by_id(name, x_iam_token=x_iam_token, working=working)

Retrieve ca-profile by ID

Retrieve operation of resource: ca-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of ca-profile
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve ca-profile by ID
    api_response = api_instance.retrieve_iceberg_profile_security_ca_profile_by_
    id(name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_profile_security_ca_
    profile_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of ca-profile	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****CaProfileSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.332 retrieve_iceberg_profile_security_ca_profiles

list[str] retrieve_iceberg_profile_security_ca_profiles(x_iam_token=x_iam_token, working=working)

Retrieve ca-profile

Retrieve entire ca-profiles configuration.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
```

(continues on next page)

(continued from previous page)

```

working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve ca-profile
    api_response = api_instance.retrieve_iceberg_profile_security_ca_profiles(x_iam_
↪token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_profile_security_ca_
↪profiles: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.333 retrieve_iceberg_profile_security_local_certificate_by_id

LocalCertificateSchema retrieve_iceberg_profile_security_local_certificate_by_id(name,
x_iam_token=x_iam_token, working=working)

Retrieve local-certificate by ID

Retrieve operation of resource: local-certificate

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of local-certificate
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve local-certificate by ID
    api_response = api_instance.retrieve_iceberg_profile_security_local_certificate_
↪by_id(name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_profile_security_local_
↪certificate_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of local-certificate	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****LocalCertificateSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.334 retrieve_iceberg_profile_security_local_certificates

```
list[str] retrieve_iceberg_profile_security_local_certificates(x_iam_token=x_iam_token, working=working)
```

Retrieve local-certificate

Retrieve entire local-certificates configuration.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve local-certificate
    api_response = api_instance.retrieve_iceberg_profile_security_local_
    ↪certificates(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_profile_security_local_
    ↪certificates: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.335 retrieve_iceberg_profile_security_ssh_key_profile_by_id

SshKeyProfileSchema retrieve_iceberg_profile_security_ssh_key_profile_by_id(name, authorization=authorization, working=working)

Retrieve ssh-key-profile by ID

Retrieve operation of resource: ssh-key-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of ssh-key-profile
authorization = 'authorization_example' # str | authentication header object
↳ (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve ssh-key-profile by ID
    api_response = api_instance.retrieve_iceberg_profile_security_ssh_key_profile_by_
↳ id(name, authorization=authorization, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_profile_security_ssh_
↳ key_profile_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of ssh-key-profile	
authorization	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****SshKeyProfileSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.336 retrieve_iceberg_profile_security_ssh_key_profiles

list[str] retrieve_iceberg_profile_security_ssh_key_profiles(authorization=authorization, working=working)

Retrieve ssh-key-profile

Retrieve entire ssh-key-profiles configuration.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
authorization = 'authorization_example' # str | authentication header object
↳ (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve ssh-key-profile
    api_response = api_instance.retrieve_iceberg_profile_security_ssh_key_
↳ profiles(authorization=authorization, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_profile_security_ssh_
↳ key_profiles: %s\n" % e)

```

Name	Type	Description	Notes
authorization	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.337 retrieve_iceberg_profiles

ProfilesSchema retrieve_iceberg_profiles(x_iam_token=x_iam_token, working=working)

Retrieve profile

Retrieve entire profile configuration.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve profile

```

(continues on next page)

(continued from previous page)

```

    api_response = api_instance.retrieve_iceberg_profiles(x_iam_token=x_iam_token,
↳working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_iceberg_profiles: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****ProfilesSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.338 retrieve_sensors

```
list[str] retrieve_sensors(sensor_type, x_iam_token=x_iam_token, sensor_name=sensor_name,
depth=depth, append=append, snmp_table=snmp_table)
```

List all OpenConfig sensors.

Get a list of all the sensors for the filters provided. Filtering is possible with the use of query parameters. If you have a sensor /1/2/3/4/5/6/ and sensor_name=/1 and depth=3, the result would be /2/3/4. If you use append=true, then the result would be /1/2/3/4.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
sensor_type = 'sensor_type_example' # str | Sensor type
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
sensor_name = 'sensor_name_example' # str | Sensor name prefix. (optional)
depth = 56 # int | Relative depth to the `sensor_name`. (optional)
append = True # bool | Returns full path of the sensor. (optional)
snmp_table = 'snmp_table_example' # str | Returns list of all the columns for the_
↳particular snmp_table (optional)

try:
    # List all OpenConfig sensors.
    api_response = api_instance.retrieve_sensors(sensor_type, x_iam_token=x_iam_token,
↳ sensor_name=sensor_name, depth=depth, append=append, snmp_table=snmp_table)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->retrieve_sensors: %s\n" % e)

```

Name	Type	Description	Notes
sensor_type	str	Sensor type	
x_iam_token	str	authentication header object	[optional]
sensor_name	str	Sensor name prefix.	[optional]
depth	int	Relative depth to the <code>sensor_name</code> .	[optional]
append	bool	Returns full path of the sensor.	[optional]
snmp_table	str	Returns list of all the columns for the particular <code>snmp_table</code>	[optional]

`list[str]`

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.339 update_dynamic_tagging_by_key

`update_dynamic_tagging_by_key(key_name, dynamic_tagging_obj, x_iam_token=x_iam_token)`

Updates Dynamic-tagging key-value

Update operation of Dynamic-tagging key

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
key_name = 'key_name_example' # str | Dynamic-tagging Key
dynamic_tagging_obj = swagger_client.DynamicTaggingSchemaObject() # DynamicTaggingSchemaObject | Dynamic-tagging object containing key-value pair
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Updates Dynamic-tagging key-value
    api_instance.update_dynamic_tagging_by_key(key_name, dynamic_tagging_obj, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_dynamic_tagging_by_key: %s\n" % e)
```

Name	Type	Description	Notes
key_name	str	Dynamic-tagging Key	
dynamic_tagging_obj	**DynamicTaggingSchemaObject**	Dynamic-tagging object containing key-value pair	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.340 update_healthbot_deployment_deployment_by_id

update_healthbot_deployment_deployment_by_id(deployment, x_iam_token=x_iam_token)

Update deployment by ID

Update operation of resource: deployment

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
deployment = swagger_client.DeploymentSchema() # DeploymentSchema | deploymentbody_
↳object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update deployment by ID
    api_instance.update_healthbot_deployment_deployment_by_id(deployment, x_iam_
↳token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_deployment_deployment_
↳by_id: %s\n" % e)
```

Name	Type	Description	Notes
deployment	**DeploymentSchema**	deploymentbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.341 update_healthbot_dynamic_tagging

list[str] update_healthbot_dynamic_tagging(dynamic_tagging, x_iam_token=x_iam_token)

Update dynamic-tagging by ID

Update operation of resource: dynamic-tagging

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
dynamic_tagging = swagger_client.DynamicTaggingsSchemaObject() #_
↳DynamicTaggingsSchemaObject | dynamic_taggingbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update dynamic-tagging by ID
    api_response = api_instance.update_healthbot_dynamic_tagging(dynamic_tagging, x_
↳iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_dynamic_tagging: %s\n"
↳ % e)

```

Name	Type	Description	Notes
dynamic_tagging	**DynamicTaggingsSchemaObject**	dynamic_taggingbody object	
x_iam_token	str	authentication header object	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.342 update_healthbot_ingest_byoi_custom_plugin_by_id

update_healthbot_ingest_byoi_custom_plugin_by_id(name, custom_plugin, x_iam_token=x_iam_token)

Update custom-plugin by ID

Update operation of resource: custom-plugin

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of custom-plugin
custom_plugin = swagger_client.CustomPluginSchema() # CustomPluginSchema | custom_
↳pluginbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

```

(continues on next page)

(continued from previous page)

```

try:
    # Update custom-plugin by ID
    api_instance.update_healthbot_ingest_byoi_custom_plugin_by_id(name, custom_plugin,
↪ x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_byoi_custom_
↪ plugin_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of custom-plugin	
custom_plugin	**CustomPluginSchema**	custom_pluginbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.343 update_healthbot_ingest_byoi_default_plugin_tlive_kafka_by_id

```

update_healthbot_ingest_byoi_default_plugin_tlive_kafka_by_id(name, tlive_kafka,
x_iam_token=x_iam_token)

```

Update tlive-kafka-oc by ID

Update operation of resource: tlive-kafka-oc

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of tlive-kafka-oc
tlive_kafka = swagger_client.TliveKafkaOcSchema() # TliveKafkaOcSchema | tlive_kafka_
↪ body object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update tlive-kafka-oc by ID
    api_instance.update_healthbot_ingest_byoi_default_plugin_tlive_kafka_by_id(name,
↪ tlive_kafka, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_byoi_default_
↪ plugin_tlive_kafka_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of tlive-kafka-oc	
tlive_kafka	**TliveKafkaOcSchema**	tlive_kafka body object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.344 update_healthbot_ingest_byoi_ingest_mapping_by_id

```
update_healthbot_ingest_byoi_ingest_mapping_by_id(name, ingest_mapping,
x_iam_token=x_iam_token)
```

Update ingest-mapping by ID

Update ingest-mapping by name

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of ingest-mapping
ingest_mapping = swagger_client.IngestMappingSchema() # IngestMappingSchema | ingest_
↳mappingbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update ingest-mapping by ID
    api_instance.update_healthbot_ingest_byoi_ingest_mapping_by_id(name, ingest_
↳mapping, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_byoi_ingest_
↳mapping_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of ingest-mapping	
ingest_mapping	**IngestMappingSchema**	ingest_mappingbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json

- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.345 update_healthbot_ingest_frequency_profile_by_id

update_healthbot_ingest_frequency_profile_by_id(name, frequency_profile, x_iam_token=x_iam_token)

Update frequency-profile by ID

Update operation of resource: frequency-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | ID of name
frequency_profile = swagger_client.FrequencyProfileSchema() # FrequencyProfileSchema_
↪ | frequency_profilebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update frequency-profile by ID
    api_instance.update_healthbot_ingest_frequency_profile_by_id(name, frequency_
↪ profile, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_frequency_
↪ profile_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	ID of name	
frequency_profile	**FrequencyProfileSchema**	frequency_profilebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.346 update_healthbot_ingest_outbound_ssh

update_healthbot_ingest_outbound_ssh(outbound_ssh, x_iam_token=x_iam_token)

Update outbound-ssh by ID

Update operation of resource: outbound-ssh

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
outbound_ssh = swagger_client.OutboundSshSchema() # OutboundSshSchema | outbound_
↳ sshbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update outbound-ssh by ID
    api_instance.update_healthbot_ingest_outbound_ssh(outbound_ssh, x_iam_token=x_iam_
↳ token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_outbound_ssh:
↳ %s\n" % e)

```

Name	Type	Description	Notes
outbound_ssh	**OutboundSshSchema**	outbound_sshbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.347 update_healthbot_ingest_settings_byoi_custom_plugin_by_id

```

update_healthbot_ingest_settings_byoi_custom_plugin_by_id(name, custom_plugin,
x_iam_token=x_iam_token)

```

Update custom-plugin by ID

Update operation of resource: custom-plugin

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of custom-plugin
custom_plugin = swagger_client.CustomPluginSchema() # CustomPluginSchema | custom_
↳ pluginbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

```

(continues on next page)

(continued from previous page)

```

try:
    # Update custom-plugin by ID
    api_instance.update_healthbot_ingest_settings_byoi_custom_plugin_by_id(name,
    ↪custom_plugin, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_settings_byoi_
    ↪custom_plugin_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of custom-plugin	
custom_plugin	**CustomPluginSchema**	custom_pluginbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.348 update_healthbot_ingest_settings_byoi_default_plugin_tlive_kafka_by_id

```

update_healthbot_ingest_settings_byoi_default_plugin_tlive_kafka_by_id(name,
x_iam_token=x_iam_token)

```

Update tlive-kafka-oc by ID

Update operation of resource: tlive-kafka-oc

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of tlive-kafka-oc
tlive_kafka = swagger_client.TliveKafkaOcSchema() # TliveKafkaOcSchema | tlive_kafka_
    ↪body object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update tlive-kafka-oc by ID
    api_instance.update_healthbot_ingest_settings_byoi_default_plugin_tlive_kafka_by_
    ↪id(name, tlive_kafka, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_settings_byoi_
    ↪default_plugin_tlive_kafka_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of tlive-kafka-oc	
tlive_kafka	**TliveKafkaOcSchema**	tlive_kafka body object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.349 update_healthbot_ingest_settings_byoi_ingest_mapping_by_id

```
update_healthbot_ingest_settings_byoi_ingest_mapping_by_id(name, ingest_mapping,
x_iam_token=x_iam_token)
```

Update ingest-mapping by ID

Update ingest-mapping by name

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of ingest-mapping
ingest_mapping = swagger_client.IngestMappingSchema() # IngestMappingSchema | ingest_
↳mappingbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update ingest-mapping by ID
    api_instance.update_healthbot_ingest_settings_byoi_ingest_mapping_by_id(name, _
↳ingest_mapping, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_settings_byoi_
↳ingest_mapping_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of ingest-mapping	
ingest_mapping	**IngestMappingSchema**	ingest_mappingbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json

- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.350 update_healthbot_ingest_settings_frequency_profile_by_id

update_healthbot_ingest_settings_frequency_profile_by_id(name, frequency_profile,
x_iam_token=x_iam_token)

Update frequency-profile by ID

Update operation of resource: frequency-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | ID of name
frequency_profile = swagger_client.FrequencyProfileSchema() # FrequencyProfileSchema_
↪ | frequency_profilebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update frequency-profile by ID
    api_instance.update_healthbot_ingest_settings_frequency_profile_by_id(name, ↪
↪ frequency_profile, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_settings_
↪ frequency_profile_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	ID of name	
frequency_profile	**FrequencyProfileSchema**	frequency_profilebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.351 update_healthbot_ingest_settings_tagging_profile_by_id

update_healthbot_ingest_settings_tagging_profile_by_id(name, tagging_profile,
x_iam_token=x_iam_token)

Update tagging-profile by ID

Update operation of resource: tagging-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | ID of name
tagging_profile = swagger_client.TaggingProfileSchema() # TaggingProfileSchema |
↳tagging_profilebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update tagging-profile by ID
    api_instance.update_healthbot_ingest_settings_tagging_profile_by_id(name, tagging_
↳profile, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_settings_
↳tagging_profile_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	ID of name	
tagging_profile	**TaggingProfileSchema**	tagging_profilebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.352 update_healthbot_ingest_settings_tagging_profiles

```
list[str]                                update_healthbot_ingest_settings_tagging_profiles(tagging_profiles,
x_iam_token=x_iam_token)
```

Update tagging-profile by ID

Update operation of resource: tagging-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
```

(continues on next page)

(continued from previous page)

```

tagging_profiles = swagger_client.TaggingProfilesSchema() # TaggingProfilesSchema |
↳tagging_profilebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update tagging-profile by ID
    api_response = api_instance.update_healthbot_ingest_settings_tagging_
↳profiles(tagging_profiles, x_iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_settings_
↳tagging_profiles: %s\n" % e)

```

Name	Type	Description	Notes
tagging_profiles	**TaggingProfilesSchema**	tagging_profilebody object	
x_iam_token	str	authentication header object	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.353 update_healthbot_ingest_sflow

update_healthbot_ingest_sflow(sflow, x_iam_token=x_iam_token)

Update sflow by ID

Update operation of resource: sflow

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
sflow = swagger_client.SflowSchema() # SflowSchema | sflowbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update sflow by ID
    api_instance.update_healthbot_ingest_sflow(sflow, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_sflow: %s\n" %
↳e)

```

Name	Type	Description	Notes
sflow	**SflowSchema**	sflowbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.354 update_healthbot_ingest_sflow_counter_record_by_id

```
update_healthbot_ingest_sflow_counter_record_by_id(record_name, counter_record,
x_iam_token=x_iam_token)
```

Update counter-record by ID

Update operation of resource: counter-record

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
record_name = 'record_name_example' # str | ID of record-name
counter_record = swagger_client.CounterRecordSchema() # CounterRecordSchema | counter_
↳recordbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update counter-record by ID
    api_instance.update_healthbot_ingest_sflow_counter_record_by_id(record_name,
↳counter_record, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_sflow_counter_
↳record_by_id: %s\n" % e)
```

Name	Type	Description	Notes
record_name	str	ID of record-name	
counter_record	**CounterRecordSchema**	counter_recordbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.355 update_healthbot_ingest_sflow_flow_record_by_id

```
update_healthbot_ingest_sflow_flow_record_by_id(record_name, flow_record,
x_iam_token=x_iam_token)
```

Update flow-record by ID

Update operation of resource: flow-record

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
record_name = 'record_name_example' # str | ID of record-name
flow_record = swagger_client.FlowRecordSchema() # FlowRecordSchema | flow_recordbody_
↳object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update flow-record by ID
    api_instance.update_healthbot_ingest_sflow_flow_record_by_id(record_name, flow_
↳record, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_sflow_flow_
↳record_by_id: %s\n" % e)
```

Name	Type	Description	Notes
record_name	str	ID of record-name	
flow_record	**FlowRecordSchema**	flow_recordbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.356 update_healthbot_ingest_sflow_protocol_by_id

```
update_healthbot_ingest_sflow_protocol_by_id(protocol_name, protocol, x_iam_token=x_iam_token)
```

Update protocol by ID

Update operation of resource: protocol

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
protocol_name = 'protocol_name_example' # str | ID of protocol-name
protocol = swagger_client.ProtocolSchema() # ProtocolSchema | protocolbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update protocol by ID
    api_instance.update_healthbot_ingest_sflow_protocol_by_id(protocol_name, protocol,
↳ x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_sflow_protocol_
↳ by_id: %s\n" % e)

```

Name	Type	Description	Notes
protocol_name	str	ID of protocol-name	
protocol	**ProtocolSchema**	protocolbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.357 update_healthbot_ingest_sflow_sample_by_id

update_healthbot_ingest_sflow_sample_by_id(sample_name, sample, x_iam_token=x_iam_token)

Update sample by ID

Update operation of resource: sample

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
sample_name = 'sample_name_example' # str | ID of sample-name
sample = swagger_client.SampleSchema() # SampleSchema | samplebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:

```

(continues on next page)

(continued from previous page)

```

# Update sample by ID
api_instance.update_healthbot_ingest_sflow_sample_by_id(sample_name, sample, x_
↳ iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_sflow_sample_by_
↳ id: %s\n" % e)

```

Name	Type	Description	Notes
sample_name	str	ID of sample-name	
sample	**SampleSchema**	samplebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.358 update_healthbot_ingest_snmp_notification

update_healthbot_ingest_snmp_notification(snmp_notification, x_iam_token=x_iam_token)

Update snmp-notification by ID

Update operation of resource: snmp-notification

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
snmp_notification = swagger_client.SnmpNotificationSchema() # SnmpNotificationSchema_
↳ | snmp_notification body object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update snmp-notification by ID
    api_instance.update_healthbot_ingest_snmp_notification(snmp_notification, x_iam_
↳ token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_snmp_
↳ notification: %s\n" % e)

```

Name	Type	Description	Notes
snmp_notification	**SnmpNotificationSchema**	snmp_notification body object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.359 update_healthbot_ingest_snmp_notification_v3_usm_user_by_id

```
update_healthbot_ingest_snmp_notification_v3_usm_user_by_id(name, usm_user,
x_iam_token=x_iam_token)
```

Update SNMPv3 user by UserName(ID)

Update operation of resource: snmp v3 usm user

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | User Name
usm_user = swagger_client.Snmpv3UsmUserSchema() # Snmpv3UsmUserSchema | snmp_v3_usm_
↪user object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update SNMPv3 user by UserName(ID)
    api_instance.update_healthbot_ingest_snmp_notification_v3_usm_user_by_id(name,
↪usm_user, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_snmp_
↪notification_v3_usm_user_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	User Name	
usm_user	**Snmpv3UsmUserSchema**	snmp_v3_usm user object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.360 update_healthbot_ingest_syslog_header_pattern_by_id

update_healthbot_ingest_syslog_header_pattern_by_id(name, pattern, x_iam_token=x_iam_token)

Update pattern by ID

Update operation of resource: header-pattern

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | ID of name
pattern = swagger_client.HeaderPatternSchema() # HeaderPatternSchema | header_
↳patternbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update pattern by ID
    api_instance.update_healthbot_ingest_syslog_header_pattern_by_id(name, pattern, x_
↳iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_syslog_header_
↳pattern_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	ID of name	
pattern	**HeaderPatternSchema**	header_patternbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.361 update_healthbot_ingest_tagging_profile_by_id

update_healthbot_ingest_tagging_profile_by_id(name, tagging_profile, x_iam_token=x_iam_token)

Update tagging-profile by ID

Update operation of resource: tagging-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
```

(continues on next page)

(continued from previous page)

```

from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | ID of name
tagging_profile = swagger_client.TaggingProfileSchema() # TaggingProfileSchema |
↳tagging_profilebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update tagging-profile by ID
    api_instance.update_healthbot_ingest_tagging_profile_by_id(name, tagging_profile,
↳x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_tagging_profile_
↳by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	ID of name	
tagging_profile	**TaggingProfileSchema**	tagging_profilebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.362 update_healthbot_ingest_tagging_profiles

list[str] update_healthbot_ingest_tagging_profiles(tagging_profiles, x_iam_token=x_iam_token)

Update tagging-profile by ID

Update operation of resource: tagging-profile

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
tagging_profiles = swagger_client.TaggingProfilesSchema() # TaggingProfilesSchema |
↳tagging_profilebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update tagging-profile by ID
    api_response = api_instance.update_healthbot_ingest_tagging_profiles(tagging_
↳profiles, x_iam_token=x_iam_token)

```

(continues on next page)

(continued from previous page)

```

pprint(api_response)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_ingest_tagging_
    ↳profiles: %s\n" % e)

```

Name	Type	Description	Notes
tagging_profiles	**TaggingProfilesSchema**	tagging_profilebody object	
x_iam_token	str	authentication header object	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.363 update_healthbot_organization_organization_by_id

```

update_healthbot_organization_organization_by_id(organization_name, organization,
x_iam_token=x_iam_token)

```

Update organization by ID

Update operation of resource: organization

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
organization_name = 'organization_name_example' # str | ID of organization-name
organization = swagger_client.OrganizationSchema() # OrganizationSchema |
    ↳organizationbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update organization by ID
    api_instance.update_healthbot_organization_organization_by_id(organization_name,
    ↳organization, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_organization_
    ↳organization_by_id: %s\n" % e)

```

Name	Type	Description	Notes
organization_name	str	ID of organization-name	
organization	**OrganizationSchema**	organizationbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.364 update_healthbot_profile_rollup_summarization_field_profile_field_profile

```
update_healthbot_profile_rollup_summarization_field_profile_field_profile_by_id(profile_id,
field_profile, x_iam_token=x_iam_token)
```

Update field-profile by ID

Update operation of resource: field-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
profile_id = 'profile_id_example' # str | ID of profile-id
field_profile = swagger_client.RollupSummarizationSchema() # RollupSummarizationSchema | field_profilebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update field-profile by ID
    api_instance.update_healthbot_profile_rollup_summarization_field_profile_field_
    profile_by_id(profile_id, field_profile, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_profile_rollup_
    summarization_field_profile_field_profile_by_id: %s\n" % e)
```

Name	Type	Description	Notes
profile_id	str	ID of profile-id	
field_profile	**RollupSummarizationSchema**	field_profilebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.365 update_healthbot_system_time_series_database_time_series_database_by_id

```
update_healthbot_system_time_series_database_time_series_database_by_id(time_series_database,
                                force_tsdb=force_tsdb)
```

Update time-series-database by ID

Update operation of resource: time-series-database

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
time_series_database = swagger_client.TsdbSchema() # TsdbSchema | time_series_
↳databasebody object
force_tsdb = False # bool | force update tsdb when force is set to True (optional)
↳(default to false)

try:
    # Update time-series-database by ID
    api_instance.update_healthbot_system_time_series_database_time_series_database_by_
↳id(time_series_database, force_tsdb=force_tsdb)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_system_time_series_
↳database_time_series_database_by_id: %s\n" % e)
```

Name	Type	Description	Notes
time_series_database	**Tsdb- Schema**	time_series_databasebody object	
force_tsdb	bool	force update tsdb when force is set to True	[optional] [default to false]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.366 update_healthbot_system_trigger_action

```
update_healthbot_system_trigger_action(trigger_action)
```

Update trigger-action

Update operation of resource: trigger-action

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
trigger_action = swagger_client.TriggerActionSchema() # TriggerActionSchema | trigger_
↳ action object

try:
    # Update trigger-action
    api_instance.update_healthbot_system_trigger_action(trigger_action)
except ApiException as e:
    print("Exception when calling DefaultApi->update_healthbot_system_trigger_action:
↳ %s\n" % e)
```

Name	Type	Description	Notes
trigger_action	**TriggerActionSchema**	trigger_action object	

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.367 update_iceberg_ingest

update_iceberg_ingest(ingest_settings, x_iam_token=x_iam_token)

Update ingest by ID

Update operation of resource: ingest

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
ingest_settings = swagger_client.IngestSettingsSchema() # IngestSettingsSchema |
↳ ingest_settingsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update ingest by ID
    api_instance.update_iceberg_ingest(ingest_settings, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_ingest: %s\n" % e)
```

Name	Type	Description	Notes
ingest_settings	**IngestSettingsSchema**	ingest_settingsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.368 update_iceberg_ingest_flow

update_iceberg_ingest_flow(flow, x_iam_token=x_iam_token)

Update flow by ID

Update operation of resource: flow

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
flow = swagger_client.FlowSchema() # FlowSchema | flowbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update flow by ID
    api_instance.update_iceberg_ingest_flow(flow, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_ingest_flow: %s\n" % e)
```

Name	Type	Description	Notes
flow	**FlowSchema**	flowbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.369 update_iceberg_ingest_flow_template_by_id

update_iceberg_ingest_flow_template_by_id(name, template, x_iam_token=x_iam_token)

Update template by ID

Update operation of resource: template

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of template
template = swagger_client.TemplateSchema() # TemplateSchema | templatebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update template by ID
    api_instance.update_iceberg_ingest_flow_template_by_id(name, template, x_iam_
↪token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_ingest_flow_template_by_
↪id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of template	
template	**TemplateSchema**	templatebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.370 update_iceberg_ingest_native_gpb

update_iceberg_ingest_native_gpb(native_gpb, x_iam_token=x_iam_token)

Update native-gpb by ID

Update operation of resource: native-gpb

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint
```

(continues on next page)

(continued from previous page)

```
# create an instance of the API class
api_instance = swagger_client.DefaultApi()
native_gpb = swagger_client.NativeGpbSchema() # NativeGpbSchema | native_gpbbody_
↳object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update native-gpb by ID
    api_instance.update_iceberg_ingest_native_gpb(native_gpb, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_ingest_native_gpb: %s\n"
    ↳% e)
```

Name	Type	Description	Notes
native_gpb	**NativeGpbSchema**	native_gpbbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.371 update_iceberg_ingest_settings

update_iceberg_ingest_settings(ingest_settings, x_iam_token=x_iam_token)

Update ingest-settings by ID

Update operation of resource: ingest-settings

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
ingest_settings = swagger_client.IngestSettingsSchema() # IngestSettingsSchema |_
↳ingest_settingsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update ingest-settings by ID
    api_instance.update_iceberg_ingest_settings(ingest_settings, x_iam_token=x_iam_
    ↳token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_ingest_settings: %s\n" %_
    ↳e)
```

Name	Type	Description	Notes
ingest_settings	**IngestSettingsSchema**	ingest_settingsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.372 update_iceberg_ingest_settings_flow

update_iceberg_ingest_settings_flow(flow, x_iam_token=x_iam_token)

Update flow by ID

Update operation of resource: flow

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
flow = swagger_client.FlowSchema() # FlowSchema | flowbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update flow by ID
    api_instance.update_iceberg_ingest_settings_flow(flow, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_ingest_settings_flow:
↪ %s\n" % e)
```

Name	Type	Description	Notes
flow	**FlowSchema**	flowbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.373 update_iceberg_ingest_settings_flow_template_by_id

update_iceberg_ingest_settings_flow_template_by_id(name, template, x_iam_token=x_iam_token)

Update template by ID

Update operation of resource: template

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of template
template = swagger_client.TemplateSchema() # TemplateSchema | templatebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update template by ID
    api_instance.update_iceberg_ingest_settings_flow_template_by_id(name, template, x_
    iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_ingest_settings_flow_
    template_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of template	
template	**TemplateSchema**	templatebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.374 update_iceberg_ingest_settings_syslog

update_iceberg_ingest_settings_syslog(syslog, x_iam_token=x_iam_token)

Update syslog by ID

Update operation of resource: syslog

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint
```

(continues on next page)

(continued from previous page)

```
# create an instance of the API class
api_instance = swagger_client.DefaultApi()
syslog = swagger_client.SyslogSchema() # SyslogSchema | syslogbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update syslog by ID
    api_instance.update_iceberg_ingest_settings_syslog(syslog, x_iam_token=x_iam_
↪token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_ingest_settings_syslog:
↪%s\n" % e)
```

Name	Type	Description	Notes
syslog	**SyslogSchema**	syslogbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.375 update_iceberg_ingest_settings_syslog_pattern_by_id

update_iceberg_ingest_settings_syslog_pattern_by_id(name, pattern, x_iam_token=x_iam_token)

Update pattern by ID

Update operation of resource: pattern

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of pattern
pattern = swagger_client.PatternSchema() # PatternSchema | patternbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update pattern by ID
    api_instance.update_iceberg_ingest_settings_syslog_pattern_by_id(name, pattern, x_
↪iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_ingest_settings_syslog_
↪pattern_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of pattern	
pattern	**PatternSchema**	patternbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.376 update_iceberg_ingest_settings_syslog_pattern_set_by_id

```
update_iceberg_ingest_settings_syslog_pattern_set_by_id(name, pattern_set,
x_iam_token=x_iam_token)
```

Update pattern-set by ID

Update operation of resource: pattern-set

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of pattern-set
pattern_set = swagger_client.PatternSetSchema() # PatternSetSchema | pattern_setbody_
↳object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update pattern-set by ID
    api_instance.update_iceberg_ingest_settings_syslog_pattern_set_by_id(name,
↳pattern_set, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_ingest_settings_syslog_
↳pattern_set_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of pattern-set	
pattern_set	**PatternSetSchema**	pattern_setbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json

- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.377 update_iceberg_ingest_syslog

update_iceberg_ingest_syslog(syslog, x_iam_token=x_iam_token)

Update syslog by ID

Update operation of resource: syslog

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
syslog = swagger_client.SyslogSchema() # SyslogSchema | syslogbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update syslog by ID
    api_instance.update_iceberg_ingest_syslog(syslog, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_ingest_syslog: %s\n" % e)
```

Name	Type	Description	Notes
syslog	**SyslogSchema**	syslogbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.378 update_iceberg_ingest_syslog_pattern_by_id

update_iceberg_ingest_syslog_pattern_by_id(name, pattern, x_iam_token=x_iam_token)

Update pattern by ID

Update operation of resource: pattern

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
```

(continues on next page)

(continued from previous page)

```

from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of pattern
pattern = swagger_client.PatternSchema() # PatternSchema | patternbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update pattern by ID
    api_instance.update_iceberg_ingest_syslog_pattern_by_id(name, pattern, x_iam_
↪token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_ingest_syslog_pattern_by_
↪id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of pattern	
pattern	**PatternSchema**	patternbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.379 update_iceberg_ingest_syslog_pattern_set_by_id

update_iceberg_ingest_syslog_pattern_set_by_id(name, pattern_set, x_iam_token=x_iam_token)

Update pattern-set by ID

Update operation of resource: pattern-set

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of pattern-set
pattern_set = swagger_client.PatternSetSchema() # PatternSetSchema | pattern_setbody_
↪object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update pattern-set by ID
    api_instance.update_iceberg_ingest_syslog_pattern_set_by_id(name, pattern_set, x_
↪iam_token=x_iam_token)

```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_ingest_syslog_pattern_
↳set_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of pattern-set	
pattern_set	**PatternSetSchema**	pattern_setbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.380 update_iceberg_profile_data_summarization_raw_by_id

```
update_iceberg_profile_data_summarization_raw_by_id(name, raw_data_summarization,
x_iam_token=x_iam_token)
```

Update raw-data-summarization by ID

Update operation of resource: raw-data-summarization

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of raw-data-summarization
raw_data_summarization = swagger_client.RawSchema() # RawSchema | raw_data_
↳summarizationbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update raw-data-summarization by ID
    api_instance.update_iceberg_profile_data_summarization_raw_by_id(name, raw_data_
↳summarization, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_profile_data_
↳summarization_raw_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of raw-data-summarization	
raw_data_summarization	**RawSchema**	raw_data_summarizationbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.381 update_iceberg_profile_security_ca_profile_by_id

update_iceberg_profile_security_ca_profile_by_id(name, ca_profile, x_iam_token=x_iam_token)

Update ca-profile by ID

Update operation of resource: ca-profile

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of ca-profile
ca_profile = swagger_client.CaProfileSchema() # CaProfileSchema | ca_profilebody_
↪object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update ca-profile by ID
    api_instance.update_iceberg_profile_security_ca_profile_by_id(name, ca_profile, x_
↪iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_profile_security_ca_
↪profile_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of ca-profile	
ca_profile	**CaProfileSchema**	ca_profilebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.382 update_iceberg_profile_security_local_certificate_by_id

```
update_iceberg_profile_security_local_certificate_by_id(name, local_certificate,
x_iam_token=x_iam_token)
```

Update local-certificate by ID

Update operation of resource: local-certificate

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of local-certificate
local_certificate = swagger_client.LocalCertificateSchema() # LocalCertificateSchema_
↪ | local_certificatebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update local-certificate by ID
    api_instance.update_iceberg_profile_security_local_certificate_by_id(name, local_
↪ certificate, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_profile_security_local_
↪ certificate_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of local-certificate	
local_certificate	**LocalCertificateSchema**	local_certificatebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.383 update_iceberg_profile_security_ssh_key_profile_by_id

```
update_iceberg_profile_security_ssh_key_profile_by_id(name, ssh_key_profile, authoriza-
tion=authorization)
```

Update ssh-key-profile by ID

Update operation of resource: ssh-key-profile


```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
name = 'name_example' # str | Name of ssh-key-profile
ssh_key_profile = swagger_client.SshKeyProfileSchema() # SshKeyProfileSchema | ssh_
↳key_profilebody object
authorization = 'authorization_example' # str | authentication header object,
↳(optional)

try:
    # Update ssh-key-profile by ID
    api_instance.update_iceberg_profile_security_ssh_key_profile_by_id(name, ssh_key_
↳profile, authorization=authorization)
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_profile_security_ssh_key_
↳profile_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of ssh-key-profile	
ssh_key_profile	**SshKeyProfileSchema**	ssh_key_profilebody object	
authorization	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.384 update_iceberg_profiles

update_iceberg_profiles(profile, x_iam_token=x_iam_token)

Update profile by ID

Update entire profile configuration.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DefaultApi()
profile = swagger_client.ProfilesSchema() # ProfilesSchema | profilebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

```

(continues on next page)

(continued from previous page)

```
try:
    # Update profile by ID
    api_instance.update_iceberg_profiles(profile, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DefaultApi->update_iceberg_profiles: %s\n" % e)
```

Name	Type	Description	Notes
profile	**ProfilesSchema**	profilebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.385 InlineResponse2009

2.385.1 Properties

Name	Type	Description	Notes
group_id	str	ID generated by system	[optional]
group_name	str	Name of the group	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.386 DevicegroupSchemaLoggingNativegpb

2.386.1 Properties

Name	Type	Description	Notes
daemons	list[str]		[optional]
log_level	str	Set the logging level	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.387 DevicegroupSchemaLoggingByoi

2.387.1 Properties

Name	Type	Description	Notes
service	**list[DevicegroupSchemaLoggingByoiService]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.388 IngestsettingsSchemaIngestsettingsByoiDefaultplugin

2.388.1 Properties

Name	Type	Description	Notes
tlive_kafka_oc	**list[TLiveKafkaOcSchema]**	TLive Kafka ingest	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.389 RoleSchemaInner

2.389.1 Properties

Name	Type	Description	Notes
role_id	str	ID generated by system	[optional]
role_name	str	Name of the role	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.390 AssociatedUserSchemaInner

2.390.1 Properties

Name	Type	Description	Notes
user_id	str		[optional]
user_name	str		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.391 IngestsettingsSchemaIngestsettingsFlowRecognitionpattern

2.391.1 Properties

Name	Type	Description	Notes
exclude_fields	list[str]		[optional]
include_fields	list[str]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.392 RuleSchemaWhenMaxrateofincrease

2.392.1 Properties

Name	Type	Description	Notes
all	list[object]	With this flag, result is set to True only if all the data matches the given condition	[optional]
any	list[object]	With this flag, result is set to True if any one of the data matches the condition	[optional]
field_name	str	Field name on which rate should be compared	
rate	str	Rate	[optional]
time_range	str	How much back in time should we look for data. Specify positive integer followed by s/m/h/d/w/y/o representing seconds/minutes/hours/days/weeks/years/offset. Eg: 2s	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.393 DestinationSchemaDisk

2.393.1 Properties

Name	Type	Description	Notes
max_reports	int	Maximux repots to store on disk	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.394 RuleSchemaAgent

2.394.1 Properties

Name	Type	Description	Notes
args	**list[RuleSchemaAgentArgs]**		[optional]
file	str	File where table and views are defined	
frequency	str	Frequency at which the iagent should execute the commands and extract the data. Specify positive integer followed by s/m/h/d/w/y representing seconds/minutes/hours/days/weeks/years. Eg: 2s	
table	str	Table which needs to be used to extract the data	
target	str	To run command on FPC, specify FPC target (optional)	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.395 IngestMappingsSchema

2.395.1 Properties

Name	Type	Description	Notes
ingest_mapping	**list[IngestMappingSchema]**		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.396 DevicegroupSchemaScheduler

2.396.1 Properties

Name	Type	Description	Notes
in-stance_id	str	Unique ID of the variable instance. This should be unique per playbook and rule combination. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	
play-book	str	Name of the playbook in which the variable instance needs to be used	
rule	str	Name of the rule. This should be of the format <topic-name>/<rule-name>;	
schedule	str	Name of the schedule that play/pauses the playbook instance automatically	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.397 Password

2.397.1 Properties

Name	Type	Description	Notes
newpassword	str	New password	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.398 RetentionPoliciesSchema

2.398.1 Properties

Name	Type	Description	Notes
retention_policy	**list[RetentionPolicySchema]**		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.399 ReportSchemaCanvaspanel

2.399.1 Properties

Name	Type	Description	Notes
name	str	Name of the panel.	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.400 DevicegroupSchemaLoggingMLmodelbuilder

2.400.1 Properties

Name	Type	Description	Notes
log_level	str	Set the logging level	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.401 Error

2.401.1 Properties

Name	Type	Description	Notes
detail	str		
status	int		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.402 RuleSchema

2.402.1 Properties

Name	Type	Description	Notes
description	str	Description about the rule	[optional]
field	**list[RuleSchemaField]**		[optional]
function	**list[RuleSchemaFunction]**		[optional]
keys	list[str]		[optional]
network_rule	list[object]	Flag to denote a network rule	[optional]
disable_no_data_alarm	list[object]	Disable No Data Alarm	[optional]
rule_frequency	str	Frequency at which the rule's field, reference, and vector elements should be computed. Required only when a rule doesn't have a sensor defined. Specify integer > 0 followed by s/m/h/d/w/y representing seconds/minutes/hours/days/weeks/years. Eg: 2s	[optional]
rule_name	str	Name of the rule. Should be of pattern [a-z][a-z0-9_-]*	
sensor	**list[RuleSchemaSensor1]**		[optional]
synopsis	str	Synopsis about the rule	[optional]
field_aggregation_time_range	str	How much back in time should we look for field aggregation. Specify positive integer followed by o/s/m/h/d/w/y/offset representing seconds/minutes/hours/days/weeks/years. Eg: 2s	[optional]
trigger	**list[RuleSchemaTrigger]**		[optional]
variable	**list[RuleSchemaVariable]**	Playbook variable configuration	[optional]
vector	**list[RuleSchemaVector]**		[optional]
rule_properties	RuleSchemaRuleproperties**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.403 RuleSchemaFormula1Or

2.403.1 Properties

Name	Type	Description	Notes
left_vector	str	Vector name. Pattern for giving vector name is @[a-z][a-zA-Z0-9_-]*	
right_vector	str	Vector name. Pattern for giving vector name is @[a-z][a-zA-Z0-9_-]*	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.404 Tsdbschema

2.404.1 Properties

Name	Type	Description	Notes
dedicate	bool	Dedicate given nodes only for tsdb instances. No other services will be spawned on tsdb nodes when set to true	[optional]
nodes	list[str]		[optional]
replication_factor	int	High availability. Number of copies of data to be stored	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.405 Ruleschemaformulastddev

2.405.1 Properties

Name	Type	Description	Notes
field_name	str	Field name on which standard deviation operation needs to be performed	
time_range	str	How much back in time should we look for data. Specify positive integer followed by s/m/h/d/w/y/o representing seconds/minutes/hours/days/weeks/years/offset. Eg: 2s	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.406 Userschema

2.406.1 Properties

Name	Type	Description	Notes
user_name	str	Name of the user	[optional]
first_name	str	First name of the user	[optional]
last_name	str	Last name of the user	[optional]
email	str	Email of the user	[optional]
password	str	Password of the user	[optional]
active	bool	Status of the user	[optional]
groups	**list[UserSchemaGroups]**	list of groups associated	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.407 DevicegroupSchemaLoggingAgent

2.407.1 Properties

Name	Type	Description	Notes
daemons	list[str]		[optional]
log_level	str	Set the logging level	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.408 IngestsettingsSchemaIngestsettingsFlowTemplate

2.408.1 Properties

Name	Type	Description	Notes
description	str		[optional]
key_fields	list[str]		[optional]
name	str		
priority	int		[optional]
protocol_version	str		[optional]
recognition_pattern	**IngestsettingsSchemaIngestsettingsFlowRecognitionpattern**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.409 NetworkHealthTree

2.409.1 Properties

Name	Type	Description	Notes
children	**list[NetworkHealthTree]**		
color	str		[optional]
data	str		[optional]
name	str		
timestamp	datetime		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.410 Token

2.410.1 Properties

Name	Type	Description	Notes
refresh_token	str	Refresh token	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.411 DevicegroupSchemaLoggingFlow

2.411.1 Properties

Name	Type	Description	Notes
daemons	list[str]		[optional]
log_level	str	Set the logging level	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.412 RuleSchemaNativegpb

2.412.1 Properties

Name	Type	Description	Notes
frequency	str	Sensor subscription duration. Specify integer > 0 followed by s/m/h/d/w/y representing seconds/minutes/hours/days/weeks/years. Eg: 2s. A frequency of zero should be used only in case of events subscription	[optional]
port	int	Port on which the native sensors will be received	
sensor_name	str	Sensor to subscribe	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.413 RuleSchemaFormulaMean

2.413.1 Properties

Name	Type	Description	Notes
field_name	str	Field name on which mean operation needs to be performed	
time_range	str	How much back in time should we look for data. Specify positive integer followed by s/m/h/d/w/y/o representing seconds/minutes/hours/days/weeks/years/offset. Eg: 2s	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.414 ReportSchema

2.414.1 Properties

Name	Type	Description	Notes
capture_fields	list[str]		[optional]
destination	list[str]		
format	str	Generated report format	
graph_canvas	**list[ReportSchemaGraphcanvas]**	Canvas name	[optional]
name	str	Name of the report	
schedule	list[str]		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.415 swagger_client.DebugApi

All URIs are relative to *http://api-server/api/v2*

Method	HTTP request	Description
**healthbot_debug_generate_configuration	POST /debug/configuration/	Request Healthbot MGD service to generate the debug related configuration for healthbot debugger to consume.
**retrieve_debug_for_scenario	POST /debug/scenario/{scenario_name}/	Run debugging for the given scenario name

2.416 healthbot_debug_generate_configuration

healthbot_debug_generate_configuration(x_iam_token=x_iam_token)

Request Healthbot MGD service to generate the debug related configuration for healthbot debugger to consume.

Request Healthbot MGD service to generate the debug related configuration for healthbot debugger to consume.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DebugApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Request Healthbot MGD service to generate the debug related configuration for
    ↪healthbot debugger to consume.
    api_instance.healthbot_debug_generate_configuration(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DebugApi->healthbot_debug_generate_configuration:
    ↪ %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.417 retrieve_debug_for_scenario

object retrieve_debug_for_scenario(scenario_name, x_iam_token=x_iam_token, de-
bug_arguments=debug_arguments)

Run debugging for the given scenario name

Run debugging for the given scenario name

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DebugApi()
scenario_name = 'scenario_name_example' # str | Scenario name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
debug_arguments = swagger_client.DebugArgumentsSchema() # DebugArgumentsSchema |
↳ Debug arguments object (optional)

try:
    # Run debugging for the given scenario name
    api_response = api_instance.retrieve_debug_for_scenario(scenario_name, x_iam_
↳ token=x_iam_token, debug_arguments=debug_arguments)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DebugApi->retrieve_debug_for_scenario: %s\n" % e)
```

Name	Type	Description	Notes
scenario_name	str	Scenario name	
x_iam_token	str	authentication header object	[optional]
debug_arguments	**DebugArgumentsSchema**	Debug arguments object	[optional]

object

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.418 DeviceSchemaVendorCisco

2.418.1 Properties

Name	Type	Description	Notes
operating_system	str	Operating system of the device	
platform	str	Platform name of the device, Example: MX240	[optional]
product	str	Product category of the device, Example: MX	[optional]
release	str	Release string of the device, Example: 19.2R1	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.419 CustompluginSchemaSecurityparameters

2.419.1 Properties

Name	Type	Description	Notes
tls	**CustompluginSchemaSecurityparametersTls**		[optional]
user_authentication	**CustompluginSchemaSecurityparametersUserauthentication**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.420 DeviceHealthTree

2.420.1 Properties

Name	Type	Description	Notes
children	**list[DeviceHealthTree]**		
color	str		[optional]
data	str		[optional]
name	str		
timestamp	datetime		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.421 DeviceSchemaAgent

2.421.1 Properties

Name	Type	Description	Notes
port	int	Netconf port	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.422 IngestmappingSchemaSnmp

2.422.1 Properties

Name	Type	Description	Notes
for_device_groups	list[str]		[optional]
use_plugin	**IngestmappingSchemaIAgentUseplugin**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.423 RetentionPolicySchema

2.423.1 Properties

Name	Type	Description	Notes
duration	str	Schedule duration in days or hours, Should be of pattern [1-9][0-9]*[dh]	[optional]
replication	int	Number of independent copies if stored in the cluster	[optional]
retention_policy_name	str	Name of the retention-policy. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.424 NetworkGroupsSchema

2.424.1 Properties

Name	Type	Description	Notes
network_group	**list[NetworkGroupSchema]**		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.425 DevicegroupSchemaLoggingByoiService

2.425.1 Properties

Name	Type	Description	Notes
daemons	list[str]		[optional]
log_level	str	Set the logging level	
name	str	Name of the service	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.426 RuleSchemaByoiPluginParameters

2.426.1 Properties

Name	Type	Description	Notes
key	str	Key of the parameter	
value	str	Value of the parameter	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.427 CustomPluginsSchema

2.427.1 Properties

Name	Type	Description	Notes
custom_plugin	**list[CustomPluginSchema]**		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.428 RuleSchemaWhen

2.428.1 Properties

Name	Type	Description	Notes
does_not_match_with	<code>**list[RuleSchemaWhenDoesnotmatchwith]**</code>		[optional]
equal_to	<code>**list[RuleSchemaWhenEqualto]**</code>		[optional]
exists	<code>**list[RuleSchemaWhenExists]**</code>		[optional]
greater_than	<code>**list[RuleSchemaWhenEqualto]**</code>		[optional]
greater_than_or_equal_to	<code>**list[RuleSchemaWhenEqualto]**</code>		[optional]
increasing_at_least_by_rate	<code>**list[RuleSchemaWhenIncreasingatleastbyrate]**</code>	Rate of increase between successive values is at least given rate	[optional]
increasing_at_least_by_value	<code>**list[RuleSchemaWhenIncreasingatleastbyvalue]**</code>	Increase between successive values is at least given value	[optional]
increasing_at_most_by_rate	<code>**list[RuleSchemaWhenIncreasingatmostbyrate]**</code>	Rate of increase between successive values is at most given rate	[optional]
increasing_at_most_by_value	<code>**list[RuleSchemaWhenIncreasingatmostbyvalue]**</code>	Increase between successive values is at most given value	[optional]
less_than	<code>**list[RuleSchemaWhenEqualto]**</code>		[optional]
less_than_or_equal_to	<code>**list[RuleSchemaWhenEqualto]**</code>		[optional]
matches_with	<code>**list[RuleSchemaWhenDoesnotmatchwith]**</code>		[optional]
max_rate_of_increase	<code>**list[RuleSchemaWhenMaxrateofincrease]**</code>		[optional]
min_rate_of_increase	<code>**list[RuleSchemaWhenMaxrateofincrease]**</code>		[optional]
not_equal_to	<code>**list[RuleSchemaWhenEqualto]**</code>		[optional]
range	<code>**list[RuleSchemaWhenRange]**</code>		[optional]
user_defined_function	<code>**list[RuleSchemaWhenUserdefinedfunction]**</code>		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.429 SyslogSchema

2.429.1 Properties

Name	Type	Description	Notes
syslog	<code>**SyslogSchemaSyslog**</code>		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.430 RuleSchemaFormulaSum

2.430.1 Properties

Name	Type	Description	Notes
field_name	str	Field name on which sum operation needs to be performed	
time_range	str	How much back in time should we look for data. Specify positive integer followed by s/m/h/d/w/y/o representing seconds/minutes/hours/days/weeks/years/offset. Eg: 2s	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.431 AssociatedRoleSchema

2.431.1 Properties

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.432 DevicegroupSchemaFlowNetflow

2.432.1 Properties

Name	Type	Description	Notes
ports	list[int]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.433 LicenseFeaturesSchema

2.433.1 Properties

Name	Type	Description	Notes
license_feature	**list[LicenseFeatureSchema]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.434 RuleSchemaArgument

2.434.1 Properties

Name	Type	Description	Notes
argument_name	str	Name of the argument. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	
mandatory	list[object]	Flag to indicate a mandatory attribute	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.435 NotificationSchemaEmails

2.435.1 Properties

Name	Type	Description	Notes
ids	list[str]		
filter	**NotificationSchemaEmailsFilter**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.436 RuleSchemaRuleproperties

2.436.1 Properties

Name	Type	Description	Notes
author	str	E-mail address of the rule writer	[optional]
catalogue	**RuleSchemaRulepropertiesCatalogue**		[optional]
contributor	str		[optional]
_date	str		[optional]
helper_files	**list[RuleSchemaRulepropertiesHelperfiles]**		[optional]
supported_devices	**RuleSchemaRuleproperties-Supporteddevices**		[optional]
supported_healthbot_version	str	Healthbot version in which is rule is supported	[optional]
version	int	Rule version, an integer value needs to be incremented for any major change	[optional]
apply_macro	**list[ApplyMacroSchema]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.437 ApplyMacroSchema

2.437.1 Properties

Name	Type	Description	Notes
data	**list[ApplymacroSchemaData]**		[optional]
name	str	Name of the macro to be expanded	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.438 swagger_client.InstanceScheduleStateApi

All URIs are relative to *http://api-server/api/v2*

Method	HTTP request	Description
re- <code>retrieve_instances_schedule_state</code>	GET /config/instances-schedule-state/{group_type}/{group_name}/	Get scheduled state of playbook instances with schedule.
up- <code>update_instances_schedule_state</code>	PUT /config/instances-schedule-state/{group_type}/{group_name}/	Update scheduled state of playbook instances with schedule.

2.439 retrieve_instances_schedule_state

`InstancesScheduleStateSchema` `retrieve_instances_schedule_state(group_name, group_type, x_iam_token=x_iam_token)`

Get scheduled state of playbook instances with schedule.

Retrieve the scheduled state of instances with an active scheduler attached to it and present under the group with name passed in the path parameter.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.InstanceScheduleStateApi()
group_name = 'group_name_example' # str | Group name
group_type = 'group_type_example' # str | Group type
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Get scheduled state of playbook instances with schedule.
    api_response = api_instance.retrieve_instances_schedule_state(group_name, group_type, x_iam_token=x_iam_token)
    pprint(api_response)

```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling InstanceScheduleStateApi->retrieve_instances_
↳schedule_state: %s\n" % e)
```

Name	Type	Description	Notes
group_name	str	Group name	
group_type	str	Group type	
x_iam_token	str	authentication header object	[optional]

****InstancesScheduleStateSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.440 update_instances_schedule_state

```
update_instances_schedule_state(group_name,          group_type,          instances_schedule_state,
                                x_iam_token=x_iam_token)
```

Update scheduled state of playbook instances with schedule.

Update the scheduled state of instances with active scheduler attached to it and present under the group with name passed in the path parameter.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.InstanceScheduleStateApi()
group_name = 'group_name_example' # str | Group name
group_type = 'group_type_example' # str | Group type
instances_schedule_state = swagger_client.InstancesScheduleStateSchema() #
↳InstancesScheduleStateSchema | List of instances and their scheduled state
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update scheduled state of playbook instances with schedule.
    api_instance.update_instances_schedule_state(group_name, group_type, instances_
↳schedule_state, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling InstanceScheduleStateApi->update_instances_schedule_
↳state: %s\n" % e)
```

Name	Type	Description	Notes
group_name	str	Group name	
group_type	str	Group type	
in- stances_schedule_state	**InstancesScheduleStateSchema**	List of instances and their scheduled state	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.441 DevicegroupSchemaLoggingNonsensorrules

2.441.1 Properties

Name	Type	Description	Notes
daemons	list[str]		[optional]
log_level	str	Set the logging level	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.442 FlowSchemaFlow

2.442.1 Properties

Name	Type	Description	Notes
template	**list[FlowSchemaFlowTemplate]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.443 DevicegroupSchemaLoggingReportsgeneration

2.443.1 Properties

Name	Type	Description	Notes
log_level	str	Set the logging level	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.444 CustompluginSchemaSecurityparametersTls

2.444.1 Properties

Name	Type	Description	Notes
ca_profile	str	CA profile name	[optional]
insecure_skip_verify	bool	Use TLS but skip verification of certificate chain and host	[optional]
local_certificate_profile	str	Local certificate profile name	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.445 DeviceSchemaFlow

2.445.1 Properties

Name	Type	Description	Notes
source_ip_addresses	list[str]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.446 RawDataSummarizationsSchema

2.446.1 Properties

Name	Type	Description	Notes
raw_data_summarization	**list[RawSchema]**		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.447 ProfilesSchemaProfile

2.447.1 Properties

Name	Type	Description	Notes
security	**ProfileSchemaSecurity**		[optional]
data_summarization	**ProfileSchemaDatsummarization**		[optional]
rollup_summarization	**ProfileSchemaRollupsummarization**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.448 DeviceSchemaVariable

2.448.1 Properties

Name	Type	Description	Notes
in-stance_id	str	Name of the variable instance. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	
playbook	str	Name of the playbook in which the variable instance needs to be used	
rule	str	Name of the rule. This must be of the format <topic-name>/<rule-name>;	
variable_value	**list[DevicegroupSchemaVariablevalue]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.449 RuleSchemaFormulaOutlierdetectionAlgorithm

2.449.1 Properties

Name	Type	Description	Notes
dbscan	**RuleSchemaFormulaOutlierdetectionAlgorithmDbscan**		[optional]
k_fold_3sigma	**RuleSchemaFormulaOutlierdetectionAlgorithmKfold3sigma**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.450 SyslogSchemaSyslog

2.450.1 Properties

Name	Type	Description	Notes
port	int	Port to listen for syslog messages, default is 514	[optional]
header_pattern	**list[HeaderPatternSchema]**		[optional]
pattern	**list[PatternSchema]**		[optional]
pattern_set	**list[PatternSetSchema]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.451 FlowSchema

2.451.1 Properties

Name	Type	Description	Notes
flow	**FlowSchemaFlow**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.452 RuleSchemaRulepropertiesCatalogue

2.452.1 Properties

Name	Type	Description	Notes
tier	str		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.453 HealthSchema

2.453.1 Properties

Name	Type	Description	Notes
device_health	**DeviceHealthSchema**		[optional]
network_health	**GroupHealthSchema**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.454 RuleSchemaWhenUserdefinedfunction

2.454.1 Properties

Name	Type	Description	Notes
all	list[object]	With this flag, result is set to True only if all the data matches the given condition	[optional]
any	list[object]	With this flag, result is set to True if any one of the data matches the condition	[optional]
argument	**list[RuleSchemaThenArgument]**		[optional]
function_name	str	Function name	
time_range	str	How much back in time should we look for data. Specify positive integer followed by s/m/h/d/w/y/o representing seconds/minutes/hours/days/weeks/years/offset. Eg: 2s	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.455 ProfilesSchema

2.455.1 Properties

Name	Type	Description	Notes
profile	**ProfilesSchemaProfile**		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.456 RuleSchemaSensor1

2.456.1 Properties

Name	Type	Description	Notes
description	str	Description about the sensor	[optional]
sflow	**RuleSchemaSflow**		[optional]
flow	**RuleSchemaFlow**		[optional]
i_agent	**RuleSchemaIAgent**		[optional]
native_gpb	**RuleSchemaNativegpb**		[optional]
open_config	**RuleSchemaOpenconfig**		[optional]
server_monitoring	**RuleSchemaOpenconfig**		[optional]
sensor_name	str	Name of sensor. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	
snmp	**RuleSchemaSnmp**		[optional]
snmp_notification	**RuleSchemaSnmpnotification**		[optional]
syslog	**RuleSchemaSyslog**		[optional]
synopsis	str	Synopsis about the sensor	[optional]
byoi	**RuleSchemaByoi**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.457 ServiceStatus

2.457.1 Properties

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.458 swagger_client.ConfigurationApi

All URIs are relative to *http://api-server/api/v2*

Method	HTTP request
check_device_group_unsaved_configuration	POST /config/configuration/check/device-group/{device_group_name}/
check_network_group_unsaved_configuration	POST /config/configuration/check/network-group/{network_group_name}/
commit_unsaved_configuration	POST /config/configuration/
create_healthbot_organizations_organizations	POST /config/organizations/
create_healthbot_topic_resource_resource_by_id	POST /config/topic/{topic_name}/resource/{resource_name}/
create_iceberg_device_device_by_id	POST /config/device/{device_id}/
create_iceberg_device_group_device_group_by_id	POST /config/device-group/{device_group_name}/
create_iceberg_device_groups_device_groups_by_id	POST /config/device-groups/
create_iceberg_devices_devices_by_id	POST /config/devices/
create_iceberg_network_group_network_group_by_id	POST /config/network-group/{network_group_name}/
create_iceberg_network_groups_network_groups_by_id	POST /config/network-groups/
create_iceberg_notification_notification_by_id	POST /config/notification/{notification_name}/
create_iceberg_notifications_notifications_by_id	POST /config/notifications/
create_iceberg_playbook_playbook_by_id	POST /config/playbook/{playbook_name}/
create_iceberg_playbooks_playbooks_by_id	POST /config/playbooks/
create_iceberg_retention_policies_retention_policies_by_id	POST /config/retention-policies/
create_iceberg_retention_policy_retention_policy_by_id	POST /config/retention-policy/{retention_policy_name}/
create_iceberg_system_destination_by_id	POST /config/system/report-generation/destination/{name}/
create_iceberg_system_destinations	POST /config/system/report-generation/destinations/
create_iceberg_system_report_by_id	POST /config/system/report-generation/report/{name}/
create_iceberg_system_reports	POST /config/system/report-generation/reports/
create_iceberg_system_scheduler_by_id	POST /config/system/scheduler/{name}/
create_iceberg_system_schedulers	POST /config/system/schedulers/
create_iceberg_system_settings_destination_by_id	POST /config/system-settings/report-generation/destination/{name}/
create_iceberg_system_settings_destinations	POST /config/system-settings/report-generation/destinations/
create_iceberg_system_settings_report_by_id	POST /config/system-settings/report-generation/report/{name}/
create_iceberg_system_settings_reports	POST /config/system-settings/report-generation/reports/
create_iceberg_system_settings_scheduler_by_id	POST /config/system-settings/scheduler/{name}/
create_iceberg_system_settings_schedulers	POST /config/system-settings/schedulers/
create_iceberg_system_settings_system_settings_by_id	POST /config/system-settings/
create_iceberg_system_system_by_id	POST /config/system/
create_iceberg_topic_rule_rule_by_id	POST /config/topic/{topic_name}/rule/{rule_name}/
create_iceberg_topic_topic_by_id	POST /config/topic/{topic_name}/
create_iceberg_topics_topics_by_id	POST /config/topics/
delete_healthbot_ingest_byoi_ingest_mappings	DELETE /config/ingest/byoi/ingest-mappings/
delete_healthbot_ingest_settings_byoi_ingest_mappings	DELETE /config/ingest-settings/byoi/ingest-mappings/
delete_healthbot_organizations_organizations	DELETE /config/organizations/
delete_healthbot_topic_resource_resource_by_id	DELETE /config/topic/{topic_name}/resource/{resource_name}/

Table 2 – continued from previous page

Method	HTTP request
delete_iceberg_device_device_by_id	DELETE /config/device/{device_id}/
delete_iceberg_device_group_device_group_by_id	DELETE /config/device-group/{device_group_name}/
delete_iceberg_device_groups_device_groups_by_id	DELETE /config/device-groups/
delete_iceberg_devices_devices_by_id	DELETE /config/devices/
delete_iceberg_network_group_network_group_by_id	DELETE /config/network-group/{network_group_name}/
delete_iceberg_network_groups_network_groups_by_id	DELETE /config/network-groups/
delete_iceberg_notification_notification_by_id	DELETE /config/notification/{notification_name}/
delete_iceberg_notifications_notifications_by_id	DELETE /config/notifications/
delete_iceberg_playbook_playbook_by_id	DELETE /config/playbook/{playbook_name}/
delete_iceberg_playbooks_playbooks_by_id	DELETE /config/playbooks/
delete_iceberg_retention_policies_retention_policies_by_id	DELETE /config/retention-policies/
delete_iceberg_retention_policy_retention_policy_by_id	DELETE /config/retention-policy/{retention_policy_name}/
delete_iceberg_system_destination_by_id	DELETE /config/system/report-generation/destination/{name}/
delete_iceberg_system_destinations	DELETE /config/system/report-generation/destinations/
delete_iceberg_system_report_by_id	DELETE /config/system/report-generation/report/{name}/
delete_iceberg_system_reports	DELETE /config/system/report-generation/reports/
delete_iceberg_system_scheduler_by_id	DELETE /config/system/scheduler/{name}/
delete_iceberg_system_schedulers	DELETE /config/system/schedulers/
delete_iceberg_system_settings_destination_by_id	DELETE /config/system-settings/report-generation/destination/
delete_iceberg_system_settings_destinations	DELETE /config/system-settings/report-generation/destinations
delete_iceberg_system_settings_report_by_id	DELETE /config/system-settings/report-generation/report/{name}
delete_iceberg_system_settings_reports	DELETE /config/system-settings/report-generation/reports/
delete_iceberg_system_settings_scheduler_by_id	DELETE /config/system-settings/scheduler/{name}/
delete_iceberg_system_settings_schedulers	DELETE /config/system-settings/schedulers/
delete_iceberg_system_settings_system_settings_by_id	DELETE /config/system-settings/
delete_iceberg_system_system_by_id	DELETE /config/system/
delete_iceberg_topic_rule_rule_by_id	DELETE /config/topic/{topic_name}/rule/{rule_name}/
delete_iceberg_topic_topic_by_id	DELETE /config/topic/{topic_name}/
delete_iceberg_topics_topics_by_id	DELETE /config/topics/
first_login	POST /first-login/
initialize	POST /config/initialize/
retrieve_affected_groups	GET /config/configuration/
retrieve_device_group_status	GET /device-group/{device_group_name}/status/
retrieve_device_group_trigger_info	GET /device-group/{device_group_name}/trigger_info/
retrieve_healthbot_organizations_organizations	GET /config/organizations/
retrieve_iceberg_device_device	GET /config/device/
retrieve_iceberg_device_device_by_id	GET /config/device/{device_id}/
retrieve_iceberg_device_group_device_group	GET /config/device-group/
retrieve_iceberg_device_group_device_group_by_id	GET /config/device-group/{device_group_name}/
retrieve_iceberg_device_groups_device_groups	GET /config/device-groups/
retrieve_iceberg_devices_devices	GET /config/devices/
retrieve_iceberg_network_group_network_group	GET /config/network-group/
retrieve_iceberg_network_group_network_group_by_id	GET /config/network-group/{network_group_name}/
retrieve_iceberg_network_groups_network_groups	GET /config/network-groups/
retrieve_iceberg_notification_notification	GET /config/notification/
retrieve_iceberg_notification_notification_by_id	GET /config/notification/{notification_name}/
retrieve_iceberg_notifications_notifications_by_id	GET /config/notifications/
retrieve_iceberg_playbook_playbook	GET /config/playbook/
retrieve_iceberg_playbook_playbook_by_id	GET /config/playbook/{playbook_name}/

Table 2 – continued from previous page

Method	HTTP request
retrieve_iceberg_playbooks_playbooks_by_id	GET /config/playbooks/
retrieve_iceberg_retention_policies_retention_policies_by_id	GET /config/retention-policies/
retrieve_iceberg_retention_policy_retention_policy	GET /config/retention-policy/
retrieve_iceberg_retention_policy_retention_policy_by_id	GET /config/retention-policy/{retention_policy_name}/
retrieve_iceberg_system_destination_by_id	GET /config/system/report-generation/destination/{name}/
retrieve_iceberg_system_destinations	GET /config/system/report-generation/destinations/
retrieve_iceberg_system_report_by_id	GET /config/system/report-generation/report/{name}/
retrieve_iceberg_system_reports	GET /config/system/report-generation/reports/
retrieve_iceberg_system_scheduler_by_id	GET /config/system/scheduler/{name}/
retrieve_iceberg_system_schedulers	GET /config/system/schedulers/
retrieve_iceberg_system_settings_destination_by_id	GET /config/system-settings/report-generation/destination/{name}/
retrieve_iceberg_system_settings_destinations	GET /config/system-settings/report-generation/destinations/
retrieve_iceberg_system_settings_report_by_id	GET /config/system-settings/report-generation/report/{name}/
retrieve_iceberg_system_settings_reports	GET /config/system-settings/report-generation/reports/
retrieve_iceberg_system_settings_scheduler_by_id	GET /config/system-settings/scheduler/{name}/
retrieve_iceberg_system_settings_schedulers	GET /config/system-settings/schedulers/
retrieve_iceberg_system_settings_system_settings	GET /config/system-settings/
retrieve_iceberg_system_system	GET /config/system/
retrieve_iceberg_topic_rule_rule	GET /config/topic/{topic_name}/rule/
retrieve_iceberg_topic_rule_rule_by_id	GET /config/topic/{topic_name}/rule/{rule_name}/
retrieve_iceberg_topic_topic	GET /config/topic/
retrieve_iceberg_topic_topic_by_id	GET /config/topic/{topic_name}/
retrieve_iceberg_topics_topics	GET /config/topics/
retrieve_network_group_status	GET /network-group/{network_group_name}/status/
retrieve_network_group_trigger_info	GET /network-group/{network_group_name}/trigger_info/
retrieve_orchestrator	GET /orchestrator/
rollback_unsaved_configuration	DELETE /config/configuration/
update_healthbot_organizations_organizations	PUT /config/organizations/
update_healthbot_topic_resource_resource_by_id	PUT /config/topic/{topic_name}/resource/{resource_name}/
update_iceberg_device_device_by_id	PUT /config/device/{device_id}/
update_iceberg_device_group_device_group_by_id	PUT /config/device-group/{device_group_name}/
update_iceberg_device_groups_device_groups_by_id	PUT /config/device-groups/
update_iceberg_devices_devices_by_id	PUT /config/devices/
update_iceberg_network_group_network_group_by_id	PUT /config/network-group/{network_group_name}/
update_iceberg_network_groups_network_groups_by_id	PUT /config/network-groups/
update_iceberg_notification_notification_by_id	PUT /config/notification/{notification_name}/
update_iceberg_notifications_notifications_by_id	PUT /config/notifications/
update_iceberg_playbook_playbook_by_id	PUT /config/playbook/{playbook_name}/
update_iceberg_playbooks_playbooks_by_id	PUT /config/playbooks/
update_iceberg_retention_policies_retention_policies_id	PUT /config/retention-policies/
update_iceberg_retention_policy_retention_policy_by_id	PUT /config/retention-policy/{retention_policy_name}/
update_iceberg_system_destination_by_id	PUT /config/system/report-generation/destination/{name}/
update_iceberg_system_destinations	PUT /config/system/report-generation/destinations/
update_iceberg_system_report_by_id	PUT /config/system/report-generation/report/{name}/
update_iceberg_system_reports	PUT /config/system/report-generation/reports/
update_iceberg_system_scheduler_by_id	PUT /config/system/scheduler/{name}/
update_iceberg_system_schedulers	PUT /config/system/schedulers/
update_iceberg_system_settings_destination_by_id	PUT /config/system-settings/report-generation/destination/{name}/
update_iceberg_system_settings_destinations	PUT /config/system-settings/report-generation/destinations/

Table 2 – continued from previous page

Method	HTTP request
<code>**update_iceberg_system_settings_report_by_id**</code>	PUT /config/system-settings/report-generation/report/{name}/
<code>**update_iceberg_system_settings_reports**</code>	PUT /config/system-settings/report-generation/reports/
<code>**update_iceberg_system_settings_scheduler_by_id**</code>	PUT /config/system-settings/scheduler/{name}/
<code>**update_iceberg_system_settings_schedulers**</code>	PUT /config/system-settings/schedulers/
<code>**update_iceberg_system_settings_system_settings_by_id**</code>	PUT /config/system-settings/
<code>**update_iceberg_system_system_by_id**</code>	PUT /config/system/
<code>**update_iceberg_topic_rule_rule_by_id**</code>	PUT /config/topic/{topic_name}/rule/{rule_name}/
<code>**update_iceberg_topic_topic_by_id**</code>	PUT /config/topic/{topic_name}/
<code>**update_iceberg_topics_topics_by_id**</code>	PUT /config/topics/

2.459 check_device_group_unsaved_configuration

`check_device_group_unsaved_configuration(device_group_name, x_iam_token=x_iam_token)`

Check if the un-committed configuration of the given device group is correct

Checks if the un-committed configuration of a device-group is correct. The un-committed changes are merged with the committed configuration and the complete configuration required for the supplied device-group is validated.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
device_group_name = 'device_group_name_example' # str | Name of device group
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Check if the un-committed configuration of the given device group is correct
    api_instance.check_device_group_unsaved_configuration(device_group_name, x_iam_
↪token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->check_device_group_unsaved_
↪configuration: %s\n" % e)
```

Name	Type	Description	Notes
<code>device_group_name</code>	str	Name of device group	
<code>x_iam_token</code>	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.460 check_network_group_unsaved_configuration

`check_network_group_unsaved_configuration(network_group_name, x_iam_token=x_iam_token)`

Check if the unsaved configuration of the given network group is correct.

Checks if the un-committed configuration of a network-group is correct. The un-committed changes are merged with the committed configuration and the complete configuration required for the supplied network-group is validated.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
network_group_name = 'network_group_name_example' # str | Name of network group
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Check if the unsaved configuration of the given network group is correct.
    api_instance.check_network_group_unsaved_configuration(network_group_name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->check_network_group_unsaved_configuration: %s\n" % e)
```

Name	Type	Description	Notes
<code>network_group_name</code>	<code>str</code>	Name of network group	
<code>x_iam_token</code>	<code>str</code>	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.461 commit_unsaved_configuration

`commit_unsaved_configuration(x_iam_token=x_iam_token, sync=sync)`

Commit unsaved configuration.

Commit the configuration in configuration database. Services of all the affected groups are started or restarted. If there is an error in the configuration, changes would not be saved into the database. If there is some system error, changes would be saved into the database.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
```

(continues on next page)

(continued from previous page)

```

from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
sync = True # bool | Boolean variable is set to false allow the commit to go
↳ asynchronously, default value is true which means commit will go synchronously
↳ (optional) (default to true)

try:
    # Commit unsaved configuration.
    api_instance.commit_unsaved_configuration(x_iam_token=x_iam_token, sync=sync)
except ApiException as e:
    print("Exception when calling ConfigurationApi->commit_unsaved_configuration: %s\n"
↳ " % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
sync	bool	Boolean variable is set to false allow the commit to go asynchronously, default value is true which means commit will go synchronously	[optional] [default to true]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.462 create_healthbot_organizations_organizations

create_healthbot_organizations_organizations(organizations, x_iam_token=x_iam_token)

Update or create multiple organizations.

Create/Update multiple organizations. The new content for the existing organizations updates the existing content and the new organizations are created.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
organizations = swagger_client.OrganizationsSchema() # OrganizationsSchema |
↳ organizations body object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update or create multiple organizations.
    api_instance.create_healthbot_organizations_organizations(organizations, x_iam_
↳ token=x_iam_token)

```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_healthbot_organizations_
↳organizations: %s\n" % e)
```

Name	Type	Description	Notes
organizations	**OrganizationsSchema**	organizations body object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.463 create_healthbot_topic_resource_resource_by_id

create_healthbot_topic_resource_resource_by_id(topic_name, resource_name, resource, authorization=authorization)

Update or create a resource

Create/Update a resource by resource-name. The resource-name specified in URL and the request body must match. If the resource already exists then, the existing resource's configuration will be updated with the new content

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
topic_name = 'topic_name_example' # str | ID of topic-name
resource_name = 'resource_name_example' # str | ID of resource-name
resource = swagger_client.ResourceSchema() # ResourceSchema | resourcebody object
authorization = 'authorization_example' # str | authentication header object_
↳(optional)

try:
    # Update or create a resource
    api_instance.create_healthbot_topic_resource_resource_by_id(topic_name, resource_
↳name, resource, authorization=authorization)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_healthbot_topic_resource_
↳resource_by_id: %s\n" % e)
```

Name	Type	Description	Notes
topic_name	str	ID of topic-name	
resource_name	str	ID of resource-name	
resource	**ResourceSchema**	resourcebody object	
authorization	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.464 create_iceberg_device_device_by_id

create_iceberg_device_device_by_id(device_id, device, x_iam_token=x_iam_token)

Update or create a device.

Create/Update a device by device-id. The device-id specified in URL and the request body must match. If the device already exists then, old content will be updated with the new content.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
device_id = 'device_id_example' # str | ID of device-id
device = swagger_client.DeviceSchema() # DeviceSchema | devicebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update or create a device.
    api_instance.create_iceberg_device_device_by_id(device_id, device, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_device_device_by_id: %s\n" % e)
```

Name	Type	Description	Notes
device_id	str	ID of device-id	
device	**DeviceSchema**	devicebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.465 create_iceberg_device_group_device_group_by_id

```
create_iceberg_device_group_device_group_by_id(device_group_name, device_group,
x_iam_token=x_iam_token)
```

Update or create a device-group.

Create/Update a device-group by device-group-name. The device-group-name specified in URL and the request body must match. If the device-group already exists then, old content will be updated with the new content

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
device_group_name = 'device_group_name_example' # str | ID of device-group-name
device_group = swagger_client.DeviceGroupSchema() # DeviceGroupSchema | device_
↳groupbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update or create a device-group.
    api_instance.create_iceberg_device_group_device_group_by_id(device_group_name,
↳device_group, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_device_group_
↳device_group_by_id: %s\n" % e)
```

Name	Type	Description	Notes
device_group_name	str	ID of device-group-name	
device_group	**DeviceGroupSchema**	device_groupbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.466 create_iceberg_device_groups_device_groups_by_id

```
create_iceberg_device_groups_device_groups_by_id(device_groups, x_iam_token=x_iam_token)
```

Update or create multiple device-groups.

Create/Update multiple device-groups. The new content for the existing device-groups updates the existing content and new device-groups are created.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
device_groups = swagger_client.DeviceGroupsSchema() # DeviceGroupsSchema | device-
↳groupsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update or create multiple device-groups.
    api_instance.create_iceberg_device_groups_by_id(device_groups, x_
↳iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_device_groups_
↳device_groups_by_id: %s\n" % e)

```

Name	Type	Description	Notes
device_groups	**DeviceGroupsSchema**	device-groupsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.467 create_iceberg_devices_devices_by_id

create_iceberg_devices_devices_by_id(devices, x_iam_token=x_iam_token)

Update or create multiple devices.

Create/Update multiple devices. The new content for the existing devices updates the existing content and the new devices are created.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
devices = swagger_client.DevicesSchema() # DevicesSchema | devicesbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update or create multiple devices.

```

(continues on next page)

(continued from previous page)

```

    api_instance.create_iceberg_devices_devices_by_id(devices, x_iam_token=x_iam_
↪token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_devices_devices_by_
↪id: %s\n" % e)

```

Name	Type	Description	Notes
devices	**DevicesSchema**	devicesbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.468 create_iceberg_network_group_network_group_by_id

```

create_iceberg_network_group_network_group_by_id(network_group_name,          network_group,
x_iam_token=x_iam_token)

```

Update or create a network-group.

Create/Update a network-group by network-group-name. The network-group-name parameter specified in URL and the request body must match. If the network-group already exists then, the existing network-group's configuration will be updated with the new content.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
network_group_name = 'network_group_name_example' # str | ID of network-group-name
network_group = swagger_client.NetworkGroupSchema() # NetworkGroupSchema | network_
↪groupbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update or create a network-group.
    api_instance.create_iceberg_network_group_network_group_by_id(network_group_name, ↪
↪network_group, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_network_group_
↪network_group_by_id: %s\n" % e)

```

Name	Type	Description	Notes
network_group_name	str	ID of network-group-name	
network_group	**NetworkGroupSchema**	network_groupbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.469 create_iceberg_network_groups_network_groups_by_id

create_iceberg_network_groups_network_groups_by_id(network_groups, x_iam_token=x_iam_token)

Update or create multiple network-groups.

Create/Update multiple network-groups. The new content for the existing network-groups updates the existing content and the new network-groups are created.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
network_groups = swagger_client.NetworkGroupsSchema() # NetworkGroupsSchema | network-
↳ groupsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update or create multiple network-groups.
    api_instance.create_iceberg_network_groups_network_groups_by_id(network_groups, x_
↳ iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_network_groups_
↳ network_groups_by_id: %s\n" % e)
```

Name	Type	Description	Notes
network_groups	**NetworkGroupsSchema**	network-groupsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.470 create_iceberg_notification_notification_by_id

```
create_iceberg_notification_notification_by_id(notification_name, notification,
x_iam_token=x_iam_token)
```

Update or create a notification

Create/Update a notification by notification-name. The notification-name specified in URL and the request body must match. If the notification already exists then, the existing notification's configuration will be updated with the new content.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
notification_name = 'notification_name_example' # str | ID of notification-name
notification = swagger_client.NotificationSchema() # NotificationSchema |
↳notificationbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update or create a notification
    api_instance.create_iceberg_notification_notification_by_id(notification_name,
↳notification, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_notification_
↳notification_by_id: %s\n" % e)
```

Name	Type	Description	Notes
notification_name	str	ID of notification-name	
notification	**NotificationSchema**	notificationbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.471 create_iceberg_notifications_notifications_by_id

```
create_iceberg_notifications_notifications_by_id(notifications, x_iam_token=x_iam_token)
```

Update or create multiple notifications.

Create/Update multiple notifications. The new content for the existing notifications updates the existing content and the new notifications are created.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
notifications = swagger_client.NotificationsSchema() # NotificationsSchema | ↪notificationsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update or create multiple notifications.
    api_instance.create_iceberg_notifications_notifications_by_id(notifications, x_
    ↪iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_notifications_
    ↪notifications_by_id: %s\n" % e)

```

Name	Type	Description	Notes
notifications	**NotificationsSchema**	notificationsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.472 create_iceberg_playbook_playbook_by_id

create_iceberg_playbook_playbook_by_id(playbook_name, playbook, x_iam_token=x_iam_token)

Update or create a playbook.

Create/Update a playbook by `playbook-name`. The `playbook-name` specified in URL and the request body must match. If the playbook already exists then, the existing playbook's configuration will be updated with the new content.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
playbook_name = 'playbook_name_example' # str | ID of playbook-name
playbook = swagger_client.PlaybookSchema() # PlaybookSchema | playbookbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

```

(continues on next page)

(continued from previous page)

```

try:
    # Update or create a playbook.
    api_instance.create_iceberg_playbook_playbook_by_id(playbook_name, playbook, x_
↳ iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_playbook_playbook_
↳ by_id: %s\n" % e)

```

Name	Type	Description	Notes
playbook_name	str	ID of playbook-name	
playbook	**PlaybookSchema**	playbookbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.473 create_iceberg_playbooks_playbooks_by_id

create_iceberg_playbooks_playbooks_by_id(playbooks, x_iam_token=x_iam_token)

Update or create multiple playbooks.

Create/Update multiple playbooks. The new content for the existing playbooks updates the existing content and the new playbooks are created.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
playbooks = swagger_client.PlaybooksSchema() # PlaybooksSchema | playbooksbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update or create multiple playbooks.
    api_instance.create_iceberg_playbooks_playbooks_by_id(playbooks, x_iam_token=x_
↳ iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_playbooks_
↳ playbooks_by_id: %s\n" % e)

```

Name	Type	Description	Notes
playbooks	**PlaybooksSchema**	playbooksbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.474 create_iceberg_retention_policies_retention_policies_by_id

```
create_iceberg_retention_policies_retention_policies_by_id(retention_policies,
x_iam_token=x_iam_token)
```

Update or create multiple retention-policies.

Create/Update multiple retention-policies. The new content for the existing retention-policies update the existing content and the new retention-policies are created.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
retention_policies = swagger_client.RetentionPoliciesSchema() #_
↳RetentionPoliciesSchema | retention-policiesbody object object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update or create multiple retention-policies.
    api_instance.create_iceberg_retention_policies_retention_policies_by_id(retention_
↳policies, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_retention_policies_
↳retention_policies_by_id: %s\n" % e)
```

Name	Type	Description	Notes
retention_policies	**RetentionPoliciesSchema**	retention-policiesbody object object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.475 create_iceberg_retention_policy_retention_policy_by_id

```
create_iceberg_retention_policy_retention_policy_by_id(retention_policy_name, retention_policy,
x_iam_token=x_iam_token)
```

Update or create a retention-policy.

Create/Update a retention-policy by `retention-policy-name`. The `retention-policy-name` specified in URL and the request body must match. If the retention-policy exists then, the existing retention-policy's configuration will be updated by the new content.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
retention_policy_name = 'retention_policy_name_example' # str | ID of retention-
↳policy-name
retention_policy = swagger_client.RetentionPolicySchema() # RetentionPolicySchema |
↳retention_policybody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update or create a retention-policy.
    api_instance.create_iceberg_retention_policy_retention_policy_by_id(retention_
↳policy_name, retention_policy, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_retention_policy_
↳retention_policy_by_id: %s\n" % e)
```

Name	Type	Description	Notes
retention_policy_name	str	ID of retention-policy-name	
retention_policy	**RetentionPolicySchema**	retention_policybody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.476 create_iceberg_system_destination_by_id

```
create_iceberg_system_destination_by_id(name, destination, x_iam_token=x_iam_token)
```

Create destination by name

Create/Update a destination by `name`. The `name` specified in URL and the request body must match. If the destination exists then, the existing destination's configuration will be updated by the new content.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of destination
destination = swagger_client.DestinationSchema() # DestinationSchema | ↪
↪ destinationsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create destination by name
    api_instance.create_iceberg_system_destination_by_id(name, destination, x_iam_
    ↪ token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_system_destination_
    ↪ by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of destination	
destination	**DestinationSchema**	destinationsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.477 create_iceberg_system_destinations

create_iceberg_system_destinations(destinations, x_iam_token=x_iam_token)

Create destinations by name

Create/Update multiple destinations. The new content for the existing destinations updates the existing content and the new destinations are created.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
destinations = swagger_client.DestinationsSchema() # DestinationsSchema | ↪
↪ destinationsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

```

(continues on next page)

(continued from previous page)

```

try:
    # Create destinations by name
    api_instance.create_iceberg_system_destinations(destinations, x_iam_token=x_iam_
↳token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_system_
↳destinations: %s\n" % e)

```

Name	Type	Description	Notes
destinations	**DestinationsSchema**	destinationsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.478 create_iceberg_system_report_by_id

create_iceberg_system_report_by_id(name, report, x_iam_token=x_iam_token)

Create report by name

Create/Update a report by name. The name specified in URL and the request body must match. If the report exists then, the existing report's configuration will be updated by the new content.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of report
report = swagger_client.ReportSchema() # ReportSchema | reportsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create report by name
    api_instance.create_iceberg_system_report_by_id(name, report, x_iam_token=x_iam_
↳token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_system_report_by_
↳id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of report	
report	**ReportSchema**	reportsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.479 create_iceberg_system_reports

```
create_iceberg_system_reports(reports, x_iam_token=x_iam_token)
```

Create reports by name

Create/Update multiple reports. The new content for the existing reports updates the existing content and the new reports are created.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
reports = swagger_client.ReportsSchema() # ReportsSchema | reportsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create reports by name
    api_instance.create_iceberg_system_reports(reports, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_system_reports:
↪ %s\n" % e)
```

Name	Type	Description	Notes
reports	**ReportsSchema**	reportsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.480 create_iceberg_system_scheduler_by_id

create_iceberg_system_scheduler_by_id(name, scheduler, x_iam_token=x_iam_token)

Create scheduler by name

Create/Update a scheduler by name. The name specified in URL and the request body must match. If the scheduler exists then, the existing scheduler's configuration will be updated by the new content.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of Scheduler
scheduler = swagger_client.SchedulerSchema() # SchedulerSchema | schedulerbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create scheduler by name
    api_instance.create_iceberg_system_scheduler_by_id(name, scheduler, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_system_scheduler_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of Scheduler	
scheduler	**SchedulerSchema**	schedulerbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.481 create_iceberg_system_schedulers

create_iceberg_system_schedulers(schedulers, x_iam_token=x_iam_token)

Create schedulers by name

Create/Update multiple schedulers. The new content for the existing schedulers updates the existing content and the new schedulers are created.

```
from __future__ import print_function
import time
import swagger_client
```

(continues on next page)

(continued from previous page)

```

from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
schedulers = swagger_client.SchedulersSchema() # SchedulersSchema | schedulersbody_
↳object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create schedulers by name
    api_instance.create_iceberg_system_schedulers(schedulers, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_system_schedulers:
↳%s\n" % e)

```

Name	Type	Description	Notes
schedulers	**SchedulersSchema**	schedulersbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.482 create_iceberg_system_settings_destination_by_id

create_iceberg_system_settings_destination_by_id(name, destination, x_iam_token=x_iam_token)

Create destination by name

Create/Update a destination by name. The name specified in URL and the request body must match. If the destination exists then, the existing destination's configuration will be updated by the new content.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of destination
destination = swagger_client.DestinationSchema() # DestinationSchema |_
↳destinationbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create destination by name
    api_instance.create_iceberg_system_settings_destination_by_id(name, destination,
↳x_iam_token=x_iam_token)

```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_system_settings_
↳destination_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of destination	
destination	**DestinationSchema**	destinationsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.483 create_iceberg_system_settings_destinations

```
create_iceberg_system_settings_destinations(destinations, x_iam_token=x_iam_token)
```

Create destinations by name

Create/Update multiple destinations. The new content for the existing destinations updates the existing content and the new destinations are created.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
destinations = swagger_client.DestinationsSchema() # DestinationsSchema | _
↳destinationsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create destinations by name
    api_instance.create_iceberg_system_settings_destinations(destinations, x_iam_
↳token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_system_settings_
↳destinations: %s\n" % e)
```

Name	Type	Description	Notes
destinations	**DestinationsSchema**	destinationsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.484 create_iceberg_system_settings_report_by_id

create_iceberg_system_settings_report_by_id(name, report, x_iam_token=x_iam_token)

Create report by name

Create/Update a report by name. The name specified in URL and the request body must match. If the report exists then, the existing report's configuration will be updated by the new content.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of report
report = swagger_client.ReportSchema() # ReportSchema | reportsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create report by name
    api_instance.create_iceberg_system_settings_report_by_id(name, report, x_iam_
    ↪token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_system_settings_
    ↪report_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of report	
report	**ReportSchema**	reportsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.485 create_iceberg_system_settings_reports

create_iceberg_system_settings_reports(reports, x_iam_token=x_iam_token)

Create reports by name

Create/Update multiple reports. The new content for the existing reports updates the existing content and the new reports are created.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
reports = swagger_client.ReportsSchema() # ReportsSchema | reportsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create reports by name
    api_instance.create_iceberg_system_settings_reports(reports, x_iam_token=x_iam_
↳token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_system_settings_
↳reports: %s\n" % e)
```

Name	Type	Description	Notes
reports	**ReportsSchema**	reportsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.486 create_iceberg_system_settings_scheduler_by_id

create_iceberg_system_settings_scheduler_by_id(name, scheduler, x_iam_token=x_iam_token)

Create scheduler by name

Create/Update a scheduler by name. The name specified in URL and the request body must match. If the scheduler exists then, the existing scheduler's configuration will be updated by the new content.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of Scheduler
scheduler = swagger_client.SchedulerSchema() # SchedulerSchema | schedulerbody object
```

(continues on next page)

(continued from previous page)

```
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create scheduler by name
    api_instance.create_iceberg_system_settings_scheduler_by_id(name, scheduler, x_
↳ iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_system_settings_
↳ scheduler_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of Scheduler	
scheduler	**SchedulerSchema**	schedulerbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.487 create_iceberg_system_settings_schedulers

create_iceberg_system_settings_schedulers(schedulers, x_iam_token=x_iam_token)

Create schedulers by name

Create/Update multiple schedulers. The new content for the existing schedulers updates the existing content and the new schedulers are created.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
schedulers = swagger_client.SchedulersSchema() # SchedulersSchema | schedulersbody_
↳ object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create schedulers by name
    api_instance.create_iceberg_system_settings_schedulers(schedulers, x_iam_token=x_
↳ iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_system_settings_
↳ schedulers: %s\n" % e)
```

Name	Type	Description	Notes
schedulers	**SchedulersSchema**	schedulersbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.488 create_iceberg_system_settings_system_settings_by_id

```
create_iceberg_system_settings_system_settings_by_id(system_settings, x_iam_token=x_iam_token,
force_tsdb=force_tsdb)
```

Create system-settings

Create/Update system-settings to populate persis-raw-data, schedulers, destinations and reports.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
system_settings = swagger_client.SystemSettingsSchema() # SystemSettingsSchema | ↪
system_settings body object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
force_tsdb = False # bool | force update tsdb when force is set to True (optional) ↪
# (default to False)

try:
    # Create system-settings
    api_instance.create_iceberg_system_settings_system_settings_by_id(system_settings,
    ↪ x_iam_token=x_iam_token, force_tsdb=force_tsdb)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_system_settings_
    ↪ system_settings_by_id: %s\n" % e)
```

Name	Type	Description	Notes
sys-tem_settings	**SystemSettingsS-chema**	system_settings body object	
x_iam_token	str	authentication header object	[optional]
force_tsdb	bool	force update tsdb when force is set to True	[optional] [default to false]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.489 create_iceberg_system_system_by_id

```
create_iceberg_system_system_by_id(system_settings, x_iam_token=x_iam_token,
force_tsdb=force_tsdb)
```

Create system

Create/Update system to populate persist-raw-data, schedulers, destinations and reports.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
system_settings = swagger_client.SystemSettingsSchema() # SystemSettingsSchema |_
↳system_settings body object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
force_tsdb = False # bool | force update tsdb when force is set to True (optional)_
↳(default to false)

try:
    # Create system
    api_instance.create_iceberg_system_system_by_id(system_settings, x_iam_token=x_
↳iam_token, force_tsdb=force_tsdb)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_system_system_by_
↳id: %s\n" % e)
```

Name	Type	Description	Notes
sys-tem_settings	**SystemSettingsS-chema**	system_settings body object	
x_iam_token	str	authentication header object	[optional]
force_tsdb	bool	force update tsdb when force is set to True	[optional] [default to false]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.490 create_iceberg_topic_rule_rule_by_id

create_iceberg_topic_rule_rule_by_id(topic_name, rule_name, rule, x_iam_token=x_iam_token)

Update or create a rule.

Create/Update a rule by rule-name. The rule-name specified in URL and the request body must match. If the rule already exists then, the existing rule's configuration will be updated with the new content

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
topic_name = 'topic_name_example' # str | ID of topic-name
rule_name = 'rule_name_example' # str | ID of rule-name
rule = swagger_client.RuleSchema() # RuleSchema | rulebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update or create a rule.
    api_instance.create_iceberg_topic_rule_rule_by_id(topic_name, rule_name, rule, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_topic_rule_rule_by_id: %s\n" % e)
```

Name	Type	Description	Notes
topic_name	str	ID of topic-name	
rule_name	str	ID of rule-name	
rule	**RuleSchema**	rulebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.491 create_iceberg_topic_topic_by_id

create_iceberg_topic_topic_by_id(topic_name, topic, x_iam_token=x_iam_token)

Update or create a topic.

Create/Update a topic by topic-name. The topic-name specified in URL and the request body must match. If the topic already exists then, the existing topic's configuration will be updated with the new content.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
topic_name = 'topic_name_example' # str | ID of topic-name
topic = swagger_client.TopicSchema() # TopicSchema | topicbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update or create a topic.
    api_instance.create_iceberg_topic_topic_by_id(topic_name, topic, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_topic_topic_by_id: %s\n" % e)

```

Name	Type	Description	Notes
topic_name	str	ID of topic-name	
topic	**TopicSchema**	topicbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.492 create_iceberg_topics_topics_by_id

create_iceberg_topics_topics_by_id(topics, x_iam_token=x_iam_token)

Update or create multiple topics.

Create/Update multiple topics. The new content for the existing topics updates the existing content and the new topics are created.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
topics = swagger_client.TopicsSchema() # TopicsSchema | topicsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:

```

(continues on next page)

(continued from previous page)

```

    # Update or create multiple topics.
    api_instance.create_iceberg_topics_topics_by_id(topics, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->create_iceberg_topics_topics_by_
↳id: %s\n" % e)

```

Name	Type	Description	Notes
topics	**TopicsSchema**	topicsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.493 delete_healthbot_ingest_byoi_ingest_mappings

```
delete_healthbot_ingest_byoi_ingest_mappings(x_iam_token=x_iam_token)
```

Delete all ingest-mappings.

Delete all ingest-mappings.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete all ingest-mappings.
    api_instance.delete_healthbot_ingest_byoi_ingest_mappings(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_healthbot_ingest_byoi_
↳ingest_mappings: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.494 delete_healthbot_ingest_settings_byoi_ingest_mappings

`delete_healthbot_ingest_settings_byoi_ingest_mappings(x_iam_token=x_iam_token)`

Delete all ingest-mappings.

Delete all ingest-mappings.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete all ingest-mappings.
    api_instance.delete_healthbot_ingest_settings_byoi_ingest_mappings(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_healthbot_ingest_settings_byoi_ingest_mappings: %s\n" % e)
```

Name	Type	Description	Notes
<code>x_iam_token</code>	<code>str</code>	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.495 delete_healthbot_organizations_organizations

`delete_healthbot_organizations_organizations(x_iam_token=x_iam_token)`

Delete all organizations.

Delete all organizations. This will fail if any organization edge is referenced in any device-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint
```

(continues on next page)

(continued from previous page)

```
# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete all organizations.
    api_instance.delete_healthbot_organizations_organizations(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_healthbot_organizations_
↳organizations: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.496 delete_healthbot_topic_resource_resource_by_id

delete_healthbot_topic_resource_resource_by_id(topic_name, resource_name, authoriza-
tion=authorization)

Delete resource

Delete a resource by 'resource-name'

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
topic_name = 'topic_name_example' # str | ID of topic-name
resource_name = 'resource_name_example' # str | ID of resource-name
authorization = 'authorization_example' # str | authentication header object,
↳(optional)

try:
    # Delete resource
    api_instance.delete_healthbot_topic_resource_resource_by_id(topic_name, resource_
↳name, authorization=authorization)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_healthbot_topic_resource_
↳resource_by_id: %s\n" % e)
```

Name	Type	Description	Notes
topic_name	str	ID of topic-name	
resource_name	str	ID of resource-name	
authorization	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.497 delete_iceberg_device_device_by_id

`delete_iceberg_device_device_by_id(device_id, x_iam_token=x_iam_token)`

Delete device.

Delete a device by device-id. Delete will fail if the device is being referenced by a device-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
device_id = 'device_id_example' # str | ID of device-id
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete device.
    api_instance.delete_iceberg_device_device_by_id(device_id, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_device_device_by_id: %s\n" % e)
```

Name	Type	Description	Notes
device_id	str	ID of device-id	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.498 delete_iceberg_device_group_device_group_by_id

```
delete_iceberg_device_group_device_group_by_id(device_group_name, x_iam_token=x_iam_token)
```

Delete device-group.

Delete a device-group by device-group-name. Delete will fail if the device-group's services are running.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
device_group_name = 'device_group_name_example' # str | ID of device-group-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete device-group.
    api_instance.delete_iceberg_device_group_device_group_by_id(device_group_name, x_
↳ iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_device_group_
↳ device_group_by_id: %s\n" % e)
```

Name	Type	Description	Notes
<code>device_group_name</code>	<code>str</code>	ID of device-group-name	
<code>x_iam_token</code>	<code>str</code>	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.499 delete_iceberg_device_groups_device_groups_by_id

```
delete_iceberg_device_groups_device_groups_by_id(x_iam_token=x_iam_token)
```

Delete all device-groups.

Delete all device-groups. Delete fails if services are still running for the device groups.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
```

(continues on next page)

(continued from previous page)

```

api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete all device-groups.
    api_instance.delete_iceberg_device_groups_device_groups_by_id(x_iam_token=x_iam_
↪token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_device_groups_
↪device_groups_by_id: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.500 delete_iceberg_devices_devices_by_id

delete_iceberg_devices_devices_by_id(x_iam_token=x_iam_token)

Delete all devices.

Delete all devices. This will fail if any device is referenced in any device-group.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete all devices.
    api_instance.delete_iceberg_devices_devices_by_id(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_devices_devices_by_
↪id: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.501 delete_iceberg_network_group_network_group_by_id

```
delete_iceberg_network_group_network_group_by_id(network_group_name,  
x_iam_token=x_iam_token)
```

Delete network-group.

Delete a network-group by network-group-name. Delete will fail if the network-group's services are running.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
network_group_name = 'network_group_name_example' # str | ID of network-group-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete network-group.
    api_instance.delete_iceberg_network_group_network_group_by_id(network_group_name,
↪x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_network_group_
↪network_group_by_id: %s\n" % e)
```

Name	Type	Description	Notes
network_group_name	str	ID of network-group-name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.502 delete_iceberg_network_groups_network_groups_by_id

```
delete_iceberg_network_groups_network_groups_by_id(x_iam_token=x_iam_token)
```

Delete all network-groups.

Delete all network-groups. Delete will fail if services are still running for the network groups.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete all network-groups.
    api_instance.delete_iceberg_network_groups_network_groups_by_id(x_iam_token=x_iam_
↪token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_network_groups_
↪network_groups_by_id: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.503 delete_iceberg_notification_notification_by_id

delete_iceberg_notification_notification_by_id(notification_name, x_iam_token=x_iam_token)

Delete a notification.

Delete a notification by notification-name. Delete will fail if the notification is referenced by a device-group.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
notification_name = 'notification_name_example' # str | ID of notification-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete a notification.
    api_instance.delete_iceberg_notification_notification_by_id(notification_name, x_
↪iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_notification_
↪notification_by_id: %s\n" % e)

```

(continues on next page)

Name	Type	Description	Notes
notification_name	str	ID of notification-name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.504 delete_iceberg_notifications_notifications_by_id

delete_iceberg_notifications_notifications_by_id(x_iam_token=x_iam_token)

Delete all notifications.

Delete all notifications. This will fail if any notification is referenced in any device-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete all notifications.
    api_instance.delete_iceberg_notifications_notifications_by_id(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_notifications_notifications_by_id: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.505 delete_iceberg_playbook_playbook_by_id

```
delete_iceberg_playbook_playbook_by_id(playbook_name, x_iam_token=x_iam_token)
```

Delete a playbook.

Delete a playbook by `playbook-name`. Delete will fail if the playbook is referenced by a device-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
playbook_name = 'playbook_name_example' # str | ID of playbook-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete a playbook.
    api_instance.delete_iceberg_playbook_playbook_by_id(playbook_name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_playbook_playbook_by_id: %s\n" % e)
```

Name	Type	Description	Notes
playbook_name	str	ID of playbook-name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.506 delete_iceberg_playbooks_playbooks_by_id

```
delete_iceberg_playbooks_playbooks_by_id(x_iam_token=x_iam_token)
```

Delete all playbooks.

Delete all playbooks. This will fail if any playbook is referenced in any device-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
```

(continues on next page)

(continued from previous page)

```

api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete all playbooks.
    api_instance.delete_iceberg_playbooks_playbooks_by_id(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_playbooks_
    ↳playbooks_by_id: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.507 delete_iceberg_retention_policies_retention_policies_by_id

delete_iceberg_retention_policies_retention_policies_by_id(x_iam_token=x_iam_token)

Delete all retention-policies.

Delete all the retention policies. This will fail if any retention-policy is referenced in any device-group.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete all retention-policies.
    api_instance.delete_iceberg_retention_policies_retention_policies_by_id(x_iam_
    ↳token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_retention_policies_
    ↳retention_policies_by_id: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.508 delete_iceberg_retention_policy_retention_policy_by_id

```
delete_iceberg_retention_policy_retention_policy_by_id(retention_policy_name,
x_iam_token=x_iam_token)
```

Delete a retention-policy.

Delete a retention-policy by retention-policy-name. Delete will fail if the retention-policy is referenced by a device-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
retention_policy_name = 'retention_policy_name_example' # str | ID of retention-
↳policy-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete a retention-policy.
    api_instance.delete_iceberg_retention_policy_retention_policy_by_id(retention_
↳policy_name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_retention_policy_
↳retention_policy_by_id: %s\n" % e)
```

Name	Type	Description	Notes
retention_policy_name	str	ID of retention-policy-name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.509 delete_iceberg_system_destination_by_id

```
delete_iceberg_system_destination_by_id(name, x_iam_token=x_iam_token)
```

Delete destination by name

Delete a destination by `name`. Delete will fail if the destination is being referenced by a report.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of destination
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete destination by name
    api_instance.delete_iceberg_system_destination_by_id(name, x_iam_token=x_iam_
↪token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_system_destination_
↪by_id: %s\n" % e)
```

Name	Type	Description	Notes
<code>name</code>	<code>str</code>	Name of destination	
<code>x_iam_token</code>	<code>str</code>	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.510 delete_iceberg_system_destinations

`delete_iceberg_system_destinations(x_iam_token=x_iam_token)`

Delete destinations by name

Delete all destinations. This will fail if any destination is referenced in any report.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete destinations by name
```

(continues on next page)

(continued from previous page)

```

    api_instance.delete_iceberg_system_destinations(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_system_
↳destinations: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.511 delete_iceberg_system_report_by_id

```
delete_iceberg_system_report_by_id(name, x_iam_token=x_iam_token)
```

Delete report by name

Delete a report by name. Delete will fail if the report is being referenced by a device-group or network-group.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of report
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete report by name
    api_instance.delete_iceberg_system_report_by_id(name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_system_report_by_
↳id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of report	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.512 delete_iceberg_system_reports

```
delete_iceberg_system_reports(x_iam_token=x_iam_token)
```

Delete reports by name

Delete all reports. This will fail if any report is referenced in any device-group or network-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete reports by name
    api_instance.delete_iceberg_system_reports(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_system_reports:
↪ %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.513 delete_iceberg_system_scheduler_by_id

```
delete_iceberg_system_scheduler_by_id(name, x_iam_token=x_iam_token)
```

Delete scheduler by name

Delete a scheduler by name. Delete will fail if the scheduler is being referenced by a report.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
```

(continues on next page)

(continued from previous page)

```

api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of Scheduler
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete scheduler by name
    api_instance.delete_iceberg_system_scheduler_by_id(name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_system_scheduler_
↳by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of Scheduler	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.514 delete_iceberg_system_schedulers

delete_iceberg_system_schedulers(x_iam_token=x_iam_token)

Delete schedulers by name

Delete all schedulers. This will fail if any scheduler is referenced in any report.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete schedulers by name
    api_instance.delete_iceberg_system_schedulers(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_system_schedulers:
↳%s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.515 delete_iceberg_system_settings_destination_by_id

delete_iceberg_system_settings_destination_by_id(name, x_iam_token=x_iam_token)

Delete destination by name

Delete a destination by name. Delete will fail if the destination is being referenced by a report.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of destination
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete destination by name
    api_instance.delete_iceberg_system_settings_destination_by_id(name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_system_settings_destination_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of destination	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.516 delete_iceberg_system_settings_destinations

delete_iceberg_system_settings_destinations(x_iam_token=x_iam_token)

Delete destinations by name

Delete all destinations. This will fail if any destination is referenced in any report.


```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete destinations by name
    api_instance.delete_iceberg_system_settings_destinations(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_system_settings_
↪destinations: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.517 delete_iceberg_system_settings_report_by_id

delete_iceberg_system_settings_report_by_id(name, x_iam_token=x_iam_token)

Delete report by name

Delete a report by name. Delete will fail if the report is being referenced by a device-group or network-group.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of report
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete report by name
    api_instance.delete_iceberg_system_settings_report_by_id(name, x_iam_token=x_iam_
↪token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_system_settings_
↪report_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of report	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.518 delete_iceberg_system_settings_reports

delete_iceberg_system_settings_reports(x_iam_token=x_iam_token)

Delete reports by name

Delete all reports. This will fail if any report is referenced in any device-group or network-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete reports by name
    api_instance.delete_iceberg_system_settings_reports(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_system_settings_
↵reports: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.519 delete_iceberg_system_settings_scheduler_by_id

delete_iceberg_system_settings_scheduler_by_id(name, x_iam_token=x_iam_token)

Delete scheduler by name

Delete a scheduler by name. Delete will fail if the scheduler is being referenced by a report.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of Scheduler
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete scheduler by name
    api_instance.delete_iceberg_system_settings_scheduler_by_id(name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_system_settings_scheduler_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of Scheduler	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.520 delete_iceberg_system_settings_schedulers

delete_iceberg_system_settings_schedulers(x_iam_token=x_iam_token)

Delete schedulers by name

Delete all schedulers. This will fail if any scheduler is referenced in any report.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete schedulers by name
```

(continues on next page)

(continued from previous page)

```
api_instance.delete_iceberg_system_settings_schedulers(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_system_settings_
↳schedulers: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.521 delete_iceberg_system_settings_system_settings_by_id

delete_iceberg_system_settings_system_settings_by_id(x_iam_token=x_iam_token)

Delete system-settings

Delete system-settings. This will delete all the reports, destinations and schedulers. The request will fail if any of the reports is being referenced by a device-group or network-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete system-settings
    api_instance.delete_iceberg_system_settings_system_settings_by_id(x_iam_token=x_
↳iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_system_settings_
↳system_settings_by_id: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.522 delete_iceberg_system_system_by_id

```
delete_iceberg_system_system_by_id(x_iam_token=x_iam_token)
```

Delete system

Delete system. This will delete all the reports, destinations and schedulers. The request will fail if any of the reports is being referenced by a device-group or network-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete system
    api_instance.delete_iceberg_system_system_by_id(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_system_system_by_
↪id: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.523 delete_iceberg_topic_rule_rule_by_id

```
delete_iceberg_topic_rule_rule_by_id(topic_name, rule_name, x_iam_token=x_iam_token)
```

Delete a rule.

Delete a rule by rule-name. Delete will fail if the rule is referenced by any other playbook.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint
```

(continues on next page)

(continued from previous page)

```
# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
topic_name = 'topic_name_example' # str | ID of topic-name
rule_name = 'rule_name_example' # str | ID of rule-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete a rule.
    api_instance.delete_iceberg_topic_rule_rule_by_id(topic_name, rule_name, x_iam_
↳token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_topic_rule_rule_by_
↳id: %s\n" % e)
```

Name	Type	Description	Notes
topic_name	str	ID of topic-name	
rule_name	str	ID of rule-name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.524 delete_iceberg_topic_topic_by_id

delete_iceberg_topic_topic_by_id(topic_name, x_iam_token=x_iam_token)

Delete a topic.

Delete a topic by topic-name. Delete will fail if the topic is referenced by any other playbook.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
topic_name = 'topic_name_example' # str | ID of topic-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete a topic.
    api_instance.delete_iceberg_topic_topic_by_id(topic_name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_topic_topic_by_id:
↳ %s\n" % e)
```

Name	Type	Description	Notes
topic_name	str	ID of topic-name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.525 delete_iceberg_topics_topics_by_id

delete_iceberg_topics_topics_by_id(x_iam_token=x_iam_token)

Delete all topics.

Delete all topics. This will fail if any topic is referenced in any playbook.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str / authentication header object (optional)

try:
    # Delete all topics.
    api_instance.delete_iceberg_topics_topics_by_id(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->delete_iceberg_topics_topics_by_
↪id: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.526 first_login

first_login(credential)

Change password after first login

Change password in first login

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
credenetial = swagger_client.Credenetial() # Credenetial | set new password

try:
    # Change password after first login
    api_instance.first_login(credenetial)
except ApiException as e:
    print("Exception when calling ConfigurationApi->first_login: %s\n" % e)
```

Name	Type	Description	Notes
credenetial	**Credenetial**	set new password	

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.527 initialize

```
initialize(x_iam_token=x_iam_token, restart_groups=restart_groups, reload_rules=reload_rules,
reload_playbooks=reload_playbooks, reload_syslog_patterns=reload_syslog_patterns,
reload_syslog_pattern_sets=reload_syslog_pattern_sets, reload_flow_templates=reload_flow_templates,
reload_sflow_schema=reload_sflow_schema)
```

Initialize config-server

Initialize config-server

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
restart_groups = true # bool | Boolean variable is set to true if group services have
↳to be restarted. Defaults to true. (optional) (default to true)
reload_rules = true # bool | Boolean variable is set to true if default rules have to
↳reloaded. Defaults to true. (optional) (default to true)
```

(continues on next page)

(continued from previous page)

```

reload_playbooks = true # bool | Boolean variable is set to true if default playbooks_
↳have to be reloaded. Defaults to true. (optional) (default to true)
reload_syslog_patterns = true # bool | Boolean variable is set to true if syslog_
↳patterns have to be reloaded. Defaults to true. (optional) (default to true)
reload_syslog_pattern_sets = true # bool | Boolean variable is set to true if syslog_
↳pattern sets have to be reloaded. Defaults to true. (optional) (default to true)
reload_flow_templates = true # bool | Boolean variable is set to true if flow_
↳templates have to be reloaded. Defaults to true. (optional) (default to true)
reload_sflow_schema = true # bool | Boolean variable is set to true if sflow schema_
↳has to be reloaded. Defaults to true. (optional) (default to true)

try:
    # Initialize config-server
    api_instance.initialize(x_iam_token=x_iam_token, restart_groups=restart_groups,
↳reload_rules=reload_rules, reload_playbooks=reload_playbooks, reload_syslog_
↳patterns=reload_syslog_patterns, reload_syslog_pattern_sets=reload_syslog_pattern_
↳sets, reload_flow_templates=reload_flow_templates, reload_sflow_schema=reload_sflow_
↳schema)
except ApiException as e:
    print("Exception when calling ConfigurationApi->initialize: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
restart_groups	bool	Boolean variable is set to true if group services have to be restarted. Defaults to true.	[optional] [default to true]
reload_rules	bool	Boolean variable is set to true if default rules have to reloaded. Defaults to true.	[optional] [default to true]
reload_playbooks	bool	Boolean variable is set to true if default playbooks have to be reloaded. Defaults to true.	[optional] [default to true]
reload_syslog_patterns	bool	Boolean variable is set to true if syslog patterns have to be reloaded. Defaults to true.	[optional] [default to true]
reload_syslog_pattern_sets	bool	Boolean variable is set to true if syslog pattern sets have to be reloaded. Defaults to true.	[optional] [default to true]
reload_flow_templates	bool	Boolean variable is set to true if flow templates have to be reloaded. Defaults to true.	[optional] [default to true]
reload_sflow_schema	bool	Boolean variable is set to true if sflow schema has to be reloaded. Defaults to true.	[optional] [default to true]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.528 retrieve_affected_groups

AffectedGroups retrieve_affected_groups(x_iam_token=x_iam_token)

Get all groups affected by un-committed configuration changes.

Get all groups that are affected by the un-committed configuration changes.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Get all groups affected by un-committed configuration changes.
    api_response = api_instance.retrieve_affected_groups(x_iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_affected_groups: %s\n" % e)
    ↪e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

****AffectedGroups****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.529 retrieve_device_group_status

ServiceStatus retrieve_device_group_status(device_group_name, x_iam_token=x_iam_token)

Get device-group's status.

Get information about the status of a device-group's services.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
device_group_name = 'device_group_name_example' # str | Name of device-group
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Get device-group's status.
    api_response = api_instance.retrieve_device_group_status(device_group_name, x_iam_
    ↪token=x_iam_token)
    pprint(api_response)
```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_device_group_status: %s\n"
↳ " % e)
```

Name	Type	Description	Notes
device_group_name	str	Name of device-group	
x_iam_token	str	authentication header object	[optional]

****ServiceStatus****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.530 retrieve_device_group_trigger_info

TriggerSchema retrieve_device_group_trigger_info(device_group_name, x_iam_token=x_iam_token)

Get device-group's trigger info.

Get information about the triggers in a device-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
device_group_name = 'device_group_name_example' # str | Name of device-group
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Get device-group's trigger info.
    api_response = api_instance.retrieve_device_group_trigger_info(device_group_name,
↳ x_iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_device_group_trigger_
↳ info: %s\n" % e)
```

Name	Type	Description	Notes
device_group_name	str	Name of device-group	
x_iam_token	str	authentication header object	[optional]

****TriggerSchema****

No authorization required

- **Content-Type:** application/json, multipart/form-data

- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.531 retrieve_healthbot_organizations_organizations

OrganizationsSchema retrieve_healthbot_organizations_organizations(x_iam_token=x_iam_token,
working=working)

Get all organizations' configuration.

Get the configuration details of all organizations.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # Get all organizations' configuration.
    api_response = api_instance.retrieve_healthbot_organizations_organizations(x_iam_
↪token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_healthbot_organizations_
↪organizations: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

****OrganizationsSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.532 retrieve_iceberg_device_device

list[str] retrieve_iceberg_device_device(x_iam_token=x_iam_token, working=working)

List all device-ids.

Get a list of all the device IDs.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # List all device-ids.
    api_response = api_instance.retrieve_iceberg_device_device(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_device_device: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.533 retrieve_iceberg_device_device_by_id

DeviceSchema retrieve_iceberg_device_device_by_id(device_id, x_iam_token=x_iam_token, working=working)

Get a device's configuration.

Get the configuration details of a device by its device-id.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
device_id = 'device_id_example' # str | ID of device-id
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:

```

(continues on next page)

(continued from previous page)

```

# Get a device's configuration.
api_response = api_instance.retrieve_iceberg_device_device_by_id(device_id, x_iam_
↳token=x_iam_token, working=working)
pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_device_device_by_
↳id: %s\n" % e)

```

Name	Type	Description	Notes
device_id	str	ID of device-id	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

****DeviceSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.534 retrieve_iceberg_device_group_device_group

list[str] retrieve_iceberg_device_group_device_group(x_iam_token=x_iam_token, working=working)

List all device-group names.

Get a list of all the device-group names.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # List all device-group names.
    api_response = api_instance.retrieve_iceberg_device_group_device_group(x_iam_
↳token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_device_group_
↳device_group: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.535 retrieve_iceberg_device_group_device_group_by_id

DeviceGroupSchema retrieve_iceberg_device_group_device_group_by_id(device_group_name, x_iam_token=x_iam_token, working=working)

Get device-group's configuration.

Get configuration details of a device group by the device group name.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
device_group_name = 'device_group_name_example' # str | ID of device-group-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # Get device-group's configuration.
    api_response = api_instance.retrieve_iceberg_device_group_device_group_by_id(
device_group_name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_device_group_device_group_by_id: %s\n" % e)
```

Name	Type	Description	Notes
device_group_name	str	ID of device-group-name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

****DeviceGroupSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.536 retrieve_iceberg_device_groups_device_groups

DeviceGroupsSchema retrieve_iceberg_device_groups_device_groups(x_iam_token=x_iam_token,
working=working)

Get all device-groups' configuration.

Get configuration details of all the device-groups.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # Get all device-groups' configuration.
    api_response = api_instance.retrieve_iceberg_device_groups_device_groups(x_iam_
↪token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_device_groups_
↪device_groups: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

****DeviceGroupsSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.537 retrieve_iceberg_devices_devices

DevicesSchema retrieve_iceberg_devices_devices(x_iam_token=x_iam_token, working=working)

Get all devices' configuration.

Get the configuration details of all devices.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint
```

(continues on next page)

(continued from previous page)

```
# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # Get all devices' configuration.
    api_response = api_instance.retrieve_iceberg_devices_devices(x_iam_token=x_iam_
↪token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_devices_devices:
↪%s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

****DevicesSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.538 retrieve_iceberg_network_group_network_group

```
list[str] retrieve_iceberg_network_group_network_group(x_iam_token=x_iam_token, work-
ing=working)
```

List all network-group names.

Get a list of all the network-group-names.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # List all network-group names.
    api_response = api_instance.retrieve_iceberg_network_group_network_group(x_iam_
↪token=x_iam_token, working=working)
    pprint(api_response)
```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_network_group_
↳network_group: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.539 retrieve_iceberg_network_group_network_group_by_id

NetworkGroupSchema retrieve_iceberg_network_group_network_group_by_id(network_group_name, x_iam_token=x_iam_token, working=working)

Get network-group's configuration.

Get the configuration details of a network group by its network group name.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
network_group_name = 'network_group_name_example' # str | ID of network-group-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # Get network-group's configuration.
    api_response = api_instance.retrieve_iceberg_network_group_network_group_by_
↳id(network_group_name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_network_group_
↳network_group_by_id: %s\n" % e)
```

Name	Type	Description	Notes
network_group_name	str	ID of network-group-name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

****NetworkGroupSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.540 retrieve_iceberg_network_groups_network_groups

NetworkGroupsSchema retrieve_iceberg_network_groups_network_groups(x_iam_token=x_iam_token, working=working)

Get all network-groups' configuration.

Get configuration of all network-groups.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # Get all network-groups' configuration.
    api_response = api_instance.retrieve_iceberg_network_groups_network_groups(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_network_groups_network_groups: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

****NetworkGroupsSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.541 retrieve_iceberg_notification_notification

list[str] retrieve_iceberg_notification_notification(x_iam_token=x_iam_token, working=working)

List all notification-names.

Get a list of all the notification-names.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # List all notification-names.
    api_response = api_instance.retrieve_iceberg_notification_notification(x_iam_
↪token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_notification_
↪notification: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.542 retrieve_iceberg_notification_notification_by_id

NotificationSchema retrieve_iceberg_notification_notification_by_id(notification_name,
x_iam_token=x_iam_token, working=working)

Get a notification's configuration.

Get the configuration details of a notification by notification-name.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
notification_name = 'notification_name_example' # str | ID of notification-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
```

(continues on next page)

(continued from previous page)

```

working = true # bool | true queries un-committed configuration (optional)

try:
    # Get a notification's configuration.
    api_response = api_instance.retrieve_iceberg_notification_notification_by_
↳id(notification_name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_notification_
↳notification_by_id: %s\n" % e)

```

Name	Type	Description	Notes
notification_name	str	ID of notification-name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

****NotificationSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json, application/x-gzip

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.543 retrieve_iceberg_notifications_notifications_by_id

NotificationsSchema retrieve_iceberg_notifications_notifications_by_id(x_iam_token=x_iam_token, working=working)

Get all notifications' configuration.

Get the configuration details of all notifications.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries un-committed configuration (optional)

try:
    # Get all notifications' configuration.
    api_response = api_instance.retrieve_iceberg_notifications_notifications_by_id(x_
↳iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_notifications_
↳notifications_by_id: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

****NotificationsSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.544 retrieve_iceberg_playbook_playbook

list[str] retrieve_iceberg_playbook_playbook(x_iam_token=x_iam_token, working=working)

List all playbook-names.

Get a list of all the playbook-names.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # List all playbook-names.
    api_response = api_instance.retrieve_iceberg_playbook_playbook(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_playbook_playbook: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.545 retrieve_iceberg_playbook_playbook_by_id

```
PlaybookSchema retrieve_iceberg_playbook_playbook_by_id(playbook_name,
x_iam_token=x_iam_token, working=working, download=download)
```

Get a playbook's configuration.

Get the configuration details of a playbook by `playbook-name`.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
playbook_name = 'playbook_name_example' # str | ID of playbook-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)
download = True # bool | Download as compressed .playbook file (optional)

try:
    # Get a playbook's configuration.
    api_response = api_instance.retrieve_iceberg_playbook_playbook_by_id(playbook_
↪name, x_iam_token=x_iam_token, working=working, download=download)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_playbook_
↪playbook_by_id: %s\n" % e)
```

Name	Type	Description	Notes
playbook_name	str	ID of playbook-name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]
download	bool	Download as compressed .playbook file	[optional]

****PlaybookSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.546 retrieve_iceberg_playbooks_playbooks_by_id

```
PlaybooksSchema retrieve_iceberg_playbooks_playbooks_by_id(x_iam_token=x_iam_token, work-
ing=working)
```

Get all playbooks' configuration.

Get the configuration of all playbooks.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # Get all playbooks' configuration.
    api_response = api_instance.retrieve_iceberg_playbooks_playbooks_by_id(x_iam_
↪token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_playbooks_
↪playbooks_by_id: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

****PlaybooksSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.547 retrieve_iceberg_retention_policies_retention_policies_by_id

RetentionPoliciesSchema retrieve_iceberg_retention_policies_retention_policies_by_id(x_iam_token=x_iam_token, working=working)

Get all retention-policies' configuration.

Get the configuration of all the retention-policies.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # Get all retention-policies' configuration.

```

(continues on next page)

(continued from previous page)

```

    api_response = api_instance.retrieve_iceberg_retention_policies_retention_
↳policies_by_id(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_retention_
↳policies_retention_policies_by_id: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

****RetentionPoliciesSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.548 retrieve_iceberg_retention_policy_retention_policy

```
list[str]    retrieve_iceberg_retention_policy_retention_policy(x_iam_token=x_iam_token,    work-
ing=working)
```

List all retention-policy-names.

Get a list of all the retention-policy-names.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # List all retention-policy-names.
    api_response = api_instance.retrieve_iceberg_retention_policy_retention_policy(x_
↳iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_retention_policy_
↳retention_policy: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.549 retrieve_iceberg_retention_policy_retention_policy_by_id

RetentionPolicySchema retrieve_iceberg_retention_policy_retention_policy_by_id(retention_policy_name, x_iam_token=x_iam_token, working=working)

Get a retention-policy's configuration.

Get the configuration details of a retention policy by retention-policy-name.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
retention_policy_name = 'retention_policy_name_example' # str | ID of retention-
↳policy-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # Get a retention-policy's configuration.
    api_response = api_instance.retrieve_iceberg_retention_policy_retention_policy_by_
↳id(retention_policy_name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_retention_policy_
↳retention_policy_by_id: %s\n" % e)
```

Name	Type	Description	Notes
retention_policy_name	str	ID of retention-policy-name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

****RetentionPolicySchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.550 retrieve_iceberg_system_destination_by_id

DestinationSchema retrieve_iceberg_system_destination_by_id(name, x_iam_token=x_iam_token, working=working)

Retrieve destination by name

Get the configuration details of a destination by its name.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of destination
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve destination by name
    api_response = api_instance.retrieve_iceberg_system_destination_by_id(name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_system_destination_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of destination	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****DestinationSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.551 retrieve_iceberg_system_destinations

DestinationsSchema retrieve_iceberg_system_destinations(x_iam_token=x_iam_token, working=working)

Retrieve destinations by name

Get the configuration details of all destinations.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve destinations by name
    api_response = api_instance.retrieve_iceberg_system_destinations(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_system_destinations: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****DestinationsSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.552 retrieve_iceberg_system_report_by_id

ReportSchema retrieve_iceberg_system_report_by_id(name, x_iam_token=x_iam_token, working=working)

Retrieve report by name

Get the configuration details of a report by its name.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of report
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:

```

(continues on next page)

(continued from previous page)

```

# Retrieve report by name
api_response = api_instance.retrieve_iceberg_system_report_by_id(name, x_iam_
↳token=x_iam_token, working=working)
pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_system_report_by_
↳id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of report	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****ReportSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.553 retrieve_iceberg_system_reports

ReportsSchema retrieve_iceberg_system_reports(x_iam_token=x_iam_token, working=working)

Retrieve reports by name

Get the configuration details of all reports.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve reports by name
    api_response = api_instance.retrieve_iceberg_system_reports(x_iam_token=x_iam_
↳token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_system_reports:
↳%s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****ReportsSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.554 retrieve_iceberg_system_scheduler_by_id

SchedulerSchema retrieve_iceberg_system_scheduler_by_id(name, x_iam_token=x_iam_token, working=working)

Retrieve scheduler by name

Get the configuration details of a scheduler by its name.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of Scheduler
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve scheduler by name
    api_response = api_instance.retrieve_iceberg_system_scheduler_by_id(name, x_iam_
↪token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_system_scheduler_
↪by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of Scheduler	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****SchedulerSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.555 retrieve_iceberg_system_schedulers

SchedulersSchema retrieve_iceberg_system_schedulers(x_iam_token=x_iam_token, working=working)

Retrieve schedulers by name

Get the configuration details of all schedulers.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve schedulers by name
    api_response = api_instance.retrieve_iceberg_system_schedulers(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_system_schedulers: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****SchedulersSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.556 retrieve_iceberg_system_settings_destination_by_id

DestinationSchema retrieve_iceberg_system_settings_destination_by_id(name, x_iam_token=x_iam_token, working=working)

Retrieve destination by name

Get the configuration details of a destination by its name.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint
```

(continues on next page)

(continued from previous page)

```
# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of destination
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve destination by name
    api_response = api_instance.retrieve_iceberg_system_settings_destination_by_
    ↪id(name, x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_system_settings_
    ↪destination_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of destination	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****DestinationSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.557 retrieve_iceberg_system_settings_destinations

DestinationsSchema retrieve_iceberg_system_settings_destinations(x_iam_token=x_iam_token, working=working)

Retrieve destinations by name

Get the configuration details of all destinations.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve destinations by name
    api_response = api_instance.retrieve_iceberg_system_settings_destinations(x_iam_
    ↪token=x_iam_token, working=working)
```

(continues on next page)

(continued from previous page)

```

pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_system_settings_
↳ destinations: %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****DestinationsSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.558 retrieve_iceberg_system_settings_report_by_id

ReportSchema retrieve_iceberg_system_settings_report_by_id(name, x_iam_token=x_iam_token, working=working)

Retrieve report by name

Get the configuration details of a report by its name.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of report
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve report by name
    api_response = api_instance.retrieve_iceberg_system_settings_report_by_id(name, x_
↳ iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_system_settings_
↳ report_by_id: %s\n" % e)

```

Name	Type	Description	Notes
name	str	Name of report	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****ReportSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.559 retrieve_iceberg_system_settings_reports

ReportsSchema retrieve_iceberg_system_settings_reports(x_iam_token=x_iam_token, working=working)

Retrieve reports by name

Get the configuration details of all reports.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve reports by name
    api_response = api_instance.retrieve_iceberg_system_settings_reports(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_system_settings_reports: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****ReportsSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.560 retrieve_iceberg_system_settings_scheduler_by_id

SchedulerSchema retrieve_iceberg_system_settings_scheduler_by_id(name, x_iam_token=x_iam_token, working=working)

Retrieve scheduler by name

Get the configuration details of a scheduler by its name.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of Scheduler
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve scheduler by name
    api_response = api_instance.retrieve_iceberg_system_settings_scheduler_by_id(name,
    ↪ x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_system_settings_
    ↪scheduler_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of Scheduler	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****SchedulerSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.561 retrieve_iceberg_system_settings_schedulers

SchedulersSchema retrieve_iceberg_system_settings_schedulers(x_iam_token=x_iam_token, work-
ing=working)

Retrieve schedulers by name

Get the configuration details of all schedulers.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
```

(continues on next page)

(continued from previous page)

```
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve schedulers by name
    api_response = api_instance.retrieve_iceberg_system_settings_schedulers(x_iam_
↪token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_system_settings_
↪schedulers: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****SchedulersSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.562 retrieve_iceberg_system_settings_system_settings

SystemSettingsSchema retrieve_iceberg_system_settings_system_settings(x_iam_token=x_iam_token,
working=working)

Retrieve system-settings

Retrieve system-settings

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = true # bool | true queries undeployed configuration (optional)

try:
    # Retrieve system-settings
    api_response = api_instance.retrieve_iceberg_system_settings_system_settings(x_
↪iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_system_settings_
↪system_settings: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****SystemSettingsSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.563 retrieve_iceberg_system_system

SystemSettingsSchema retrieve_iceberg_system_system(x_iam_token=x_iam_token, working=working)

Retrieve system data

Retrieve system details

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries undeployed configuration (optional)

try:
    # Retrieve system data
    api_response = api_instance.retrieve_iceberg_system_system(x_iam_token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_system_system: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries undeployed configuration	[optional]

****SystemSettingsSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.564 retrieve_iceberg_topic_rule_rule

list[str] retrieve_iceberg_topic_rule_rule(topic_name, x_iam_token=x_iam_token, working=working)

List all rule-names in a topic.

Get a list of all the rule-names in a topic.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
topic_name = 'topic_name_example' # str | ID of topic-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # List all rule-names in a topic.
    api_response = api_instance.retrieve_iceberg_topic_rule_rule(topic_name, x_iam_
↪ token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_topic_rule_rule:
↪ %s\n" % e)
```

Name	Type	Description	Notes
topic_name	str	ID of topic-name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.565 retrieve_iceberg_topic_rule_rule_by_id

RuleSchema retrieve_iceberg_topic_rule_rule_by_id(topic_name, rule_name, x_iam_token=x_iam_token, working=working, download=download)

Get a rule's configuration.

Get the configuration details of a rule by rule-name.

```
from __future__ import print_function
import time
import swagger_client
```

(continues on next page)

(continued from previous page)

```

from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
topic_name = 'topic_name_example' # str | ID of topic-name
rule_name = 'rule_name_example' # str | ID of rule-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)
download = True # bool | Download a compressed .rule file (optional)

try:
    # Get a rule's configuration.
    api_response = api_instance.retrieve_iceberg_topic_rule_rule_by_id(topic_name,
↳rule_name, x_iam_token=x_iam_token, working=working, download=download)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_topic_rule_rule_
↳by_id: %s\n" % e)

```

Name	Type	Description	Notes
topic_name	str	ID of topic-name	
rule_name	str	ID of rule-name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]
download	bool	Download a compressed .rule file	[optional]

****RuleSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.566 retrieve_iceberg_topic_topic

list[str] retrieve_iceberg_topic_topic(x_iam_token=x_iam_token, working=working)

List all topic-names.

Get a list of all the topic-names.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

```

(continues on next page)

(continued from previous page)

```

try:
    # List all topic-names.
    api_response = api_instance.retrieve_iceberg_topic_topic(x_iam_token=x_iam_token,
↳working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_topic_topic: %s\n
↳" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

list[str]

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.567 retrieve_iceberg_topic_topic_by_id

TopicSchema retrieve_iceberg_topic_topic_by_id(topic_name, x_iam_token=x_iam_token, working=working)

Get a topic's configuration.

Get the configuration details of a topic by the topic-name.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
topic_name = 'topic_name_example' # str | ID of topic-name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)

try:
    # Get a topic's configuration.
    api_response = api_instance.retrieve_iceberg_topic_topic_by_id(topic_name, x_iam_
↳token=x_iam_token, working=working)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_topic_topic_by_
↳id: %s\n" % e)

```


Name	Type	Description	Notes
topic_name	str	ID of topic-name	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]

****TopicSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json, application/x-gzip

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.568 retrieve_iceberg_topics_topics

TopicsSchema retrieve_iceberg_topics_topics(x_iam_token=x_iam_token, working=working, sort=sort)

Get all topics' configuration.

Get the configuration details of all topics.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)
sort = 'sort_example' # str | asc/desc queries sorted configuration (optional)

try:
    # Get all topics' configuration.
    api_response = api_instance.retrieve_iceberg_topics_topics(x_iam_token=x_iam_
↪ token, working=working, sort=sort)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_iceberg_topics_topics:
↪ %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]
sort	str	asc/desc queries sorted configuration	[optional]

****TopicsSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.569 retrieve_network_group_status

ServiceStatus retrieve_network_group_status(network_group_name, x_iam_token=x_iam_token)

Get network-group's status.

Get information about the status of a network-group's services.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
network_group_name = 'network_group_name_example' # str | Name of network-group
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Get network-group's status.
    api_response = api_instance.retrieve_network_group_status(network_group_name, x_
    iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_network_group_status:
    %s\n" % e)
```

Name	Type	Description	Notes
network_group_name	str	Name of network-group	
x_iam_token	str	authentication header object	[optional]

****ServiceStatus****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.570 retrieve_network_group_trigger_info

TriggerSchema retrieve_network_group_trigger_info(network_group_name, x_iam_token=x_iam_token)

Get network-group's trigger info.

Get information about the triggers in a device-group.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
network_group_name = 'network_group_name_example' # str | Name of network-group
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Get network-group's trigger info.
    api_response = api_instance.retrieve_network_group_trigger_info(network_group_
↪name, x_iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_network_group_trigger_
↪info: %s\n" % e)

```

Name	Type	Description	Notes
network_group_name	str	Name of network-group	
x_iam_token	str	authentication header object	[optional]

TriggerSchema

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.571 retrieve_orchestrator

retrieve_orchestrator(x_iam_token=x_iam_token)

Get Orchestrator type

Get orchestrator type. Will be one of kubernetes or compose.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Get Orchestrator type
    api_instance.retrieve_orchestrator(x_iam_token=x_iam_token)

```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling ConfigurationApi->retrieve_orchestrator: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.572 rollback_unsaved_configuration

rollback_unsaved_configuration(x_iam_token=x_iam_token, ems_sanity=ems_sanity)

Delete the un-committed configuration.

The API server follows a commit model. Unsaved configuration is called a working configuration. This API call deletes the working configuration.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
ems_sanity = False # bool | DEBUG (Use with caution): roll-back a faulty transaction,
↳ in HB-EMS communication (optional) (default to false)

try:
    # Delete the un-committed configuration.
    api_instance.rollback_unsaved_configuration(x_iam_token=x_iam_token, ems_
↳ sanity=ems_sanity)
except ApiException as e:
    print("Exception when calling ConfigurationApi->rollback_unsaved_configuration:
↳ %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
ems_sanity	bool	DEBUG (Use with caution): roll-back a faulty transaction in HB-EMS communication	[optional] [default to false]

void (empty response body)

No authorization required

- **Content-Type:** application/json

- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.573 update_healthbot_organizations_organizations

update_healthbot_organizations_organizations(organizations, x_iam_token=x_iam_token)

Overwrite organizations.

Overwrite the existing organizations configuration. New organizations are created and existing organizations are overwritten with new content. If some of the existing organizations are not present in the payload, such organizations are deleted. This will fail if any of the organization edges that are not present in the payload are referenced by a device-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
organizations = swagger_client.OrganizationsSchema() # OrganizationsSchema | ↪
↪ organizations body object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Overwrite organizations.
    api_instance.update_healthbot_organizations_organizations(organizations, x_iam_
↪ token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_healthbot_organizations_
↪ organizations: %s\n" % e)
```

Name	Type	Description	Notes
organizations	**OrganizationsSchema**	organizations body object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.574 update_healthbot_topic_resource_resource_by_id

update_healthbot_topic_resource_resource_by_id(topic_name, resource_name, resource, authorization=authorization)

Overwrite a resource

Overwrite a rule by the `resource-name`. The `resource-name` specified in URL and the request body must match.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
topic_name = 'topic_name_example' # str | ID of topic-name
resource_name = 'resource_name_example' # str | ID of resource-name
resource = swagger_client.ResourceSchema() # ResourceSchema | resourcebody object
authorization = 'authorization_example' # str | authentication header object,
↳ (optional)

try:
    # Overwrite a resource
    api_instance.update_healthbot_topic_resource_resource_by_id(topic_name, resource_
↳ name, resource, authorization=authorization)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_healthbot_topic_resource_
↳ resource_by_id: %s\n" % e)
```

Name	Type	Description	Notes
topic_name	str	ID of topic-name	
resource_name	str	ID of resource-name	
resource	**ResourceSchema**	resourcebody object	
authorization	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.575 update_iceberg_device_device_by_id

```
update_iceberg_device_device_by_id(device_id, device, x_iam_token=x_iam_token)
```

Overwrite a device.

Overwrite a device by device ID. The device ID specified in the URL and the request body must match.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint
```

(continues on next page)

(continued from previous page)

```
# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
device_id = 'device_id_example' # str | ID of device-id
device = swagger_client.DeviceSchema() # DeviceSchema | devicebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Overwrite a device.
    api_instance.update_iceberg_device_device_by_id(device_id, device, x_iam_token=x_
↳ iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_device_device_by_
↳ id: %s\n" % e)
```

Name	Type	Description	Notes
device_id	str	ID of device-id	
device	**DeviceSchema**	devicebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.576 update_iceberg_device_group_device_group_by_id

```
update_iceberg_device_group_device_group_by_id(device_group_name, device_group,
x_iam_token=x_iam_token)
```

Overwrite a device-group.

Overwrite a device-group by its device-group-name. The device-group-name specified in the URL and the request body must match.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
device_group_name = 'device_group_name_example' # str | ID of device-group-name
device_group = swagger_client.DeviceGroupSchema() # DeviceGroupSchema | device_
↳ groupbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Overwrite a device-group.
```

(continues on next page)

(continued from previous page)

```

    api_instance.update_iceberg_device_group_device_group_by_id(device_group_name,
↳device_group, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_device_group_
↳device_group_by_id: %s\n" % e)

```

Name	Type	Description	Notes
device_group_name	str	ID of device-group-name	
device_group	**DeviceGroupSchema**	device_groupbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.577 update_iceberg_device_groups_device_groups_by_id

update_iceberg_device_groups_device_groups_by_id(device_groups, x_iam_token=x_iam_token)

Overwrite device-groups.

Overwrite the existing configuration of device-groups. New device-groups are created and the existing device-groups are overwritten with new content. If some existing device-groups are not present in the payload, such device-groups are deleted. This will fail if any of the device-groups that are not present in the payload have running services.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
device_groups = swagger_client.DeviceGroupsSchema() # DeviceGroupsSchema | device-
↳groupsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Overwrite device-groups.
    api_instance.update_iceberg_device_groups_device_groups_by_id(device_groups, x_
↳iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_device_groups_
↳device_groups_by_id: %s\n" % e)

```

Name	Type	Description	Notes
device_groups	**DeviceGroupsSchema**	device-groupsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.578 update_iceberg_devices_devices_by_id

update_iceberg_devices_devices_by_id(devices, x_iam_token=x_iam_token)

Overwrite devices.

Overwrite the existing configuration of devices. New devices are created and the existing devices are overwritten with new content. If some existing devices are not present in the payload, such devices are deleted. This will fail if any of the devices that are not present in the payload are referenced by a device-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
devices = swagger_client.DevicesSchema() # DevicesSchema | devicesbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Overwrite devices.
    api_instance.update_iceberg_devices_devices_by_id(devices, x_iam_token=x_iam_
↪token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_devices_devices_by_
↪id: %s\n" % e)
```

Name	Type	Description	Notes
devices	**DevicesSchema**	devicesbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.579 update_iceberg_network_group_network_group_by_id

```
update_iceberg_network_group_network_group_by_id(network_group_name, network_group,
x_iam_token=x_iam_token)
```

Overwrite a network-group.

Overwrite a network-group by the network-group-name. The network-group-name specified in the URL and the request body must match.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
network_group_name = 'network_group_name_example' # str | ID of network-group-name
network_group = swagger_client.NetworkGroupSchema() # NetworkGroupSchema | network_
↳groupbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Overwrite a network-group.
    api_instance.update_iceberg_network_group_network_group_by_id(network_group_name,
↳network_group, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_network_group_
↳network_group_by_id: %s\n" % e)
```

Name	Type	Description	Notes
network_group_name	str	ID of network-group-name	
network_group	**NetworkGroupSchema**	network_groupbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.580 update_iceberg_network_groups_network_groups_by_id

```
update_iceberg_network_groups_network_groups_by_id(network_groups, x_iam_token=x_iam_token)
```

Overwrite network-groups.

Overwrite the existing network-group configuration. New network-groups are created and the existing network-groups are overwritten with new content. If some of the existing network-groups are not present in the payload, such network-groups are deleted. This will fail if any of the network-groups that are not present in the payload have running services.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
network_groups = swagger_client.NetworkGroupsSchema() # NetworkGroupsSchema | network-
↳groupsboby object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Overwrite network-groups.
    api_instance.update_iceberg_network_groups_network_groups_by_id(network_groups, x_
↳iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_network_groups_
↳network_groups_by_id: %s\n" % e)

```

Name	Type	Description	Notes
network_groups	**NetworkGroupsSchema**	network-groupsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.581 update_iceberg_notification_notification_by_id

```

update_iceberg_notification_notification_by_id(notification_name, notification,
x_iam_token=x_iam_token)

```

Overwrite a notification.

Overwrite a notification by the notification-name. The notification-name specified in URL and the request body must match.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
notification_name = 'notification_name_example' # str | ID of notification-name
notification = swagger_client.NotificationSchema() # NotificationSchema | _
↳notificationbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

```

(continues on next page)

(continued from previous page)

```

try:
    # Overwrite a notification.
    api_instance.update_iceberg_notification_notification_by_id(notification_name,
↳notification, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_notification_
↳notification_by_id: %s\n" % e)

```

Name	Type	Description	Notes
notification_name	str	ID of notification-name	
notification	**NotificationSchema**	notificationbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.582 update_iceberg_notifications_notifications_by_id

update_iceberg_notifications_notifications_by_id(notifications, x_iam_token=x_iam_token)

Overwrite notifications.

Overwrite the existing notifications configuration. New notifications are created and existing notifications are overwritten with new content. If some of the existing notifications are not present in the payload, such notifications are deleted. This will fail if any of the notifications that are not present in the payload are referenced by a device-group.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
notifications = swagger_client.NotificationsSchema() # NotificationsSchema |
↳notificationsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Overwrite notifications.
    api_instance.update_iceberg_notifications_notifications_by_id(notifications, x_
↳iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_notifications_
↳notifications_by_id: %s\n" % e)

```

Name	Type	Description	Notes
notifications	**NotificationsSchema**	notificationsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.583 update_iceberg_playbook_playbook_by_id

update_iceberg_playbook_playbook_by_id(playbook_name, playbook, x_iam_token=x_iam_token)

Overwrite a playbook.

Overwrite a playbook by the `playbook-name`. The `playbook-name` specified in the URL and the request body must match.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
playbook_name = 'playbook_name_example' # str | ID of playbook-name
playbook = swagger_client.PlaybookSchema() # PlaybookSchema | playbookbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Overwrite a playbook.
    api_instance.update_iceberg_playbook_playbook_by_id(playbook_name, playbook, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_playbook_playbook_by_id: %s\n" % e)
```

Name	Type	Description	Notes
playbook_name	str	ID of playbook-name	
playbook	**PlaybookSchema**	playbookbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.584 update_iceberg_playbooks_playbooks_by_id

update_iceberg_playbooks_playbooks_by_id(playbooks, x_iam_token=x_iam_token)

Overwrite all playbooks.

Overwrite the existing playbooks configuration. New playbooks are created and existing playbooks are overwritten with new content. If some of the existing playbooks are not present in the payload, such playbooks are deleted. This will fail if any of the playbooks that are not present in the payload are referenced by a device-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
playbooks = swagger_client.PlaybooksSchema() # PlaybooksSchema | playbooksbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Overwrite all playbooks.
    api_instance.update_iceberg_playbooks_playbooks_by_id(playbooks, x_iam_token=x_
↪iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_playbooks_
↪playbooks_by_id: %s\n" % e)
```

Name	Type	Description	Notes
playbooks	**PlaybooksSchema**	playbooksbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.585 update_iceberg_retention_policies_retention_policies_id

update_iceberg_retention_policies_retention_policies_id(retention_policies, x_iam_token=x_iam_token)

Overwrite all retention-policies.

Overwrite the existing retention-policies configuration. New retention-policies are created and existing retention-policies are overwritten with new content. If some existing retention-policies are not present in the payload, such retention-policies are deleted. This will fail if any of the retention-policies that are not present in the payload are referenced by a device-group.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
retention_policies = swagger_client.RetentionPoliciesSchema() # ↪
↪RetentionPoliciesSchema / retention-policies body object
x_iam_token = 'x_iam_token_example' # str / authentication header object (optional)

try:
    # Overwrite all retention-policies.
    api_instance.update_iceberg_retention_policies_retention_policies_id(retention_
↪policies, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_retention_policies_
↪retention_policies_id: %s\n" % e)

```

Name	Type	Description	Notes
retention_policies	**RetentionPoliciesSchema**	retention-policies body object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.586 update_iceberg_retention_policy_retention_policy_by_id

```

update_iceberg_retention_policy_retention_policy_by_id(retention_policy_name,      retention_policy,
x_iam_token=x_iam_token)

```

Overwrite a retention-policy.

Overwrite a retention-policy by the retention-policy-name. The retention-policy-name specified in URL and the request body must match.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
retention_policy_name = 'retention_policy_name_example' # str / ID of retention-
↪policy-name
retention_policy = swagger_client.RetentionPolicySchema() # RetentionPolicySchema ↪
↪retention_policybody object

```

(continues on next page)

(continued from previous page)

```
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Overwrite a retention-policy.
    api_instance.update_iceberg_retention_policy_retention_policy_by_id(retention_
↳policy_name, retention_policy, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_retention_policy_
↳retention_policy_by_id: %s\n" % e)
```

Name	Type	Description	Notes
retention_policy_name	str	ID of retention-policy-name	
retention_policy	**RetentionPolicySchema**	retention_policybody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.587 update_iceberg_system_destination_by_id

update_iceberg_system_destination_by_id(name, destination, x_iam_token=x_iam_token)

Update destination by name

Overwrite a destination by destination name. The destination name specified in the URL and the request body must match.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of destination
destination = swagger_client.DestinationSchema() # DestinationSchema |_
↳destinationsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update destination by name
    api_instance.update_iceberg_system_destination_by_id(name, destination, x_iam_
↳token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_system_destination_
↳by_id: %s\n" % e)
```


Name	Type	Description	Notes
name	str	Name of destination	
destination	**DestinationSchema**	destinationsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.588 update_iceberg_system_destinations

update_iceberg_system_destinations(destinations, x_iam_token=x_iam_token)

Update destinations by name

Overwrite the existing configuration of destinations. New destinations are created and the existing destinations are overwritten with new content. If some existing destinations are not present in the payload, such destinations are deleted. This will fail if any of the destinations that are not present in the payload are referenced by a report.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
destinations = swagger_client.DestinationsSchema() # DestinationsSchema | ↪ destinationsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update destinations by name
    api_instance.update_iceberg_system_destinations(destinations, x_iam_token=x_iam_token) ↪ token
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_system_ ↪ destinations: %s\n" % e)
```

Name	Type	Description	Notes
destinations	**DestinationsSchema**	destinationsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.589 update_iceberg_system_report_by_id

update_iceberg_system_report_by_id(name, report, x_iam_token=x_iam_token)

Update report by name

Overwrite a report by report name. The report name specified in the URL and the request body must match.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of report
report = swagger_client.ReportSchema() # ReportSchema | reportsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update report by name
    api_instance.update_iceberg_system_report_by_id(name, report, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_system_report_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of report	
report	**ReportSchema**	reportsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.590 update_iceberg_system_reports

update_iceberg_system_reports(reports, x_iam_token=x_iam_token)

Update reports by name

Overwrite the existing configuration of reports. New reports are created and the existing reports are overwritten with new content. If some existing reports are not present in the payload, such reports are deleted. This will fail if any of the reports that are not present in the payload are referenced by a device-group or network-group.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
reports = swagger_client.ReportsSchema() # ReportsSchema | reportsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update reports by name
    api_instance.update_iceberg_system_reports(reports, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_system_reports:
↪ %s\n" % e)

```

Name	Type	Description	Notes
reports	**ReportsSchema**	reportsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.591 update_iceberg_system_scheduler_by_id

update_iceberg_system_scheduler_by_id(name, scheduler, x_iam_token=x_iam_token)

Update scheduler by name

Overwrite a scheduler by scheduler name. The scheduler name specified in the URL and the request body must match.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of Scheduler
scheduler = swagger_client.SchedulerSchema() # SchedulerSchema | schedulerbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update scheduler by name
    api_instance.update_iceberg_system_scheduler_by_id(name, scheduler, x_iam_token=x_
↪ iam_token)

```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_system_scheduler_
↳by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of Scheduler	
scheduler	**SchedulerSchema**	schedulerbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.592 update_iceberg_system_schedulers

update_iceberg_system_schedulers(schedulers, x_iam_token=x_iam_token)

Update schedulers by name

Update operation of resource: schedulers

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
schedulers = swagger_client.SchedulersSchema() # SchedulersSchema | schedulersbody_
↳object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update schedulers by name
    api_instance.update_iceberg_system_schedulers(schedulers, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_system_schedulers:
↳%s\n" % e)
```

Name	Type	Description	Notes
schedulers	**SchedulersSchema**	schedulersbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json

- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.593 update_iceberg_system_settings_destination_by_id

update_iceberg_system_settings_destination_by_id(name, destination, x_iam_token=x_iam_token)

Update destination by name

Overwrite a destination by destination name. The destination name specified in the URL and the request body must match.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of destination
destination = swagger_client.DestinationSchema() # DestinationSchema | ↪
↪ destinationsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update destination by name
    api_instance.update_iceberg_system_settings_destination_by_id(name, destination, ↪
↪ x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_system_settings_
↪ destination_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of destination	
destination	**DestinationSchema**	destinationsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.594 update_iceberg_system_settings_destinations

update_iceberg_system_settings_destinations(destinations, x_iam_token=x_iam_token)

Update destinations by name

Overwrite the existing configuration of destinations. New destinations are created and the existing destinations are overwritten with new content. If some existing destinations are not present in the payload, such destinations are deleted. This will fail if any of the destinations that are not present in the payload are referenced by a report.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
destinations = swagger_client.DestinationsSchema() # DestinationsSchema |
↳ destinationsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update destinations by name
    api_instance.update_iceberg_system_settings_destinations(destinations, x_iam_
↳ token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_system_settings_
↳ destinations: %s\n" % e)
```

Name	Type	Description	Notes
destinations	**DestinationsSchema**	destinationsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.595 update_iceberg_system_settings_report_by_id

update_iceberg_system_settings_report_by_id(name, report, x_iam_token=x_iam_token)

Update report by name

Overwrite a report by report name. The report name specified in the URL and the request body must match.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of report
report = swagger_client.ReportSchema() # ReportSchema | reportsbody object
```

(continues on next page)

(continued from previous page)

```
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update report by name
    api_instance.update_iceberg_system_settings_report_by_id(name, report, x_iam_
↳token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_system_settings_
↳report_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of report	
report	**ReportSchema**	reportsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.596 update_iceberg_system_settings_reports

update_iceberg_system_settings_reports(reports, x_iam_token=x_iam_token)

Update reports by name

Overwrite the existing configuration of reports. New reports are created and the existing reports are overwritten with new content. If some existing reports are not present in the payload, such reports are deleted. This will fail if any of the reports that are not present in the payload are referenced by a device-group or network-group.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
reports = swagger_client.ReportsSchema() # ReportsSchema | reportsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update reports by name
    api_instance.update_iceberg_system_settings_reports(reports, x_iam_token=x_iam_
↳token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_system_settings_
↳reports: %s\n" % e)
```

Name	Type	Description	Notes
reports	**ReportsSchema**	reportsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.597 update_iceberg_system_settings_scheduler_by_id

update_iceberg_system_settings_scheduler_by_id(name, scheduler, x_iam_token=x_iam_token)

Update scheduler by name

Overwrite a scheduler by scheduler name. The scheduler name specified in the URL and the request body must match.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
name = 'name_example' # str | Name of Scheduler
scheduler = swagger_client.SchedulerSchema() # SchedulerSchema | schedulerbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update scheduler by name
    api_instance.update_iceberg_system_settings_scheduler_by_id(name, scheduler, x_
↳ iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_system_settings_
↳ scheduler_by_id: %s\n" % e)
```

Name	Type	Description	Notes
name	str	Name of Scheduler	
scheduler	**SchedulerSchema**	schedulerbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.598 update_iceberg_system_settings_schedulers

```
update_iceberg_system_settings_schedulers(schedulers, x_iam_token=x_iam_token)
```

Update schedulers by name

Update operation of resource: schedulers

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
schedulers = swagger_client.SchedulersSchema() # SchedulersSchema | schedulersbody_
↪object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update schedulers by name
    api_instance.update_iceberg_system_settings_schedulers(schedulers, x_iam_token=x_
↪iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_system_settings_
↪schedulers: %s\n" % e)
```

Name	Type	Description	Notes
schedulers	**SchedulersSchema**	schedulersbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.599 update_iceberg_system_settings_system_settings_by_id

```
update_iceberg_system_settings_system_settings_by_id(system_settings, x_iam_token=x_iam_token,
force_tsdb=force_tsdb)
```

Update system-settings by ID

Overwrite the existing configuration of system-settings. New system-settings are created and existing system-settings are overwritten with new content. If some existing system-settings are not present in the payload, such system-settings are deleted. This will fail if any of the reports in system-settings that are not present in the payload are referenced by a device-group or network-group.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
system_settings = swagger_client.SystemSettingsSchema() # SystemSettingsSchema |
↳ system_settingsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
force_tsdb = False # bool | force update tsdb when force is set to True (optional)
↳ (default to False)

try:
    # Update system-settings by ID
    api_instance.update_iceberg_system_settings_system_settings_by_id(system_settings,
↳ x_iam_token=x_iam_token, force_tsdb=force_tsdb)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_system_settings_
↳ system_settings_by_id: %s\n" % e)

```

Name	Type	Description	Notes
sys- tem_settings	**SystemSettingsS- chema**	system_settingsbody object	
x_iam_token	str	authentication header object	[optional]
force_tsdb	bool	force update tsdb when force is set to True	[optional] [default to false]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.600 update_iceberg_system_system_by_id

```

update_iceberg_system_system_by_id(system_settings,
force_tsdb=force_tsdb)
x_iam_token=x_iam_token,

```

Update system by ID

New endpoint to over-write the existing configuration of system-settings. New system-settings are created and existing system-settings are overwritten with new content. If some existing system-settings are not present in the payload, such system settings are deleted. This will fail if any of the reports in system-settings that are not present in the payload are referenced by a device-group or network-group.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException

```

(continues on next page)

(continued from previous page)

```

from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
system_settings = swagger_client.SystemSettingsSchema() # SystemSettingsSchema |
↳ system_settings body object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
force_tsdb = False # bool | force update tsdb when force is set to True (optional)
↳ (default to False)

try:
    # Update system by ID
    api_instance.update_iceberg_system_system_by_id(system_settings, x_iam_token=x_
↳ iam_token, force_tsdb=force_tsdb)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_system_system_by_
↳ id: %s\n" % e)

```

Name	Type	Description	Notes
system_settings	**SystemSettingsSchema**	system_settings body object	
x_iam_token	str	authentication header object	[optional]
force_tsdb	bool	force update tsdb when force is set to True	[optional] [default to false]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.601 update_iceberg_topic_rule_rule_by_id

update_iceberg_topic_rule_rule_by_id(topic_name, rule_name, rule, x_iam_token=x_iam_token)

Overwrite a rule.

Overwrite a rule by the rule-name. The rule-name specified in URL and the request body must match.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
topic_name = 'topic_name_example' # str | ID of topic-name
rule_name = 'rule_name_example' # str | ID of rule-name
rule = swagger_client.RuleSchema() # RuleSchema | rulebody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

```

(continues on next page)

(continued from previous page)

```

try:
    # Overwrite a rule.
    api_instance.update_iceberg_topic_rule_rule_by_id(topic_name, rule_name, rule, x_
    ↳ iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_topic_rule_rule_by_
    ↳ id: %s\n" % e)

```

Name	Type	Description	Notes
topic_name	str	ID of topic-name	
rule_name	str	ID of rule-name	
rule	**RuleSchema**	rulebody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.602 update_iceberg_topic_topic_by_id

update_iceberg_topic_topic_by_id(topic_name, topic, x_iam_token=x_iam_token)

Overwrite a topic.

Overwrite a topic by the topic-name. The topic-name specified in URL and the request body must match.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
topic_name = 'topic_name_example' # str | ID of topic-name
topic = swagger_client.TopicSchema() # TopicSchema | topicbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Overwrite a topic.
    api_instance.update_iceberg_topic_topic_by_id(topic_name, topic, x_iam_token=x_
    ↳ iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_topic_topic_by_id:
    ↳ %s\n" % e)

```

Name	Type	Description	Notes
topic_name	str	ID of topic-name	
topic	**TopicSchema**	topicbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.603 update_iceberg_topics_topics_by_id

update_iceberg_topics_topics_by_id(topics, x_iam_token=x_iam_token)

Overwrite topics.

Overwrite the existing topics configuration. New topics are created and existing topics are overwritten with new content. If some existing topics are not present in the payload, such topics are deleted. This will fail if any of the topics that are not present in the payload are referenced by a playbook.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.ConfigurationApi()
topics = swagger_client.TopicsSchema() # TopicsSchema | topicsbody object
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Overwrite topics.
    api_instance.update_iceberg_topics_topics_by_id(topics, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling ConfigurationApi->update_iceberg_topics_topics_by_
↳ id: %s\n" % e)
```

Name	Type	Description	Notes
topics	**TopicsSchema**	topicsbody object	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.604 Event

2.604.1 Properties

Name	Type	Description	Notes
color	str	Event severity	[optional]
event_name	str	Event name	[optional]
frequency	int	Frequency of the event.	[optional]
timestamp	datetime		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.605 TableSchema

2.605.1 Properties

Name	Type	Description	Notes
name	str	Name of the table	
type	str		
db_name	str	Database name in which the measurement is present.	[optional]
retention_policy	str	Retention policy of the measurement	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.606 IngestsettingsSchemaIngestsettingsSyslogPatternset

2.606.1 Properties

Name	Type	Description	Notes
description	str	Pattern-set description	[optional]
name	str	Name of a pattern-set. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	
pattern_names	list[str]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.607 InstancesScheduleStateSchema

2.607.1 Properties

Name	Type	Description	Notes
instance	**list[InstanceScheduleStateSchema]**		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.608 RuleSchemaSyslog

2.608.1 Properties

Name	Type	Description	Notes
pattern_set	str	Pattern-set applicable for this sensor	
maximum_hold_period	str	Maximum time (in units of seconds/minutes/hours/days) system will wait for all fields to arrive before flushing all the field data. Default is 1 second	[optional] [default to '1s']

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.609 IngestmappingSchemaOpenconfig

2.609.1 Properties

Name	Type	Description	Notes
for_device_groups	list[str]		[optional]
use_plugin	**IngestmappingSchemaIAgentUseplugin**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.610 RefreshToken

2.610.1 Properties

Name	Type	Description	Notes
token	str	Refresh token	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.611 ReportGenerationSchema

2.611.1 Properties

Name	Type	Description	Notes
destination	**list[DestinationSchema]**		[optional]
report	**list[ReportSchema]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.612 SchedulerSchemaRunfor

2.612.1 Properties

Name	Type	Description	Notes
days	int	Duration of time in days	[optional]
hours	int	Duration of time in hours	[optional]
minutes	int	Duration of time in minutes	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.613 User

2.613.1 Properties

Name	Type	Description	Notes
first_name	str	First name of the user	[optional]
last_name	str	Last name of the user	[optional]
email	str	Email of the user	[optional]
password	str	Password of the user	[optional]
active	bool	Status of the user	[optional]
groups	**AssociatedGroupSchema**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.614 NotificationSchema

2.614.1 Properties

Name	Type	Description	Notes
description	str	Description about the notification	[optional]
http_post	**NotificationSchemaHttp-post**		[optional]
notification_name	str	Name of the notification. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	
slack	**NotificationSchemaSlack**		[optional]
microsoft_teams	**NotificationSchemaMicrosoftteams**		[optional]
emails	**NotificationSchemaEmails**		[optional]
kafka_publish	**NotificationSchemaKafka-publish**		[optional]
amqp_publish	**NotificationSchemaAmqp-publish**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.615 SchedulerSchema

2.615.1 Properties

Name	Type	Description	Notes
end_time	str	End scheduler at this time	[optional]
name	str	Name of the scheduler	
repeat	**SchedulerSchemaRepeat**		
start_time	str	Start scheduler at this time	
run_for	**SchedulerSchemaRunfor**		[optional]
type	str	Type of the scheduler.	[optional] [default to 'continuous']

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.616 NotificationSchemaHttppostBasic

2.616.1 Properties

Name	Type	Description	Notes
password	str	Password for http basic authentication	
username	str	Username for http basic authentication	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.617 DeviceSchemaVendor

2.617.1 Properties

Name	Type	Description	Notes
arista	**DeviceSchemaVendorArista**		[optional]
cisco	**DeviceSchemaVendorCisco**		[optional]
juniper	**DeviceSchemaVendorJuniper**		[optional]
linux	**DeviceSchemaVendorLinux**		[optional]
other_vendor	**DeviceSchemaVendorOthervendor**		[optional]
paloalto	**DeviceSchemaVendorPaloalto**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.618 LicenseKeySchema

2.618.1 Properties

Name	Type	Description	Notes
license_id	str	Unique ID of the license	
start_date	datetime	License start date and time	
end_date	datetime	License end date and time	
valid-ity_type	str	License validity type	
version	int	License key version, an integer value indicating version of license vendor info	
sku_name	str	License stock keeping unit name, indicates category of purchased license	
cus-tomer_id	str	Identification of customer who has purchased this license	
or-der_type	str	License purchase order type	
sw_serial_id	str	Software serial number used for license activation	[optional]
mode	str	License mode of operation	[optional]
features	**list[LicenseKeySchemaFeatures]	Features which are part of the license	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.619 swagger_client.DataStoreApi

All URIs are relative to *http://api-server/api/v2*

Method	HTTP request	Description
create_data_store	POST /config/data-store/{group_name}/	Create dashboard details.
delete_data_store	DELETE /config/data-store/{group_name}/	Delete dashboard details.
retrieve_data_store	GET /config/data-store/{group_name}/	Delete dashboard details.
update_data_store	PUT /config/data-store/{group_name}/	Update data_store details.

2.620 create_data_store

`create_data_store(key, data, group_name, x_iam_token=x_iam_token)`

Create dashboard details.

Store data-store details in database for the requested group name and key.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
```

(continues on next page)

(continued from previous page)

```

from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DataStoreApi()
key = 'key_example' # str | Key of data_store object
data = swagger_client.DatastoreSchema() # DatastoreSchema | Value of data_store object
group_name = 'group_name_example' # str | Group name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Create dashboard details.
    api_instance.create_data_store(key, data, group_name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DataStoreApi->create_data_store: %s\n" % e)

```

Name	Type	Description	Notes
key	str	Key of data_store object	
data	**DatastoreSchema**	Value of data_store object	
group_name	str	Group name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.621 delete_data_store

`delete_data_store(group_name, x_iam_token=x_iam_token, key=key)`

Delete dashboard details.

Delete data_store details for the given group-name, or as per the keys passed in query.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DataStoreApi()
group_name = 'group_name_example' # str | Group name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
key = ['key_example'] # list[str] | ID of dashboard (optional)

try:
    # Delete dashboard details.
    api_instance.delete_data_store(group_name, x_iam_token=x_iam_token, key=key)

```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling DataStoreApi->delete_data_store: %s\n" % e)
```

Name	Type	Description	Notes
group_name	str	Group name	
x_iam_token	str	authentication header object	[optional]
key	**list[str]**	ID of dashboard	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.622 retrieve_data_store

DatastoreSchema retrieve_data_store(group_name, x_iam_token=x_iam_token, key=key)

Delete dashboard details.

Retrieve data_store details for the given group-name, or as per the keys passed in query.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DataStoreApi()
group_name = 'group_name_example' # str | Group name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
key = ['key_example'] # list[str] | Key of data_store object (optional)

try:
    # Delete dashboard details.
    api_response = api_instance.retrieve_data_store(group_name, x_iam_token=x_iam_
    token, key=key)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling DataStoreApi->retrieve_data_store: %s\n" % e)
```

Name	Type	Description	Notes
group_name	str	Group name	
x_iam_token	str	authentication header object	[optional]
key	**list[str]**	Key of data_store object	[optional]

****DatastoreSchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.623 update_data_store

update_data_store(key, data, group_name, x_iam_token=x_iam_token)

Update data_store details.

Update data-store details in database for the requested group name and key.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DataStoreApi()
key = 'key_example' # str | key of data_store
data = swagger_client.DatastoreSchema() # DatastoreSchema | value of data_store object
group_name = 'group_name_example' # str | Group name
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update data_store details.
    api_instance.update_data_store(key, data, group_name, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling DataStoreApi->update_data_store: %s\n" % e)
```

Name	Type	Description	Notes
key	str	key of data_store	
data	**DatastoreSchema**	value of data_store object	
group_name	str	Group name	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.624 RuleSchemaFormulaCount

2.624.1 Properties

Name	Type	Description	Notes
field_name	str	Field name on which count operation needs to be performed	
time_range	str	How much back in time should we look for data. Specify positive integer followed by s/m/h/d/w/y/o representing seconds/minutes/hours/days/weeks/yours/offset. Eg: 2s	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.625 AssociatedGroupSchema

2.625.1 Properties

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.626 ProfileSchemaDatsummarizationRaw

2.626.1 Properties

Name	Type	Description	Notes
data_type	**list[RawSchemaDatatype]**		[optional]
name	str	Name of raw-data summarization profile	
path	**list[ProfileSchemaDatsummarizationPath]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.627 RuleSchemaTrigger

2.627.1 Properties

Name	Type	Description	Notes
description	str	Description about the trigger	[optional]
frequency	str	Frequency or time interval at which the trigger needs to be evaluated. Specify positive integer followed by s/m/h/d/w/y/o representing seconds/minutes/hours/days/weeks/years/offset. Eg: 2s	[optional]
synopsis	str	Synopsis about the trigger	[optional]
disable_alarm_deduplication	list[object]	Disable alarm deduplication, so that alarms are always generated	[optional]
term	**list[RuleSchemaTerm]**		
trigger_name	str	Trigger name. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.628 RuleSchemaByoi

2.628.1 Properties

Name	Type	Description	Notes
plugin	**RuleSchemaByoiPlugin**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.629 swagger_client.FactsApi

All URIs are relative to *http://api-server/api/v2*

Method	HTTP request	Description
retrieve_iceberg_device_device_facts_by_id	GET /config/device/{device_id}/facts/	Get a device's facts.
retrieve_iceberg_devices_devices_facts	GET /config/devices/facts/	Get devices facts.
retrieve_iceberg_devices_facts_by_group	GET /config/device-group/{device_group_name}/facts/	Get a devices facts for given group.

2.630 retrieve_iceberg_device_device_facts_by_id

DeviceSchema retrieve_iceberg_device_device_facts_by_id(device_id, x_iam_token=x_iam_token, working=working, update=update, timeout=timeout)

Get a device's facts.

Get the fact details of a device by its device-id.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.FactsApi()
device_id = 'device_id_example' # str | ID of device-id
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)
update = True # bool | true will first update facts from device and then return facts_
↳ (optional)
timeout = 56 # int | timeout in seconds to wait for facts from given device id_
↳ (optional)

try:
    # Get a device's facts.
    api_response = api_instance.retrieve_iceberg_device_device_facts_by_id(device_id,
↳ x_iam_token=x_iam_token, working=working, update=update, timeout=timeout)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling FactsApi->retrieve_iceberg_device_device_facts_by_
↳ id: %s\n" % e)
```

Name	Type	Description	Notes
device_id	str	ID of device-id	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]
update	bool	true will first update facts from device and then return facts	[optional]
timeout	int	timeout in seconds to wait for facts from given device id	[optional]

****DeviceSchema****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.631 retrieve_iceberg_devices_devices_facts

```
DeviceSchema retrieve_iceberg_devices_devices_facts(x_iam_token=x_iam_token, working=working,
update=update, timeout=timeout)
```

Get devices facts.

Get the fact details of every device


```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.FactsApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)
update = True # bool | true will first update facts from device and then return facts_
↳ (optional)
timeout = 56 # int | timeout in seconds to wait for facts from every device (optional)

try:
    # Get devices facts.
    api_response = api_instance.retrieve_iceberg_devices_devices_facts(x_iam_token=x_
↳ iam_token, working=working, update=update, timeout=timeout)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling FactsApi->retrieve_iceberg_devices_devices_facts:
↳ %s\n" % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]
update	bool	true will first update facts from device and then return facts	[optional]
timeout	int	timeout in seconds to wait for facts from every device	[optional]

****DeviceSchema****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.632 retrieve_iceberg_devices_facts_by_group

```

DeviceSchema.retrieve_iceberg_devices_facts_by_group(device_group_name,
x_iam_token=x_iam_token, working=working, update=update, timeout=timeout)

```

Get a devices facts for given group.

Get the fact details of every device under given group

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class

```

(continues on next page)

(continued from previous page)

```

api_instance = swagger_client.FactsApi()
device_group_name = 'device_group_name_example' # str | ID of group
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
working = True # bool | true queries un-committed configuration (optional)
update = True # bool | true will first update facts from device and then return facts_
↳ (optional)
timeout = 56 # int | timeout in seconds to wait for facts from every device (optional)

try:
    # Get a devices facts for given group.
    api_response = api_instance.retrieve_iceberg_devices_facts_by_group(device_group_
↳ name, x_iam_token=x_iam_token, working=working, update=update, timeout=timeout)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling FactsApi->retrieve_iceberg_devices_facts_by_group:
↳ %s\n" % e)

```

Name	Type	Description	Notes
device_group_name	str	ID of group	
x_iam_token	str	authentication header object	[optional]
working	bool	true queries un-committed configuration	[optional]
update	bool	true will first update facts from device and then return facts	[optional]
timeout	int	timeout in seconds to wait for facts from every device	[optional]

****DeviceSchema****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.633 DebugJobResponseSchema

2.633.1 Properties

Name	Type	Description	Notes
job_id	str		[optional]
job_status	str		[optional]
job_details	str		[optional]
debug_data	str		[optional]
debug_type	str		[optional]
debug_name	str		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.634 TlivekafkaocSchemaSecuritySasl

2.634.1 Properties

Name	Type	Description	Notes
password	str	SASL password	[optional]
username	str	SASL username	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.635 GroupHealthSchema

2.635.1 Properties

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.636 DestinationSchema

2.636.1 Properties

Name	Type	Description	Notes
disk	**DestinationSchemaDisk**		[optional]
email	**DestinationSchemaEmail**		[optional]
name	str	Name of the destination. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.637 RuleSchemaWhenExists

2.637.1 Properties

Name	Type	Description	Notes
all	list[object]	With this flag, result is set to True only if all the data matches the given condition	[optional]
any	list[object]	With this flag, result is set to True if any one of the data matches the condition	[optional]
field_name	str	Field name which needs to be present	
time_range	str	How much back in time should we look for data. Specify positive integer followed by s/m/h/d/w/y/o representing seconds/minutes/hours/days/weeks/years/offset. Eg: 2s	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.638 RawSchema

2.638.1 Properties

Name	Type	Description	Notes
data_type	**list[RawSchemaDatatype]**		[optional]
name	str	Name of raw-data summarization profile	
path	**list[RawSchemaPath]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.639 RuleSchemaOpenconfig

2.639.1 Properties

Name	Type	Description	Notes
frequency	str	Sensor subscription duration. Specify integer > 0 followed by s/m/h/d/w/y representing seconds/minutes/hours/days/weeks/years. Eg: 2s. A frequency of zero should be used only in case of events subscription	
sensor_name	str	Sensor to subscribe	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.640 ProfileSchemaDatasummarization

2.640.1 Properties

Name	Type	Description	Notes
raw	**list[ProfileSchemaDatasummarizationRaw]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.641 IngestsettingsSchemaIngestsettings

2.641.1 Properties

Name	Type	Description	Notes
flow	**IngestsettingsSchemaIngestsettingsFlow**		[optional]
syslog	**IngestsettingsSchemaIngestsettingsSyslog**		[optional]
byoi	**IngestsettingsSchemaIngestsettingsByoi**		[optional]
frequency_profile	**list[IngestsettingsSchemaIngestsettingsFrequencyprofile]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.642 DestinationsSchema

2.642.1 Properties

Name	Type	Description	Notes
destination	**list[DestinationSchema]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.643 swagger_client.SystemApi

All URIs are relative to *http://api-server/api/v2*

Method	HTTP request	Description
generate_resource_dependencies	GET /config/rca/generate-resource-dependencies	Resource dependencies
query_tsdb	GET /tsdb/query	TSDB query
query_tsdb_post	POST /tsdb/query	TSDB query
retrieve_available_nodes	GET /nodes/	List of available nodes
retrieve_sensor_device_group	GET /config/sensor/device-group/{device_group_name}/	Get all All API's.
retrieve_system_details	GET /system-details/	Retrieve system details.
retrieve_tsdb_counters	GET /tsdb-counters/	TSDB counters

2.644 generate_resource_dependencies

`generate_resource_dependencies(x_iam_token=x_iam_token)`

Resource dependencies

Get resource dependency events. Internal API

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.SystemApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Resource dependencies
```

(continues on next page)

(continued from previous page)

```

    api_instance.generate_resource_dependencies(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling SystemApi->generate_resource_dependencies: %s\n" %
    ↪e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.645 query_tsdb

TsdbResults query_tsdb(db, device_group, device, measurement=measurement, topic=topic, rule=rule, trigger=trigger, fields=fields, order=order, group_by=group_by, limit=limit, where=where, q=q)

TSDB query

Query TSDB

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.SystemApi()
db = 'db_example' # str | Name of the database. Multiple databases should be
↪separated by ','. '*' can be used to specify all databases.
device_group = 'device_group_example' # str | Name of the deviceGroup(s). Multiple
↪device groups should be separated by ','. This can be used in combination with
↪device, but is not mandatory. If device is given, then query will be executed only
↪for that particular devices in the given device group, else all devices in group
↪will be considered. Given devices will be applicable for all give device-groups.
device = 'device_example' # str | Name of the device. Multiple device should be
↪separated by ','. This should be used along with deviceGroup. Without deviceGroup,
↪this config will not be considered
measurement = 'measurement_example' # str | Name of the measurement. Optional if
↪topic/rule/trigger is used (optional)
topic = 'topic_example' # str | Name of Healthbot topic. Optional if measurement is
↪used (optional)
rule = 'rule_example' # str | Name of Healthbot rule. Required if topic is used.
↪Optional if measurement is used (optional)
trigger = 'trigger_example' # str | Name of Healthbot trigger. Optional if
↪measurement is used or rule table is being queried (optional)
fields = 'fields_example' # str | Fields that needs to be retrieved. Use * for to
↪query all fields. Eg: fields=field1, field2 (optional)

```

(continues on next page)

(continued from previous page)

```

order = 'order_example' # str | Sort points in descending order based on time. By
↳ default points will be sorted in ascending order. Eg: order=desc (optional)
group_by = 'group_by_example' # str | Group results based on specified tags. Use * to
↳ group by all tags. Eg: groupBy=key1, key2 (optional)
limit = 'limit_example' # str | Limit number of points in the result. If groupBy is
↳ used limit is applied per group. Eg: limit=10 (optional)
where = 'where_example' # str | Where clause filters data based on fields, tags, and/
↳ or timestamps. Eg: where="interface-name" = 'ge-0/0/1' and "in-pkts" > 0
↳ (optional)
q = 'q_example' # str | Influx query string. Use this when custom query format does
↳ not support a query (optional)

try:
    # TSDB query
    api_response = api_instance.query_tsdb(db, device_group, device,
↳ measurement=measurement, topic=topic, rule=rule, trigger=trigger, fields=fields,
↳ order=order, group_by=group_by, limit=limit, where=where, q=q)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling SystemApi->query_tsdb: %s\n" % e)

```

Name	Type	Description	Notes
db	str	Name of the database. Multiple databases should be separated by ','. '*' can be used to specify all databases.	
device_group	str	Name of the deviceGroup(s). Multiple device groups should be separated by ','. This can be used in combination with device, but is not mandatory. If device is given, then query will be executed only for that particular devices in the given device group, else all devices in group will be considered. Given devices will be applicable for all give device-groups.	
device	str	Name of the device. Multiple device should be separated by ','. This should be used along with deviceGroup. Without deviceGroup, this config will not be considered	
measurement	str	Name of the measurement. Optional if topic/rule/trigger is used	[optional]
topic	str	Name of Healthbot topic. Optional if measurement is used	[optional]
rule	str	Name of Healthbot rule. Required if topic is used. Optional if measurement is used	[optional]
trigger	str	Name of Healthbot trigger. Optional if measurement is used or rule table is being queried	[optional]
fields	str	Fields that needs to be retrieved. Use * for to query all fields. Eg: fields==field1, field2	[optional]
order	str	Sort points in descending order based on time. By default points will be sorted in ascending order. Eg: order==desc	[optional]
group_by	str	Group results based on specified tags. Use * to group by all tags. Eg: groupBy==key1, key2	[optional]
limit	str	Limit number of points in the result. If groupBy is used limit is applied per group. Eg: limit==10	[optional]
where	str	Where clause filters data based on fields, tags, and/or timestamps. Eg: where=="interface-name" = 'ge-0/0/1' and "in-pkts" > 0	[optional]
q	str	Influx query string. Use this when custom query format does not support a query	[optional]

****TsdBResults****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.646 query_tsdB_post

```
TsdBResults query_tsdB_post(db, device_group, device, tsdb_query_body=tsdb_query_body,
                             measurement=measurement, topic=topic, rule=rule, trigger=trigger, fields=fields, order=order,
                             group_by=group_by, limit=limit, where=where, q=q)
```

TSDB query

Query TSDB

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.SystemApi()
db = 'db_example' # str | Name of the database. Multiple databases should be
↳ separated by ','. '*' can be used to specify all databases.
device_group = 'device_group_example' # str | Name of the deviceGroup(s). Multiple
↳ device groups should be separated by ','. This can be used in combination with
↳ device, but is not mandatory. If device is given, then query will be executed only
↳ for that particular devices in the given device group, else all devices in group
↳ will be considered. Given devices will be applicable for all give device-groups.
device = 'device_example' # str | Name of the device. Multiple device should be
↳ separated by ','. This should be used along with deviceGroup. Without deviceGroup,
↳ this config will not be considered
tsdb_query_body = swagger_client.TsdBPostBody() # TsdBPostBody | Query TSDB body
↳ object (optional)
measurement = 'measurement_example' # str | Name of the measurement. Optional if
↳ topic/rule/trigger is used (optional)
topic = 'topic_example' # str | Name of Healthbot topic. Optional if measurement is
↳ used (optional)
rule = 'rule_example' # str | Name of Healthbot rule. Required if topic is used.
↳ Optional if measurement is used (optional)
trigger = 'trigger_example' # str | Name of Healthbot trigger. Optional if
↳ measurement is used or rule table is being queried (optional)
fields = 'fields_example' # str | Fields that needs to be retrieved. Use * for to
↳ query all fields. Eg: fields=field1, field2 (optional)
order = 'order_example' # str | Sort points in descending order based on time. By
↳ default points will be sorted in ascending order. Eg: order=desc (optional)
group_by = 'group_by_example' # str | Group results based on specified tags. Use * to
↳ group by all tags. Eg: groupBy=key1, key2 (optional)
limit = 'limit_example' # str | Limit number of points in the result. If groupBy is
↳ used limit is applied per group. Eg: limit=10 (optional)
where = 'where_example' # str | Where clause filters data based on fields, tags, and/
↳ or timestamps. Eg: where=\"interface-name\" = 'ge-0/0/1' and \"in-pkts\" > 0
↳ (optional)
```

(continues on next page)

(continued from previous page)

```

q = 'q_example' # str | Influx query string. Use this when custom query format does
↳not support a query (optional)

try:
    # TSDB query
    api_response = api_instance.query_tsdb_post(db, device_group, device, tsdb_query_
↳body=tsdb_query_body, measurement=measurement, topic=topic, rule=rule,
↳trigger=trigger, fields=fields, order=order, group_by=group_by, limit=limit,
↳where=where, q=q)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling SystemApi->query_tsdb_post: %s\n" % e)

```

Name	Type	Description	Notes
db	str	Name of the database. Multiple databases should be separated by ','. '*' can be used to specify all databases.	
device_group	str	Name of the deviceGroup(s). Multiple device groups should be separated by ','. This can be used in combination with device, but is not mandatory. If device is given, then query will be executed only for that particular devices in the given device group, else all devices in group will be considered. Given devices will be applicable for all give device-groups.	
device	str	Name of the device. Multiple device should be separated by ','. This should be used along with deviceGroup. Without deviceGroup, this config will not be considered	
tsdb_query_body	**Tsdb-Post-Body**	Query TSDB body object	[optional]
measurement	str	Name of the measurement. Optional if topic/rule/trigger is used	[optional]
topic	str	Name of Healthbot topic. Optional if measurement is used	[optional]
rule	str	Name of Healthbot rule. Required if topic is used. Optional if measurement is used	[optional]
trigger	str	Name of Healthbot trigger. Optional if measurement is used or rule table is being queried	[optional]
fields	str	Fields that needs to be retrieved. Use * for to query all fields. Eg: fields=field1, field2	[optional]
order	str	Sort points in descending order based on time. By default points will be sorted in ascending order. Eg: order=desc	[optional]
group_by	str	Group results based on specified tags. Use * to group by all tags. Eg: groupBy=key1, key2	[optional]
limit	str	Limit number of points in the result. If groupBy is used limit is applied per group. Eg: limit=10	[optional]
where	str	Where clause filters data based on fields, tags, and/or timestamps. Eg: where="interface-name" = 'ge-0/0/1' and "in-pkts" > 0	[optional]
q	str	Influx query string. Use this when custom query format does not support a query	[optional]

****TsdbResults****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json, application/octet-stream

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.647 retrieve_available_nodes

retrieve_available_nodes(x_iam_token=x_iam_token)

List of available nodes

Get the list of available nodes in the installation.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.SystemApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # List of available nodes
    api_instance.retrieve_available_nodes(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling SystemApi->retrieve_available_nodes: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.648 retrieve_sensor_device_group

retrieve_sensor_device_group(device_group_name, x_iam_token=x_iam_token)

Get all All API's.

GET sensors subscribed for a device-group

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint
```

(continues on next page)

(continued from previous page)

```
# create an instance of the API class
api_instance = swagger_client.SystemApi()
device_group_name = 'device_group_name_example' # str | Device Group
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Get all All API's.
    api_instance.retrieve_sensor_device_group(device_group_name, x_iam_token=x_iam_
    token)
except ApiException as e:
    print("Exception when calling SystemApi->retrieve_sensor_device_group: %s\n" % e)
```

Name	Type	Description	Notes
device_group_name	str	Device Group	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.649 retrieve_system_details

retrieve_system_details(x_iam_token=x_iam_token, service_name=service_name)

Retrieve system details.

Retrieve system details for HealthBot system.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.SystemApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)
service_name = 'service_name_example' # str | service name takes in the name of the_
    service for which details are required. (optional)

try:
    # Retrieve system details.
    api_instance.retrieve_system_details(x_iam_token=x_iam_token, service_
    name=service_name)
except ApiException as e:
    print("Exception when calling SystemApi->retrieve_system_details: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
service_name	str	service name takes in the name of the service for which details are required.	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.650 retrieve_tsdb_counters

```
retrieve_tsdb_counters(x_iam_token=x_iam_token)
```

TSDB counters

Get TSDB counters

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.SystemApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # TSDB counters
    api_instance.retrieve_tsdb_counters(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling SystemApi->retrieve_tsdb_counters: %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.651 RuleSchemaThen

2.651.1 Properties

Name	Type	Description	Notes
next	list[object]	Continue evaluating next term in a trigger	[optional]
status	**RuleSchemaThenStatus**		[optional]
user_defined_action	**list[RuleSchemaThenUserdefinedaction]**		[optional]
workflow	**list[RuleSchemaThenWorkflow]**	Trigger workflow execution	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.652 RawSchemaPath

2.652.1 Properties

Name	Type	Description	Notes
aggregation_functions	list[str]		
name	str	Sensor field path for which summarization should be changed. Apart from JTI OC sensor path, '<sensor-name>:' should be prepended to the sensor path	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.653 RuleSchemaFormulaUserdefinedfunctionArgument

2.653.1 Properties

Name	Type	Description	Notes
argument	str	Argument name	
value	str	Argument value	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.654 PatternSetSchema

2.654.1 Properties

Name	Type	Description	Notes
description	str	Pattern-set description	[optional]
name	str	Name of a pattern-set. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	
pattern_names	list[str]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.655 RuleSchemaFormulaMin

2.655.1 Properties

Name	Type	Description	Notes
field_name	str	Field name on which min operation needs to be performed	
time_range	str	How much back in time should we look for data. Specify positive integer followed by s/m/h/d/w/y/o representing seconds/minutes/hours/days/weeks/years/offset. Eg: 2s	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.656 SchedulerSchemaRepeatInterval

2.656.1 Properties

Name	Type	Description	Notes
days	int	Duration of time in days	[optional]
hours	int	Duration of time in hours	[optional]
minutes	int	Duration of time in minutes	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.657 RuleSchemaFormulaOutlierdetectionAlgorithmDbscanSensitivity

2.657.1 Properties

Name	Type	Description	Notes
absolute_percentage	float	Absolute percentage of members that are to be marked as outliers	[optional]
level	str	Fuzzy level of outliers to be detected	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.658 RuleSchemaAgentArgs

2.658.1 Properties

Name	Type	Description	Notes
arg_name	str	name of argument	
arg_value	str	value of argument	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.659 swagger_client.LicenseApi

All URIs are relative to *http://api-server/api/v2*

Method	HTTP request	Description
create_iceberg_add_license_from_file	POST /license/keys/	Add license from file.
delete_iceberg_delete_all_license	DELETE /license/keys/	Delete all licenses.
delete_iceberg_delete_license_by_id	DELETE /license/key/{license_id}/	Delete a license.
retrieve_iceberg_get_all_license_id	GET /license/keys/	List of available license id's.
retrieve_iceberg_license_features_info	GET /license/status/	Status of all the licensed features.
retrieve_iceberg_license_file_by_license_id	GET /license/key/{license_id}/	Download license file.
retrieve_iceberg_license_key_contents	GET /license/keys/contents/	Get the contents of all licenses.
retrieve_iceberg_license_key_contents_by_id	GET /license/key/{license_id}/contents/	Get the contents of a license.
update_iceberg_replace_license	PUT /license/keys/	Update the license.

2.660 create_iceberg_add_license_from_file

InlineResponse2001 create_iceberg_add_license_from_file(license_file, x_iam_token=x_iam_token)

Add license from file.

Add license keys from file.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.LicenseApi()
license_file = '/path/to/file.txt' # file | License key file content
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
```

(continues on next page)

(continued from previous page)

```

# Add license from file.
api_response = api_instance.create_iceberg_add_license_from_file(license_file, x_
↳ iam_token=x_iam_token)
pprint(api_response)
except ApiException as e:
    print("Exception when calling LicenseApi->create_iceberg_add_license_from_file:
↳ %s\n" % e)

```

Name	Type	Description	Notes
license_file	file	License key file content	
x_iam_token	str	authentication header object	[optional]

****InlineResponse2001****

No authorization required

- **Content-Type:** multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.661 delete_iceberg_delete_all_license

delete_iceberg_delete_all_license(x_iam_token=x_iam_token)

Delete all licenses.

Delete all the previously added license keys.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.LicenseApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete all licenses.
    api_instance.delete_iceberg_delete_all_license(x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling LicenseApi->delete_iceberg_delete_all_license: %s\n
↳ " % e)

```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json, multipart/form-data

- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.662 delete_iceberg_delete_license_by_id

delete_iceberg_delete_license_by_id(license_id, x_iam_token=x_iam_token)

Delete a license.

Delete a license matching the license id.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.LicenseApi()
license_id = 'license_id_example' # str | License id
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Delete a license.
    api_instance.delete_iceberg_delete_license_by_id(license_id, x_iam_token=x_iam_token)
except ApiException as e:
    print("Exception when calling LicenseApi->delete_iceberg_delete_license_by_id: %s\n" % e)
```

Name	Type	Description	Notes
license_id	str	License id	
x_iam_token	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.663 retrieve_iceberg_get_all_license_id

list[str] retrieve_iceberg_get_all_license_id(x_iam_token=x_iam_token)

List of available license id's.

Get the list of all available license id's.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.LicenseApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # List of available license id's.
    api_response = api_instance.retrieve_iceberg_get_all_license_id(x_iam_token=x_iam_
↪token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling LicenseApi->retrieve_iceberg_get_all_license_id:
↪%s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

list[str]

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.664 retrieve_iceberg_license_features_info

LicenseFeaturesSchema retrieve_iceberg_license_features_info(x_iam_token=x_iam_token)

Status of all the licensed features.

Get the status of all the licensed features. Also provides the compliance info per feature

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.LicenseApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Status of all the licensed features.
    api_response = api_instance.retrieve_iceberg_license_features_info(x_iam_token=x_
↪iam_token)
    pprint(api_response)
```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling LicenseApi->retrieve_iceberg_license_features_info:
↳ %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

****LicenseFeaturesSchema****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.665 retrieve_iceberg_license_file_by_license_id

file retrieve_iceberg_license_file_by_license_id(license_id, x_iam_token=x_iam_token)

Download license file.

Download the specified license file based on license id.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.LicenseApi()
license_id = 'license_id_example' # str | License id
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Download license file.
    api_response = api_instance.retrieve_iceberg_license_file_by_license_id(license_
↳ id, x_iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling LicenseApi->retrieve_iceberg_license_file_by_
↳ license_id: %s\n" % e)
```

Name	Type	Description	Notes
license_id	str	License id	
x_iam_token	str	authentication header object	[optional]

****file****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/octet-stream, application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.666 retrieve_iceberg_license_key_contents

LicenseKeysSchema retrieve_iceberg_license_key_contents(x_iam_token=x_iam_token)

Get the contents of all licenses.

Get the license key contents for all the available licenses.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.LicenseApi()
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Get the contents of all licenses.
    api_response = api_instance.retrieve_iceberg_license_key_contents(x_iam_token=x_
↪ iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling LicenseApi->retrieve_iceberg_license_key_contents:
↪ %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]

****LicenseKeysSchema****

No authorization required

- **Content-Type:** application/json, multipart/form-data
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.667 retrieve_iceberg_license_key_contents_by_id

LicenseKeySchema retrieve_iceberg_license_key_contents_by_id(license_id,
x_iam_token=x_iam_token)

Get the contents of a license.

Get the license key contents by the license id.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
```

(continues on next page)

(continued from previous page)

```

from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.LicenseApi()
license_id = 'license_id_example' # str | License id
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Get the contents of a license.
    api_response = api_instance.retrieve_iceberg_license_key_contents_by_id(license_
↪id, x_iam_token=x_iam_token)
    pprint(api_response)
except ApiException as e:
    print("Exception when calling LicenseApi->retrieve_iceberg_license_key_contents_
↪by_id: %s\n" % e)

```

Name	Type	Description	Notes
license_id	str	License id	
x_iam_token	str	authentication header object	[optional]

****LicenseKeySchema****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.668 update_iceberg_replace_license

InlineResponse2001 update_iceberg_replace_license(license_raw_keys, x_iam_token=x_iam_token)

Update the license.

Update existing license keys with the new one provided in this request.

```

from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.LicenseApi()
license_raw_keys = swagger_client.LicenseRawKeysSchema() # LicenseRawKeysSchema | ↪
↪License raw keys contents
x_iam_token = 'x_iam_token_example' # str | authentication header object (optional)

try:
    # Update the license.
    api_response = api_instance.update_iceberg_replace_license(license_raw_keys, x_
↪iam_token=x_iam_token)
    pprint(api_response)

```

(continues on next page)

(continued from previous page)

```
except ApiException as e:
    print("Exception when calling LicenseApi->update_iceberg_replace_license: %s\n" % e)
    ↪e)
```

Name	Type	Description	Notes
license_raw_keys	**LicenseRawKeysSchema**	License raw keys contents	
x_iam_token	str	authentication header object	[optional]

****InlineResponse2001****

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.669 IngestmappingSchemaAgent

2.669.1 Properties

Name	Type	Description	Notes
for_device_groups	list[str]		[optional]
use_plugin	**IngestmappingSchemaAgentUseplugin**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.670 swagger_client.AdministrationApi

All URIs are relative to *http://api-server/api/v2*

Method	HTTP request	Description
healthbot_alter_app_settings	POST /config/app-settings/	Change runtime app-settings

2.671 healthbot_alter_app_settings

healthbot_alter_app_settings(x_iam_token=x_iam_token, app_settings=app_settings)

Change runtime app-settings

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint
```

(continues on next page)

(continued from previous page)

```
# create an instance of the API class
api_instance = swagger_client.AdministrationApi()
x_iam_token = 'x_iam_token_example' # str / authentication header object (optional)
app_settings = NULL # object / Maintenance endpoint to change app-settings. Not_
↳ accessible externally. (optional)

try:
    # Change runtime app-settings
    api_instance.healthbot_alter_app_settings(x_iam_token=x_iam_token, app_
↳ settings=app_settings)
except ApiException as e:
    print("Exception when calling AdministrationApi->healthbot_alter_app_settings:
↳ %s\n" % e)
```

Name	Type	Description	Notes
x_iam_token	str	authentication header object	[optional]
app_settings	object	Maintenance endpoint to change app-settings. Not accessible externally.	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.672 Groups

2.672.1 Properties

Name	Type	Description	Notes
group_name	str	Name of the group	[optional]
group_description	str	Details of the group	[optional]
roles	**AssociatedRoleSchema**		[optional]
users	**AssociatedUserSchema**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.673 InlineResponse2004

2.673.1 Properties

Name	Type	Description	Notes
user_id	str	ID generated by system	[optional]
user_name	str	Name of the user	[optional]
first_name	str	First name of the user	[optional]
last_name	str	Last name of the user	[optional]
email	str	Email of the user	[optional]
active	bool	Status of the user	[optional]
groups	**AssociatedGroupSchema**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.674 RuleSchemaWhenDoesnotmatchwith

2.674.1 Properties

Name	Type	Description	Notes
all	list[object]	With this flag, result is set to True only if all the data matches the given condition	[optional]
any	list[object]	With this flag, result is set to True if any one of the data matches the condition	[optional]
ignore_case	list[object]	Flag to ignore case while matching the string	[optional]
left_operand	str	Left operand. This is the string in which we have to match the expression.	
right_operand	str	Right operand. This is the match expression.	
time_range	str	How much back in time should we look for data. Specify positive integer followed by s/m/h/d/w/y/o representing seconds/minutes/hours/days/weeks/years/offset. Eg: 2s	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.675 CustomPluginSchema

2.675.1 Properties

Name	Type	Description	Notes
name	str	Name is the identifier of this config, referred in sensor config under topic/rule	
parameters	**list[CustompluginSchemaParameters]**	Plugin specific parameters (config)	[optional]
plugin_name	str	Name of the loaded input plugin of BYOI	[optional]
security_parameters	**CustompluginSchemaSecurityparameters**		[optional]
service_name	str	Name of the service (docker container) which implements this plugin	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.676 RuleSchemaReference

2.676.1 Properties

Name	Type	Description	Notes
data_if_missing	Reference-Dataifmissing**		[optional]
path	str	Reference to a field or trigger in different rule. Format is /topic[topic-name=<topic-name>]/rule[rule-name=<rule-name>]/field[<condition>]/<field-name> for field reference and /topic[topic-name=<topic-name>]/rule[rule-name=<rule-name>]/trigger[trigger-name=<trigger-name>]/key[condition]/trigger_field for trigger reference. Filtering part where field and key are mentioned is optional	
time_range	str	How much back in time should we look for data. Specify positive integer followed by s/m/h/d/w/y/o representing seconds/minutes/hours/days/weeks/years/offset. Eg: 2s	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.677 PatternSchemaField

2.677.1 Properties

Name	Type	Description	Notes
de- scrip- tion	str	Field description	[op- tional]
_from	str	Field that supplies the value. For a structured syslog, this will be the attribute name from the message. For a grok pattern, this will be name of the field given in the pattern. For a regex pattern, this will be the capture group number prefixed by \$, eg: \$1, \$2	[op- tional]
name	str	Field name	
type	str	Data type of field	[op- tional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.678 IngestsettingsSchemaIngestsettingsByoi

2.678.1 Properties

Name	Type	Description	Notes
cus- tom_plugin	**list[CustomPluginSchema]**		[op- tional]
de- fault_plugin	**IngestsettingsSchemaIngestsettingsByoiDefault- plugin**		[op- tional]
in- gest_mapping	**list[IngestMappingSchema]**	Ingest to sensor/device map- ping	[op- tional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.679 IngestsettingsSchemaIngestsettingsSensor

2.679.1 Properties

Name	Type	Description	Notes
fre- quency	str	Sensor subscription duration. Specify integer >= 0 followed by s/m/h/d/w/y representing seconds/minutes/hours/days/weeks/years. Eg: 2s. A frequency of zero should be used only in case of events subscription	
sen- sor_name	str	Name of sensor. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.680 RuleSchemaRulepropertiesSupporteddevices

2.680.1 Properties

Name	Type	Description	Notes
juniper	<code>**RuleSchemaRulepropertiesSupporteddevicesJuniper**</code>		[optional]
other_vendor	<code>**list[RuleSchemaRulepropertiesSupporteddevicesOthervendorSupported devices**</code>	other-vendor	[optional]
sensors	<code>list[str]</code>		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.681 IngestmappingSchemaNetflow

2.681.1 Properties

Name	Type	Description	Notes
for_device_groups	<code>list[str]</code>		[optional]
use_plugin	<code>**IngestmappingSchemaIAgentUseplugin**</code>		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.682 DevicegroupSchemaAuthentication

2.682.1 Properties

Name	Type	Description	Notes
password	<code>**DevicegroupSchemaAuthenticationPassword**</code>		[optional]
ssh	<code>**DevicegroupSchemaAuthenticationSsh**</code>		[optional]
ssl	<code>**DevicegroupSchemaAuthenticationSsl**</code>		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.683 RuleSchemaRulepropertiesSupporteddevicesJuniperProducts

2.683.1 Properties

Name	Type	Description	Notes
plat-forms	**list[RuleSchemaRulepropertiesSupporteddevicesJuniperProductsPlatforminformation]**	Platform information	[optional]
product_name	str	Product name, Ex: MX, SRX. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	
releases	**list[RuleSchemaRulepropertiesSupporteddevicesJuniperProductsReleaseinformation]**	Release information for the products	[optional]
sensors	list[str]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.684 RuleSchemaWhenIncreasingatleastbyrate

2.684.1 Properties

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.685 DevicegroupSchemaPublish

2.685.1 Properties

Name	Type	Description	Notes
destination	list[str]		
field	list[str]		[optional]
sensor	list[str]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.686 RuleSchemaFormulaDynamicthreshold

2.686.1 Properties

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.687 InlineResponse2005

2.687.1 Properties

Name	Type	Description	Notes
user_id	str	ID generated by system	[optional]
user_name	str	Name of the user	[optional]
first_name	str	First name of the user	[optional]
last_name	str	Last name of the user	[optional]
email	str	Email of the user	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.688 TliveKafkaOcSchema

2.688.1 Properties

Name	Type	Description	Notes
brokers	list[str]		
collector_settings	object		[optional]
name	str	Name of this instance	
security	**TlivekafkaocSchemaSecurity**		[optional]
topics	list[str]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.689 RuleSchemaFormulaMicroburst

2.689.1 Properties

Name	Type	Description	Notes
if_name	str	Interface name. This should be field name where interface names are being stored	
packets	str	Queue egress packets. This should be field name where queue egress packets are being stored	
percentage	str	Queue buffer occupancy percentage. This should be field name where queue buffer occupancy percentage are being stored	
queue_no	str	Queue numbers. This should be field name where queue numbers are being stored	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.690 DatastoreSchema

2.690.1 Properties

Name	Type	Description	Notes
group_name	str	group name	[optional]
key	str	key name for the group	[optional]
value	object	value for the key	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.691 TemplateSchema

2.691.1 Properties

Name	Type	Description	Notes
description	str	Template description.	[optional]
key_fields	list[str]		[optional]
name	str	Name of the template.	
priority	int	Priority given to template during matching.	[optional]
protocol_version	str	Flow protocol version.	[optional]
recognition_pattern	**FlowSchemaFlowRecognitionpattern**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.692 AffectedGroups

2.692.1 Properties

Name	Type	Description	Notes
device_groups	list[str]		[optional]
network_groups	list[str]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.693 IngestMappingSchema

2.693.1 Properties

Name	Type	Description	Notes
i_agent	**IngestmappingSchemaIAgent**		[optional]
name	str	Name of the mapping	
native_gpb	**IngestmappingSchemaNativegpb**		[optional]
netflow	**IngestmappingSchemaNetflow**		[optional]
open_config	**IngestmappingSchemaOpenconfig**		[optional]
server_monitoring	**IngestmappingSchemaOpenconfig**		[optional]
snmp	**IngestmappingSchemaSnmp**		[optional]
syslog	**IngestmappingSchemaSyslog**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.694 CommitJob

2.694.1 Properties

Name	Type	Description	Notes
detail	str		
status	int		
url	str		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.695 NotificationSchemaKafkapublishSasl

2.695.1 Properties

Name	Type	Description	Notes
certificate	str	File path to kafka CA-Certificate. Should be of pattern .+.pem	[optional]
password	str	Password for sasl_ssl authentication	[optional]
username	str	Username for sasl_ssl authentication	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.696 DevicegroupSchemaSyslog

2.696.1 Properties

Name	Type	Description	Notes
ports	list[int]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.697 NotificationSchemaEmailsFilter

2.697.1 Properties

Name	Type	Description	Notes
rules	list[str]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.698 SshKeyProfileSchema

2.698.1 Properties

Name	Type	Description	Notes
name	str	SSH Key profile name. Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	
ssh_private_key_file	str	SSH private key file name	
ssh_private_key_passphrase	str	SSH private key passphrase	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.699 RuleSchemaSnmp

2.699.1 Properties

Name	Type	Description	Notes
frequency	str	Frequency at which data needs to be extracted from given SNMP table. Specify positive integer followed by s/m/h/d/w/y representing seconds/minutes/hours/days/weeks/years. Eg: 2s	
scalars	list[str]		[optional]
table	str	OID of an SNMP table	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.700 IngestmappingSchemaAgentUseplugin

2.700.1 Properties

Name	Type	Description	Notes
instance	str	Plugin instance name	[optional]
name	str	BYOI plugin name	
type	str	Plugin type	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.701 DeviceSchemaVendorOthervendor

2.701.1 Properties

Name	Type	Description	Notes
operat-ing_system	str	Vendor operating system, Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	[optional]
platform	str	Platform name of the device, Example: MX240	[optional]
product	str	Product category of the device, Example: MX	[optional]
release	str	Release string of the device, Example: 19.2R1	[optional]
vendor_name	str	Vendor-name, Should be of pattern [a-zA-Z][a-zA-Z0-9_-]*	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.702 RuleSchemaFormulaAnomalydetection

2.702.1 Properties

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.703 swagger_client.DataSourceApi

All URIs are relative to *http://api-server/api/v1*

Method	HTTP request	Description
create_data_store	POST /data-store/{group_name}/	Create dashboard details.

2.704 create_data_store

`create_data_store(key, data, group_name, authorization=authorization)`

Create dashboard details.

Store data-store details in database for the requested group name and key.

```
from __future__ import print_function
import time
import swagger_client
from swagger_client.rest import ApiException
from pprint import pprint

# create an instance of the API class
api_instance = swagger_client.DataSourceApi()
key = 'key_example' # str | Key of data_store object
data = swagger_client.DatastoreSchema() # DatastoreSchema | Value of data_store object
group_name = 'group_name_example' # str | Group name
authorization = 'authorization_example' # str | authentication header object,
↳ (optional)

try:
    # Create dashboard details.
    api_instance.create_data_store(key, data, group_name, authorization=authorization)
except ApiException as e:
    print("Exception when calling DataSourceApi->create_data_store: %s\n" % e)
```

Name	Type	Description	Notes
key	str	Key of data_store object	
data	**DatastoreSchema**	Value of data_store object	
group_name	str	Group name	
authorization	str	authentication header object	[optional]

void (empty response body)

No authorization required

- **Content-Type:** application/json
- **Accept:** application/json

[\[Back to top\]](#) [\[Back to API list\]](#) [\[Back to Model list\]](#) [\[Back to README\]](#)

2.705 RuleSchemaFormulaOutlierdetection

2.705.1 Properties

Name	Type	Description	Notes
algorithm	**RuleSchemaFormulaOutlierdetectionAlgorithm**		[optional]
dataset	str	Variable containing the list of XPATHs to the data	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.706 NotificationSchemaKafkapublish

2.706.1 Properties

Name	Type	Description	Notes
boot-strap_servers	list[str]		
sasl	**NotificationSchemaKafka-publishSasl**		[optional]
topic	str	Kafka topic to which Healthbot should publish. Should be of pattern <code>./a-zA-Z0-9*-/+/a-zA-Z0-9.-]*</code> , Default value is derived from <code><device/network-group>.<device-id>.<topic>.<rule>.<trigger></code>	[optional]
use_hash_partitioner	bool	If true, key will be generated which will be hashed to provide a consistent partition number for the given kafka topic	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.707 RuleSchemaRulepropertiesSupporteddevicesJuniperOperatingssystem

2.707.1 Properties

Name	Type	Description	Notes
os_name	str	Operating system for the supported devices	
products	**list[RuleSchemaRulepropertiesSupporteddevicesJuniperProducts]**	Products information of the device	[optional]
sensors	list[str]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.708 DeviceGroupsSchema

2.708.1 Properties

Name	Type	Description	Notes
device_group	**list[DeviceGroupSchema]**		

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.709 RuleSchemaReferenceDataifmissing

2.709.1 Properties

Name	Type	Description	Notes
value	str	Assign given default value for field in case of data missing	[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.710 NotificationSchemaSlack

2.710.1 Properties

Name	Type	Description	Notes
channel	str	Channel on which notification should be posted	
url	str	URL on which slack notification needs to be posted	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.711 InlineResponse2001

2.711.1 Properties

Name	Type	Description	Notes
license_id	str		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.712 FlowSchemaFlowTemplate

2.712.1 Properties

Name	Type	Description	Notes
description	str	Template description.	[optional]
key_fields	list[str]		[optional]
name	str	Name of the template.	
priority	int	Priority given to template during matching.	[optional]
protocol_version	str	Flow protocol version.	[optional]
recognition_pattern	**FlowSchemaFlowRecognitionpattern**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.713 IngestsettingsSchemaIngestsettingsFrequencyprofile

2.713.1 Properties

Name	Type	Description	Notes
name	str	Frequency profile name	
non_sensor	**list[FrequencyprofileSchemaNonsensor]**		[optional]
sensor	**list[IngestsettingsSchemaIngestsettingsSensor]**		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.714 RuleSchemaFormula1And

2.714.1 Properties

Name	Type	Description	Notes
left_vector	str	Vector name. Pattern for giving vector name is @[a-z][a-zA-Z0-9_-]*	
right_vector	str	Vector name. Pattern for giving vector name is @[a-z][a-zA-Z0-9_-]*	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.715 RuleSchemaFormulaUserdefinedfunction

2.715.1 Properties

Name	Type	Description	Notes
argument	**list[RuleSchemaFormulaUserdefinedfunctionArgument]**		[optional]
function_name	str	Function name	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.716 RuleSchemaThenArgument

2.716.1 Properties

Name	Type	Description	Notes
argument	str	Argument name	
value	str	Argument value	

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

2.717 NetworkgroupSchemaPublish

2.717.1 Properties

Name	Type	Description	Notes
destination	list[str]		
field	list[str]		[optional]

[\[Back to Model list\]](#) [\[Back to API list\]](#) [\[Back to README\]](#)

CHAPTER 3

Indices and tables

- `genindex`
- `modindex`
- `search`

j

- `jnpr.healthbot.healthbot`, [32](#)
- `jnpr.healthbot.modules.database`, [32](#)
- `jnpr.healthbot.modules.devices`, [3](#)
- `jnpr.healthbot.modules.playbooks`, [14](#)
- `jnpr.healthbot.modules.profiles`, [26](#)
- `jnpr.healthbot.modules.rules`, [10](#)
- `jnpr.healthbot.modules.settings`, [17](#)

method), 8

api (*jnpr.healthbot.healthbot.HealthBotClient* attribute), 34

api (*jnpr.healthbot.modules.database.Database* attribute), 32

apiopt_candidate (*jnpr.healthbot.healthbot.HealthBotClient* attribute), 32

apply () (*jnpr.healthbot.modules.playbooks.PlayBookInstanceBuilder* method), 17

C

CaProfile (class in *jnpr.healthbot.modules.profiles*), 27

check_device_in_group () (*jnpr.healthbot.modules.devices.DeviceGroup* method), 7

clear () (*jnpr.healthbot.modules.playbooks.PlayBookInstanceBuilder* method), 17

close () (*jnpr.healthbot.healthbot.HealthBotClient* method), 35

commit () (*jnpr.healthbot.healthbot.HealthBotClient* method), 34

config_url (*jnpr.healthbot.healthbot.HealthBotClient* attribute), 33

D

Database (class in *jnpr.healthbot.modules.database*), 32

DataSummarization (class in *jnpr.healthbot.modules.profiles*), 31

delete () (*jnpr.healthbot.modules.devices.Device* method), 4

delete () (*jnpr.healthbot.modules.devices.DeviceGroup* method), 6

delete () (*jnpr.healthbot.modules.devices.NetworkGroup* method), 9

delete () (*jnpr.healthbot.modules.playbooks.Playbook* method), 15

delete () (*jnpr.healthbot.modules.playbooks.PlayBookInstanceBuilder* method), 17

delete () (*jnpr.healthbot.modules.profiles.CaProfile* method), 27

delete () (*jnpr.healthbot.modules.profiles.LocalCertificate* method), 29

delete () (*jnpr.healthbot.modules.profiles.Raw* method), 31

delete () (*jnpr.healthbot.modules.profiles.SshKeyProfile* method), 30

delete () (*jnpr.healthbot.modules.rules.Rule* method), 13

delete () (*jnpr.healthbot.modules.settings.Destination* method), 23

delete () (*jnpr.healthbot.modules.settings.LicenseKeyManagement* method), 26

delete () (*jnpr.healthbot.modules.settings.Notification* method), 18

delete () (*jnpr.healthbot.modules.settings.Report* method), 25

delete () (*jnpr.healthbot.modules.settings.RetentionPolicy* method), 20

delete () (*jnpr.healthbot.modules.settings.Scheduler* method), 21

Destination (class in *jnpr.healthbot.modules.settings*), 22

Device (class in *jnpr.healthbot.modules.devices*), 3

device_variable (*jnpr.healthbot.modules.playbooks.PlayBookInstanceBuilder* attribute), 17

DeviceGroup (class in *jnpr.healthbot.modules.devices*), 6

G

get () (*jnpr.healthbot.modules.devices.Device* method), 4

get () (*jnpr.healthbot.modules.devices.DeviceGroup* method), 7

get () (*jnpr.healthbot.modules.devices.NetworkGroup* method), 9

get () (*jnpr.healthbot.modules.playbooks.Playbook* method), 15

get () (*jnpr.healthbot.modules.profiles.CaProfile* method), 27

get () (*jnpr.healthbot.modules.profiles.LocalCertificate* method), 28

get () (*jnpr.healthbot.modules.profiles.Raw* method), 31

get () (*jnpr.healthbot.modules.profiles.SshKeyProfile* method), 30

get () (*jnpr.healthbot.modules.rules.Rule* method), 13

get () (*jnpr.healthbot.modules.rules.Topic* method), 14

get () (*jnpr.healthbot.modules.settings.Destination* method), 22

get () (*jnpr.healthbot.modules.settings.LicenseKeyManagement* method), 26

get () (*jnpr.healthbot.modules.settings.Notification* method), 18

get () (*jnpr.healthbot.modules.settings.Report* method), 24

get () (*jnpr.healthbot.modules.settings.RetentionPolicy* method), 19

get () (*jnpr.healthbot.modules.settings.Scheduler* method), 21

get_facts () (*jnpr.healthbot.modules.devices.Device* method), 5

get_features () (*jnpr.healthbot.modules.settings.LicenseKeyManagement* method), 25

get_ids () (*jnpr.healthbot.modules.devices.Device* method), 4

get_ids () (*jnpr.healthbot.modules.settings.LicenseKeyManagement* method), 25

`get_table()` (*jnpr.healthbot.modules.database.Database* attribute), 32

`grafana_url` (*jnpr.healthbot.healthbot.HealthBotClient* attribute), 34

H

`hbot_session` (*jnpr.healthbot.healthbot.HealthBotClient* attribute), 33

`health()` (*jnpr.healthbot.healthbot.HealthBotClient* method), 35

`health()` (*jnpr.healthbot.modules.devices.Device* method), 6

`health()` (*jnpr.healthbot.modules.devices.DeviceGroup* method), 8

`health()` (*jnpr.healthbot.modules.devices.NetworkGroup* method), 10

`HealthBotClient` (class in *jnpr.healthbot.healthbot*), 32

J

`jnpr.healthbot.healthbot` (module), 32

`jnpr.healthbot.modules.database` (module), 32

`jnpr.healthbot.modules.devices` (module), 3

`jnpr.healthbot.modules.playbooks` (module), 14

`jnpr.healthbot.modules.profiles` (module), 26

`jnpr.healthbot.modules.rules` (module), 10

`jnpr.healthbot.modules.settings` (module), 17

L

`LicenseKeyManagement` (class in *jnpr.healthbot.modules.settings*), 25

`LocalCertificate` (class in *jnpr.healthbot.modules.profiles*), 28

`login()` (*jnpr.healthbot.healthbot.HealthBotClient* method), 33

`logout()` (*jnpr.healthbot.healthbot.HealthBotClient* method), 33

N

`NetworkGroup` (class in *jnpr.healthbot.modules.devices*), 8

`Notification` (class in *jnpr.healthbot.modules.settings*), 18

O

`open()` (*jnpr.healthbot.healthbot.HealthBotClient* method), 33

P

`Playbook` (class in *jnpr.healthbot.modules.playbooks*), 14

`playbook_schema` (*jnpr.healthbot.modules.playbooks.PlayBookInstanceBuilder* attribute), 17

`PlayBookInstanceBuilder` (class in *jnpr.healthbot.modules.playbooks*), 16

`Profile` (class in *jnpr.healthbot.modules.profiles*), 26

R

`Raw` (class in *jnpr.healthbot.modules.profiles*), 31

`Report` (class in *jnpr.healthbot.modules.settings*), 23

`RetentionPolicy` (class in *jnpr.healthbot.modules.settings*), 19

`rollback()` (*jnpr.healthbot.healthbot.HealthBotClient* method), 34

`Rule` (class in *jnpr.healthbot.modules.rules*), 10

`rule_variables` (*jnpr.healthbot.modules.playbooks.PlayBookInstanceBuilder* attribute), 17

`rules` (*jnpr.healthbot.modules.playbooks.PlayBookInstanceBuilder* attribute), 17

S

`Scheduler` (class in *jnpr.healthbot.modules.settings*), 20

`Security` (class in *jnpr.healthbot.modules.profiles*), 27

`set_user_token()` (*jnpr.healthbot.healthbot.HealthBotClient* method), 33

`Settings` (class in *jnpr.healthbot.modules.settings*), 17

`SshKeyProfile` (class in *jnpr.healthbot.modules.profiles*), 30

T

`tenant` (*jnpr.healthbot.healthbot.HealthBotClient* attribute), 33

`Topic` (class in *jnpr.healthbot.modules.rules*), 14

`tsdb` (*jnpr.healthbot.healthbot.HealthBotClient* attribute), 33

U

`update()` (*jnpr.healthbot.modules.devices.Device* method), 5

`update()` (*jnpr.healthbot.modules.devices.DeviceGroup* method), 7

`update()` (*jnpr.healthbot.modules.devices.NetworkGroup* method), 9

`update()` (*jnpr.healthbot.modules.playbooks.Playbook* method), 15

`update()` (*jnpr.healthbot.modules.profiles.CaProfile* method), 28

`update()` (*jnpr.healthbot.modules.profiles.LocalCertificate* method), 29

`update()` (*jnpr.healthbot.modules.profiles.Raw* method), 31

`update()` (*jnpr.healthbot.modules.profiles.SshKeyProfile* method), 31

`update()` (*jnpr.healthbot.modules.rules.Rule method*),
13

`update()` (*jnpr.healthbot.modules.settings.Destination
method*), 23

`update()` (*jnpr.healthbot.modules.settings.Notification
method*), 19

`update()` (*jnpr.healthbot.modules.settings.Report
method*), 25

`update()` (*jnpr.healthbot.modules.settings.RetentionPolicy
method*), 20

`update()` (*jnpr.healthbot.modules.settings.Scheduler
method*), 22

`upload_helper_file()`
(*jnpr.healthbot.healthbot.HealthBotClient
method*), 34

`upload_playbook_file()`
(*jnpr.healthbot.modules.playbooks.Playbook
method*), 16

`upload_rule_file()`
(*jnpr.healthbot.modules.rules.Rule method*), 14

`url` (*jnpr.healthbot.healthbot.HealthBotClient attribute*),
33

`user_token` (*jnpr.healthbot.healthbot.HealthBotClient
attribute*), 33

V

`version` (*jnpr.healthbot.healthbot.HealthBotClient at-
tribute*), 34